Comparison of Firewalls vs. Data Diodes for Unidirectional Communication

Feature	Data Diode	Firewall
Unidirectional Data Flow	Enforced **physically** at the hardware level. Communication is guaranteed to be one-way.	Firewalls are incapable of supporting uni-directional data flow. Firewalls can limit access from side to side but once a session is created, it will always be bi-directional.
Physical Security	Built with a physical separation (e.g., optical diodes) to prevent any reverse data flow.	No physical mechanism to ensure unidirectional flow. Rules can be bypassed if compromised.
Dependence on Software	Operates independently of software. No need for operating systems or software configurations.	Fully dependent on software rules and configurations, making it susceptible to bugs and exploits.
No IP or MAC Dependency (at core security element)	Core does not have an **IP address** or **MAC address**, ensuring complete anonymity and protection from network spoofing.	Requires IP and MAC addresses, making it vulnerable to network-based attacks like spoofing or DDoS.
Configuration Complexity	Simple setup requiring no complex configurations or ongoing maintenance.	Requires extensive configuration and maintenance, increasing the risk of human error.
Resistance to Exploits	Core security element is immune to **protocol-level exploits** like spoofing, replay attacks, and reverse traffic injection.	Vulnerable to advanced attacks that manipulate protocols or bypass filtering rules.
Statefulness	Core element Stateless operation—does not require acknowledgment or session management.	Often stateful—tracks session information, inherently enabling two-way traffic.
Insider Threats	No software or configurations at core element to manipulate, making insider threats ineffective.	Administrative access can be abused to modify firewall rules, enabling bidirectional traffic.
Protocol Support	Local termination of all TCP/UDP sessions, no touring/bridging performed. Original packets destroyed; only raw data is forwarded.	All TCP/UDP traffic traverses through the FW as sent by originator including all portions of the packet, often uninspected.
Hardware-Based Security	Provides **100% isolation** between networks through physical design.	Relies on software based access rules, which can be compromised.
Impact of Misconfigurations	No risk of misconfiguration; data flow is unidirectional by design.	Misconfigured rules or exceptions can accidentally allow bidirectional traffic.

Terafence Ltd.
Tel +972 4 850 0101 › Fax +972 4 855 1491 › www.terafence.com
Nahum Het 5,Haifa, Israel 3508504

Private and confidential. Proprietary of Terafence Ltd.

Feature	Data Diode	Firewall
Zero-Day Vulnerability	Immune to software-based vulnerabilities, as it does not rely on software or operating systems.	Highly vulnerable to zero-day attacks targeting its software.
Patch Updates	Core element needs no **patch updates** since it lacks an operating system or software dependencies.	Requires regular updates and patches to remain effective.
Invisibility to Hackers	Core element is completely invisible to attackers because it lacks network identifiers like IP addresses, MAC addresses, or OS.	Visible on the network due to IP and MAC address requirements, making it a target for reconnaissance.
Cost of Ownership	Higher initial cost but low maintenance	Lower initial cost but higher ongoing maintenance, updates, and patch management.
Scalability	Designed for highly secure, critical infrastructure where unidirectional flow is essential.	General-purpose security tool; not ideal for unidirectional applications in critical systems.
Certifications and Standards	Often certified for use in critical infrastructure (e.g., defense, utilities, and power grids).	May lack certifications for use in high-security unidirectional applications.
Usage in Critical Systems	Ideal for SCADA, OT networks, and ICS where **100% security and isolation** are required.	Used for general-purpose network security but unsuitable for critical unidirectional needs.
Maintenance Requirements	Minimal; operates independently of updates or patches.	Requires regular updates and patches to remain effective.

Key Advantage: Invisibility to Hackers

1. **No Network Exposure**:
   Data Diodes totally hide all networking information on both sides, rendering them completely invisible during network scans or reconnaissance attempts. Hackers cannot target what they cannot see.

2. **No Exploitable Surface**:
   As a data-diode uses a hardware chip with no MAC/IP Address, there is no attack surface for hackers to exploit. Firewalls, on the other hand, are exposed to attackers due to their reliance on IP/MAC addresses and software vulnerabilities.

Private and confidential. Proprietary of Terafence Ltd.

Why Firewalls Fail as Unidirectional Gateways

Using firewalls as a substitute for Data Diodes exposes critical systems to risks due to:

- **Uni-directional traffic support:** By design, Firewalls are incapable of enforcing uni-directional data flow. Firewalls excel in limiting access from side to side, but once access has been granted a Firewall will always allow full bi-directional date-flow.
- **Network Visibility**: Firewalls require IP and MAC addresses, making them discoverable and exploitable during attacks.
- **Logical Configurations**: Unlike Data Diodes, which enforce unidirectionality through physical hardware, firewalls depend on software rules that can be bypassed by skilled attackers.
- **Vulnerability to Exploits**: Firewalls are prone to zero-day vulnerabilities, protocol manipulation, and insider threats.

Data Diodes are purpose-built solutions offering **absolute unidirectional security** for critical systems like SCADA, OT networks, and ICS. Their hardware-based design ensures they are invisible to hackers and immune to network-based attacks. Unlike firewalls, Data Diodes core security element does not rely on IP addresses, MAC addresses, or operating systems, providing unmatched protection without requiring software updates or patches.

Firewalls, while effective for general network security, are unsuitable as unidirectional gateways in high-security environments. For guaranteed isolation and protection, organizations must prioritize deploying Data Diodes over firewalls.

Terafence Ltd.
Tel +972 4 850 0101 › Fax +972 4 855 1491 › www.terafence.com
Nahum Het 5,Haifa, Israel 3508504

Private and confidential. Proprietary of Terafence Ltd.