

1 Basics

Luay is a hard fork of LuaJ for (selfish) purposes

- since luaj 3.0.2 seems to remain static, a new evolution is needed.
- scripting under java is fun and has applications
- jme is dead
- several extensions added in

Refer: <https://github.com/luaj/luaj>

Refer: <https://www.lua.org/manual/5.2/manual.html#2>

1.1 What has been done

- import LuaJ 3.0.2 sources
- maven-ize build system
- remove Java ME-isms
- move to luay namespace
- 64-bit ints, with bit64 operator library (check also bitop below ↓)
- array-only tables
- hash-only tables
- hack coerce for java Map and List interface objects to pose as native
- hack module loader to allow loading using servicelader bader libraries
- implement lua 5.3 – io – only partially – implemented file:read options without '*', but keeping compat with 5.2
- implement lua 5.3 – utf8 – only partially – see docs
- extend the core modules with functions from ZDF – ONGOING.
- lua-stringy – Fast lua string operations (should we move that to core ?)

2 Introduction

Refer: <https://www.lua.org/manual/5.2/manual.html#1>

3 The Language

Refer: <https://www.lua.org/manual/5.2/manual.html#3>

4 Java API

TODO

5 lua aux lib

TODO

6 Standard Libraries

All libraries are implemented and provided as separate Java classes modules. Currently, Lua-5.2 has the following standard libraries:

- basic library (extended by Luay)
- coroutine library
- package library
- string manipulation
- table manipulation (extended by Luay)
- mathematical functions
- bitwise operations (extended by Luay)
- input and output
- operating system facilities
- debug facilities

Except for the basic and the package libraries, each library provides all its functions as fields of a global table or as methods of its objects.

In addition to the extensions of the standard libraries, Luay provides the following additional libraries:

- hash library (md5, sha1, ...)

6.1 Basic Functions

Refer: <http://www.lua.org/manual/5.2/manual.html#6.1>

- `assert (v [, message])`
- `collectgarbage ([opt [, arg]])`
- `dofile ([filename])`
- `error (message [, level])`
- `_G`
- `ipairs (t) -> iterator, t, 0`
- `load (ld [, source [, mode [, env]]])`
- `loadfile ([filename [, mode [, env]]])`
- `next (table [, index])`
- `pairs (t) -> iterator, t, nil`
- `pcall (f [, arg1, ...])`
- `print (...)`
- `rawequal (v1, v2)`
- `rawget (table, index)`
- `rawlen (v)`
- `rawset (table, index, value)`
- `select (index, ...)`
- `setmetatable (table, metatable)`
- `tonumber (e [, base])`
- `tostring (v)`
- `type (v)`
- `_VERSION`
- `xpcall (f, msgch [, arg1, ...])`

6.1.1 Luay Extensions

- `stringify (string[, type])`
- `printf (...)`
- `apairs(v1[, ...,vN]) -> iterator, list, 0` — inspired from idle-lang
- `list(value[, value ...]) -> list-only-table`
- `map(key1, value1 [, keyN, valueN ...]) -> map-only-table`
- `__FILE__` — filepath of the initial executed script, if available.
- `__PATH__` — path containing the initial executed script, if available.

6.2 Coroutine Manipulation

```
local coroutine = require('coroutine');
```

Refer: <http://www.lua.org/manual/5.2/manual.html#6.2>

- `coroutine.create (f)`
- `coroutine.resume (co [, val1, ...])`
- `coroutine.running ()`
- `coroutine.status (co)`
- `coroutine.wrap (f)`
- `coroutine.yield (...)`

6.3 Modules

Refer: <http://www.lua.org/manual/5.2/manual.html#6.3>

- `require (modname)`
- `package.config`
- `package.loaded`
- `package.loadlib (libname, funcname)` — not implemented
- `package.path`
- `package.preload`
- `package.searchers`
- `package.searchpath (name, path [, sep [, rep]])`

6.3.1 Luay Extensions

- `package.addpath(path [, ...]) -> _, string` — prepends to existing search path
- `package.setpath(path [, ...]) -> _, string` — replaces existing search path
- `package.loadlib (javaclassname or luayextname)`

6.4 String Manipulation

```
local string = require('string');
```

Refer: <http://www.lua.org/manual/5.2/manual.html#6.4>

- `string.byte (s [, i [, j]])` -> `bytei[, ..., bytej]`
- `string.char (...)` -> `charstring`
- `string.dump (function)` -> `string`
- `string.find (s, pattern [, init [, plain]])` -> `index1, index2 [, captures ...]`
- `string.format (formatstring, ...)` -> `string`
- `string.gmatch (s, pattern)` -> `iterator`

```
s = "hello world from Lua"
for w in string.gmatch(s, "%a+") do
    print(w)
end

t = {}
s = "from=world, to=Lua"
for k, v in string.gmatch(s,("(%w+)=(%w+)") do
    t[k] = v
end
```
- `string.gsub (s, pattern, repl [, n])` -> `string`
- `string.len (s)` -> `int`
- `string.lower (s)`
- `string.match (s, pattern [, init])`
- `string.rep (s, n [, sep])`
- `string.reverse (s)`
- `string.sub (s, i [, j])`
- `string.upper (s)`

Refer: <http://www.lua.org/manual/5.3/manual.html#6.4>

TODO

- `string.pack (fmt, v1, v2, ...)`
- `string.packsize (fmt)`
- `string.unpack (fmt, s [, pos])`

6.4.1 Patterns

Refer: <http://www.lua.org/manual/5.2/manual.html#6.4.1>

6.4.2 Format Strings for Pack and Unpack

TODO

Refer: <http://www.lua.org/manual/5.3/manual.html#6.4.2>

6.4.3 Luay Extensions

- `string.concat (v1[, ..., vN])` -> `string`
 - `string.concat (table)` -> `string`
 - `string.split (sep, string)` -> `list`
 - `string.split (sep, string, limit)` -> `list`
- Java `String.split`

- `string.explode(string) -> list`
- `string.explode(sep, string) -> list`
- `string.explode(sep, string, limit) -> list`
Java StringTokenizer, default all whitespace
- `string.implode(sep, v1[, ..., vN]) -> string`
- `string.implode(sep, table) -> string`
- `string.mformat(fmt, v1[, ..., vN]) -> string`
Java MessageFormatter
- `string.sformat(fmt, v1[, ..., vN]) -> string`
Java String.format

6.5 UTF-8 Support

```
local utf8 = require('utf8');
```

Refer: <http://www.lua.org/manual/5.3/manual.html#6.5>

- `utf8.char (...)` -> string
- `utf8.charpattern` (NOT IMPLEMENTED)
- `utf8.codes (s)` (NOT IMPLEMENTED)
- `utf8.codepoint (s [, i [, j]])` -> list
- `utf8.len (s [, i [, j]])` (NOT IMPLEMENTED)
- `utf8.offset (s, n [, i])` (NOT IMPLEMENTED)

6.5.1 Luay Extensions

- `utf8.length (s)` -> int
- `utf8.substr (s, n [, i])` -> string
- `utf8.indexof (s, n [, i])` -> int/nil
- `utf8.lastindexof (s, n [, i])` -> int/nil
- `utf8.lower (s)` -> string
- `utf8.upper (s)` -> string
- `utf8.find(hay, needle [, start])` -> offset or nil
- `utf8.count(hay, needle [, start])` -> offset of nil
- `utf8.contains(hay, needle)` -> boolean
- `utf8.matches(hay, rx)` -> boolean
- `utf8.startswith(hay, needle)` -> boolean
- `utf8.endswith(hay, needle)` -> boolean
- `utf8.rxsplitle(hay, rx)` -> list
- `utf8.split(hay, sep)` -> list
- `utf8.join(sep, hay, ...)` -> string
- `utf8.format(fmt, ...)` -> string
- `utf8.repeat(part, int)` -> string
- `utf8.trim(hay)` -> string
- `utf8.strip(hay)` -> string
- `utf8.striptrailing(hay)` -> string
- `utf8.stripleading(hay)` -> string
- `utf8.replace(string, charFrom, charTo)` -> string
- `utf8.replace(string, table)` -> string
- `utf8.rxreplace(string, rx, to)` -> string

6.6 Table Manipulation

```
local table = require('table');
```

Refer: <http://www.lua.org/manual/5.2/manual.html#6.5>

- `table.concat (list [, sep [, i [, j]])`
- `table.insert (list, [pos,] value)`
- `table.pack (...)`
- `table.remove (list [, pos]) -> value`
- `table.sort (list [, comp])`
- `table.unpack (list [, i [, j]])`

Refer: <http://www.lua.org/manual/5.3/manual.html#6.6>

TODO

```
table.move (a1, f, e, t [,a2])
```

Moves elements from table `a1` to table `a2`, performing the equivalent to the following multiple assignment: `a2[t],... = a1[f],...,a1[e]`. The default for `a2` is `a1`. The destination range can overlap with the source range. The number of elements to be moved must fit in a Lua integer.

6.7 Mathematical Functions

```
local math = require('math');
```

Refer: <http://www.lua.org/manual/5.2/manual.html#6.6>

- `math.abs (x)`
- `math.acos (x)`
- `math.asin (x)`
- `math.atan (x)`
- `math.atan2 (y, x)`
- `math.ceil (x)`
- `math.cos (x)`
- `math.cosh (x)`
- `math.deg (x)`
- `math.exp (x)`
- `math.floor (x)`
- `math.fmod (x, y)`
- `math.frexp (x)`
- `math.huge`
- `math.ldexp (m, e)`
- `math.log (x [, base])`
- `math.max (x, ...)`
- `math.min (x, ...)`
- `math.modf (x)`
- `math.pi`
- `math.pow (x, y)`
- `math.rad (x)`
- `math.random ([m [, n]])`
- `math.randomseed (x)`
- `math.sin (x)`
- `math.sinh (x)`
- `math.sqrt (x)`
- `math.tan (x)`
- `math.tanh (x)`

6.8 Bitwise Operations

```
local bit32 = require('bit32');
```

Refer: <http://www.lua.org/manual/5.2/manual.html#6.7>

- `bit32.arshift (x, disp)`
- `bit32.band (...)`
- `bit32.bnot (x)`
- `bit32.bor (...)`
- `bit32.btest (...)`
- `bit32.bxor (...)`
- `bit32.extract (n, field [, width])`
- `bit32.replace (n, v, field [, width])`
- `bit32.lrotate (x, disp)`
- `bit32.lshift (x, disp)`
- `bit32.rrotate (x, disp)`
- `bit32.rshift (x, disp)`

6.8.1 Luay Extension

```
local bit64 = require('bit64');
```

- `bit64.arshift (x, disp)`
- `bit64.band (...)`
- `bit64.bnot (x)`
- `bit64.bor (...)`
- `bit64.btest (...)`
- `bit64.bxor (...)`
- `bit64.extract (n, field [, width])`
- `bit64.replace (n, v, field [, width])`
- `bit64.lrotate (x, disp)`
- `bit64.lshift (x, disp)`
- `bit64.rrotate (x, disp)`
- `bit64.rshift (x, disp)`

6.9 IO Functions

```
local io = require('io');
```

Refer: <http://www.lua.org/manual/5.2/manual.html#6.8>

- `io.close ([file])`
- `io.flush ()`
- `io.input ([file])`
- `io.lines ([filename ...])`
- `io.open (filename [, mode]) -> file`
- `io.output ([file])`
- `io.popen (prog [, mode])`
- `io.read (...)`
- `io.tmpfile () -> file`
- `io.type (obj)`
- `io.write (...)`
- `file:close ()`
- `file:flush ()`
- `file:lines (...)`
- `file:read (...)`
- `file:seek ([whence [, offset]])`
- `file:setvbuf (mode [, size])`
- `file:write (...)`

6.9.1 Luay Extensions

- `io.loadasstring(file[, mode]) -> string, err`
- `io.loadastable(file[, mode]) -> list, err`

6.10 Operating System Facilities

```
local os = require('os');
```

Refer: <http://www.lua.org/manual/5.2/manual.html#6.9>

- `os.clock ()`
- `os.date ([format [, time]])`
- `os.difftime (t2, t1)`
- `os.execute ([command])`
- `os.exit ([code [, close]])`
- `os.getenv (varname)`
- `os.remove (filename)`
- `os.rename (oldname, newname)`
- `os.setlocale (locale [, category])`
- `os.time ([table])`
- `os.tmpname ()`

7 Luay Core Libraries

Libraries that only depend on Luay Core and the JVM standard Classpath.

7.1 hash Library

```
local hash = require('hash');
```

- hash.md5 (bytes) -> bytes
- hash.sha1 (bytes) -> bytes
- hash.sha256 (bytes) -> bytes
- hash.sha512 (bytes) -> bytes
- hash.to_hex (bytes) -> string
- hash.from_hex (string) -> bytes
- hash.to_b32 (bytes) -> string
- hash.from_b32 (string) -> bytes
- hash.to_b64 (bytes) -> string
- hash.from_b64 (string) -> bytes
- hash.to_b26 (bytes) -> string
- hash.to_b36 (bytes) -> string
- hash.to_b62 (bytes) -> string
- hash.to_uuid (bytes) -> string
- hash.to_xid (bytes) -> string
- hash.to_xxid (bytes, bytes) -> string
- hash.random_string (int [, string[, string]]) -> string

7.1.1 hash object

```
local _md = hash.new_hash('MD5');  
_md:update('this');  
_md:update('hello', 'world');  
print('md5 hex =', hash.to_hex(_md:finish()))
```

7.1.2 mac object

```
local _mh = hash.new_mac('HMACMD5', 's3cr3t');  
_mh:update('this');  
_mh:update('hello', 'world');  
print('hmacmd5 hex =', hash.to_hex(_mh:finish()))
```

7.2 LuaZDF inspired Libraries

7.2.1 array

```
local array = require('array');
```

- `array.array(value[, value ...])` -> array-only-table
- `array.list(value[, value ...])` -> list-only-table
- `array.push (list, value[, value ...])` -> list
Appends the values onto the list, returns the list.
- `array.pop (list)` -> value
Removes the last element from the list and returns it.
- `array.unshift (list, value[, value ...])` -> list
Prepends the values to the list, returns the list.
- `array.shift (table)` -> value
Removes the first element from the list and return it.
- `array.append (list, value[, value ...])` -> table
Alias for push.
- `array.appendall (table, tbl1[, ..., tblN])` -> table
Append all k,v from following tables to the first one, return the first.
- `array.chunk(list, size)` -> list(lst1, ..., lstN)
Function to split array into /size/ chunks.
- `array.split(list, size)` -> lst1, lst2
Function to split array in two at /size/.
- `array.collect (table[, ..., tableN])` -> list(v1, ..., vX)
Function to collect all values for the list of tables.
- `array.count (table, fv)` -> table
Sorts a list into groups and returns a count for the number of objects in each group. Similar to `groupBy`, but instead of returning a list of values, returns a count for the number of values in that group.
- `array.difference (list1, list2)` -> list
Computes the values of list1 that not occure in list2.
- `array.find(list, value [, init])` -> v, i
- `array.findif(list, fv [, init])` -> v, i
Looks through an array table and returning the first element that matches.
- `array.indexof(list, value [, init])` -> i
- `array.indexof(list, fv [, init])` -> i
Looks through an array table and returning the index of the first element that matches.

7.2.2 map

```
local map = require('map');
```

- `map.map (k1,v1[, ..., kN, vN]) -> map-only-table`
Function to collect all kv-pairs into a map-only table.
- `map.collectk (table[, ..., tableN]) -> list(k1, ..., kX)`
Function to collect all keys for the list of tables.
- `map.collectv (table[, ..., tableN]) -> list(v1, ..., vX)`
Function to collect all values for the list of tables.
- `map.collect (table[, ..., tableN]) -> table`
Function to collect all k,v for the list of tables.
- `map.count (table, fv) -> table`
Sorts a list into groups and returns a count for the number of objects in each group. Similar to `groupBy`, but instead of returning a list of values, returns a count for the number of values in that group.

7.3 getopt

option processing for lists/arrays.

7.3.1 Functions

- `getopt.std(pattern, arglist) -> map, list`
roughly emulates single character mode of `getopt(3)`.
 - option processing always stops at a standalone double-dash (ie. `'--'`).
 - option characters followed by a colon (ie. `':'`), the option takes an argument
 - if pattern is prefixed by a dash (ie. `'-'`), invalid options will be ignored
 - if pattern is prefixed by a colon (ie. `':'`), invalid options will be processed as zero-arg options
 - if pattern is prefixed by a plus (ie. `'+'`), the first non-option argument will stop processing
 - short options can be abbreviated like
 - `'f:vx'` on `-fvx file -> f=file, v=true, x=true`
 - `'f:vx'` on `-vfx file -> f=file, v=true, x=true`
 - `'f:vx'` on `-vxf file -> f=file, v=true, x=true`
- `getopt.long([pattern,] optionmap, arglist) -> map, list`
non-standard long-option processing in addition or instead of `getopt(3)`.
 - optionmap is given as `map('zero-arg-option', 0, 'arg-option', 1)`
 - invalid options cause error.
 - option-arguments can be given as `--zero-arg-option` or `--arg-option option-value` or `--arg-option=option-value`
- `getopt.simple(arglist) -> map, list`
hard-wired option rules processing.
 - option processing always stops at a standalone double-dash (ie. `'--'`).
 - option processing always stops at a standalone dash (ie. `'-'`).
 - option processing always stops at the first non-option argument.
 - short options are zero-arg
 - short options cannot be abbreviated, the arg option start immediately like `-ffile -v -x -> f=file, v=true, x=true`
 - if a single-dash option string includes an equal sign, it is parsed like `-f=file -file=file -> f=file, file=file`
 - short options starting with a plus (ie. `'+'`) are inverted like `-v +x -> v=true, x=false`
 - long options are always parsed as `--zero-arg-option` or `--arg-option=option-value`
- `getopt.stdext(pattern, arglist) -> list<pair>, list`
- `getopt.longext([pattern,] optionmap, arglist) -> list<pair>, list`
- `getopt.simplext(arglist) -> list<pair>, list`

7.4 filesystems

posix file system functions mostly inspired by libUseful.

7.4.1 Functions

- `filesystems.basename(Path)` -> map, list
gets a filename (basename) from a path
- `filesystems.dirname(Path)`
gets a directory part of a path, clipping off the last part that should be the filename
- `filesystems.filename(Path)`
gets a file name from a path, this is name without extension, so distinct from basename
- `filesystems.exists(Path)`
return true if a filesystem object (file, directory, etc) exists at path 'Path', false otherwise
- `filesystems.extn(Path)`
gets a file extension from a path
- `filesystems.mkdir(Path)`
make a directory. DirMask is the 'mode' of the created directory, and is optional
- `filesystems.mkdirPath(Path)`
make a directory, CREATING ALL PARENT DIRECTORIES AS NEEDED.
- `filesystems.size(Path)`
get size of a file
- `filesystems.mtime(Path)`
get modification time of a file
- `filesystems.chown(Path, Owner)`
change owner of a file. 'Owner' is the name, not the uid
- `filesystems.chgrp(Path, Group)`
change group of a file. 'Group' is the group name, not the gid
- `filesystems.chmod(Path, Mode)`
change mode/permissions of a file. Perms can be a numeric value like '0666' or rwx string like 'rw-rw-rw'
- `filesystems.rename(from, to)`
- `filesystems.rmdir(path)`
remove directory. Directory must be empty
- `filesystems.copy(src, dest)`
make a copy of a file
- `filesystems.copydir(src, dest)`
make a recursive copy of a directory
- `filesystems.find(File, path)` -> path
- `filesystems.symlink(path, symlink)`
create a symbolic link at 'symlink' pointing to file/directory at 'path'
- `filesystems.link(path, linkname)`
create a hard link at 'linkname' pointing to file/directory at 'path'
- `filesystems.is_file(filename)` -> boolean
- `filesystems.is_dir(filename)` -> boolean
- `filesystems.list_dirs(dirname [, ext, ...])` -> list
- `filesystems.list_dir(dirname [, ext, ...])` -> list

8 Luay Extension Libraries

8.1 ldapjndi

Read-only Ldap access via JNDI.

8.1.1 Functions

- `ldapjndi.connect(uri, admin dn, admin pw [, mode, starttls])` -> session
uri = "ldap://ldap.forumsys.com:port/" or "ldaps://ldap.forumsys.com:port/"
- `ldapjndi.disconnect(session)`
- `ldapjndi.close(session)`
- `ldapjndi.get(session. dn [, a1, ..., aN])` -> map
- `ldapjndi.search(session. basedn, filter [, scope, a1, ..., aN])` -> list of maps
- `ldapjndi.authdn(session. dn, pw [, mode])` -> bool

8.2 bytebuf

Java Buffer/ByteBuffer.

8.2.1 Functions

- `bytebuf.alloc(size[, direct]) -> bytebuf`
- `bytebuf.free(bytebuf)`
- `bytebuf.duplicate(bytebuf) -> bytebuf`
- `bytebuf.slice(bytebuf) -> bytebuf`
- `bytebuf.orderbe(bytebuf)`
- `bytebuf.orderle(bytebuf)`
- `bytebuf.clear(bytebuf)`
- `bytebuf.flip(bytebuf)`
- `bytebuf.compact(bytebuf)`
- `bytebuf.reset(bytebuf)`
- `bytebuf.rewind(bytebuf)`
- `bytebuf.mark(bytebuf)`
- `bytebuf.capacity(bytebuf) -> int`
- `bytebuf.remaining(bytebuf) -> int`
- `bytebuf.hasremaining(bytebuf) -> bool`
- `bytebuf.limit(bytebuf[, newlimit]) -> int`
- `bytebuf.position(bytebuf[, newposition]) -> int`
- `bytebuf.write(bytebuf, bytebuf)`
- `bytebuf.readbytes(bytebuf[, size]) -> bytes`
- `bytebuf.getbytes(bytebuf, index[, size]) -> bytes`
- `bytebuf.writebytes(bytebuf, bytes)`
- `bytebuf.setbytes(bytebuf, index, bytes)`
- `bytebuf.readbyte(bytebuf) -> byte`
- `bytebuf.getbyte(bytebuf, index) -> byte`
- `bytebuf.writebyte(bytebuf, byte)`
- `bytebuf.setbyte(bytebuf, index, byte)`
- `bytebuf.readshort(bytebuf) -> short`
- `bytebuf.getshort(bytebuf, index) -> short`
- `bytebuf.writeshort(bytebuf, short)`
- `bytebuf.setshort(bytebuf, index, short)`
- `bytebuf.readint(bytebuf) -> int`
- `bytebuf.getint(bytebuf, index) -> int`
- `bytebuf.writeint(bytebuf, int)`
- `bytebuf.setint(bytebuf, index, int)`
- `bytebuf.readlong(bytebuf) -> long`
- `bytebuf.getlong(bytebuf, index) -> long`
- `bytebuf.writelong(bytebuf, long)`

- `bytebuf.setlong(bytebuf, index, long)`
- `bytebuf.readfloat(bytebuf) -> float`
- `bytebuf.getFloat(bytebuf, index) -> float`
- `bytebuf.writefloat(bytebuf, float)`
- `bytebuf.setfloat(bytebuf, index, float)`
- `bytebuf.readdouble(bytebuf) -> double`
- `bytebuf.getDouble(bytebuf, index) -> double`
- `bytebuf.writedouble(bytebuf, double)`
- `bytebuf.setdouble(bytebuf, index, double)`
- `bytebuf.readchar(bytebuf) -> int`
- `bytebuf.getchar(bytebuf, index) -> int`
- `bytebuf.writechar(bytebuf, int)`
- `bytebuf.setchar(bytebuf, index, int)`

8.3 snmp

SNMP.

8.3.1 Functions

- `snmp.oid(i1 [, ..., iN]) -> oidstring`
- `snmp.snmpv2(address [, port [, community]]) -> session`
- `snmp.close(session)`
- `snmp.closeall()`
- `snmp.getall(session, timeout, oid [, ..., oid]) -> tablelist`
- `snmp.get(session, oid [, timeout]) -> table`
- `snmp.next(session, oid [, timeout]) -> table`
- `snmp.walk(session, oid [, timeout [, quiteness]]) -> tablelist`

8.3.2 return table

- `/1/` – oid
- `/2/` – type-id
- `/3/` – value.toString
- `/4/` – snmpToLuaValue

8.4 sql

jdbc access to sql databases.

8.4.1 Functions

- `sql.xlsql(hostportorpath) -> connection`
- `sql.sqlite(hostportorpath, username, password) -> connection`
- `sql.mysql(hostportorpath, username, password) -> connection`
- `sql.mysql5(hostportorpath, username, password) -> connection`
- `sql.oracle(hostportorpath, username, password) -> connection`
- `sql.mariadb(hostportorpath, username, password) -> connection`
- `sql.mssql(hostportorpath, username, password) -> connection`
- `sql.jtds(hostportorpath, username, password) -> connection`
- `sql.pgsql(hostportorpath, username, password) -> connection`
- `sql.jdbc(type, driver, uri, username, password) -> connection`

8.4.2 jdbc database types

POSTGRES, ORACLE, MSSQL, SYBASE, DB2, H2, SQLITE, CRATE, ANSI, MYSQL

8.4.3 Connection object

- `connection:autocommit(boolean)`
- `connection:commit()`
- `connection:rollback()`
- `connection:execute(sqlquery) -> rc, err`
- `connection:execute(sqlquery, map) -> rc, err`
- `connection:execute(sqlquery, list) -> rc, err`
- `connection:execute(sqlquery, ...) -> rc, err`
- `connection:insert(sqlquery) -> rc, err`
- `connection:insert(sqlquery, map) -> rc, err`
- `connection:insert(sqlquery, list) -> rc, err`
- `connection:insert(sqlquery, ...) -> rc, err`
- `connection:query(sqlquery) -> maplist, err`
- `connection:query(sqlquery, map) -> maplist, err`
- `connection:query(sqlquery, list) -> maplist, err`
- `connection:query(sqlquery, ...) -> maplist, err`
- `connection:close()`

9 Extending the Runtime with Libraries

These are my observations on how to add additional libraries to the runtime that can be `require'd`.

9.1 The old LuaJ Way.

In LuaJ each available library comes in 3 forms:

- A `.lua` file on the filesystem or classpath (ie. `searchpath`), using the standard lua way.
- A predefined/preloaded Java Class that extends from `TwoArgFunction` that is provided to the runtime at setup time. This is the most restrictive option as the library must provide its own setup and the executor the registration code.
- A Java Class that extends from `TwoArcFunction` available on classpath, with exact naming conventions. This can either return a library or a single function.

9.1.1 Library Case

```
public class extlib extends TwoArgFunction
{
    public extlib() {}

    @Override
    public LuaValue call(LuaValue modname, LuaValue env) {
        // setup code
        LuaTable _extlib = new LuaTable();
        _extlib.set('extfunction', new _extfunction());
        env.set("extlib", _extlib);
        if (!env.get("package").isnil())
            env.get("package").get("loaded").set("extlib", _extlib);
        return _extlib;
    }

    static class _extfunction extends VarArgFunction
    {
        @Override
        public Varargs invoke(Varargs args) {
            // function code
            return ...;
        }
    }
}
```

9.1.2 Single Function Case

```
public class jtest extends TwoArgFunction
{
    @Override
    public LuaValue call(LuaValue _name, LuaValue _env) {
        return AbstractLibrary._zeroArgFunctionWrapper.from(_name.tojstring(), jtest::);
    }

    public static LuaValue _call()
    {
        return LuaValue.TRUE;
    }
}
```


9.2 LuayBuilder support for preload.

```
luayContext = LuayBuilder.create()
    .inputStream(System.in)
    .outputStream(System.out)
    .errorStream(System.err)
    .baseLibraries()
    .extensionLibrary(new extlib())
    .build();
```

9.3 The Luay Way

Luay extends the library loader with a serviceloader, so classes can have arbitrary names and paths.

9.3.1 LuaySimpleLibraryFactory

This is the simplest option. You implement a glue-factory class that provides proper library name and object instance, the java object will be auto-coerced and all methods be exposed.

```
public class ExtLibFactory implements LuaySimpleLibraryFactory
{
    @Override
    public String getName() {
        return "extlib";
    }

    @Override
    public Object getInstance() {
        return Class.forName("ext.ExtLib").newInstance();
    }
}

public class ExtLib
{
    // library methods
    // ...
}
```

9.3.2 LuayLibraryFactory

If you need more control over which methods get exposed, use this option. Note: your class needs to extend AbstractLibrary and some setup code.

```
public class ExtLibFactory implements LuayLibraryFactory
{
    @Override
    public String getName() {
        return "extlib";
    }

    @Override
    @SneakyThrows
    public AbstractLibrary getInstance() {
        return (AbstractLibrary) Class.forName("ext.ExtLib").newInstance();
    }
}

public class ExtLib extends AbstractLibrary
{
    @Override
    public List<LuaFunction> getLibraryFunctions() {
```

```
        return toList(  
            _varArgFunctionWrapper.from("extfunc", ExtLib::extFunc)  
        );  
    }  
  
    public static LuaValue extFunc(Varargs args) {  
        // function code ...  
    }  
}
```

