

1	P00	SPI.CLK	SCLK
2	P01	U5.13	
3	P02	LED_Red	
4	P03	SPI.CS	
5	P30	-	
6	P04	UART_TX	
7	P05	SPI.SO	DC
8	P21	U5.12	CS
9	P06	SPI.SI	SDI
10	P07	U5.11	RST
11	32Kp		
12	32Km		
13	P22	U5.1	
14	VBAT_RF		
15	VBAT3V		
16	GND		
17	RST		
18	P23	PWR_EN	
19	VDCDC		
20	P24	接U4	
21	SWITCH		
22	P10	U5.10	
23	VBAT1V		
24	P11	U5.9	
25	SWDIO		
26	SWCLK		
27	P12	-	
28	P13	-	
29	16Mp		
30	16Mm		
31	VDCDC_RF		
32	P25	LED_Green	
33	P26	-	
34	RFIOm		
35	RFIOp		
36	P27	-	
37	P28	-	
38	VDD		
39	P29	LED_Blue	
40	P20	U5.14	BUSY

P22

P11

P10

P07

P21

P01

P20

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24

在Flash的0x39000处，保存有GPIO的配

HLT_CTL
GDR
RESE
VGL
VGH
TSCL
TSDA
BS
nBUSY
nRST
D/C
nCS
SCLK
SDI
VDDIO
VCI
VSS
VDDIO
VPP
VSH
PREVGH
VSL
PREVGL
VCOM

温控IIC接口

1:3线 0:4线

置信息