Analytics Engineering: Session 2

Setting Up dbt & Building First Models

Agenda

- Introduction to DuckDB
- Setting up the environment and database
- Git workflow: forking & cloning
- The VS Code IDE & dbt Power User
- The dbt project structure (`dbt_project.yml`)
- Building your first model
- The `ref()` macro & modularity
- Key dbt commands
- Compiled vs run SQL (`target/`)
- Naming conventions

Introduction to DuckDB

Why DuckDB?

- **"SQLite for analytics"**: an in-process SQL OLAP database.
- **Serverless**: no server to install, configure, or maintain.
- **Fast**: columnar storage, vectorized execution — optimized for analytical queries.
- **Integrated**: reads Parquet/CSV directly, works natively with Python and dbt.

In this course, **DuckDB acts as our Data Warehouse**, running locally on your machine. The file `my_database.duckdb` *is* our warehouse.

Setting up the Environment

We use `uv` as the Python package manager — fast, modern, and reproducible.

1. **Sync dependencies** (reads `pyproject.toml`, creates `.venv/`, writes `uv.lock`):

```
uv sync
```

2. **Activate the virtual environment**:

```
source .venv/bin/activate          # macOS / Linux
.\.venv\Scripts\Activate.ps1       # Windows PowerShell
```

3. **Install dbt packages** (from `packages.yml`):

```
dbt deps
```

Setting up the Database

We load the raw Parquet files into DuckDB with a helper script:

```
python create_db.py
```

This creates `my_database.duckdb` with 14 raw tables: `customers`, `orders`, `order_items`, `products`, `shipping`, `payments`, `reviews`, and more.

Verify the dbt connection:

```
dbt debug
```

If everything is green, you are ready to build.

Git Workflow: Forking & Cloning

All your work lives inside **your own fork**. Nothing gets pushed back to the instructor's repo.

1. **Fork** `dgarhdez/dbt-ie` on GitHub — this creates `YOUR_USERNAME/dbt-ie`, which you own and can push to.
2. **Clone your fork** locally:

```
git clone https://github.com/YOUR_USERNAME/dbt-ie.git
```

3. **Branch** for each piece of work:

```
git checkout -b feature/my-first-model
```

4. **Commit, push, and open a PR** *inside your fork* (feature branch → your own `main`). Merge it yourself.

Same PR-based workflow used in industry — just scoped to your fork.

The VS Code IDE

We use **Visual Studio Code** as our Integrated Development Environment.

Recommended extensions:

- **Python** — run scripts and manage environments.
- **dbt Power User** (by Innoverio) — dbt-specific features.
- **SQLTools** + **SQLTools DuckDB driver** — query the warehouse directly.
- **Rainbow CSV** — readable CSV previews.

The dbt Power User Extension

Bridges the gap between your code and dbt execution.

Install: Extensions view (`Cmd+Shift+X`) → search "dbt Power User" → Install.

Features you will use daily:

- **Go to Definition** — `Cmd+Click` on a `ref()` to jump to the referenced model.
- **Query Preview** — run the current model's SQL against DuckDB without a full `dbt run`.
- **Compiled SQL panel** — see the compiled output live.
- **Lineage view** — visualize upstream/downstream dependencies.

The dbt Project Structure

Every dbt project is defined by `dbt_project.yml` at the repo root.

```yaml
name: 'dbt_ie'
version: '1.0.0'
profile: 'default'          # which profile from profiles.yml to use

model-paths:    ["models"]
seed-paths:     ["seeds"]
macro-paths:    ["macros"]
snapshot-paths: ["snapshots"]
test-paths:     ["tests"]

models:
  dbt_ie:
    staging:
      materialized: view    # default materialization for models/staging/
```

Project Directory Layout

```
dbt-ie/
├── dbt_project.yml          # project config
├── packages.yml             # dbt packages to install
├── models/                  # your transformations (SQL + Python)
│   ├── staging/
│   ├── intermediate/
│   └── marts/
├── seeds/                   # static CSVs loaded as tables
├── macros/                  # reusable Jinja snippets
├── snapshots/               # SCD Type 2 tracking
├── tests/                   # singular (custom) tests
├── analyses/                # ad-hoc SQL, never executed by `dbt run`
├── target/                  # compiled + run artifacts (gitignored)
└── logs/                    # dbt run logs (gitignored)
```

Building Your First Model

A **dbt model** is a `SELECT` statement saved as a `.sql` file under `models/`.

```sql
-- models/staging/stg_customers.sql
select
    customer_id,
    first_name,
    last_name,
    email,
    country
from main.customers
```

Build it:

```
dbt run -s stg_customers
```

We read directly from `main.customers` for now. Next session we will wrap raw tables with

The `ref()` Macro & Modularity

`ref()` is how models reference each other — it is the core of dbt's **DAG**.

```sql
-- models/intermediate/int_customer_orders.sql
select
    c.customer_id,
    c.first_name,
    count(o.order_id) as n_orders
from {{ ref('stg_customers') }} as c
left join {{ ref('stg_orders') }}    as o
    on c.customer_id = o.customer_id
group by 1, 2
```

- dbt resolves `ref()` to the correct schema/table **at compile time**.
- It builds a **Directed Acyclic Graph** of all models.
- It determines the correct **execution order** automatically.

Why `ref()` Matters

Without `ref()`:

```
-- brittle: hardcoded schema, no dependency tracking
from main.stg_customers
```

With `ref()`:

```
from {{ ref('stg_customers') }}
```

- **Portable**: same code works across dev, staging, and prod schemas.
- **DAG-aware**: dbt knows to build `stg_customers` *before* any model that refs it.
- **Safe refactoring**: rename a model → dbt flags every downstream consumer.

Key dbt Commands

Command	Purpose
`dbt debug`	Verify connection and project configuration
`dbt deps`	Install packages from `packages.yml`
`dbt compile`	Compile Jinja → SQL, no execution
`dbt run`	Execute all models
`dbt run -s model_name`	Build a single model
`dbt run -s +mart_orders`	Build `mart_orders` and everything upstream
`dbt build`	`run` + `test` + `seed` + `snapshot` in DAG order

Compiled vs Run SQL

After `dbt compile` or `dbt run`, dbt writes two kinds of output under `target/`:

- `target/compiled/` — the SQL **after Jinja rendering**, before execution.
  Exactly what dbt would send to the warehouse.
- `target/run/` — the SQL **wrapped in the materialization DDL** (e.g. `create table as ...`).
  The full statement dbt actually executed.

```
target/compiled/dbt_ie/models/staging/stg_customers.sql   # pure SELECT
target/run/dbt_ie/models/staging/stg_customers.sql        # CREATE VIEW ... AS SELECT
```

Always check compiled SQL when debugging — it is the ground truth of what your Jinja produced.

Naming Conventions

Consistent naming helps teams collaborate and keeps the DAG readable.

Layer	Prefix	Example
Staging	`stg_`	`stg_customers`, `stg_orders`
Intermediate	`int_`	`int_order_items_summary`
Dimensions	`dim_`	`dim_customers`, `dim_products`
Marts / Facts	`mart_`	`mart_orders`, `mart_revenue_by_segment`

We will apply these consistently for the rest of the course — they map directly to the three-layer architecture introduced in Session 1.

What have we learned in this session

- Set up the environment with `uv sync` and loaded data into DuckDB
- Forked and cloned the course repo; understood the PR workflow
- Configured VS Code with the dbt Power User extension
- Navigated the dbt project structure and `dbt_project.yml`
- Built our first model and used `ref()` to create a dependency
- Learned the core dbt commands: `debug`, `deps`, `compile`, `run`, `build`
- Inspected compiled vs run SQL in `target/`

Next session: Sources, Seeds, Dependencies & First Tests.