Synthetic Stakeholders? Agreement and Stability of Open-Weight LLM Agent Panels in Participatory Model Selection

Tereza Blazkova[1,*]

[1] Center for Social Data Science, University of Copenhagen

tereza.blazkova@sodas.ku.dk

[*] Corresponding author.

Abstract

LLM agents are proposed as synthetic participants, but rarely compared with a real deliberation. We replay a three-hour workshop in which 9 students and 3 advisors set the rules for selecting a university dropout early-warning model, using 12-agent panels from three open-weight model families under the same scripted protocol (20 runs each). On average, the panels matched only one to three of the seven rules the humans set, and two of the three families chose the same model, not the humans' one, in every run. Deliberation barely changed the agents' answers (a few of 23 items; humans: 10), and they hedged: 97% of their final votes were "support with reservations", while the humans' votes ranged from support to block.

1 Motivation

Participatory AI asks affected people to shape algorithmic systems (Birhane et al., 2022; Delgado et al., 2023), which is costly; LLMs can simulate survey respondents and human-subject studies (Argyle et al., 2023; Aher et al., 2023), suggesting stand-in participants, but they misportray and flatten groups (Wang et al., 2025), diverge from their opinions (Santurkar et al., 2023) and, as simulated users, are "excessively cooperative" and "stylistically uniform" (Zhou et al., 2026). Chen et al. (2026) list as an open question for which use cases simulated users are a useful proxy for human ones; we test one, comparing synthetic panels with what a real participatory process produced, before and after deliberation.

2 Human reference and design

In a three-hour deliberative workshop at a Danish university (Blazkova et al., 2026), 9 students and 3 student advisors answered a survey before and after deliberation (Fishkin, 2009), pricing each step on two ladders in students identified per 100: adding data (course performance, enrolment, LMS activity, sensitive attributes) and lowering explainability (from a credit rule to




Figure 1 | Design. Both lanes take the same survey before and after the same protocol and are compared at both points. Grey steps are not simulated: one algorithm turns endline medians into rules and a model. Only the model family varies.

a neural network). Applied to the candidate models on a held-out test cohort, their endline medians selected logistic regression on credits and performance (recall 62.3% vs. 23.5% for the credit rule). This workshop is one draw, not a ground truth: how much workshops with similar people would differ is unknown, and its participants' own baseline rules match their endline ones on only 3 of 7, so we report agreement next to random panels and the same humans before deliberation. Synthetic panels replay the full process (Figure 1): 12 fictional personas matching the human workshop's role and demographic mix, the verbatim survey, and a scripted facilitator running the human protocol (table discussions, plenary, 1-2-4-All, final assessment). Families are Qwen 3.5 27B, Gemma 3 27B and Mistral Small 3.2 24B (4-bit, temperature 1), 20 seeded runs each, since consistency across runs is part of reliability (Rabanser et al., 2026). Scoring and the random-panel reference were fixed before any model output; no personal data or transcripts were used.

3 Results

Rules and selected model. Qwen and Gemma panels matched fewer human rules than the humans' own baseline answers did, Mistral about as many (Figure 2a). The decisive difference is enrolment data: the humans admitted it only for a large gain, while almost all panels (54 of 60) accepted it for less and so selected logistic regression with enrolment data instead of the human model. This choice was already in their baseline answers, as the humans' was in theirs; only Mistral ever chose the human model, and Qwen and Gemma never varied.




Figure 2 | (a) Panels' endline answer per rule; marker size = runs (of 20) giving that answer; boxes: human endline (solid), baseline if different (dashed). Rules matched (of 7, mean): Qwen 1.9, Gemma 1.35, Mistral 3.1 (humans' baseline: 3); human model chosen: 0/20, 0/20, 3/20 runs. (b) Items (of 23) whose panel median moved; % = share of human moves repeated. (c) Final votes.

What deliberation changed. Deliberation changed humans far more than agents (Figure 2b). The humans revised 10 of 23 answers, mostly toward more restriction, including 4 of the 7 rules and most sensitive attributes. Agent panels revised few, rarely in the humans' direction: Qwen also became stricter, but mostly on other items, while Gemma and Mistral mostly loosened sensitive attributes. Nearly all Gemma and Qwen agents reported becoming more critical. No agent gave plain support in the final assessment: 97% of votes were "support with reservations"; humans' ranged from support to block (Figure 2c).

Limitations and implications. With one workshop, agreement is not validity, but uniform choices, little movement and hedged votes hold regardless and match the "systematically more cooperative" simulated users Chen et al. (2026) warn of, and may manufacture rather than reach consensus (cf. Dafoe et al., 2020; Tessler et al., 2024). **Ongoing work** compares deliberation: like humans, agents weighed surveillance against helping students in need and named the harm of being flagged; they dwelt on advisor resources and student wellbeing but did not raise intersectionality or question the system's purpose or its idea of a "good" student.

References

Gati V. Aher, Rosa I. Arriaga, and Adam Tauman Kalai. Using large language models to simulate multiple humans and replicate human subject studies. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pages 337–371, 2023. Cited at: 1.

Lisa P. Argyle, Ethan C. Busby, Nancy Fulda, Joshua R. Gubler, Christopher Rytting, and David Wingate. 2023. Out of one, many: Using language models to simulate human samples. *Political Analysis*, 31 (3):337–351. https://doi.org/10.1017/pan.2023.2. Cited at: 1.

Abeba Birhane, William Isaac, Vinodkumar Prabhakaran, Mark Diaz, Madeleine Clare Elish, Iason Gabriel, et al. Power to the People? Opportunities and Challenges for Participatory AI. In *Equity and Access in Algorithms Mechanisms and Optimization*, pages 1–8, Arlington VA USA, October 2022. ACM. ISBN 978-1-4503-9477-2. https://doi.org/10.1145/3551624.3555290. Cited at: 1.

Tereza Blazkova, René F. Kizilcec, Allison Koenecke, and Andreas Bjerre-Nielsen. [Title withheld during double-blind review]. Manuscript under review, 2026. Cited at: 1.

Felix Chen, Stephan Rabanser, Peter Kirgis, Nitya Nadgir, Rishi Bommasani, Magda Dubois, et al. Emerging trends in AI agent evaluation. https://sage.cs.princeton.edu/trends/, October 2026. Cited at: 1, 2.

Allan Dafoe, Edward Hughes, Yoram Bachrach, Tantum Collins, Kevin R. McKee, Joel Z. Leibo, et al. Open problems in cooperative AI, 2020. Cited at: 1.

Fernando Delgado, Stephen Yang, Michael Madaio, and Qian Yang. The Participatory Turn in AI Design: Theoretical Foundations and the Current State of Practice. In *Proceedings of the 3rd ACM Conference on Equity and Access in Algorithms, Mechanisms, and Optimization*, EAAMO '23, pages 1–23, New York, NY, USA, October 2023. Association for Computing Machinery. ISBN 979-8-4007-0381-2. https://doi.org/10.1145/3617694.3623261. Cited at: 1.

James Fishkin. *When the people speak: Deliberative democracy and public consultation*. Oup Oxford, 2009. Cited at: 1.

Stephan Rabanser, Sayash Kapoor, Peter Kirgis, Kangheng Liu, Saiteja Utpala, and Arvind Narayanan. Towards a science of AI agent reliability, 2026. Cited at: 1.

Shibani Santurkar, Esin Durmus, Faisal Ladhak, Cinoo Lee, Percy Liang, and Tatsunori Hashimoto. Whose opinions do language models reflect? In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pages 29971–30004, 2023. Cited at: 1.

Michael Henry Tessler, Michiel A. Bakker, Daniel Jarrett, Hannah Sheahan, Martin J. Chadwick, Raphael Koster, et al. 2024. AI can help humans find common ground in democratic deliberation. *Science*, 386(6719). https://doi.org/10.1126/science.adq2852. Cited at: 1.

Angelina Wang, Jamie Morgenstern, and John P. Dickerson. 2025. Large language models that replace human participants can harmfully misportray and flatten identity groups. *Nature Machine Intelligence*, 7(3):400–411. https://doi.org/10.1038/s42256-025-00986-z. Cited at: 1.

Xuhui Zhou, Weiwei Sun, Qianou Ma, Yiqing Xie, Jiarui Liu, Weihua Du, et al. Mind the Sim2Real gap in user simulation for agentic tasks, 2026. Cited at: 1.