FPGA Interfaces | Peripheral Pins | HPS Clocks | SDRAM

Ethernet Media Access Controller

EMAC0 pin:	Unused
EMAC0 mode:	N/A
EMAC1 pin:	HPS I/O Set 0
EMAC1 mode:	RGMII

NAND Flash Controller

Quad SPI Flash Controller

QSPI pin:	HPS I/O Set 0
QSPI mode:	1 SS

SD/MMC Controller

SDIO pin:	HPS I/O Set 0
SDIO mode:	4-bit Data

USB Controllers

USB0 pin:	Unused
USB0 PHY interface mode:	N/A
USB1 pin:	HPS I/O Set 0
USB1 PHY interface mode:	SDR with PHY clock output mode

SPI Controllers

SPIM0 pin:	Unused
SPIM0 mode:	N/A
SPIM1 pin:	HPS I/O Set 0
SPIM1 mode:	Single Slave Select
SPIS0 pin:	Unused
SPIS0 mode:	N/A
SPIS1 pin:	Unused
SPIS1 mode:	N/A

UART Controllers

UART0 pin:	HPS I/O Set 0
UART0 mode:	No Flow Control
UART1 pin:	Unused
UART1 mode:	N/A

I2C Controllers

I2C0 pin:	HPS I/O Set 0
I2C0 mode:	I2C
I2C1 pin:	HPS I/O Set 0
I2C1 mode:	I2C
I2C2 pin:	Unused
I2C2 mode:	N/A
I2C3 pin:	Unused
I2C3 mode:	N/A