Signal Tap Logic Analyzer - //vmware-host/Shared Folders/Documents/DEV/plasmax/proj/quartus/DE1_SOC - DE1_SOC - [stp1.stp]*

File Edit View Project Processing Tools Window Help

Search altera.com

Instance Manager: Start Rapid Recompile to continue

Instance	Status	Enabled	LEs: 2812	Memory: 26880	Small: 0/0	Medium: 6/397	Large: 0/0
auto_signaltap_0	Not running	☑	2812 cells	26880 bits	0 blocks	6 blocks	0 blocks

JTAG Chain Configuration: JTAG ready

Hardware: DE-SoC [USB-1] Setup...

Device: @2: 5CSE(BA5|MA5)/5CSTFD5 Scan Chain

>> SOF Manager:

auto_signaltap_0 Lock mode: Allow all changes

Type	Alias	Node Name	Data Enable 210	Trigger Enable 210	Trigger Conditions 1 Basic AND
		de1_soc:de1_soc|plasma_soc_top:plasma_soc_0|avm_address[31..0]	☑	☑	XXXXXXXXh
		de1_soc:de1_soc|plasma_soc_top:plasma_soc_0|avm_byteenable[3..0]	☑	☑	Xh
		de1_soc:de1_soc|plasma_soc_top:plasma_soc_0|avm_readdata[31..0]	☑	☑	XXXXXXXXh
		de1_soc:de1_soc|plasma_soc_top:plasma_soc_0|avm_response[1..0]	☑	☑	Xh
		de1_soc:de1_soc|plasma_soc_top:plasma_soc_0|avm_writedata[31..0]	☑	☑	XXXXXXXXh
		de1_soc:de1_soc|plasma_soc_top:plasma_soc_0|avm_read	☑	☑	
		de1_soc:de1_soc|plasma_soc_top:plasma_soc_0|avm_waitrequest_n	☑	☑	
		de1_soc:de1_soc|plasma_soc_top:plasma_soc_0|avm_write	☑	☑	
		de1_soc:de1_soc|plasma_soc_top:plasma_soc_0|avs_address[31..0]	☑	☑	XXXXXXXXh
		de1_soc:de1_soc|plasma_soc_top:plasma_soc_0|avs_byteenable[3..0]	☑	☑	Xh
		de1_soc:de1_soc|plasma_soc_top:plasma_soc_0|avs_readdata[31..0]	☑	☑	XXXXXXXXh
		de1_soc:de1_soc|plasma_soc_top:plasma_soc_0|avs_response[1..0]	☑	☑	Xh
		de1_soc:de1_soc|plasma_soc_top:plasma_soc_0|avs_writedata[31..0]	☑	☑	XXXXXXXXh
		de1_soc:de1_soc|plasma_soc_top:plasma_soc_0|avs_read	☑	☑	
		de1_soc:de1_soc|plasma_soc_top:plasma_soc_0|avs_waitrequest_n	☑	☑	
		de1_soc:de1_soc|plasma_soc_top:plasma_soc_0|avs_write	☑	☑	

Signal Configuration:

Clock: CLOCK_50

Data

Sample depth: 128 RAM type: Auto

Segmented: 2 64 sample segments

Nodes Allocated: Auto Manual: 210

Pipeline Factor: 0

Storage qualifier:

Type: Continuous

Input port:

Nodes Allocated: Auto Manual: 210

Record data discontinuities

Disable storage qualifier

Trigger

Nodes Allocated: Auto Manual: 210

Trigger flow control: Sequential

Trigger position: Pre trigger position

Trigger conditions: 1

Trigger in

Pin:

Node:

Instance:

Hard Processor System (HPS) trigger out

Pattern: High

Trigger out

Pin:

Instance:

Hard Processor System (HPS) trigger in

Hard Processor System (HPS) event: 0

Level: Active High

Latency delay:

Data Setup

Hierarchy Display:

DE1_SOC

de1_soc:de1_soc

plasma_soc_top:plasma_...

Data Log:

auto_signaltap_0

auto_signaltap_0

50% 00:05:48