

Threaded Rods & Stud Bolts

Full Thread Rod (DIN 975), Stud Bolt (DIN 976), Anchor Rod

TERNS EXIM

Registered Merchant Exporter — Coimbatore, India

Technical Specifications

Types	Full Thread Rod (DIN 975), Stud Bolt (DIN 976), Double-End Stud, Tap-End Stud, Anchor Rod
Property Classes	4.8, 8.8 (metric); Grade B7 / B8 (ASTM A193)
Diameter	M6 – M100
Length	1000 mm – 6000 mm (standard 1 m & 2 m cuts; custom lengths on order)
Standards	DIN 975, DIN 976, ASTM A193, ASTM A307, ASTM A320, IS 1367
Materials	Carbon Steel (MS), Alloy Steel (Cr-Mo), SS 304 (A2), SS 316 (A4)
Finishes	Plain, Zinc Electroplated, Hot-Dip Galvanized (HDG)
MOQ	10,000 pieces or 700 kg
Lead Time	Quote on enquiry
Certification	Mill Test Certificate (EN 10204 Type 3.1) · Optional SGS / BV / TÜV inspection
HS Code	7318.15

Grades / Types at a Glance

Property Class	Tensile Strength (MPa)	Yield Strength (MPa)	Typical Use
4.8	400	320	General-purpose, low-stress fixing
8.8	800	640	Structural and high-load applications
Gr. B7	860+	725+	High-temp pressure bolting (ASTM A193)

Key Applications

- ✓ Anchor bolt extensions in civil foundations
- ✓ Suspended ceiling and HVAC duct hanging systems
- ✓ Pipe support hangers and strut channel assemblies
- ✓ High-pressure flange bolting in oil & gas (Grade B7)
- ✓ Structural tie rods in bridges and tension structures
- ✓ Machinery assembly and general-purpose threaded work

Export & Quality Information

Export Terms	FOB / CIF from Chennai · Tuticorin · Mumbai · Mundra
Currencies	USD · EUR · AED
MOQ	10,000 pieces or 700 kg
HS Code	7318.15
Quality	Mill Test Certificate (EN 10204 Type 3.1) · Optional SGS / BV / TÜV inspection

