

Anchor Bolts

TERNS EXIM

J-Bolt, L-Bolt, U-Bolt, Eye Bolt, Wedge Anchor

Registered Merchant Exporter - Coimbatore, India

Technical Specifications

Types	J-Bolt, L-Bolt, U-Bolt, Eye Bolt, Rag Bolt, Lewis Bolt, Wedge Anchor
Grades	Grade 36, 55, 105 (ASTM F1554); Property Class 4.6, 8.8 (IS)
Size Range	M6 - M100 diameter (M12-M48 ex-stock; larger on order)
Length	Up to 3000 mm; custom lengths from engineer drawings
Standards	ASTM F1554, IS 1367, IS 5624, DIN 529, BS 7419
Materials	Carbon Steel, SS 304 (A2), SS 316 (A4), Alloy Steel
Finishes	Zinc Electroplated, Hot-Dip Galvanized (HDG)
MOQ	10,000 pieces or 700 kg
Lead Time	Quote on enquiry
Certification	Mill Test Certificate (EN 10204 Type 3.1) - Optional SGS / BV / TUV inspection
HS Code	7318.15

Grades / Types at a Glance

Type	Shape	Typical Application
J-Bolt	Curved hook (J-shape)	Cast-in-place; machinery bases, column anchoring
L-Bolt	Right-angle 90 deg	Cast-in-place; horizontal pull-out resistance
U-Bolt	U-shaped clamp	Clamping pipes / rods to structural members
Wedge Anchor	Expansion anchor	Post-installed; existing masonry / concrete
Eye Bolt	Loop head	Lifting, rigging, and lifting lug applications

Key Applications

- Anchoring structural steel columns to concrete piers
- Pump, compressor, and heavy equipment base plates
- Transmission towers & electricity pylons
- Solar panel mounting structures & wind masts
- Precast concrete & retaining wall construction
- Overhead crane runway beams & bridge structures

Export & Quality Information

Export Terms	FOB / CIF - Chennai, Tuticorin, Mumbai, Mundra
Currencies	USD / EUR / AED
MOQ	10,000 pieces or 700 kg
HS Code	7318.15
Quality / Cert	Mill Test Certificate (EN 10204 Type 3.1) - Optional SGS / BV / TUV inspection

TERNS EXIM | sales@ternsexim.com | +91 63690 97465 | www.ternsexim.com | Fastener & Merchant Exporter