

Aurora Sensor Platform - Product Specification v2.3

1. Overview

Aurora is a wireless environmental sensor platform for commercial buildings. Each Aurora Node measures temperature, relative humidity, CO2 concentration and ambient light, and reports readings to the Aurora Gateway every 60 seconds.

2. Hardware

Aurora Node dimensions are 80 x 80 x 25 mm and it weighs 95 grams. It is powered by two AA lithium batteries with an expected battery life of 5 years at the default reporting interval. The operating temperature range is -10 to +50 degrees Celsius. The enclosure is rated IP54.

3. Connectivity

Nodes communicate with the gateway over Bluetooth Low Energy mesh. The maximum range between two nodes is 30 metres indoors. One Aurora Gateway supports up to 250 nodes. The gateway connects to the Aurora Cloud over Ethernet or LTE-M.

4. Accuracy

Temperature accuracy is +/-0.2 degrees Celsius. Humidity accuracy is +/-2 percent RH. The CO2 sensor is an NDIR sensor with an accuracy of +/-30 ppm plus 3 percent of the reading, and a measurement range of 400 to 5000 ppm.

5. Cloud and API

Readings are retained in Aurora Cloud for 25 months. The REST API is rate-limited to 600 requests per minute per organisation. Webhooks can be configured for threshold alerts, for example when CO2 exceeds 1000 ppm.

6. Pricing

The Aurora Node costs 149 euros and the Aurora Gateway costs 490 euros. The Aurora Cloud subscription costs 2 euros per node per month, billed annually.

7. Warranty

All hardware comes with a 3-year limited warranty. Batteries are not covered by the warranty.