Objects

TerraLID ID

ID and name: O0 terralid_object_id
Provided by: TerraLID system
Obligation: mandatory
Occurrences: 1
Definition: The ID of the object in the TerraLID database.
Allowed values and other constraints: t.b.d.
Example: t.b.d.

1. Collectors

ID and name: O1 object_collectors
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: Details of the creator(s), excavator(s), or other person(s) intellectually responsible for the sample collection.

with the nine subproperties:

1.1 Role

ID and name: B1.1 person_role
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n
Definition: The role in which the person is related to the linked information.
Allowed values and other constraints: controlled vocabulary
Example: Author

1.2 First names

ID and name: B1.2 person_name_first
Provided by: data provider, API (ORCID ID)
Obligation: recommended
Occurrences: 0–1
Definition: The first and middle name(s) of the person.
Allowed values and other constraints: free text
Example: Jane

1.3 Last Name

ID and name: B1.3 person_name_last
Provided by: data provider, API (ORCID ID)
Obligation: mandatory
Occurrences: 1
Definition: The last name of the person.
Allowed values and other constraints: free text
Example: Doe

1.4 Persistent Identifier

ID and name: B1.4 person_pid
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: Persistent identifier(s) assigned to the person.

with the two subproperties:

1.4.1 VALUE OF PERSISTENT IDENTIFIER

ID and name: B1.4.1 person_pid_value
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: A persistent identifier assigned to the analysed material.
Allowed values and other constraints: Valid persistent identifier according to B1.4.2 Type of persistent identifier
Example: 0000–0001–2345–678X

1.4.2 TYPE OF PERSISTENT IDENTIFIER

ID and name: B1.4.2 person_pid_type
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: The type of the persistent identifier.
Allowed values and other constraints: controlled vocabulary

1.5 Affiliation name

ID and name: B1.5 person_affiliation_name
Provided by: data provider, API (ORCID ID, ROR ID)
Obligation: mandatory
Occurrences: 1–n
Definition: The name of the person's affiliation.
Allowed values and other constraints: free text
Example: Institute of Time Travels

1.6 ROR ID

ID and name: B1.6 person_affiliation_ror
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: The ROR of the person's affiliation.
Allowed values and other constraints: is valid ROR ID
Example: 09af7gtg53

1.7 Address

ID and name: B1.7 person_affiliation_address
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: The address of the person's affiliation.
Allowed values and other constraints: free text
Example: Teleporter Avenue 123, Ankh–Morpok, United States of Humanities

1.8 Mail address

ID and name: B1.8 person_mail
Provided by: data provider, API (ORCID ID)
Obligation: recommended
Occurrences: 0–n
Definition: The mail address of the person.
Allowed values and other constraints: is valid mail address
Example: jane.doe@timetravels.int

1.9 Website

ID and name: B1.9 person_url
Provided by: data provider, API (ORCID ID)
Obligation: optional
Occurrences: 0–1
Definition: The URL of a person.
Allowed values and other constraints: is valid URL
Example: https://www.timetravels.int/members/jane–doe

2. Contributors

ID and name: O2 object_contributors
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: Individuals or organizations who have contributed to the resource.

with the nine subproperties:

2.1 Role

ID and name: B1.1 person_role
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n
Definition: The role in which the person is related to the linked information.
Allowed values and other constraints: controlled vocabulary
Example: Author

2.2 First names

ID and name: B1.2 person_name_first
Provided by: data provider, API (ORCID ID)
Obligation: recommended
Occurrences: 0–1
Definition: The first and middle name(s) of the person.
Allowed values and other constraints: free text
Example: Jane

2.3 Last Name

ID and name: B1.3 person_name_last
Provided by: data provider, API (ORCID ID)
Obligation: mandatory
Occurrences: 1
Definition: The last name of the person.
Allowed values and other constraints: free text
Example: Doe

2.4 Persistent Identifier

ID and name: B1.4 person_pid
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: Persistent identifier(s) assigned to the person.

with the two subproperties:

2.4.1 VALUE OF PERSISTENT IDENTIFIER

ID and name: B1.4.1 person_pid_value
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: A persistent identifier assigned to the analysed material.
Allowed values and other constraints: Valid persistent identifier according to B1.4.2 Type of persistent identifier
Example: 0000–0001–2345–678X

2.4.2 TYPE OF PERSISTENT IDENTIFIER

ID and name: B1.4.2 person_pid_type
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: The type of the persistent identifier.
Allowed values and other constraints: controlled vocabulary

2.5 Affiliation name

ID and name: B1.5 person_affiliation_name
Provided by: data provider, API (ORCID ID, ROR ID)
Obligation: mandatory
Occurrences: 1–n
Definition: The name of the person's affiliation.
Allowed values and other constraints: free text
Example: Institute of Time Travels

2.6 ROR ID

ID and name: B1.6 person_affiliation_ror
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: The ROR of the person's affiliation.
Allowed values and other constraints: is valid ROR ID
Example: 09af7gtg53

2.7 Address

ID and name: B1.7 person_affiliation_address
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: The address of the person's affiliation.
Allowed values and other constraints: free text
Example: Teleporter Avenue 123, Ankh–Morpok, United States of Humanities

2.8 Mail address

ID and name: B1.8 person_mail
Provided by: data provider, API (ORCID ID)
Obligation: recommended
Occurrences: 0–n
Definition: The mail address of the person.
Allowed values and other constraints: is valid mail address
Example: jane.doe@timetravels.int

2.9 Website

ID and name: B1.9 person_url
Provided by: data provider, API (ORCID ID)
Obligation: optional
Occurrences: 0–1
Definition: The URL of a person.
Allowed values and other constraints: is valid URL
Example: https://www.timetravels.int/members/jane–doe

3. Object title

ID and name: O3 object_title
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: Name of the object to make it distinguishable.
Allowed values and other constraints: free text
Example: Coin 231 of hoard from the northwest palace in Atlantis

4. Object description

ID and name: O4 object_description
Provided by: data provider
Obligation: recommended
Occurrences: 0–1
Definition: (Detailed) description of the object. Should include information about the object and its collection not captured in other properties. For example, the primary reason for object collection or selection in terms of analytics.
Allowed values and other constraints: free text
Example: Galena-rich sediment from the washing pit.

5. Object identifiers

ID and name: O5 object_identifiers
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n
Definition: Identifiers associated with the object. At least one identifier must be provided.

with the three subproperties:

5.1 Persistent Identifier

ID and name: O5.1 object_pid
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: Persistent identifier(s) assigned to the object.

with the two subproperties:

5.1.1 Value of persistent identifier

ID and name: O5.1.1 object_pid_value
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: The persistent identifier assigned to the object.
Allowed values and other constraints: Valid persistent identifier according to `O5.1.2 Type of persistent identifier`
Example: 10.60510/ABCD123EF4567

5.1.2 Type of persistent identifier

ID and name: O5.1.2 object_pid_type
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: The type of a persistent identifier that was assigned to the object.
Allowed values and other constraints: controlled vocabulary

5.2 Value of other identifier

ID and name: O5.2 object_id_value
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: Identifier by which the object is identified in a catalogue, database or comparable records (e.g., of the excavation catalogue or records of a laboratory).
Allowed values and other constraints: free text
Example: AG-01

5.3 Type of other identifier

ID and name: O5.3 object_id_type
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n
Definition: The name of the catalogue, database or comparable records to which the ID refers. Mandatory if `O5.2 Value of other identifier` is provided.

Allowed values and other constraints: free text
Example: catalogue in the final excavation report

6. Date of collection

ID and name: O6 object_collection_date
Provided by: data provider
Obligation: recommended
Occurrences: 0–1
Definition: Collection date of the object.
Allowed values and other constraints: date formatted as YYYY-MM-DD
Example: 1990-06-08

7. Collection method

ID and name: O7 object_collection_method
Provided by: data provider
Obligation: recommended
Occurrences: 0–1
Definition: How the object was collected or obtained.
Allowed values and other constraints: controlled vocabulary

8. Object housing

ID and name: O8 object_housing
Provided by: data provider
Obligation: recommended
Occurrences: 1–n
Definition: The material in which the object is currently stored or was stored at any time after its collection. At least the current state should be recorded.

with the two subproperties:

8.1 Housing material

ID and name: O8.1 object_housing_material
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: The material the object was or is stored in at the stage in its life cycle recorded in `O8.2 Stage of Storage`.
Allowed values and other constraints: controlled vocabulary

8.2 Stage of Storage

ID and name: O8.2 object_housing_stage
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: The stage of the object's life cycle when the object was stored in the material recorded in `O8.1 Housing material`.
Allowed values and other constraints: controlled vocabulary

9. Object photo

ID and name: O9 object_photo
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: Photograph of the object, preferably at the time of collection. For guidance on photographs, see e.g. L. J. Fisher (2009), Photography for Archaeologists Part II: Artefact recording (BAJR Practical Guide Series 26).
Allowed values and other constraints: Image file (File size must be smaller than 2 MB)

10. Object weight

ID and name: O10 object_weight
Provided by: data provider
Obligation: optional
Occurrences: 0–1
Definition: The weight of the object at the point of collection, before analysis.

with the three subproperties:

10.1 Value

ID and name: O10.1 object_weight_value
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: The value of the weight.
Allowed values and other constraints: decimal number
Example: 120.3

10.2 Unit

ID and name: O10.2 object_weight_unit
Provided by: data provider
Obligation: mandatory
Occurrences: 1

Definition: SI unit in which the weight is given.
Allowed values and other constraints: controlled vocabulary

10.3 Weight condition

ID and name: O10.3 object_weight_condition
Provided by: data provider
Obligation: recommended
Occurrences: 0–1
Definition: Additional information about state of object at the time the weight was measured to give a better idea how representative the measured weight is.
Allowed values and other constraints: free text
Example: dry sandy material adhering to object

11. Object dimensions

ID and name: O11 object_dimension
Provided by: data provider
Obligation: optional
Occurrences: 0–1
Definition: The dimensions of the object.

with the four subproperties:

11.1 Height

ID and name: O11.1 object_dimension_height
Provided by: data provider
Obligation: recommended
Occurrences: 0–1
Definition: The height of the object.
Allowed values and other constraints: decimal number
Example: 3.52

11.2 Length

ID and name: O11.2 object_dimension_length
Provided by: data provider
Obligation: recommended
Occurrences: 0–1
Definition: The length of the object.
Allowed values and other constraints: decimal number
Example: 10.30

11.3 Width

ID and name: O11.3 object_dimension_width
Provided by: data provider
Obligation: recommended
Occurrences: 0–1
Definition: The width of the object.
Allowed values and other constraints: decimal number
Example: 2.42

11.4 Unit of Dimensions

ID and name: O11.4 object_dimension_unit
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: Unit in which the dimension(s) of the object are provided.
Allowed values and other constraints: controlled vocabulary

12. Material

ID and name: O12 object_material
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: The material the object is made of.
Allowed values and other constraints: controlled vocabulary. This property determines which material-specific metadata will be additionally recorded.

13. Bulk Pb concentration

ID and name: O13 object_bulk_chemistry_pb
Provided by: data provider
Obligation: recommended
Occurrences: 0–1
Definition: The bulk lead concentration of the object.

with the eight subproperties:

13.1 Analytical method

ID and name: B4.1 chemistry_method
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: The method used to determine the chemical composition.
Allowed values and other constraints: controlled vocabulary

13.2 Analysed compound

ID and name: B4.2 chemistry_compound
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n
Definition: The analysed chemical compound (chemical element, oxide, isotope).
Allowed values and other constraints: controlled vocabulary, the actual measured compound must be reported if available (e.g., the isotope for mass spectrometric values rather than the element).

13.3 Value

ID and name: B4.3 chemistry_value
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n
Definition: The concentration of the analysed chemical compound.

with the two subproperties:

13.3.1 ABSOLUTE VALUE

ID and name: B4.3.1 chemistry_value_absolute
Provided by: data provider
Obligation: recommended
Occurrences: 1–n
Definition: The concentration of the analysed chemical compound.
Allowed values and other constraints: decimal number
Example: 15.3

13.3.2 QUALITATIVE VALUE

ID and name: B4.3.2 chemistry_value_relative
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: Value of qualitative results and other non-numeric values such as the reporting of detection or quantification limits rather than values.
Allowed values and other constraints: free text
Example: +++, tr, <0.4, bdl = 0.5 wt%

13.4 Unit

ID and name: B4.4 chemistry_unit
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n
Definition: The unit in which the concentration of the analysed chemical compound is given.
Allowed values and other constraints: controlled vocabulary

13.5 Uncertainty type

ID and name: B4.5 chemistry_uncertainty_type
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: The type of analytical uncertainty.
Allowed values and other constraints: controlled vocabulary

13.6 Confidence level

ID and name: B4.6 chemistry_uncertainty_sigma
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: Multiple of standard deviation (sigma) of the reported absolute analytical uncertainty.
Allowed values and other constraints: 1, 2, 3
Example: 2

13.7 Uncertainty value

ID and name: B4.7 chemistry_uncertainty_value
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: Value of the absolute analytical uncertainty.
Allowed values and other constraints: decimal number
Example: 0.3

14. Dating of object

ID and name: O14 object_date
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n
Definition: The date of the object.

with the eight subproperties:

14.1 Persistent identifier

ID and name: B3.1 date_pid
Provided by: data provider
Obligation: recommended
Occurrences: 0–n

with the two subproperties:

14.1.1 VALUE

ID and name: B3.1.1 date_pid_value
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: The value of the persistent identifier.
Allowed values and other constraints: The period's persistent identifier in one or more of the data infrastructures listed in `B3.1.2 Type`.
Example: 99152/p0qhb66vvth

14.1.2 TYPE

ID and name: B3.1.2 date_pid_type
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: The name of the data infrastructure.
Allowed values and other constraints: controlled vocabulary

14.2 Date type

ID and name: B3.2 date_type
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n
Definition: Is this an archaeological or geological age? This field controls the behavior of some dating-related metadata fields such as the unit of the absolute age (archaeological dates in calendar years, with BCE dates as negative values; geological dates in million years).
Allowed values and other constraints: geological, archaeological
Example: archaeological

14.3 Absolute Date

ID and name: B3.3 date_absolute
Provided by: data provider, API
Obligation: recommended
Occurrences: 0–1
Definition: The absolute date of a point in time or period in years before or after common era. Values in BCE are reported as negative values. If the absolute date is given with an uncertainty such as 450 +/- 50 BC, start and end date mark the lower and upper limit of the date range, i.e. -500 and -400.

with the four subproperties:

14.3.1 START

ID and name: B3.3.1 date_absolute_start
Provided by: data provider, API
Obligation: mandatory

Occurrences: 1
Definition: The oldest possible date of the range. A negative value indicates a BCE date.
Allowed values and other constraints: integer
Example: -15

14.3.2 END

ID and name: B3.3.2 date_absolute_end
Provided by: data provider, API
Obligation: recommended
Occurrences: 0–1
Definition: The youngest possible date of the range. A negative value indicates a BCE date.
Allowed values and other constraints: integer
Example: 15

14.3.3 DATING METHOD

ID and name: B3.3.3 date_absolute_method
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n
Definition: The method used to determine the absolute date.
Allowed values and other constraints: controlled vocabulary

14.3.4 UNIT OF DATE

ID and name: B3.3.4 date_absolute_unit
Provided by: TerraLID system
Obligation: mandatory
Occurrences: 1
Definition: The unit of the date: "Ma" if `B3.2 Date type` = "geological"; "a" (calendar years) if `B3.2 Date type` = "archaeological".
Allowed values and other constraints: a, Ma
Example: a

14.4 Relative Date

ID and name: B3.4 date_relative
Provided by: data provider, API
Obligation: recommended
Occurrences: 0–1
Definition: The relative date of a point in time or period.

with the two subproperties:

14.4.1 CHRONOLOGICAL UNIT

ID and name: B3.4.1 date_relative_period
Provided by: data provider, API
Obligation: mandatory

Occurrences: 1
Definition: The relative date expressed as a chronological unit.
Allowed values and other constraints: controlled vocabulary

14.4.2 DATING METHOD

ID and name: B3.4.2 date_relative_method
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n
Definition: The method used to determine the relative date.
Allowed values and other constraints: controlled vocabulary

14.5 Cultural unit

ID and name: B3.5 date_archaeo_cultural
Provided by: data provider
Obligation: optional
Occurrences: 0–n
Definition: Relevant cultural and user created labels for the relative date of the item.
Allowed values and other constraints: free text, only available if `B3.2 Date type` = "archaeological".
Example: Roman

14.6 Orogenesis

ID and name: B3.6 date_geol_orogensis
Provided by: data provider
Obligation: recommended
Occurrences: 0–1
Definition: The relative date expressed as an orogenic event.
Allowed values and other constraints: controlled vocabulary, only available if `B3.2 Date type` = "geological".

14.7 Definition of chronological unit

ID and name: B3.7 date_relative_reference
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: The reference defining the relative date or period.

with the five subproperties:

14.7.1 Persistent Identifier

ID and name: B5.1 relation_pid
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: The persistent identifier or TerraLID ID associated with a resource or related research output. Mandatory if referring to another entity in the TerraLID database; in this case, the TerraLID ID must be used and `B5.1.2 Type` is

"TerraLID". Within a submission, the identifiers of the submitted records may be used; the TerraLID system replaces them with the assigned TerraLID IDs.

with the two subproperties:

14.7.1.1 Value

ID and name: B5.1.1 relation_pid_value
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: Value of the persistent identifier or TerraLID ID. **Allowed values and other constraints:** valid persistent identifier according to the options listed in `B5.1.2 Type`, or a TerraLID ID if `B5.1.2 Type` = "TerraLID". **Example:** 10.60510/ICDP5054ESYI201

14.7.1.2 Type

ID and name: B5.1.2 relation_pid_type
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: The type of the identifier.
Allowed values and other constraints: controlled vocabulary (identifier). Use "TerraLID" for entities in the TerraLID database.

14.7.2 Full reference

ID and name: B5.2 relation_text
Provided by: data provider, API (DOI)
Obligation: recommended
Occurrences: 0–1
Definition: The full reference of a publication.
Allowed values and other constraints: free text
Example: Palinkaš, L. A., 1985, Lead isotope patterns in galenas from some selected ore deposits in Croatia and NW Bosnia, Geološki Vjesnik, 38, 175–89.

14.7.3 Kind of relation

ID and name: B5.3 relation_kind
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n
Definition: Relationship between the item and the related resource, research output, or TerraLID entity (e.g., IsPartOf for a sample taken from an object). **Allowed values and other constraints:** controlled vocabulary

14.7.4 Type of resource

ID and name: B5.4 relation_resource
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n

Definition: Type of resource or research output. Mandatory unless `B5.1.2 Type` = "TerraLID", as the type of a TerraLID entity follows from its TerraLID ID. **Allowed values and other constraints:** controlled vocabulary

14.7.5 Additional details

ID and name: B5.5 relation_detail
Provided by: data provider
Obligation: optional
Occurrences: 0–n
Definition: Additional information about the relation, e.g., if the related work addresses a specific aspect of the item (e.g., the geological setting).
Allowed values and other constraints: free text
Example: Information about the dating of the site.

15. Keywords

ID and name: O15 object_keywords
Provided by: data provider
Obligation: optional
Occurrences: 0–n
Definition: Keywords to describe aspects of the sample not covered by other metadata.
Allowed values and other constraints: free text
Example: t.b.d.

16. Object contamination

ID and name: O16 object_contamination
Provided by: data provider
Obligation: recommended
Occurrences: 0–1
Definition: Information about potential contamination or treatment of the object that might impact the relevance of retrieved information (e.g. by post-depositional processes or conservation treatment).
Allowed values and other constraints: free text
Example: Galvanic restoration of the surface in 1967

17. Status of object

ID and name: O17 object_status
Provided by: data provider
Obligation: recommended
Occurrences: 0–1
Definition: Information about the current status of the object and how to access it.

with the two subproperties:

17.1 Institution

ID and name: B2.1 status_institution
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n
Definition: The institution at which the material is located.

with the five subproperties:

17.1.1 NAME

ID and name: B2.1.1 status_institution_name
Provided by: data provider, API (ROR ID)
Obligation: mandatory
Occurrences: 1
Definition: Name of the institution.
Allowed values and other constraints: free text
Example: Institute of Time Travels

17.1.2 ROR

ID and name: B2.1.2 status_institution_ror
Provided by: data provider
Obligation: recommended
Occurrences: 0–1
Definition: ROR of the institution.
Allowed values and other constraints: is valid ROR ID
Example: 09af7gtg53

17.1.3 ADDRESS

ID and name: B2.1.3 status_institution_address
Provided by: data provider
Obligation: recommended
Occurrences: 0–1
Definition: Address of the institution.
Allowed values and other constraints: free text
Example: Teleporter Avenue 123, Ankh–Morpok, United States of Humanities

17.1.4 STORAGE LOCATION

ID and name: B2.1.4 status_institution_location
Provided by: data provider
Obligation: recommended
Occurrences: 0–1
Definition: Location of the item within the institution.
Allowed values and other constraints: free text
Example: Archive 9, shelf 3, box 1

17.1.5 CONTACT

ID and name: B2.1.5 status_institution_contact
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n
Definition: Contact information for inquiries about the material. This may include, for example, a mail address or phone number of the respective department within the institution or the identification of a specific contact person as well as constraints on the availability of the point of contact such as opening hours.
Allowed values and other constraints: free text
Example: t.b.d.

17.2 Accessibility

ID and name: B2.2 status_accessibility
Provided by: data provider
Obligation: recommended
Occurrences: 0–1
Definition: Is the material accessible to other researchers and do restrictions apply?
Allowed values and other constraints: controlled vocabulary

18. Authenticity of object

ID and name: O18 object_authenticity
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: The contemporary legal status of an object: whether it is a genuine archaeological object, contemporary imitation, or a modern imitation. For example, authentic numismatic objects were created by an authority that had the rights to do so, while contemporary imitations were not.

with the two subproperties:

18.1 Authenticity type

ID and name: O18.1 object_authenticity_type
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: The object's type of authenticity.
Allowed values and other constraints: controlled vocabulary

18.2 Reasoning

ID and name: O18.2 object_authenticity_description
Provided by: data provider
Obligation: recommended

Occurrences: 0–1
Definition: Reasoning for the given classification.
Allowed values and other constraints: free text
Example: The zinc content in the brass is higher than can be achieved with Roman technology.

19. Relations

ID and name: O19 object_relation
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n
Definition: Information about related entities, including samples belonging to the object, and other research output such as publications providing relevant information about the object. This includes any literature from which information about the object was extracted.

with the five subproperties:

19.1 Persistent Identifier

ID and name: B5.1 relation_pid
Provided by: data provider
Obligation: recommended
Occurrences: 0–n
Definition: The persistent identifier or TerraLID ID associated with a resource or related research output. Mandatory if referring to another entity in the TerraLID database; in this case, the TerraLID ID must be used and `B5.1.2 Type` is "TerraLID". Within a submission, the identifiers of the submitted records may be used; the TerraLID system replaces them with the assigned TerraLID IDs.

with the two subproperties:

19.1.1 VALUE

ID and name: B5.1.1 relation_pid_value
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: Value of the persistent identifier or TerraLID ID. **Allowed values and other constraints:** valid persistent identifier according to the options listed in `B5.1.2 Type`, or a TerraLID ID if `B5.1.2 Type` = "TerraLID". **Example:** 10.60510/ICDP5054ESYI201

19.1.2 TYPE

ID and name: B5.1.2 relation_pid_type
Provided by: data provider
Obligation: mandatory
Occurrences: 1
Definition: The type of the identifier.

Allowed values and other constraints: controlled vocabulary (identifier). Use "TerraLID" for entities in the TerraLID database.

19.2 Full reference

ID and name: B5.2 relation_text
Provided by: data provider, API (DOI)
Obligation: recommended
Occurrences: 0–1
Definition: The full reference of a publication.
Allowed values and other constraints: free text
Example: Palinkaš, L. A., 1985, Lead isotope patterns in galenas from some selected ore deposits in Croatia and NW Bosnia, Geološki Vjesnik, 38, 175–89.

19.3 Kind of relation

ID and name: B5.3 relation_kind
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n
Definition: Relationship between the item and the related resource, research output, or TerraLID entity (e.g., IsPartOf for a sample taken from an object). **Allowed values and other constraints:** controlled vocabulary

19.4 Type of resource

ID and name: B5.4 relation_resource
Provided by: data provider
Obligation: mandatory
Occurrences: 1–n
Definition: Type of resource or research output. Mandatory unless `B5.1.2 Type` = "TerraLID", as the type of a TerraLID entity follows from its TerraLID ID. **Allowed values and other constraints:** controlled vocabulary

19.5 Additional details

ID and name: B5.5 relation_detail
Provided by: data provider
Obligation: optional
Occurrences: 0–n
Definition: Additional information about the relation, e.g., if the related work addresses a specific aspect of the item (e.g., the geological setting).
Allowed values and other constraints: free text
Example: Information about the dating of the site.