

Verifiable Verbatim Grounding at Six-Orders-of-Magnitude Lower Latency

Mario Gutiérrez
Celiums Solutions LLC
Medellín, Colombia
terrizoaguimor@gmail.com

2026-05-28

Abstract

We introduce HYPHAE, a cognitive substrate that composes responses by verbatim quotation of retrieved memory fragments stitched together with a curated connective lexicon, with no large language model (LLM) in the cognition path. The architectural commitment underlying the system is dual: every quoted body is preserved byte-identically against a hash-chained substrate journal, making each emitted response *independently verifiable* against named source material; and the realizer’s bounded output runs in microseconds on a single CPU core. We compare HYPHAE against 18 LLM-based configurations (vanilla retrieval-augmented generation, HyDE plus cross-encoder reranking, and oracle context) spanning five generator models — from Anthropic, OpenAI, DeepSeek, Meta, and an in-house production router — across two corpora: the project’s own 34-query composition corpus, and 150 random samples from TriviaQA. We report two complementary metrics: NLI-grounded unsupported-claim rate (does the response stay inside the retrieved context?) and gold-answer match (does the response contain the benchmark’s reference answer?). On TriviaQA, HYPHAE reaches 1.000 gold-answer match (by construction of the corpus filter; see Section 5.1); in oracle mode, where the same gold-bearing seed body is supplied to every system, frontier LLMs reach 0.840–0.960 gold-answer. The architectural finding is that verbatim quotation removes a paraphrase-away failure mode that costs oracle-LLMs four to sixteen percentage points of correctness. HYPHAE’s NLI-grounded unsupported-claim rate is a metric-degenerate 0.000 on this corpus; the twelve LLM-based configurations that reach gold-answer ≥ 0.84 score 0.400–0.737 on the same metric. We trace the gap mechanically to the metric’s filter interacting with the substrate’s compositional template, and report both filtered and unfiltered rates throughout. Where the architectural claim is unambiguous is the cost dimension: on TriviaQA, HYPHAE’s realizer runs in 0.002 ms mean per query, against 1,858 ms for a *locally-hosted* Llama-8B-Instruct quantised baseline (no network) and 2,424 ms for GPT-4.1 with strong retrieval via a hosted API — a ratio of roughly 10^6 in both cases, confirming the network round-trip is not the dominant cost. On the own corpus, whose multi-fragment queries make HYPHAE’s composition cost $12\times$ higher (0.024 ms mean), the ratio is $\sim 10^5$. The advantage is therefore five-to-six orders of magnitude depending on working-set size, and the HYPHAE side carries no model-serving infrastructure cost at all. We do not claim the substrate universally replaces LLM-based generation. We claim that for tasks in which the unit of grounding is a discrete retrieved fragment quoted verbatim and the deployment requires audit-bound verifiability, the architectural commitment is competitive with frontier LLM correctness and dominates them on latency, memory footprint, and per-query cost by several orders of magnitude. Code, corpora, result envelopes, and hardware traces are available at <https://github.com/terrizoaguimor/hyphae-v2>.

1 Introduction

Large language models (LLMs) augmented with retrieval have become the default architecture for grounded factual question answering, conversational memory, and document summarisation. The dominant pattern — chunk a corpus, embed each chunk, retrieve top- k at query time, and condition an LLM on the retrieved passages — is deployed at substantial cost: a 70-billion-parameter generator loaded into a high-memory GPU instance, billing per token, with per-query latencies in the multiple-second range. Recent extensions of this pattern (HyDE [Gao et al., 2022], RAG-Fusion [Rackauckas, 2024], cross-encoder reranking [Nogueira and Cho, 2019, Reimers and Gurevych, 2019], GraphRAG [Edge et al., 2024]) improve retrieval quality without changing the fundamental architectural decision: the LLM remains the composer.

This paper investigates the alternative. We present HYPHAE, a cognitive substrate that produces grounded responses without invoking any LLM at inference time. HYPHAE achieves grounding not through training but through an architectural commitment: **retrieved memory fragments are quoted verbatim, and the connective tissue between quotations is drawn from a curated lexicon, never generated by a statistical model.** The substrate runs on a single CPU core, holds approximately 50 MB of resident memory, and produces composition outputs in microseconds.

We compare HYPHAE against 18 LLM-based system configurations spanning vanilla retrieval-augmented generation, HyDE plus cross-encoder reranking, and oracle context (the LLM receives the gold supporting passage directly). The five generator models include open-source SOTA (Llama-3.3-70B-Instruct, DeepSeek-V4-Pro), frontier closed-source models from Anthropic (Claude-4.6-Sonnet) and OpenAI (GPT-4.1), and a production LLM-routing system (Atlas, our own previously-shipped product). All LLMs are accessed through a uniform OpenAI-compatible endpoint at zero infrastructure provisioning cost; HYPHAE runs locally on commodity hardware (Apple Silicon laptop; Intel Xeon Platinum 8168 server).

1.1 Contributions

1. **Hash-chained verbatim quotation as an architectural commitment.** Every emitted body in a HYPHAE response is byte-identical to a fragment stored in a SHA-256 hash-chained substrate journal. An external auditor can independently confirm that the response was assembled from named fragments without re-running the system. Hard Commitment 12 (Section 3.4) makes the property load-bearing for the architecture; the empirical sections quantify what that commitment is worth on standard tasks.
2. **A two-axis correctness-and-grounding comparison against 18 LLM-based configurations.** We re-evaluate every system on both an NLI-grounded unsupported-claim rate (`unsup_f`, does the response stay inside the retrieved context?) and a gold-answer match rate (does the response contain the benchmark’s reference answer?). On TriviaQA, HYPHAE reaches 1.000 gold-answer match and a metric-degenerate 0.000 `unsup_f`, while the twelve LLM-based configurations with gold-answer match ≥ 0.84 score 0.400–0.737 `unsup_f`. The honest reading: frontier LLMs are nearly as correct on this benchmark and less efficiently grounded as measured by the chosen NLI filter.
3. **Per-query latency advantage of $\sim 10^5$ to $\sim 10^6$ depending on working-set size.** HYPHAE’s realizer runs in 0.002 ms mean per query on single-seed TriviaQA queries and 0.024 ms on the multi-fragment own corpus; the LLM baselines run in 1,858–6,083 ms regardless of corpus, whether hosted locally or via API. The ratio is therefore $\sim 10^6$ for single-seed retrieval

and $\sim 10^5$ for multi-fragment composition; the network round-trip accounts for only $\sim 30\%$ (Section 5.4). Memory footprint differs by approximately five orders of magnitude (50 MB vs multiple GB).

4. **Two corpora, with honest acknowledgement of their limits.** A 34-query project corpus designed to exercise multi-fragment composition, and a 150-query random sample from TriviaQA. The TriviaQA picture is hardened by the larger N and independent dataset; the own-corpus picture surfaces the multi-fragment regime that single-hop benchmarks do not. We discuss the partial circularity of measuring on a project-built corpus (Section 7.1).
5. **Component-level ablations.** We disable four HYPHAE components in turn (cascade-shape composition, ethics gate, lexicon scale, boundary smoothing) and measure the metric deltas. Only lexicon scale produces a measurable effect; the other three produce null deltas at this corpus size. We report null results honestly and constrain claims accordingly.
6. **Hardware matrix.** We re-run the matrix on a server-class CPU-only Linux instance. Quality metrics are hardware-invariant within ± 0.03 . The Hyphae:Llama-8B latency ratio holds at $\sim 6.5 \times 10^5$ when GPU acceleration is removed, confirming the architectural advantage generalises beyond the laptop’s Metal backend.

1.2 Roadmap

Section 2 positions HYPHAE against the relevant literature on retrieval-augmented generation, structured memory systems, and NLI-based grounding metrics. Section 3 describes the architecture, with emphasis on the verbatim-quotation commitment that underlies the empirical results. Section 4 documents the experimental protocol — the two corpora, the five generator models, the three retrieval modes, the metric set, and the hardware. Section 5 presents the headline rankings on both corpora. Section 6 disaggregates HYPHAE’s contribution by component. Section 7 discusses limitations (metric, corpus, statistical power, reader preference) and threats to validity. Section 8 concludes. The appendix contains full per-system result tables and reproduction instructions.

1.3 Reproducibility

The complete pipeline (HYPHAE source, comparator code, corpora, result envelopes, plotting code, and this paper’s L^AT_EX source) is committed at <https://github.com/terrizoaguimor/hyphae-v2>. Each result JSON envelope carries the model identifier, hardware metadata, decoding hyperparameters, and per-query trace. The TriviaQA subset is regeneratable from the original dataset under random seed 42 via the project’s `corpus_external.py` CLI. Total cost of reproducing the full experimental matrix at the LLM API layer is approximately USD 4 in inference tokens. The HYPHAE side has no cloud cost.

2 Related Work

2.1 Retrieval-Augmented Generation

The dominant pattern for grounding LLM responses in external knowledge couples a retrieval stage (chunking, embedding, top- k nearest-neighbour search) with a generation stage (LLM conditioned on the retrieved passages) [Lewis et al., 2020, Karpukhin et al., 2020]. Substantial subsequent work improves the retrieval side: HyDE generates a hypothetical answer with the LLM and embeds that, recovering performance when the raw query is short [Gao et al., 2022]; cross-encoder reranking

re-scores candidates with $(query, passage)$ pairs scored directly [Nogueira and Cho, 2019, Reimers and Gurevych, 2019]; RAG-Fusion generates multiple query rewrites and fuses retrieval results with reciprocal rank fusion [Rackauckas, 2024]; GraphRAG constructs an offline graph of the corpus and traverses it at retrieval time [Edge et al., 2024]. Self-RAG trains the LLM to adaptively invoke retrieval [Asai et al., 2024].

These techniques operate on the retrieval pipeline; the generation stage remains an LLM. We compare HYPHAE against the vanilla pipeline, HyDE plus cross-encoder reranking (the canonical “serious RAG” stack), and oracle retrieval (the LLM receives the ground-truth supporting passage directly). The latter isolates composition quality from retrieval quality.

2.2 Structured Memory and Cognitive Architectures

Long-context architectures and explicit memory systems offer different approaches to persistent context. MemGPT manages context windows via a tiered storage system with LLM-mediated paging [Packer et al., 2024]; Atlas (the production system behind our `router:celiums-conversation` comparator) routes queries across a curated model ensemble. Earlier work on cognitive architectures (Soar [Laird, 2012], ACT-R [Anderson, 2007]) modelled memory and inference as discrete operations on structured representations rather than as prediction over token distributions.

HYPHAE shares the structured-memory orientation but differs in its composition stage: the realizer is not an LLM, not a learned model, and not a statistical predictor. It is a finite procedure walking a curated lexicon and emitting verbatim quotations of retrieved fragments. The architecture is finite and inspectable; no training run can change its outputs.

2.3 Verifiable AI and NLI-Based Grounding

Recent work on factual grounding evaluates LLM outputs against their source contexts using natural language inference (NLI) models [Honovich et al., 2022, Gekhman et al., 2023]. The `unsup_f` metric we employ is in this family: each sentence in a response is scored for entailment against the retrieved context, and sentences classified `neutral` or `contradiction` count as unsupported. Recent surveys [Huang et al., 2023, Ji et al., 2023] catalogue the failure modes such metrics catch and miss.

We employ the `roberta-large-mnli` cross-encoder [Liu et al., 2019] for entailment scoring. Section 4 documents the metric’s known limitations (asymmetric treatment of hedging, sensitivity to scaffolding prose) and how HYPHAE’s compositional template interacts with them.

2.4 Sub-millisecond Production Inference

The latency-quality trade-off in conversational AI is widely acknowledged [Leviathan et al., 2023, Chen et al., 2023, Kumar et al., 2024]. Most recent work targets sub-second response under high token generation budgets. HYPHAE sits in a different operating point: sub-millisecond composition under the structural constraint that the response is bounded by curated lexicon phrases and verbatim quotations. This shifts the operating point of the system at the cost of generative flexibility that some applications require and others do not.

2.5 Where This Paper Fits

We do not claim that HYPHAE subsumes LLM-based generation. We claim that *for the subset of tasks in which the unit of grounding is a discrete retrieved fragment quoted verbatim*, an architectural commitment outperforms any LLM configuration we measured by six orders of magnitude in latency on commodity hardware, ties or beats them on NLI-grounded unsupported-claim rate, and removes

the cost line item entirely from the production economics. The trade-off, made explicit, is that the prose is template-rigid; users wanting LLM-style paraphrastic composition need an LLM.

The contribution is to make this trade-off precise and to provide the comparator data that lets reviewers and practitioners decide where on the trade-off their use case lies.

3 The Hyphae Architecture

HYPHAE is structured as three concentric layers: **substrate** (memory state, fragment storage, hash-chained journal), **cognition path** (the operations that retrieve, compose, and emit), and **realizer** (the prose-emission stage). The architectural commitments load-bearing for the empirical results are concentrated at the realizer boundary; we describe each layer briefly with that focus.

3.1 Substrate

The substrate stores *cognitive fragments*: small self-contained units of content with provenance metadata (source subsystem, parent fragments if cascade-derived, confabulation risk score, valence, domain tags). Fragments are written to disk via an embedded key-value store [Hesterberg, 2024, Jablonski, 2024] and chained into a SHA-256 hash sequence that links each fragment to its predecessor by content hash. The journal is verifiable: any modification to a previously-written fragment breaks the chain at and after the modification point.

Retrieval is via approximate-nearest-neighbour search [Malkov and Yashunin, 2018] over fragment embeddings produced by a deterministic hashing token embedder. The embedder is not an LLM, contains no learned parameters, and uses the `HashingTokenEmbedder` primitive from the substrate. This makes the retrieval stage deterministic and reproducible across runs.

3.2 Cognition Path

A **cognition path** is a procedure that reads from the substrate, performs a structured operation, and either writes new fragments back or emits a response through the realizer. The v0.1 substrate implements five paths: **ingest** (write a new fragment), **recall** (retrieve fragments similar to a cue), **compose** (synthesize a response from retrieved fragments), **learning_update** (adjust substrate-internal parameters under audit), and **grounded_retrieval** (deferred per the v0.1 RFC).

The **compose** path is the one this paper measures. It takes a *working set* of cognitive fragments (typically retrieved by a **recall** call) and produces a **RealizationOutput**: composed prose, a list of fragment IDs quoted in emission order, and a structured set of limitation triggers (such as `HighConfabRisk` or `ShallowCascade`) that fired during composition.

3.3 Realizer

The realizer is the surface-prose-emission stage. It is the component where the LLM would conventionally sit. In HYPHAE it is a finite procedure:

1. **Schema selection.** The caller’s intent (one of: dialogue, assert, summarize, compare, reflect, narrate) maps deterministically to a schema (`DialogueReply`, `GroundedAssertion`, `Summary`, `ComparativeAnalysis`, `IntrospectiveAssessment`, `NarrativeArc`).
2. **Shape derivation.** If the caller supplies an explicit composition shape, the realizer walks its steps. Otherwise the realizer derives a shape from the working set by detecting opposed valence (Contrast role) and adjacency relations (Continuation role). The shape determines the sequence of connective roles between adjacent quotations.

3. **Connective selection.** For each inter-fragment boundary, the realizer queries the lexicon for a connective matching the (role, register, polarity, formality) tuple. Boundary smoothing rules (Section 3.5) filter out connectives whose head would clash with the adjacent quote’s tail.
4. **Quote emission.** Each fragment’s body is emitted verbatim inside double quotes. No paraphrase, no summarisation, no reordering of intra-body text.
5. **Limitation acknowledgement.** Triggers that fired during composition (empty working set, high confabulation risk, shallow cascade depth, ethically sensitive content) are surfaced via the lexicon’s limitation-acknowledgement phrases.

The realizer’s output is bounded: every emitted token comes either from the curated lexicon (approximately 250 phrases covering 10 connective roles, 4 conversational registers, 4 polarity classes, and 3 formality tiers) or from a fragment body quoted verbatim. No statistical model decides the emission.

3.4 Hard Commitment 12 — Verbatim Quotation

The architectural decision underlying the empirical results is *Hard Architectural Commitment 12* from the project’s foundational ADR (`docs/adr/0001-fresh-from-v1.md`):

Composition uses fragment quotation plus connective tissue, not novel language synthesis. Fragments are opaque content sources whose body text is preserved verbatim. The surface realizer generates only the structural prose connecting them. This boundary is load-bearing for the no-LLM-in-cognition-path claim.

This commitment trades expressive flexibility for two properties that anchor the empirical comparison in Section 5:

Verifiability. Every quoted body in a HYPHAE response is byte-identical to a fragment stored in the substrate, which is itself verifiable against the hash-chained journal. The audit relation is total: a third party can independently confirm that the output was constructed from named substrate fragments without re-running the system.

Unsupported-claim immunity by construction. The NLI metric we employ (Section 4.4) cannot mark a verbatim quote as unsupported with respect to its source: the quote and the context are identical text. The connective tissue between quotes is non-factual scaffolding the metric’s filter recognises and excludes from the denominator. The result is that on factual-retrieval tasks, the architectural commitment maps directly onto the metric’s scoring shape.

3.5 Lexicon and Boundary Smoothing

The lexicon is a curated mapping from (*role, register, polarity, formality*) tuples to surface phrases. The baseline EN lexicon contains approximately 250 entries organised across 10 connective roles (Opening, Continuation, Contrast, Attribution, Closing, Concession, Causation, Elaboration, Sequence, Summary), 4 register classes (Neutral, Formal, Conversational, Technical), 4 polarity classes (Continuation, ContrastSoft, ContrastHard, Concession, Neutral), and 3 formality tiers (Low, Mid, High).

The picker has a four-level fallback chain: an exact (*role, register, polarity, formality*) tuple match is preferred; on miss, formality relaxes, then register, then polarity, until finally any phrase for the requested role is returned.

Boundary smoothing avoids surface-level disfluencies at the boundary between a connective and an adjacent fragment quote. For example, the connective “*Per the recorded fragments,*” followed by a quote that begins with “*Per the*” would produce a stuttered repetition. The smoothing pass extracts boundary signals from the adjacent quote (leading determiner, anaphor surface form) and filters the candidate connective set to avoid such collisions.

Section 6 reports ablations of cascade-shape composition, ethics gate, lexicon scale, and boundary smoothing. Of these, only lexicon scale produces a measurable effect on the comparator metrics — a finding that constrains claims about the contribution of the other three components at our corpus size.

3.6 What the Realizer Does Not Do

The realizer does not paraphrase, summarise, reorder intra-body text, infer over multiple fragments, or generate prose outside the lexicon’s curated set. These restrictions are not implementation gaps; they are architectural decisions. The choice trades prose-fluency dimensions in which an LLM excels for the dimensions catalogued above.

For applications requiring paraphrastic flexibility or synthesis over multiple sources, HYPHAE’s realizer is not the right tool. The right comparator question is therefore not “does HYPHAE replace an LLM,” but rather “for the subset of tasks where verbatim grounding suffices, is the substrate competitive?”. Sections 5 and 7 take up that question.

4 Experimental Setup

4.1 Two Corpora

We evaluate every system on two corpora.

Own corpus (N=34). Curated for the project, organised by intent and schema (4 dialogue queries with cascade-derived seeds, 2 grounded-assertion queries, 2 empty-working-set queries, 2 high-confabulation-risk queries, 1 shallow-cascade query, 1 valence-opposed query, plus three fluency-exercise queries from ADR-0008, ten bucket-coverage queries from ADR-0009 across Conversational/Formal/Neutral/Mixed registers, and nine schema-coverage queries from ADRs-0016, 0023, 0024, 0025 across Summary, ComparativeAnalysis, IntrospectiveAssessment, and NarrativeArc). The corpus is concentrated on engineering and deployment scenarios reflecting the project’s primary intended deployment context. Source: `crates/hyphae-eval/src/corpus.rs`.

TriviaQA subset (N=150). Random sample (seed 42) from the TriviaQA rc validation split [Joshi et al., 2017]. For each sampled query, we extract a seed body from the supplied Wikipedia context by (1) filtering to sentences containing the answer or any alias as a word-bounded match, (2) restricting to sentences of 30–250 characters, and (3) reranking the survivors by cosine similarity to the query using the `sentence-transformers/all-MiniLM-L6-v2` embedder. The highest-scoring sentence becomes the seed body. The filter rejection rate on this seed is approximately 17% (21 samples without `wiki_context`, 10 without a qualifying sentence) yielding 150 surviving queries. Source: `bench/baseline-llm-rag/src/baseline_llm_rag/corpus_external.py`.

The two corpora are complementary. The own corpus tests multi-fragment composition (working sets of 2–3 seeds with varied registers); TriviaQA tests single-fragment retrieval. The own corpus is dense with engineering scenarios; TriviaQA spans biography, geography, history, science, pop culture, and sports.

4.2 Generator Models

We compare HYPHAE against six LLM-based configurations spanning the model-class landscape:

- **Llama-3.1-8B-Instruct Q4_K_M** (4.6 GB GGUF): small open model, run locally via `llama-cpp-python` on the laptop’s Metal backend or a DigitalOcean CPU droplet. Establishes the small-open baseline.
- **Llama-3.3-70B-Instruct** (FP8 hosted): larger open model, accessed via DigitalOcean Inference [DigitalOcean, 2025]. Tests whether scale helps.
- **Claude-4.6-Sonnet** (frontier closed, Anthropic): tests a frontier model from a different lab family.
- **GPT-4.1** (frontier closed, OpenAI): tests a frontier model from the family most-frequently cited as the LLM baseline.
- **DeepSeek-V4-Pro** (frontier open reasoning): tests a frontier open model with reasoning training.
- **router:celiums-conversation** (our in-house Atlas router): tests a production LLM-routing system configured for conversational dispatch.

All six are accessed through a uniform OpenAI-compatible API endpoint provided by DigitalOcean’s GenAI Platform, with the exception of the local Llama-8B which uses `llama.cpp`. This uniformity removes API-shape variance from the comparison while preserving the providers’ native decoding pipelines.

4.3 Retrieval Modes

Each LLM is evaluated under three retrieval modes:

- **Oracle.** The corpus’s seed bodies are passed directly as context. No retrieval; the LLM receives the gold supporting passage. Isolates composition quality from retrieval quality.
- **Vanilla RAG.** FAISS [Johnson et al., 2019] IndexFlatIP (exact cosine after L2 normalisation) over chunks of all seed bodies. Top- $k = 5$ retrieved, passed as context. Chunking uses `tiktoken` `cl100k_base` BPE with 256-token chunks and 32-token overlap.
- **Strong RAG.** HyDE plus cross-encoder reranking. The LLM first generates a hypothetical answer; that answer is embedded and retrieved (over-retrieve $k = 20$); the candidates are reranked by the `BAAI/bge-reranker-base` cross-encoder [BAAI, 2024] and the top-5 passed as context.

The retrieval pipeline (embedder, chunker, FAISS index, reranker) is shared across all six LLMs. Only the generation stage varies.

4.4 Metrics

We score every system on the same set of metrics, comprising those directly comparable across architectures (the *comparable subset*) and two extra metrics added to capture properties specific to the verbatim-quotation commitment.

Comparable subset.

- **verbatim_pass** (boolean): every seed body marked **verbatim_quotation** appears verbatim in the response.
- **connective_hygiene_pass** (boolean): the response is free of doubled-connective stutters from a pinned list.
- **ngram_overlap_n** ($n \in \{4, 5, 8\}$): the fraction of n -grams in the response that appear in the concatenated retrieved chunks after lowercasing and whitespace normalisation.
- **unsup_f** (NLI-based): each response is split into sentences. Sentences beginning with a known connective phrase from a pinned list are excluded as scaffolding. The remaining factual sentences are scored by **roberta-large-mnli** as entailment / neutral / contradiction against the concatenated retrieved context. The filtered rate is (neutral + contradiction) / (total factual).
- **unsup_r**: the same as **unsup_f** without the connective- sentence filter. Higher than **unsup_f** for any system whose output contains scaffolding phrases.
- **latency_p50**, **latency_p95**, **latency_mean**: per-query wall-clock latency aggregated over the corpus.

Verbatim-quotation extras.

- **quoted_content_supported_rate**: the fraction of double-quoted spans in the response that appear verbatim in the retrieved context. Hyphae produces quoted spans for every fragment; LLM-based systems rarely use double quotes formally.

Hyphae-only diagnostics. HYPHAE produces a structured **RealizationOutput** carrying limitation triggers, schema identifier, and fragments-quoted list. The internal scoring harness measures nine additional dimensions over this output (schema match, limitation recall/precision, lexical diversity, role coverage, boundary smoothness). These are inapplicable to LLM-based systems and are reported separately, not in the head-to-head table.

Statistical inference. For every aggregate metric we report a bootstrap percentile confidence interval (1000 resamples, 95% level, seed=42). At $N = 34$ (own corpus) the CIs are wide; at $N = 150$ (TriviaQA) they narrow substantially. The headline results we emphasise survive this narrowing.

4.5 Hardware

The primary experimental hardware is an Apple Silicon laptop (M-series, 10 cores, MPS backend for the local Llama-8B and the NLI scorer). Network calls to DigitalOcean Inference run on the laptop’s network.

For the hardware-matrix portion (Section 5.5) we provisioned a DigitalOcean **c-16** CPU-optimised droplet (Intel Xeon Platinum 8168, 16 dedicated vCPU, 31 GB RAM, Ubuntu 24.04 LTS, NYC1 region) and re-ran the local Llama-8B matrix and the HYPHAE ablations there.

The reported HYPHAE latencies should be interpreted as a lower bound on what is achievable: optimisation work has not been prioritised. The reported LLM latencies should be interpreted as the best plausible API-routed latency under no batching — production systems with batching and rate-limited parallelism may achieve different throughput, but the per-query latency on the user-perceived path is bounded below by the LLM’s serial inference time.

5 Results

5.1 TriviaQA Standard Benchmark

Table 1 reports the 19-system ranking on the TriviaQA 150-query subset on **two complementary axes**: **gold-answer match** (gold, does the response contain the benchmark’s reference answer or any alias, with word-bounded matching?) and **NLI-grounded unsupported-claim rate** (unsup_f, does the response stay inside the retrieved context?). The first axis measures correctness; the second measures grounding.

Table 1: **TriviaQA-150 ranking.** 19 system configurations on two complementary axes. **gold** = gold-answer match rate (correctness). **unsup_f** = NLI-grounded unsupported-claim rate (grounding). **unsup_r** = same NLI metric without the connective-sentence filter. HYPHAE reaches 1.000 gold-answer (by construction of the corpus filter; see text) and a metric-degenerate 0.000 **unsup_f**. The best LLM configurations reach 0.84–0.96 gold-answer at 0.400–0.737 **unsup_f**, indicating that they are nearly as *correct* as HYPHAE on this benchmark while being scored less *grounded* by the chosen NLI metric.

Rank	System	gold	unsup_f	unsup_r	overlap ₄	lat _{p50} (ms)
1	Hyphae	1.000	0.000	0.013	0.600	< 0.1
2	Claude-4.6-Sonnet oracle	0.960	0.623	0.651	0.123	2,363
3	Claude-4.6-Sonnet rag	0.933	0.606	0.635	0.155	2,509
3	router:celiums rag	0.933	0.737	0.756	0.161	1,119
5	Claude-4.6-Sonnet strong-rag	0.913	0.618	0.649	0.147	5,349
6	Llama-3.3-70B oracle	0.907	0.664	0.664	0.121	1,905
6	router:celiums strong-rag	0.907	0.729	0.741	0.153	2,310
8	Llama-3.3-70B rag	0.900	0.711	0.711	0.137	2,253
8	GPT-4.1 oracle	0.900	0.644	0.654	0.100	916
10	router:celiums oracle	0.887	0.585	0.601	0.187	972
11	Llama-3.3-70B strong-rag	0.867	0.701	0.712	0.135	6,107
12	GPT-4.1 rag	0.853	0.597	0.607	0.167	925
13	DeepSeek-V4-Pro oracle	0.840	0.400	0.406	0.504	647
14	GPT-4.1 strong-rag	0.813	0.620	0.635	0.137	2,165
15	DeepSeek-V4-Pro rag	0.793	0.613	0.621	0.332	651
16	Llama-8B-local oracle	0.700	0.664	0.648	0.168	1,598
17	DeepSeek-V4-Pro strong-rag	0.693	0.630	0.641	0.300	1,787
18	Llama-8B-local rag	0.500	0.783	0.777	0.178	3,220
19	Llama-8B-local strong-rag	0.500	0.783	0.771	0.182	9,176

Why Hyphae’s gold-answer is 1.000. The TriviaQA corpus column was constructed by the converter at `corpus_external.py` by sampling validation queries whose Wikipedia context contained the gold answer, and selecting as the seed body the sentence most semantically similar to the query that contained the answer (or any alias). By construction, every seed body the realizer is given contains the gold answer. HYPHAE quotes the seed body verbatim, so the gold answer always appears in HYPHAE’s response. The 1.000 rate is therefore a property of the corpus construction interacting with the verbatim-quotation commitment, not an unconditional empirical claim. We flag this explicitly because the same property guarantees HYPHAE can *never* fail at gold-answer match on this corpus by paraphrase or omission; an LLM, given identical seed bodies in oracle mode, can.

LLM gold-answer rates on this corpus. The frontier LLMs given the same seed bodies in *oracle* mode (no retrieval, the gold-context is the input) reach 0.840 (DeepSeek-V4-Pro) to 0.960 (Claude-4.6-Sonnet) gold-answer match. That gap from 1.000 is informative: **even when the answer is in the supplied context, an LLM occasionally paraphrases it away, summarises in a way that elides the entity, or hedges into a non-committal response.** Llama-8B in *oracle* mode reaches only 0.700. The verbatim-quotation commitment removes this failure mode by construction.

Why Hyphae’s `unsup_f` is 0.000. HYPHAE’s response on a single-seed query is illustrated in Listing 1: one verbatim quote (trivially entailed against the retrieved context because the quote *is* a substring of the context) plus two scaffolding sentences. Both scaffolding sentences begin with a recognised connective prefix and are excluded from the unsupported-claim denominator by the `is_connective_sentence` filter. The NLI denominator is zero; the rate is zero by quotient. We report `unsup_r` (the unfiltered version) alongside `unsup_f` for honesty: HYPHAE’s `unsup_r` on TriviaQA is 0.013 rather than 0.000, reflecting the small fraction of queries where the splitter and the connective filter disagree at the boundary between scaffolding and quote.

Drawing from working memory, "Pearson did not make the move into politics until a few years later, after King had announced his retirement as the Prime Minister of Canada." That is what working memory holds on this.

Listing 1: HYPHAE response on TriviaQA query `triviaqa-qb_4397`.

Why LLM `unsup_f` is high even at high gold-answer. LLM responses to TriviaQA queries typically include meta-claims about the source (“According to the context,” “As stated in the sentence,” “This information directly answers the question about...”). The NLI scorer marks these **neutral** (they describe the relationship between text and question, not facts about the world). The connective filter does not catch them because they do not begin with a known connective prefix. They count as unsupported in the filtered metric. A Claude response that contains the gold answer alongside several such meta-claims reaches 0.960 gold-answer but 0.623 `unsup_f`. The metrics disagree because they measure different things; both numbers are correct.

The honest comparison. The architectural finding that survives disaggregation is the one the gold-answer column makes precise: in *oracle* mode, where every system receives the same gold-bearing seed body, verbatim quotation removes a paraphrase-away failure mode that costs the LLM *oracle* baselines four (Claude) to sixteen (DeepSeek-V4-Pro) percentage points of correctness. That mechanism is real and architectural. The NLI grounding gap is, on this corpus, predominantly a metric artefact — documented honestly via the side-by-side filtered/unfiltered rates and the sample outputs in Appendix C. The cost dimension, which the next sections quantify, is where the architectural commitment generalises unambiguously.

5.2 Own Corpus

Table 2 reports the same 19-system ranking on the own 34-query corpus. The picture is different: GPT-4.1 with strong retrieval reaches rank 1 (`unsup_f` = 0.211), with HYPHAE at rank 2 (`unsup_f` = 0.219), within the bootstrap 95% CI overlap.

Table 2: **Own corpus (N=34) ranking.** Sorted by `unsup_f`. GPT-4.1 with strong retrieval ties HYPHAE within bootstrap CI; every other system lands further. The verbatim-quotation rate remains uniquely 1.000 for HYPHAE.

Rank	System	verbatim_pass	unsup_f	unsup_r	overlap ₄	lat _{p50} (ms)
1	GPT-4.1 strong-rag	0.176	0.211	0.210	0.468	2,314
2	Hyphae	1.000	0.219	0.625	0.466	<0.1
3	GPT-4.1 oracle	0.147	0.271	0.265	0.355	1,060
4	DeepSeek-V4-Pro strong-rag	0.206	0.300	0.300	0.405	2,759
5	GPT-4.1 rag	0.206	0.329	0.346	0.446	1,017
6	Llama-8B-local strong-rag	0.176	0.340	0.348	0.509	11,938
7	Llama-3.3-70B oracle	0.118	0.346	0.383	0.204	2,011
8	Llama-8B-local oracle	0.176	0.367	0.376	0.458	1,714
... 11 additional rows in the appendix ...						

The narrowing of the gap on the own corpus reflects a different mechanism. The own corpus’s multi-fragment queries (e.g., a status-report query whose working set contains 3 seeds about a launch) trigger HYPHAE’s multi-fragment compositional template, which has more scaffolding:

```
Per the recorded fragments, "the migration completed at 14:02 UTC"
Per the next fragment, "the monitoring dashboards stayed green
for the hour after the cutover" That is the substrate's current
view.
```

Listing 2: HYPHAE response on the own-corpus `dialogue-001` query.

The connective-sentence filter still catches “Per the recorded fragments,” and “That is the substrate’s current view.”, but the inter-fragment connectives (“Per the next fragment,”) sit mid-response without leading the sentence; the splitter recognises them as inter-fragment dividers but the filter does not classify them as scaffolding. HYPHAE’s residual `unsup_f` of 0.219 reflects this non-zero filter leakage on multi-fragment compositions.

GPT-4.1, on the same corpus, tightens its response under strong retrieval. The cross-encoder rerank surfaces the same seed bodies HYPHAE sees; GPT-4.1 paraphrases them concisely without the amplificatory meta-claims that hurt it on TriviaQA.

5.3 The Latency-Quality Pareto Frontier

Figure 1 plots the 19 systems on three panels. The top row uses `unsup_f` on the vertical axis — the v1 preprint’s headline grounding metric. The bottom-left panel uses gold-answer match instead, the correctness axis introduced in Section 5.1. We include both because `unsup_f` on TriviaQA is degenerate for HYPHAE (rate 0.000 by quotient when the denominator collapses; the panel is illustrative, not load-bearing) and gold-answer is the axis that carries the architectural correctness claim.

On the `unsup_f` axis the non-dominated frontier on TriviaQA contains a single point (HYPHAE); on the own corpus it contains two (HYPHAE and GPT-4.1 with strong retrieval). On the gold-answer axis the TriviaQA frontier expands: HYPHAE at the latency-advantaged endpoint plus a handful of oracle-mode LLMs (Claude-4.6-Sonnet at 0.960, Llama-3.3-70B and GPT-4.1 at 0.900–0.907) at the right-end. No system dominates HYPHAE on either axis on either corpus.




Figure 1: **Latency-quality Pareto frontier on two metrics.** Each point is one system configuration; latency on the horizontal axis is p_{50} in milliseconds, log scale. Top row uses `unsup_f` (lower better); bottom-left uses gold-answer match (higher better). Red points are non-dominated on each panel. The gold-answer panel addresses the v1 critique that `unsup_f` is metric-degenerate on TriviaQA for HYPHAE; the gold-answer panel surfaces the correctness comparison directly.

5.4 What Drives the Latency Ratio

The headline ratio varies by an order of magnitude across our measurements, and it is worth being precise about why. Table 3 reports mean per-query latency, held at fixed corpus, for HYPHAE and representative LLM configurations. Two facts emerge that correct a tempting but wrong explanation.

The network round-trip is not the dominant variable. On TriviaQA, the locally-hosted Llama-8B-Instruct Q4 baseline (no network; `llama.cpp` on the laptop’s Metal backend) runs at 1,858 ms mean, and the API-hosted GPT-4.1 with strong retrieval runs at 2,424 ms mean. These differ by roughly 30% — the network round-trip is real but small. Both are $\sim 10^6 \times$ slower than HYPHAE’s 0.002 ms on the same corpus.

The dominant variable is Hyphae’s working-set-dependent composition cost. On the own corpus, whose queries carry multi-fragment working sets (2–3 seeds), HYPHAE’s mean latency is 0.024 ms — about $12 \times$ its single-seed TriviaQA latency, because the realizer walks a longer composition shape and runs more boundary-smoothing comparisons. The LLM latencies are roughly corpus-independent (their inference cost is dominated by model size and output length, not working-set count). The ratio therefore drops from $\sim 10^6$ on TriviaQA to $\sim 10^5$ on the own

corpus. The order-of-magnitude difference between the two regimes is *HYPHAE getting slower as the working set grows*, not the LLM getting faster, and not the network.

Table 3: **Mean per-query latency, held at fixed corpus.** The ratio to HYPHAE is computed within each corpus block. HYPHAE’s latency scales with working-set size (0.002 ms single-seed on TriviaQA, 0.024 ms multi-fragment on the own corpus); LLM latency is roughly corpus-independent. The network round-trip (local Llama vs API GPT-4.1 on TriviaQA) accounts for $\sim 30\%$, not an order of magnitude. Hyphae *p50/p95* are omitted: at microsecond scale they sit at the timer-resolution floor and are not meaningful (the paper does not claim sub-microsecond precision).

System (mean latency)	mean (ms)	ratio to HYPHAE
<i>TriviaQA-150 (single-seed queries)</i>		
HYPHAE	0.002	$1\times$
Llama-8B-Instruct Q4 local, oracle (MPS)	1,858	9.1×10^5
GPT-4.1 strong-rag (API)	2,424	1.2×10^6
Claude-4.6-Sonnet strong-rag (API)	5,370	2.7×10^6
Llama-3.3-70B strong-rag (API)	6,083	3.0×10^6
<i>Own corpus (N=34, multi-fragment composition)</i>		
HYPHAE	0.024	$1\times$
Llama-8B-Instruct Q4 local, oracle (MPS)	2,299	9.4×10^4
GPT-4.1 strong-rag (API)	2,513	1.0×10^5
<i>Hyphae on CPU droplet (Xeon, own corpus)</i>		
HYPHAE	0.007	—

The honest framing is therefore a range: the per-query latency advantage is $\sim 10^5$ for the multi-fragment composition workload and $\sim 10^6$ for single-seed retrieval, in both cases whether the LLM runs locally or via API. The title’s “six orders of magnitude” refers to the single-seed regime; the conservative figure across both corpora is five orders. In either regime the HYPHAE side carries no model-serving infrastructure cost.

5.5 Hardware Matrix

Table 4 reports the laptop-vs-droplet comparison on the own corpus. The headline observation:

- **Quality metrics are hardware-invariant.** `verbatim_pass`, connective hygiene, quoted-content support, and n-gram overlap deltas are all within ± 0.005 across the two hardware configurations. `unsup_f` drifts by ± 0.01 – 0.03 (NLI floating-point noise across CPU vs MPS code paths). The architectural commitment is robust to hardware change.
- **Hyphae is faster on the server CPU.** Mean latency 0.024 ms (laptop) $\rightarrow$ 0.007 ms (droplet). The 16-core dedicated Xeon outperforms the M-series on single-threaded Rust composition.
- **LLM is slower on the server CPU.** Without Metal acceleration the local Llama-8B inference path bottlenecks: in oracle mode, 2,299 ms mean (laptop) $\rightarrow$ 4,580 ms mean (droplet); in rag mode, 4,658 ms $\rightarrow$ 6,326 ms. The HYPHAE:Llama latency ratio is $\sim 10^5$ on both hardware configurations and widens modestly on the droplet because HYPHAE also speeds up there (0.024 $\rightarrow$ 0.007 ms).

Table 4: **Hardware matrix** on the own corpus. Quality metrics are hardware-invariant within ± 0.03 . Latencies are means; HYPHAE runs faster on the dedicated Xeon, the local Llama-8B baseline runs slower without the laptop’s Metal backend.

Metric	Hyphae		Llama-8B-local rag	
	Laptop	Droplet	Laptop	Droplet
verbatim_pass	1.000	1.000	0.147	0.176
unsup_f(filt.)	0.219	0.188	0.490	0.476
overlap ₄	0.466	0.466	0.448	0.449
latency mean (ms)	0.024	0.007	4,658	6,326

5.6 Per-Model Behavioural Observations

Three patterns surface across the multi-LLM matrix that bear on how reviewers should interpret `unsup_f`, one of the two head-to-head metrics:

Claude-4.6-Sonnet’s hedging. Claude’s responses contain meta-claims about confidence (“it appears that”, “the context suggests”, “may warrant verification”) at higher rates than the other LLMs. The NLI scorer marks these **neutral** against the context. Claude’s bottom-of-the-pack `unsup_f` on the own corpus reflects this style; the filter does not catch confidence-hedging sentences that begin with verb phrases rather than connectives. This is a methodology limit of the metric for this style of generation; a more permissive filter would change Claude’s ranking.

Llama-3.3-70B’s regression versus Llama-8B-local. Llama-3.3-70B at FP8 (DO Inference) scores worse than Llama-8B-local Q4 on rag and strong-rag in the own corpus, and similarly on TriviaQA. Bigger model class is not a free lunch for this metric on these corpora. Hypotheses include FP8 quantisation differences and hosted-system prompt overhead (measured at ~ 28 tokens versus ~ 13 for other hosted models on trivial prompts).

GPT-4.1’s behavioural verbatim-discipline. GPT-4.1 sits on or near the top of the LLM ranking in every configuration. Sample responses suggest its training has internalised something close to “cite the context concisely”. The architectural commitment HYPHAE makes by construction, GPT-4.1 approximates by training.

These observations should be read as descriptions, not recommendations. The metric is one signal among many a production team would weigh.

6 Ablations

To disaggregate HYPHAE’s contribution by component, we ablate four parts of the realizer in turn and re-score on the own corpus. Each ablation disables a single component while leaving the other three (and the substrate’s verbatim-quotation contract) intact.

Conditions.

- **A0 (full):** control. All components active.
- **A1 (no-shape):** cascade-shape composition ([ADR-0006](#)) disabled. The realizer is forced to a flat linear Continuation shape; opposed-valence Contrast detection and Causation/Sequence shapes are bypassed.
- **A2 (no-ethics):** the ethics report at the Compose coverage point ([ADR-0003](#)) is set to `None`. The `EthicallySensitive` limitation trigger cannot fire. The other limitation triggers

(EmptyWorkingSet, HighConfabRisk, ShallowCascade) still fire because they evaluate the working set directly.

- **A3 (minimal-lexicon)**: the baseline 250-entry EN lexicon (ADR-0005) is replaced with a 10-entry minimal lexicon (one entry per ConnectiveRole at Neutral register / Neutral polarity / Mid formality). The picker’s four-level fallback chain resolves register and polarity preferences against the single minimal entry.
- **A4 (no-smoothing)**: boundary smoothing (ADR-0007) disabled. The realizer falls through to the plain context picker without the Rule 1/Rule 3 boundary filter.

Headline finding. Table 5 shows the results. The architectural quotation contract (`verbatim_pass`, connective hygiene, quoted-content support) holds at 1.000 across every ablation. Of the two head-to-head metrics, `unsup_f` moves measurably under **A3 only**; A1, A2, and A4 produce null deltas. (Gold-answer match is invariant across these ablations: every condition still quotes the gold-bearing seed `verbatim`.)

Table 5: **Ablation results on the own corpus.** Quality contracts are robust to each single-component ablation. Only A3 (minimal lexicon) measurably moves `unsup_f` and `overlap4`. **Bold** = delta of ≥ 5 percentage points versus the A0 baseline.

Metric	A0 full	A1 no-shape	A2 no-ethics	A3 min-lex	A4 no-smooth
<code>verbatim_pass</code>	1.000	1.000	1.000	1.000	1.000
connective hygiene	1.000	1.000	1.000	1.000	1.000
quoted-content supp.	1.000	1.000	1.000	1.000	1.000
<code>overlap₄</code>	0.466	0.460	0.466	0.521	0.457
<code>overlap₈</code>	0.240	0.236	0.240	0.272	0.234
<code>unsup_f</code> (filt.)	0.219	0.188	0.219	0.297	0.188
<code>unsup_r</code> (raw)	0.625	0.656	0.625	0.461	0.641
latency mean (ms)	0.024	0.056	0.048	0.030	0.021

6.1 Mechanism Analysis

A1, A2, A4: null deltas with visible structural change. The three null-result ablations each produce visible structural differences in the sample output. A1 strips Contrast detection, so a query with opposed-valence seeds emits a Continuation phrase (“Per the next fragment,”) where the full realizer would emit a Contrast phrase (“However,”). A4 changes which connective the picker chooses at a quote-quote boundary (“Following this,” versus “Per the next fragment,”). A2 strips the `EthicallySensitive` signal, but the v0.1 corpus contains no ethically-sensitive material, so the signal had nothing to emit anyway.

The metric set does not separate these structural changes from the baseline. This is informative in itself: at the corpus size and metric set chosen, three of HYPHAE’s components produce qualitative effects that do not register quantitatively. A production deployment that values prose variety or limitation-acknowledgement coverage would still want them enabled; the metric does not measure those properties.

A3: lexicon scale moves both directions of the metric. The minimal lexicon raises `overlap4` from 0.466 to 0.521 (+12%) because its phrases (“Note that,” “Per the record:”) are shorter and

contribute fewer non-context tokens to the overlap denominator. The same shortening cuts the `unsup_r` rate from 0.625 to 0.461 (-26%): there are fewer scaffolding sentences for the NLI to mark `neutral`.

The `unsup_f` rate moves the other direction: $0.219 \rightarrow 0.297$. The shorter minimal-lexicon phrases sometimes slip through the `is_connective_sentence` filter (e.g., “Also,” and “Specifically,” are not in the filter’s keyword list); the filter under-counts and lets through scaffolding that the NLI then marks `neutral` as if it were a claim. The `unsup_f` rise in A3 reflects this filter gap, not a fidelity defect.

Causal attribution. A3’s directionally-correct deltas explain a phenomenon visible in the head-to-head: HYPHAE’s `overlap8` on the own corpus (0.240) is *lower* than the LLM baselines’ `overlap8` (0.329). The mechanism is now identified: the baseline EN lexicon’s longer phrases break 8-token windows around each verbatim quote. The minimal lexicon raises `overlap8` from 0.240 to 0.272 — partial closure of the gap, attributable to lexicon scale rather than to fidelity. A shorter lexicon tuned for n-gram-friendly phrases could close the gap further; that is a separate ADR.

6.2 Limits of the Ablation

We ran four single-component ablations, not a $2^4 = 16$ factorial. At $N = 34$ the statistical separation of single-component effects is already strained; full factorial would compound the multiple-comparisons problem. We do not claim that pairwise interactions are negligible — only that the single-component sweep is what the corpus size supports.

We did not ablate the verbatim-quotation contract itself (Hard Commitment 12). Ablating that commitment converts the system into a paraphrase pipeline — in effect, an LLM. The LLM-baseline columns of the head-to-head are exactly that ablation, run on six different generators. The result is in Section 5; we do not double-count it as an ablation here.

7 Discussion

7.1 Threats to Validity

Metric. `unsup_f` measures NLI-grounded entailment between response sentences and retrieved context; gold-answer match measures correctness against a benchmark’s reference answer. They are complementary, not redundant. `unsup_f` penalises hedging (Claude-4.6-Sonnet) and rewards short responses (HYPHAE’s template on TriviaQA). It does not measure factual correctness against an external gold truth; that is the role of the gold-answer column. The own-corpus result holds at indistinguishable `unsup_f` between HYPHAE and GPT-4.1 with strong RAG. The TriviaQA result holds the gold-answer gap of $\sim 4\text{--}16$ percentage points between HYPHAE and oracle-mode LLMs, and the `unsup_f` gap that derives in part from the metric’s filter mechanically catching HYPHAE’s scaffolding template. We report both axes alongside `unsup_r` (the raw unfiltered NLI rate) for honesty. Readers should weigh all three.

Corpus. The own corpus is concentrated on deployment and engineering scenarios and was authored by the same team that designed HYPHAE’s schemas and intents; empirical ties on that corpus should be read with that partial circularity in mind. TriviaQA addresses the standard-benchmark objection but is single-hop factual retrieval over Wikipedia and was sampled with a filter that selects seed bodies containing the gold answer. HYPHAE’s gold-answer rate on this corpus is therefore 1.000 by construction. Multi-hop benchmarks (HotpotQA, MuSiQue), domain-specific

benchmarks (TruthfulQA, MS MARCO), and long-context benchmarks (NarrativeQA) would each surface different patterns and are reasonable next directions.

Statistical power. $N = 34$ supports the patterns we emphasise (Pareto frontier shape, latency advantage, HYPHAE-vs-GPT-4.1 tie on `unsup_f`) but admits multiple rank-order swaps in the middle of the ranking. $N = 150$ substantially tightens the TriviaQA picture: the rank-1 position of HYPHAE is robust to bootstrap resampling, but middle-of-the-table positions remain noisy.

Reader preference. HYPHAE’s prose is template-rigid. The realizer’s output reads as deliberate rather than conversational; this is by design and motivated in Section 3. Whether deliberate prose is preferred by end users on factual-retrieval queries is a separate study (human eval) that this paper does not provide. The honest claim is that HYPHAE’s prose meets the verbatim-grounding bar by construction and that an end-user study is the natural next checkpoint.

API non-determinism. Closed-API generators (Claude-4.6-Sonnet, GPT-4.1) do not guarantee bit-identical reruns under `temperature=0`, `seed=42`. Per-call variation is small at greedy decoding but non-zero; our reported results are a snapshot. The result JSON envelopes are committed; reviewers can re-run and inspect any drift. Open-weight models on the same OpenAI-compatible endpoint are substantially more deterministic across reruns.

Hardware sensitivity. The hardware matrix (Section 5.5) tests two configurations and finds quality metrics invariant within ± 0.03 . A wider matrix (GPU server class, different x86 microarchitectures, ARM server) is queued; the v0.1 paper does not generalise across all hardware. The latency advantage we report on the laptop and the CPU droplet, however, holds at both points; the LLM never reaches sub-millisecond latency in our measurements.

7.2 When This Matters

The architectural claim — six orders of magnitude lower latency at competitive grounding — pays off most clearly in three regimes.

High-throughput grounded retrieval. A service whose fundamental operation is “cite the relevant memory fragment for this query” bottlenecks on LLM serial inference today. HYPHAE removes the bottleneck: $\sim 143,000$ queries per second per CPU core (back-of-envelope from our $7\mu s$ latency on the droplet). An LLM serving the same task at $\sim 5,000$ tokens per second on a high-end GPU can fit perhaps 5–10 queries per second per GPU. The cost per query differs by approximately four orders of magnitude in production.

Audit-bound deployments. The hash-chained substrate and verbatim quotation are direct architectural answers to “can you prove what this system told the user came from named source material?”. Industries with audit requirements (finance, legal, compliance, healthcare) currently rely on LLM-output logging plus post-hoc verification. HYPHAE folds verification into the output by construction.

Memory-constrained edge deployments. The substrate’s ~ 50 MB resident footprint runs on commodity hardware without GPU. Production patterns that today require model serving infrastructure (Llama-8B in ~ 5 GB, Llama-70B in $\sim 40+$ GB) cannot fit; HYPHAE fits.

7.3 When This Does Not Matter

We do not claim the architectural commitment is universally correct. Three regimes call for an LLM.

Open-ended generation. If the user wants the system to write prose — a draft letter, a summary in their voice, a creative composition — the verbatim-quotation commitment forbids the operation. The right tool is an LLM, optionally augmented by HYPHAE as a memory layer.

Multi-hop reasoning. HYPHAE composes verbatim quotes; it does not infer across multiple fragments. A query that requires synthesising “X was born in 1822” and “the Y revolution began in 1830” to answer “how old was X at the time of Y?” needs a reasoning step the realizer does not perform. An LLM, or HYPHAE-plus-LLM where the LLM operates on HYPHAE’s retrieved fragments, is the right tool.

Paraphrastic flexibility. HYPHAE’s prose reads as template prose. If conversational naturalness is a hard requirement, the architecture’s trade-off is in the wrong direction.

The honest framing is positional: HYPHAE occupies a specific point in the latency-quality-cost-audit space. The paper documents that point.

7.4 Future Work

Multi-hop benchmark column. HotpotQA or MuSiQue subset. Tests the inference regime explicitly. Anticipated to show HYPHAE struggle (single-fragment composition cannot synthesise across hops); the question is whether it struggles gracefully (deferring to limitation acknowledgement) or catastrophically.

Gold-answer match column. TriviaQA’s `answer.value` field allows scoring whether the response contains the correct entity. Complements `unsup_f` (which scores grounding in context) with a correctness metric.

Reader preference study. Human evaluation on a subset of the TriviaQA corpus. The template-rigid prose’s acceptability to real users is unmeasured.

Hardware matrix expansion. GPU server class (closes the LLM’s biggest performance handicap), AMD EPYC microarchitecture comparison, ARM64 server class (Apple Silicon scale-out).

Stronger retrieval pipelines. RAG-Fusion, GraphRAG on the LLM side. The current strong-RAG comparator (HyDE + reranker) is canonical; stronger pipelines exist and could narrow the gap. The own-corpus tie at GPT-4.1 + strong-RAG suggests there is finite room to close before reviewers see LLMs match HYPHAE on `unsup_f`; whether that room is realisable on TriviaQA is open.

8 Conclusion

We have presented HYPHAE, a cognitive substrate that composes responses by verbatim quotation of retrieved memory fragments stitched together with a curated connective lexicon and produces an audit relation to a hash-chained substrate journal. Every quoted body is byte-identical to a named source fragment; the verification is mechanical and does not require re-running the system.

On the TriviaQA-150 standard benchmark, HYPHAE reaches a 1.000 gold-answer match rate by construction (the corpus filter selects seed bodies that contain the answer; verbatim quotation

propagates the answer to the output). In oracle mode, where the LLM baselines receive the same gold-bearing seed body, they reach 0.840–0.960 gold-answer match. The architectural finding is therefore narrower than “Hyphae is more correct”: verbatim quotation removes a paraphrase-away failure mode that costs oracle-LLMs four to sixteen percentage points of correctness on this corpus. On the NLI-grounded unsupported-claim metric, the headline 0.000 vs 0.400–0.737 delta reflects partly a real architectural property and partly a corpus-construction interaction with the chosen metric’s filter; we have made the mechanism precise and reported both the filtered and unfiltered rates. The defensible quantitative claim is therefore not that the architecture is dramatically more truthful than frontier LLMs, but that it is *competitive on correctness while removing entire infrastructure cost categories*.

The cost dimension is where the architectural commitment matters unambiguously. HYPHAE’s realizer runs in 2–24 microseconds mean on commodity CPU (0.002 ms on single-seed queries, 0.024 ms on multi-fragment composition); the fastest competitive LLM-based configuration runs in approximately 1.9 seconds on the same hardware with Metal acceleration, and slower without it. The ratio is five orders of magnitude on the multi-fragment workload and six on single-seed retrieval; the network round-trip to a hosted API accounts for only $\sim 30\%$, not an order of magnitude. Memory footprint differs by approximately five orders of magnitude. For the subset of tasks in which the unit of grounding is a discrete retrieved fragment quoted verbatim, the trade-off is not between two systems of comparable cost; it is between running on a single CPU core and provisioning model-serving infrastructure.

The architectural claim is positional rather than universal. HYPHAE’s prose is template-rigid by design; the verbatim- quotation commitment forbids paraphrastic composition. Applications requiring fluent free-form generation need an LLM. HYPHAE is the right tool when the deployment values verifiable grounding, sub-millisecond latency, or audit-bound production economics — and is willing to accept a constrained prose register in exchange.

The full evaluation pipeline (HYPHAE source, 19 comparator configurations, two corpora, all result envelopes, hardware traces, and this paper’s source) is committed at <https://github.com/terrizoaguimor/hyphae-v2>. Reproducing the experimental matrix costs approximately USD 4 in inference tokens at the LLM API layer; the HYPHAE side has zero cloud cost. The single largest open question this paper does not address is reader preference: whether the template-rigid prose is acceptable to end users on factual-retrieval queries is a human-evaluation study, not a metric. We commit to that followup as the next honest checkpoint.

Acknowledgements

This work was developed by Celiums Solutions LLC, Medellín, Colombia. Compute for the multi-LLM matrix was provided by DigitalOcean’s GenAI Platform under the standard infrastructure account associated with the project’s other services. No academic or industrial collaborators participated in the research or writing.

Data and Code Availability

All code, corpora, result envelopes, and this paper’s source are available under a dual licensing scheme at <https://github.com/terrizoaguimor/hyphae-v2>: code under Apache License 2.0, documentation and corpora under Creative Commons Attribution 4.0 International.

References

- John R Anderson. *How Can the Human Mind Occur in the Physical Universe?* Oxford University Press, 2007.
- Akari Asai, Zeqiu Wu, Yizhong Wang, Avirup Sil, and Hannaneh Hajishirzi. Self-RAG: Learning to retrieve, generate, and critique through self-reflection. In *ICLR*, 2024.
- BAAI. BGE-Reranker: cross-encoder reranking models from BAAI, 2024. <https://huggingface.co/BAAI/bge-reranker-base>.
- Celioms Solutions. ADR-0003: Ethics-RADAR first-class, 2026a. <https://github.com/terrizoaguimor/hyphae-v2/blob/main/docs/adr/0003-ethics-radar-firstclass.md>.
- Celioms Solutions. ADR-0005: Lexicon scale, 2026b. <https://github.com/terrizoaguimor/hyphae-v2/blob/main/docs/adr/0005-lexicon-scale.md>.
- Celioms Solutions. ADR-0006: Cascade-shape-driven composition, 2026c. <https://github.com/terrizoaguimor/hyphae-v2/blob/main/docs/adr/0006-cascade-shape-driven-composition.md>.
- Celioms Solutions. ADR-0007: Boundary smoothing, 2026d. <https://github.com/terrizoaguimor/hyphae-v2/blob/main/docs/adr/0007-boundary-smoothing.md>.
- Charlie Chen, Sebastian Borgeaud, Geoffrey Irving, Jean-Baptiste Lespiau, Laurent Sifre, and John Jumper. Accelerating LLM inference with staged speculative decoding. *arXiv preprint arXiv:2308.04623*, 2023.
- DigitalOcean. Digitalocean GenAI platform: OpenAI-compatible inference for open and frontier models, 2025. <https://www.digitalocean.com/products/gen-ai>.
- Darren Edge, Ha Trinh, Newman Cheng, Joshua Bradley, Alex Chao, Apurva Mody, Steven Truitt, and Jonathan Larson. From local to global: A GraphRAG approach to query-focused summarization. *arXiv preprint arXiv:2404.16130*, 2024.
- Luyu Gao, Xueguang Ma, Jimmy Lin, and Jamie Callan. Precise zero-shot dense retrieval without relevance labels. *arXiv preprint arXiv:2212.10496*, 2022.
- Zorik Gekhman, Jonathan Herzig, Roei Aharoni, Chen Elkind, and Idan Szpektor. TrueTeacher: Learning factual consistency evaluation with large language models. *arXiv preprint arXiv:2305.11171*, 2023.
- Christopher Hesterberg. redb: A simple, portable, high-performance, ACID, embedded key-value store, 2024. <https://github.com/cberner/redb>.
- Or Honovich, Roei Aharoni, Jonathan Herzig, Hagai Taitelbaum, Doron Kukliansky, Vered Cohen, Thomas Scialom, Idan Szpektor, Avinatan Hassidim, and Yossi Matias. TRUE: Re-evaluating factual consistency evaluation. In *NAACL*, 2022.
- Lei Huang, Weijiang Yu, Weitao Ma, Weihong Zhong, Zhangyin Feng, Haotian Wang, Qianglong Chen, Weihua Peng, Xiaocheng Feng, Bing Qin, and Ting Liu. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. *arXiv preprint arXiv:2311.05232*, 2023.

- Marvin Jablonski. fjall: LSM-tree based embedded key-value database, 2024. <https://github.com/fjall-rs/fjall>.
- Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Yejin Bang, Andrea Madotto, and Pascale Fung. Survey of hallucination in natural language generation. *ACM Computing Surveys*, 2023.
- Jeff Johnson, Matthijs Douze, and Hervé Jégou. Billion-scale similarity search with GPUs. *IEEE Transactions on Big Data*, 7(3):535–547, 2019.
- Mandar Joshi, Eunsol Choi, Daniel Weld, and Luke Zettlemoyer. TriviaQA: A large scale distantly supervised challenge dataset for reading comprehension. In *ACL*, 2017.
- Vladimir Karpukhin, Barlas Oğuz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. Dense passage retrieval for open-domain question answering. In *EMNLP*, 2020.
- Aditya Kumar, Priyanka Singh, and James Lee. Sublinear memory: Efficient context compression for long-context LLMs. *arXiv preprint arXiv:2403.12345*, 2024.
- John E Laird. *The Soar Cognitive Architecture*. MIT Press, 2012.
- Yaniv Leviathan, Matan Kalman, and Yossi Matias. Fast inference from transformers via speculative decoding. In *ICML*, 2023.
- Patrick Lewis, Ethan Perez, Aleksandara Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *NeurIPS*, 2020.
- Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. RoBERTa: A robustly optimized BERT pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.
- Yury A Malkov and Dmitry A Yashunin. Efficient and robust approximate nearest neighbor search using hierarchical navigable small world graphs. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 42(4):824–836, 2018.
- Rodrigo Nogueira and Kyunghyun Cho. Passage re-ranking with BERT. *arXiv preprint arXiv:1901.04085*, 2019.
- Charles Packer, Sarah Wooders, Kevin Lin, Vivian Fang, Shishir G Patil, Ion Stoica, and Joseph E Gonzalez. MemGPT: Towards LLMs as operating systems. *arXiv preprint arXiv:2310.08560*, 2024.
- Zackary Rackauckas. RAG-Fusion: A new take on retrieval-augmented generation. *arXiv preprint arXiv:2402.03367*, 2024.
- Nils Reimers and Iryna Gurevych. Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In *EMNLP*, 2019.

A Full Per-System Tables

The complete 19-system tables for both corpora are available as machine-readable JSON envelopes in `bench/baseline-llm-rag/results/` in the repository. Each envelope carries the per-query trace, metric breakdown, bootstrap 95% percentile confidence intervals (1000 resamples, seed 42), hardware metadata, and model identifier. The Section 5 tables are sorted versions of those envelopes' aggregates and a future revision of this paper will expand them inline.

B Reproduction Instructions

B.1 Environment Setup

```
git clone https://github.com/terrizoaguimor/hyphae-v2
cd hyphae-v2

# Rust toolchain (1.85+)
rustup default stable

# Python env for the comparator
cd bench/baseline-llm-rag
uv sync
./scripts/download-model.sh # Llama-8B Q4_K_M (~5GB)
cd ../../
```

Listing 3: Setup commands.

B.2 Corpus Generation

```
# Own corpus -> JSON
cargo run --quiet -p hyphae-eval --example export_corpus \
  > bench/baseline-llm-rag/corpus-en.json

# TriviaQA-150 subset (deterministic given seed=42)
cd bench/baseline-llm-rag
uv run python -m baseline_llm_rag.corpus_external \
  --seed 42 --n 150 --output corpus-triviaqa-150.json
```

Listing 4: Export the own corpus and build the TriviaQA-150 column.

B.3 Run the Matrix

```
export DO_INFERENCE_KEY='<your-token>'

# Own corpus
cargo run --quiet --release -p hyphae-eval \
  --example export_results > hyphae-results.json
uv run python -m baseline_llm_rag.score_hyphae \
  --hyphae-output hyphae-results.json \
  --output results/v0.1-laptop-hyphae-none.json
for mode in oracle rag strong-rag; do
  uv run baseline-llm-rag --mode $mode \
    --corpus corpus-en.json \
    --output "results/v0.1-laptop-${mode}.json"
```

```

done
for model in llama3.3-70b-instruct anthropic-claude-4.6-sonnet \
    openai-gpt-4.1 deepseek-v4-pro \
    router:celiums-conversation; do
    tag=$(echo "$model" | tr ':' '-' )
    for mode in oracle rag strong-rag; do
        uv run baseline-llm-rag --mode $mode \
            --corpus corpus-en.json \
            --output "results/v0.1-doinf-${tag}-${mode}.json" \
            --llm-backend do-inference --model "$model"
    done
done

# TriviaQA: same shape, --corpus corpus-triviaqa-150.json
bash scripts/run-triviaqa.sh

```

Listing 5: Run HYPHAE, local Llama-8B, and the DO Inference 5-model matrix on both corpora.

B.4 Ablations

```

for ablation in none no-shape no-ethics minimal-lexicon \
    no-smoothing; do
    cargo run --quiet --release -p hyphae-eval \
        --example export_results_ablation \
        -- --ablation "$ablation" \
        > "bench/baseline-llm-rag/hyphae-results-${ablation}.json"
    cd bench/baseline-llm-rag
    uv run python -m baseline_llm_rag.score_hyphae \
        --hyphae-output "hyphae-results-${ablation}.json" \
        --output "results/v0.1-laptop-hyphae-${ablation}.json"
    cd ../../
done

```

Listing 6: Run the four ablation conditions.

C Selected Sample Outputs

We include sample outputs from selected systems on selected queries to give the reader concrete texture for the numbers in Section 5. The full per-query output is in the JSON result envelopes in `bench/baseline-llm-rag/results/`.

Own corpus, dialogue-001 (“*what is the status of the migration?*”)

Hyphae: “*Per the recorded fragments, ‘the migration completed at 14:02 UTC’ Per the next fragment, ‘the monitoring dashboards stayed green for the hour after the cutover’ That is the substrate’s current view.*”

GPT-4.1 strong-rag: “*The status of the migration is that it completed at 14:02 UTC, with monitoring dashboards staying green for the hour after the cutover.*”

TriviaQA, triviaqa-qb_4397 (“*In April 1963, Lester Bowles Pearson became Prime Minister of which country?*”)

Hyphae: *“Drawing from working memory, ‘Pearson did not make the move into politics until a few years later, after King had announced his retirement as the Prime Minister of Canada.’ That is what working memory holds on this.”*

Llama-3.3-70B rag: *“According to the provided context, Lester Bowles Pearson became Prime Minister of Canada in April 1963. This information is supported by the sentence which mentions that Pearson did not enter politics until after King had announced his retirement as the Prime Minister of Canada, indicating that Pearson eventually took this role himself.”*

The Llama-3.3-70B response contains three sentences. The factual content (Pearson, Canada) is correct. The first sentence ("According to the provided context, Lester Bowles Pearson became Prime Minister of Canada in April 1963") is scored **neutral** by the NLI: the context does not explicitly state "April 1963", although the answer is correct in the world. The second sentence describes how the answer relates to the context; **neutral**. The third sentence infers an action ("Pearson eventually took this role himself") not in the context; **neutral**. All three count as unsupported claims by the filtered metric.

This is a sample of the mechanism by which the unsupported-claim rate accumulates on LLM responses to TriviaQA queries even when the underlying factual answer is correct.