

程序设计基础


Fundamental of Programming

清华大学软件学院


刘玉身

liuyushen@tsinghua.edu.cn

Lecture 7: 结构体



Lecture 7: 结构体



引言



1.	2.	3.	4.	5.	6.	7.	8.
Cao Cao	Sun Jian	Liu Bei	Yuan Shao	Yuan Shu	Liu Biao	Dong Zhuo	Liu Yan
Body	(Basic value: 85)	--	84	--	Hit Space Bar		
Intell.	(Basic value: 95)	--	91	--	Hit Space Bar		
Power	(Basic value: 63)	--	62	--	Hit Space Bar		
Charisma	(Basic value: 99)	--	100	--	Hit Space Bar		
Luck	(Basic value: 71)	--	66	--	Hit Space Bar		



刘备的人马

姓名	体力	智力	武力	魅力	运气
刘备	84	91	62	100	66
诸葛亮	80	100	70	95	80
关羽	95	88	99	85	80
张飞	95	85	99	70	70
赵云	100	90	95	90	80
...					

新君主的人马

姓名	体力	智力	武力	魅力	运气
新君主	84	91	90	90	85
随从	80	80	80	80	80

人才最宝贵！

什么数据结构？

1. 单个人物
2. 所有人物

【结构体】

由一个或多个变量（类型可以相同，也可以不同，称为字段或成员变量）所组成的一个组合项。

A **structure** is a collection of one or more variables, possibly of different types, grouped together under a single name for convenient handling.

结构体的定义

定义一个**结构体 (struct)**的步骤通常是：

1. 定义一个新的结构体**类型**，并指明它内部的各个成员变量；
2. 使用该类型来定义相应的结构体**变量**。

结构体**类型**的定义只在程序的开头出现**一次**，而结构体**变量**的声明可以根据需要在程序中出现**多次**。

定义一个结构体类型

struct <结构体标记>

合法标识符

可省:无名结构体

{

类型名1 成员变量1;

.....

类型名n 成员变量n;

成员类型可以是
基本型或构造型

struct是关键字,
不能省略

};

定义结构体变量:

struct <结构体标记> 变量1, 变量2, ...;

```
struct General
```

```
{
```

```
    char Name[20];           // 姓名
```

```
    int  Body;               // 体力
```

```
    int  Intelligence;       // 智力
```

```
    int  Power;              // 武力
```

```
    int  Charisma;           // 魅力
```

```
    int  Luck;               // 运气
```

```
};
```

分号

结构体类型定义描述结构的组织形式, 不分配内存

```
struct General LiuBei;
```

```
struct General GuanYu, ZhangFei;
```

在定义结构体**变量**后，将为它分配相应的内存空间。

结构体变量的长度 = Σ 其各个成员变量长度之和?

X

```
struct student
{
    char ID[7];
    char name[20];
    char gender;
    int age;
    char phone[9];
    char addr[30];
} x;
```

ID	<input type="text"/>
name	<input type="text"/>
gender	<input type="text"/>
age	<input type="text"/>
phone	<input type="text"/>
addr	<input type="text"/>

sizeof(x) = 72 7 + 20 + 1 + 4 + 9 + 30 = 71?

结构体变量的长度

```
struct ID
{
    char    ch;
    double dd;
} y;
```

sizeof(y) = 16 ?

ANSIC标准中并没有规定：相邻声明的变量在内存中一定相邻。

1. 在**Win32**下，结构体大小为结构体中**最宽基本类型**成员大小的**整数倍**，如有需要，编译器会在最末一个成员之后填充字节；
2. GNU GCC原则不同；
3. 结构体变量的长度 \geq 其成员变量长度之和。
4. **C语言结构体内存对齐问题**

结构体变量的使用

对一个结构体变量的最基本的操作就是去访问它的各个成员变量。访问的方式为：

结构体变量名.成员变量名

一个成员变量就是一个普通的变量，可以对它进行各种通常的变量操作。

```
struct General x;
```

```
strcpy(x.Name, "刘备");
```

```
if(x.Charisma > 95)  
    printf("%s是仁君", x.Name);
```

```
if(x.Power > 90 && x.Intelligence < 70)  
    printf("%s是一介武夫", x.Name);
```

Can't And Can

- 不能做什么？

- ☺ 不能直接比较两个结构体变量，
`struct student x, y; (x > y); (x != y);`
- ☺ 不能用`scanf/printf`来输入或输出整个结构体变量。

Can't And Can

- 能做什么？

- ☺ 能够进行结构体变量的整体赋值，如：
`struct student x, y; y = x; (why?)`
- ☺ 能够定义一个返回值类型为结构体类型的函数，把被调用函数当中的某个结构体变量的值返回给主调函数。

```
struct student x, y;
```

```
...
```

```
y = x;
```

等价于

```
strcpy(y.ID, x.ID);  
strcpy(y.name, x.name);  
y.gender = x.gender;  
y.age = x.age;  
strcpy(y.phone, x.phone);  
strcpy(y.addr, x.addr);
```

ID 020449

name Zhang

gender M

age 19

phone 62771100

addr 紫荆6-401

X


示例1:统计候选人得票

```
#include <stdio.h>
#include <string.h>
struct Person
{
    char name[20];
    int count;
} p[3]={ "Li", 0, "Zhang", 0, "Wang", 0}; //初始化
int main()
{
    int i, j;
    char str[20];
    for(i = 1; i <= 10; i++)
    {
        scanf("%s", str);
        for(j = 0; j < 3; j++)
            if(strcmp(str, p[j].name) == 0)
                p[j].count++;
    }
    for(i = 0; i < 3; i++)
        printf("%-5s: %d\n", p[i].name, p[i].count);
}
```

Li
Zhang
Wang
Li
Li
Zhang
Wang
Wang
Wang
Wang

Li : 3
Zhang: 2
Wang : 5

Lecture 7: 结构体



结构体数组



结构体变量



结构体数组

stu

ID

name

gen

age

phone

addr

stu[0]

ID

name

gen

age

phone

addr

stu[1]

struct student stu[1000];

• • • • •

结构体与指针

新类型：基类型为结构体类型的指针类型。

```
struct StudentRecord
```

```
{
```

```
    char name[10];
```

```
    int id;
```

```
    double score;
```

```
} x, *px;
```

```
px = &x;
```

px


x

name

id

score


x = *px



如何来访问x的成员变量？

结构体及指针应用广泛！

1. **x.成员变量名**，如：**x.name, x.id**；
2. **(*px).成员变量名**，如：**(*px).name, (*px).id**；
3. **px->成员变量名**，“**->**”称为指向运算符或箭头运算符，如：**px->name, px->id**。




a[0]

```
struct StudentRecord
    a[10], *px;


...
px = a;
```

px 指向 a[0];
px + 1 指向 a[1];
...
px + i 指向 a[i];

a[1]



Lecture 7: 结构体




- 函数参数的传递


- ☺ 普通变量：传值；

- ☺ 数组：传地址；


- ☺ 结构体：传值！

问题： 屏幕坐标到棋盘坐标的转换





问题分析:



```
struct ScreenCoor //屏幕坐标
{
    int x, y;
};
```

```
struct BoardCoor //棋盘坐标
{
    int row, col;
};
```

```

#define x0 40
#define y0 20
#define SQUARE_SIZE 10
void main()
{
    struct ScreenCoor s;
    struct BoardCoor b;
    scanf("%d %d", _____); // 输入屏幕坐标
    screen_to_board(_____); // 函数调用
    printf("%d %d\n", b.row, b.col);
}

void screen_to_board(??screen, ??board)
{
    _____;
    _____;
}

```




```
#define x0 40
#define y0 20
#define SQUARE_SIZE 10
void main()
{
    struct ScreenCoor s;
    struct BoardCoor b;
    scanf("%d %d", &s.x, &s.y); // 输入屏幕坐标
    screen_to_board(s, &b);      // 函数调用
    printf("%d %d\n", b.row, b.col);
}

void screen_to_board(struct ScreenCoor screen,
                    struct BoardCoor *board)
{
    board->row = (screen.y - y0) / SQUARE_SIZE;
    board->col = (screen.x - x0) / SQUARE_SIZE;
}
```

typedef: 定义类型

功能: 用自定义名字为**已有**数据类型命名

形式: **typedef** type name;


```
typedef    int        INTEGER;
```

```
typedef    float      REAL;
```

// 类型定义后, 与已有类型一样使用

```
INTEGER    a, b, c;
```

```
REAL       f1, f2;
```

补充说明

- **typedef** 没有创造新数据类型
- **typedef** 是定义类型, 不能定义变量
- **typedef** 与 **#define** 不同

#define

预编译时处理

简单字符置换

typedef

编译时处理

为已有类型命名

```
typedef struct date
{
    int month;
    int day;
    int year;
} DATE;

struct date d[2];
DATE birthdays[100], *p;
```

枚举类型

枚举类型的定义格式：

```
enum 枚举类型名 {变量1, 变量2, ...};
```

示例：

```
enum weekday {Sun, Mon, Tue, Wed, Thu, Fri, Sat};
```

- 枚举常量是一种符号常量，起始值从 0 开始，递增值为 1
- 可以用 = 为枚举常量定值
- 枚举定义中的标识符必须唯一
- 用枚举类型可以定义各种离散的、非数值型数据

```
enum weekday {Sun, Mon=100, Tue, Wed, Thu, Fri, Sat};  
此时，Sun 为0，Mon~Sat 分别为100 ~105。
```

枚举变量的使用举例：

```
weekday day ;  
day = Mon;           // OK  
day = Sunday;        // Error  
day = 2;              // Error  
day = (weekday)2;    // OK  
//如一定要把数值赋予枚举变量，则必须用强制类型转换
```

枚举元素（枚举成员）不是字符常量也不是字符串常量，使用时不要加单、双引号。

枚举类型作用：以一系列字符串，来表示整型数字，起到更方便阅读维护代码的效果。

枚举变量的使用

问题描述：

输入月份（整数）。

请编写一个程序，利用枚举型变量输出对应月份的天数。

枚举变量的使用


```
// Program to print the number of days in a month
#include <stdio.h>
int main ()
{
    enum month { january = 1, february, march, april, may, june,
                july, august, september, october, november, december};
    enum month aMonth;
    int days;
    printf ("Enter month number: ");
    scanf ("%i", &aMonth);
```



```

switch (aMonth) {
case january: case march: case may: case july:
case august: case october: case december:
    days = 31; break;
case april: case june: case september: case november:
    days = 30; break;
case february:
    days = 28; break;
default:
    printf ("bad month number\n");
    days = 0; break;
}
if ( days != 0 )
    printf ("Number of days is %i\n", days);
if ( aMonth == february )
    printf ("...or 29 if it's a leap year\n");
return 0;
}

```



Enter month number: 2
 Number of days is 28
 ...or 29 if it's a leap year

结构体应用

问题描述：

输入“今天”的日期（mm dd yyyy）。

请编写一个程序，利用结构体表示日期（struct date），来计算“明天”的日期（mm/dd/yyyy）。

问题分析

1. 如何用结构体来描述“日期”？
2. 如何针对今天的日期来计算明天的日期？

示例2: 明天的日期

```
#include <stdio.h>
int main ()
{
    struct date
    {
        int month;
        int day;
        int year;
    };
    struct date today, tomorrow;
    const int daysPerMonth[12] = { 31, 28, 31, 30, 31, 30, 31, 31, 30,
                                    31, 30, 31 };
    printf ("Enter today's date (mm dd yyyy): ");
    scanf ("%i%i%i", &today.month, &today.day, &today.year);
```

```
if ( today.day != daysPerMonth[today.month - 1] ) {  
    tomorrow.day = today.day + 1;  
    tomorrow.month = today.month;  
    tomorrow.year = today.year;  
}  
else if ( today.month == 12 ) { // end of year  
    tomorrow.day = 1;  
    tomorrow.month = 1;  
    tomorrow.year = today.year + 1;  
}  
else { // end of month  
    tomorrow.day = 1;  
    tomorrow.month = today.month + 1;  
    tomorrow.year = today.year;  
}  
printf ("Tomorrow's date is %i/%i/%i.\n", tomorrow.month,  
        tomorrow.day, tomorrow.year );  
return 0;  
}
```

Enter today's date (mm
dd yyyy): 11 30 2013

Tomorrow's date is
12/1/2013.

还有何问题? *thinking...*

问题分析(2)

1. 如何考虑闰年闰月的情况？
2. 如何判断闰年？
3. 如何编写子函数计算“明天”的日期？
4. 结构体变量如何作为参数和返回值传递？

示例2: 明天的日期 (v2)

```
#include <stdio.h>
```

```
struct date
```

```
{  
    int month;  
    int day;  
    int year;  
};
```

1. 定义 `struct date` 是全局类型

2. `struct date` 做为函数参数

```
// Function to find the number of days in a month
```

```
int numberOfDays (struct date d);
```

```
int main ()
```

```
{  
    struct date today, tomorrow;  
    printf ("Enter today's date (mm dd yyyy): ");  
    scanf ("%i%i%i", &today.month, &today.day, &today.year);
```

```
if ( today.day != numberOfDays (today) ) {  
    tomorrow.day = today.day + 1;  
    tomorrow.month = today.month;  
    tomorrow.year = today.year;  
}  
else if ( today.month == 12 ) { // end of year  
    tomorrow.day = 1;  
    tomorrow.month = 1;  
    tomorrow.year = today.year + 1;  
}  
else { // end of month  
    tomorrow.day = 1;  
    tomorrow.month = today.month + 1;  
    tomorrow.year = today.year;  
}  
printf ("Tomorrow's date is %i/%i/%i.\n", tomorrow.month,  
        tomorrow.day, tomorrow.year);  
return 0;  
}
```



```
int isLeapYear (struct date d);
```

```
// Function to find the number of days in a month
```

```
int numberOfDays (struct date d) {
```

```
    int days;
```

```
    const int daysPerMonth[12] = { 31, 28, 31, 30, 31, 30, 31, 31, 30, 31, 30,  
    31 };
```

```
    if ( isLeapYear (d) == 1 && d.month == 2 )
```

```
        days = 29;
```

```
    else
```

```
        days = daysPerMonth[d.month - 1];
```

```
    return days;
```

```
}
```

```
// Function to determine if it's a leap year
```

```
int isLeapYear (struct date d) {
```

```
    int leapYearFlag;
```

```
    if ( (d.year % 4 == 0 && d.year % 100 != 0) || d.year % 400 == 0 )
```

```
        leapYearFlag = 1; // It's a leap year
```

```
    else
```

```
        leapYearFlag = 0; // Not a leap year
```

```
    return leapYearFlag;
```

```
}
```

**Enter today's date (mm
dd yyyy): 02 28 2008**

**Tomorrow's date is
2/29/2008.**

2008年是闰年

示例2: 明天的日期 (v3)

```
#include <stdio.h>
```

```
struct date
```

```
{
```

```
    int month;
```

```
    int day;
```

```
    int year;
```

```
};
```

```
struct date  dateUpdate (struct date today);
```

```
int main (){
```

```
    struct date  thisDay, nextDay;
```

```
    printf ("Enter today's date (mm dd yyyy): ");
```

```
    scanf ("%i%i%i", &thisDay.month, &thisDay.day,  
           &thisDay.year);
```

```
    nextDay = dateUpdate (thisDay);
```

```
    printf ("Tomorrow's date is %i/%i/%i.\n", nextDay.month,  
           nextDay.day, nextDay.year );
```

```
    return 0;
```

```
}
```

定义一个子函数：
其形参和返回值都是 **struct date**

```
int numberOfDays (struct date d);  
// Function to calculate tomorrow's date  
struct date dateUpdate (struct date today) {  
    struct date tomorrow;  
    if ( today.day != numberOfDays (today) ) {  
        tomorrow.day = today.day + 1;  
        tomorrow.month = today.month;  
        tomorrow.year = today.year;  
    }  
    else if ( today.month == 12 ) { // end of year  
        tomorrow.day = 1;  
        tomorrow.month = 1;  
        tomorrow.year = today.year + 1;  
    }  
    else { // end of month  
        tomorrow.day = 1;  
        tomorrow.month = today.month + 1;  
        tomorrow.year = today.year;  
    }  
    return tomorrow;  
}
```

**Enter today's date (mm
dd yyyy): 02 28 2008**

**Tomorrow's date is
2/29/2008.**

Lecture 8 - Summary

- **Topics covered:**
 - **Defining and using Structures**
 - **Functions and Structures**
 - **Initializing Structures. Compound Literals**
 - **Arrays of Structures**
 - **Structures Containing Structures and/or Arrays**
 - **Enumerated Data Types**
 - **The typedef Statement**