

Lab 6: Search and asynchronous state

C1800 | LO3 | Filter tasks and explain how an obsolete response is discarded.

Starting project

This folder is standalone. The React scripts, package manifest, fixture, test and (for Labs 8-10) Express API are all included. The mock data uses invented task records.

Procedure

1. Open labs/lab-06-search-and-async and inspect mock-data/tasks.json.
2. Run npm install and npm run dev; open the local Vite URL.
3. Locate the React root, App component, state, event handler and derived task count.
4. Implement the lab objective: Filter tasks and explain how an obsolete response is discarded.
5. Type a search term and verify only matching tasks display. Add an empty-result message. Sketch an AbortController cleanup for a remote search to prevent an old response replacing a new query.
6. Run npm test and npm run build. Fix any failed assertion or build error.
7. Resize to 375 px and desktop width. Confirm controls remain usable and no horizontal scroll appears.
8. Ask an AI assistant for one bounded improvement; compare its diff with the acceptance checks before accepting it.
9. Record the UI screenshot, command output and one design or security trade-off in your evidence log.

Acceptance evidence

- Fixture test and Vite build pass.
- A task can be added, toggled and searched; empty title is rejected.
- At 375 px, cards wrap and controls stay visible.
- Learner explains the input boundary, ownership, verification signal and one AI suggestion they rejected.