Lab 3 — Claude Design Project and Design System

Sample prompts and code · A3 · K2 · LO2

prompt.txt

```
Goal: project context pack with tokens, component rules and explicit design direction
Audience: Adults using a community wellness service, including users with varied digital confidence and
  accessibility needs.
Context: Create a Claude Design project and provide a compact design-system contract for the wellness
  product.
Required content: Use realistic service names, appointment times, success, empty, loading, permission and
  error states.
Design system: Use the supplied tokens and component rules. Prefer clear labels, visible focus, 44px minimum
  targets and strong contrast.
Constraints: Mobile-first; no lorem ipsum; one dominant primary action per screen; preserve user input on
  recoverable errors.
Acceptance: Uses named tokens; Defines component variants; Includes accessibility rules; Test screen matches
  the system
Output: Create the named design in Claude Design, save a version checkpoint and export or share the evidence
  requested in the README.
```

project-context.md

```
# Project context

Product: Community Wellness
Primary task: Book or reschedule an appointment
Personality: Calm, trustworthy, direct
Depth: Borders and tonal surfaces; no glassmorphism
Spacing: 4, 8, 12, 16, 24, 32
Accessibility: WCAG contrast, visible focus, 44px targets, plain-language recovery
```

tokens.css

```
:root {
  --color-ink: #161b26;
  --color-muted: #5b6372;
  --color-surface: #f5f8fc;
  --color-action: #724cd6;
  --color-success: #108a73;
  --color-warning: #c77600;
  --color-error: #c2413a;
  --color-focus: #1f6feb;
  --space-1: 4px;
  --space-2: 8px;
  --space-3: 12px;
  --space-4: 16px;
  --space-6: 24px;
  --radius-control: 8px;
  --radius-card: 12px;
  font-family: Arial, sans-serif;
}
```

component-contract.md

```
# Component contract

## Button
Variants: primary, secondary, danger
States: default, hover, focus, loading, disabled
Rules: outcome-specific label; one primary action per view; minimum 44px target

## Field
States: default, focus, valid, error, disabled
Rules: persistent label; associated help/error; preserve valid input
```