GenAI for Engineers Learner Guide

IES | v3.4 | Clear explanations and worked examples

One day, 09:00–17:00. Follow the supplied six-module lesson plan. Guided Excel exercises total 65 minutes: FMEA 20, DMAIC 20, SPC 25. The Copilot Agent is a guided paired build in Module 4; SharePoint is a guided 45-minute knowledge-base and citation activity in Module 5.

How to use this guide

The numbered topics match the presentation. First understand the question, then read the example and check the result. Use the separate Starter.xlsx in each lab. Every workbook has only the source table, one prompt sheet, and the pages needed for that activity. Starter.xlsx is optional after-class practice.

Module 1

1. GenAI for Engineers

Use Copilot to understand data and explain engineering findings.

Today: One pump case, three short Excel exercises

Your role: Check the answer before using it

Explanation: All pump data are synthetic.

2. What will we do today?

Follow the six modules in the supplied lesson plan.

Morning: Meet Copilot → write useful prompts → analyse the pump case

Afternoon: Watch agent and SharePoint examples → review AI security

Hands-on work: SPC 25 min · FMEA 20 min · DMAIC 20 min

Explanation: Here, demonstrations and discussion make up the rest of the day.

3. What is generative AI?

It produces a draft answer from your instructions and available information.

You provide: A question and relevant information

AI produces: A draft explanation, table, formula or report

You check: Does the draft agree with the information?

Explanation: A prompt is the instruction you give the AI. Copilot is Microsoft’s AI assistant. A fluent answer can still contain a wrong number or unsupported statement.

4. What can Copilot do in Excel?

For example: help you understand why a pump test result looks unusual.

Ask: “Which test results are below the usual range?”

Copilot helps: Suggest a formula or explain the chart

Engineer checks: Compare the answer with the recorded test values

Explanation: These are steps in a joint workflow, not three capabilities belonging to Copilot. Here, the last step belongs to the engineer. Editing and chart features depend on the account and Excel version.

5. Our case: is the pump delivering consistently?

A factory team tests a small pump that feeds an industrial cooling-water system.

The job: The pump should deliver about 62 litres per hour during the test.

The concern: Some later tests record less liquid than earlier tests.

Our task: Describe the change, review possible failures and summarise the evidence.

Explanation: CW-401 is only the fictional case identifier; it is not a method learners must know. A dosing skid is a pump and associated equipment mounted together. We will say pump system in class. These are delivery tests, not measurements of water-treatment compliance.

6. How is the test result measured?

Collect the liquid for two minutes, then convert the amount to litres per hour.

Measured: 2.067 litres collected in 120 seconds

Calculation: 2.067 × 3600 ÷ 120 = 62.01 L/h

Meaning: At that rate, the pump would deliver about 62 litres in one hour.

Explanation: L/h means litres per hour. This is an example calculation, rounded from the synthetic case. A test with a different duration cannot be compared using the same multiplier.

7. Use one prepared workbook today

The calculations and charts are already prepared so we can focus on asking and checking.

Open: A working copy of Worked-Reference.xlsx

Find: FMEA_Input in Lab 1, Weekly_Data in Lab 2, and Pump_Readings in Lab 3.

Then: open the matching lab workbook and select its named table before prompting.

Explanation: Starter.xlsx is optional practice after class.

Module 2

8. A prompt is an instruction to Copilot

A useful prompt tells Copilot what to use and what answer you need.

Too vague: “Analyse this.”

More useful: “Use the pump test table. Identify unusual results and explain them in three sentences.”

Why this helps: Copilot knows the information to use and the size of the answer.

Explanation: Prompt engineering means deliberately writing, checking and improving instructions. It does not mean using complicated language. The improved prompt is still a draft: add the relevant sheet and check a value.

9. Use RISE to build a clear prompt

RISE is a four-part checklist for prompts that produce reviewable engineering work: Role, Input, Steps and Expectations.

R - Role: “Act as an engineering data assistant.” The role sets the viewpoint; it does not give Copilot professional authority.

I - Input: “Use only PumpReadings: eight Baseline and four Monitoring rows.” Name the source, revision, units and boundaries.

S - Steps: “Calculate the baseline mean, sample standard deviation, UCL and LCL; flag monitoring rows; create a line chart.” Put the work in a checkable order.

E - Expectations: “Show formulas, return three sentences, and do not claim a root cause or safety conclusion.” Define the format, quality limit and acceptance check.

Weak prompt: “Analyse this pump data.”

RISE prompt: “Act as an engineering data assistant. Use only PumpReadings. Calculate the baseline mean and control limits, flag the monitoring rows, and create a line chart. Show formulas and give three cautious sentences. Do not claim a root cause.”

Iterate after checking: identify one missing item, correct the instruction, rerun the prompt, and compare the new output with the acceptance check.

10. Add the engineering details with E-MAP

E-MAP reminds you to include context, measures, assumptions and limits.

Engineering + Metrics: “This is a pump delivery test. Report flow in litres per hour.”

Assumptions: “The prepared chart uses the eight Baseline readings as its reference.”

Parameters: “Use the eight Baseline rows to calculate the limits; keep the units in L/h.”

Explanation: E-MAP means Engineering context, Metrics, Assumptions and Parameters. It complements RISE; learners do not have to memorise two competing recipes. A parameter is a value or rule the analysis must use.

11. Tell Copilot what it must not change

Constraints are simple rules that keep the task within scope.

Protect the data: “Do not change the original test records.”

Handle gaps: “If a measurement is missing, say it is missing; do not invent it.”

Limit the conclusion: “Describe the change. Do not claim that we have proved its cause.”

Explanation: Replace abstract warnings with the three exact prompt sentences. Here, a blank measurement means we do not know its value. Removing an extreme valid reading would hide a possible problem.

12. Show the format you want

Use three fields: observation, value and follow-up question.

Requested format: Observation | Supporting value | Question to investigate

Observation + value: T09, T10 and T12 are below the 61.4 L/h lower control limit.

Follow-up question: Were those tests performed under the same conditions?

Explanation: This is a format example, not a complete analysis. Use a short output to make verification practical.

13. Use three perspectives to improve a review

A persona is a requested viewpoint, not a separate expert.

Reliability engineer: “What equipment issue could explain low delivery?”

Operations engineer: “Were the test conditions and settings consistent?”

Safety reviewer: “What must be checked before changing the equipment?”

Explanation: Copilot simulates all three perspectives, so their agreement is not independent evidence. Use the same pump information for all roles.

14. Let the perspectives challenge one claim

Example claim: “Replacing the strainer solved the problem.”

Reliability asks: “Do we have evidence that the removed strainer was blocked?”

Operations asks: “A verification check also happened. Which change made the difference?”

Better conclusion: “Results improved afterwards, but we cannot isolate the cause yet.”

Explanation: A strainer catches particles before they enter equipment. In this case strainer replacement and verification happened together. Do not run an unbounded debate or force consensus.

15. Why spend time improving a prompt?

Clear instructions make the answer easier to use and easier to check.

Less rework: Specify the right sheet, units and output length at the start.

More consistency: Reuse the same structure for similar engineering tasks.

Better review: Ask for supporting values and unanswered questions.

Explanation: Measure total time including checking and correcting the answer. Prompt quality does not guarantee factual accuracy.

16. Turn a test note into a short report

Trainer example: preserve the facts while improving the writing.

Source note: “Later tests lower. Strainer replaced. Verification also done. Pilot results improved.”

Prompt: “Write a short observation and one follow-up question. Use only these facts.”

Example draft: “Delivery improved after two changes. Which change contributed to the improvement?”

Explanation: Here, polishing the language does not create new evidence. The same pattern works for inspection notes and technical reports. This is a demonstration, not another learner lab.

Module 3

Module learning outcome

Explain FMEA, Six Sigma/DMAIC and SPC in plain language, then use Microsoft 365 Copilot in Excel to draft and verify one small output for each method. Follow the sequence FMEA → DMAIC → SPC.

Why this sequence?

FMEA anticipates risk. DMAIC organises an improvement investigation. SPC then monitors whether process behaviour remains stable over time. The methods complement one another but answer different questions.

FMEA — what it is and when it is used

Failure Mode and Effects Analysis is a structured review of what could fail, what the effect would be, why it might happen, and what current control could prevent or detect it. Use it before a new design or process is released, and when an existing system changes or shows recurring problems.

Read an FMEA row from left to right

Function: what the item must do. Failure mode: how it could fail. Effect: what happens if it fails. Cause: why it might fail. Control: what currently prevents or detects it. These are potential scenarios unless evidence says an event actually occurred.

Severity, Occurrence, Detection and RPN

Severity (S) rates how serious the effect is. Occurrence (O) rates how likely the cause is. Detection (D) rates how difficult it is to detect the issue before the effect; a higher D score means harder to detect. RPN = S × O × D. Example: FM01 = 7 × 5 × 4 = 140.

Act on the RPN with engineering judgement

Rank higher RPNs for review, but also apply severity gates. A high-severity item can need immediate attention even when its RPN is lower. Confirm the evidence, assign an owner and due date, implement the action, then reassess residual risk. RPN is a priority aid; it is not a probability or approval.

Lab 1 — create and verify an FMEA draft

11:45–12:05. Open Labs/Lab-01-FMEA/Starter.xlsx, select a cell in FMEAInput, open Copilot in Excel, and paste the prompt from Copilot_Prompt. Copilot preserves the four supplied rows, calculates and ranks RPNs, and adds evidence requests and actions.

Prompt: Act as an FMEA facilitator. Use only FMEAInput and preserve every row and supplied rating. Calculate RPN = Severity × Occurrence × Detection, rank the rows, and flag Severity 9 or higher. Add one evidence request and action per row. Show the formula. Do not invent incidents, change ratings or approve the design.

Independent check: Verify FM01: 7 × 5 × 4 = 140; confirm FM04 is flagged because Severity = 9.

Six Sigma and DMAIC — what they are and when they are used

Six Sigma is a data-based approach for reducing defects and variation. DMAIC is its five-phase improvement cycle for an existing process whose performance needs to improve. Use it when the problem can be defined and measured and the team needs a disciplined path from evidence to a sustained change.

The five DMAIC phases

Define: state the problem, customer need and boundary. Measure: establish trustworthy baseline data and a metric. Analyse: examine patterns and test possible causes. Improve: select and trial a change. Control: monitor the result, assign ownership and define a response if performance worsens.

Everyday DMAIC tools

Pareto: order problem categories from largest to smallest to decide where to focus. Fishbone or Ishikawa: organise possible causes under categories such as Machine, Method, Measurement, People, Material and Environment. 5-Whys: follow one possible causal chain by repeatedly asking why, then stop when evidence is missing and name the next check. These tools generate priorities and hypotheses; they do not prove root cause.

Lab 2 — create and verify a DMAIC summary

12:05–12:25. Open Labs/Lab-02-DMAIC/Starter.xlsx, select WeeklyData, open Copilot, and paste the supplied prompt. Copilot calculates the two rates and drafts one concise row for each phase.

Prompt: Act as a Six Sigma project assistant. Use only WeeklyData. Calculate Baseline and Pilot deviation rates. Create a five-row Define, Measure, Analyse, Improve, Control summary. Separate facts from hypotheses, show formulas, and state that the short pilot does not prove cause.

Independent check: Verify Baseline = 36/400 = 9.0% and Pilot = 7/200 = 3.5%; do not claim causation.

SPC — what it is and when it is used

Statistical Process Control uses measurements in time order to judge whether a process is behaving consistently. Use it for repeated operations when the team wants to detect unusual change early and monitor the effect of process controls.

Read a control chart

The centre line represents the process average. Upper and lower control limits describe the expected range from the chosen baseline. Common-cause variation is the usual fluctuation built into the current process. Special-cause variation is an unusual signal that should be investigated. A control-chart signal identifies when to investigate; it does not diagnose the cause.

Control limits, specification limits and capability

Control limits come from process data; specification limits come from requirements. Cp asks whether the process spread could fit between the specification limits if centred. Cpk also accounts for how far the process average is from the centre. Values above 1 mean the estimated process spread fits inside the limits; larger values give more margin. Use Cp/Cpk only with suitable, stable data and engineering context.

Lab 3 — create and verify an SPC review

12:25–12:50. Open Labs/Lab-03-SPC/Starter.xlsx, select PumpReadings, open Copilot, and paste the supplied prompt. Copilot creates formula-based limits, flags four monitoring rows and drafts the line chart.

Prompt: Act as an engineering data assistant. Use only PumpReadings. From the eight Baseline rows, calculate the mean, sample standard deviation, UCL and LCL. Flag T09–T12, create a line chart with the limits, and give a three-sentence interpretation. Show formulas. Do not claim a root cause or that the pump is safe.

Independent check: Verify T10 = 59.4 L/h against the calculated LCL; interpret a signal as a reason to investigate.

Module 3 review

12:50–13:00. State one useful output and one evidence limit for each method: FMEA prioritises potential failure risk; DMAIC structures improvement; SPC monitors variation. Record one correction or limitation before saving each Copilot output.

Module 4

LO4 guided activity - IES Pump FMEA Assistant

Purpose: build and use one Copilot Agent that performs a six-step FMEA-to-report workflow. This is completed within Module 4 and does not add a fourth lab.

1. Open Microsoft 365 Copilot. Under Agents, select New agent. If the tenant routes you to Copilot Studio, continue in the agent designer.

2. Name the agent “IES Pump FMEA Assistant”. Describe its purpose: turn one supplied FMEA row into a checked report draft.

3. Open Trainer-Demonstrations/FMEA-AGENT-INSTRUCTIONS.md and paste the six-step instruction into the Instructions area.

4. Add FMEA-REPORT-TEMPLATE.md as knowledge or copy its headings into the instruction. Use only synthetic training files.

5. Add the starter prompt: “Review FM01 from the supplied FMEA input and prepare a checked draft.” Save the agent.

6. Test FM01. A passing result preserves S=7, O=5 and D=4, calculates RPN=140, keeps the cause as a hypothesis, and waits for APPROVE DRAFT.

7. Test again without the Detection rating. A passing result stops and asks for the missing value. Refine Step 2 if the agent guesses.

8. Reply APPROVE DRAFT only after checking the row and calculation. Confirm that the report uses Status, Evidence, Risk priority, Proposed action, Owner, Due date and Open question.

9. Create, publish or share the agent using the tenant-approved route and approved training users. If publishing is unavailable, retain the saved draft and preview-test evidence and record the limitation.

10. Save evidence: agent name, instruction version, both test results, one correction, deployment status and the final audit summary.

Official guidance

Build your own agent with Microsoft 365 Copilot: https://support.microsoft.com/en-us/Microsoft-365-Copilot/build-your-own-agent-with-microsoft-365-copilot

Microsoft Copilot Studio documentation: https://learn.microsoft.com/microsoft-copilot-studio

Write agent instructions: https://learn.microsoft.com/en-us/microsoft-copilot-studio/authoring-instructions

Publish an agent: https://learn.microsoft.com/en-us/microsoft-copilot-studio/agents-experience/publication-publish-agent

LO5 guided activity - Researcher and Analyst

Purpose: use Researcher for a cited technical comparison and Analyst for a checked data analysis. This 20-minute activity reuses the pump case and does not add another lab.

Part A - Researcher, 8 minutes

Open Microsoft 365 Copilot at https://m365.cloud.microsoft/chat. Select Agents, then Researcher. Attach or reference Trainer-Demonstrations/TR-401-Training-Extract.pdf. Paste the Researcher prompt from REASONING-AGENT-PROMPTS.md. Review the one-page claim-source-evidence-limitation table. Open at least one citation and confirm that it supports the adjacent claim. Keep the missing calibration evidence unresolved.

Part B - Analyst, 8 minutes

Under Agents, select Analyst. Attach Labs/Lab-02-DMAIC/Starter.xlsx. Paste the Analyst prompt from REASONING-AGENT-PROMPTS.md. Check that it uses only the six rows in WeeklyData and separates Baseline W1-W4 from Pilot W5-W6.

Verify the result, 4 minutes

Recalculate Baseline = 36/400 = 9.0%; Pilot = 7/200 = 3.5%; change = -5.5 percentage points; relative reduction = 61.1%. The valid conclusion is that the recorded rate is lower in the two pilot weeks. The data do not prove cause or sustained improvement.

Save the Researcher prompt and response, one opened citation, the Analyst prompt and response, the four checks, one limitation and one next evidence check. If either agent is unavailable, record not executed and use the expected checks for discussion.

Official Microsoft guidance for LO5

Get started with Researcher: https://learn.microsoft.com/en-us/microsoft-365/copilot/researcher-agent

Get started with Analyst: https://support.microsoft.com/en-US/Microsoft-365-Copilot/get-started-with-analyst-in-microsoft-365-copilot

Agents built by Microsoft: https://support.microsoft.com/en-us/Microsoft-365-Copilot/agents-built-by-microsoft

29. What is a Copilot agent?

An assistant with reusable instructions and selected information for a recurring task.

Ordinary prompt: You explain the task again each time.

Agent: The task instructions and selected reference material are already prepared.

Example: An FMEA assistant uses an agreed template and rating guidance.

Explanation: This is a trainer demonstration. Instructions are the task rules and knowledge as reference material. An agent still needs testing and human review. Learners build and test the training agent in pairs, then create or publish it only to the approved training audience.

30. Watch a prepared FMEA assistant

Follow one input through to a checked answer.

Input: Pump description, case records and rating guidance.

Agent draft: Failure modes, effects, possible causes and missing information.

Trainer check: Does each statement match the supplied records?

Explanation: Never claim a recorded live run if using a worked example.

33. Research and analysis need different checks

Research asks what a source says; analysis asks what the numbers show.

Research example: “Find the maintenance guidance in the supplied manual and cite the passage.”

Analysis example: “Compare the test rates and show the calculation.”

Check: Open the cited passage; independently calculate one result.

Explanation: The learning point is the difference in evidence, not a guarantee of access. Use prepared source and arithmetic examples if live tools are unavailable.

34. A report assistant can reuse a template

It turns recorded facts into a consistent report structure.

Recorded facts: Observation, action, owner and due date.

Report sections: Progress, outstanding issues and next actions.

Human review: Check that “proposed” has not become “completed”.

Explanation: A minutes-to-actions-to-report workflow with the same fields. Do not imply that recurring automation has been deployed or that the assistant can approve work.

Module 5

LO6 — create and use a SharePoint-grounded engineering knowledge base

By the end of this 45-minute module, you can explain SharePoint grounding, inspect a private knowledge folder, create or review a scoped agent, ask supported and unsupported questions, open a citation, and check revision, scope and permissions.

Why engineers use it

A SharePoint knowledge base keeps approved files in one managed location. A scoped agent can search those files, draft a cited answer and reduce repeated manual searching. The citation gives the engineer a path back to the evidence; it does not approve the conclusion.

Prepared private site

Open https://tertiaryinfotech.sharepoint.com/sites/IES-GenAI-for-Engineers. The prepared route is Documents > Engineering Knowledge Base. Confirm the four synthetic sources: TR-401-Training-Extract.pdf, FMEA-Starter.xlsx, DMAIC-Starter.xlsx and SPC-Starter.xlsx. The prepared agent is IES Engineering Knowledge Assistant. Do not change site membership or permissions during the activity.

Create or inspect the agent

Select the Engineering Knowledge Base folder. Choose AI actions or the folder context menu, then Create an agent. Set the name, purpose and source scope. Paste the instructions from Trainer-Demonstrations/SHAREPOINT-AGENT-INSTRUCTIONS.md. If you have read access only, inspect the trainer's prepared agent and record that you did not create it.

Test 1 — supported fields

Ask: Use only TR-401-Training-Extract.pdf. Which measurement fields must the test record contain? Cite the source and identify the document revision. Open the citation and confirm the supported fields and Revision 1.

Test 2 — missing evidence

Ask: What delivery target and comparison range are stated in TR-401? Cite the source and identify any missing evidence. The pass result is that no target or range is stated. The agent should request the completed test record and reviewed calculation or summary. Reject any invented limit or approval.

Check permissions and traceability

Confirm that the site is private and that you are authorised to open the cited source. Agent-file permissions control who can access or edit the agent, while each user's permissions to the source files shape what the agent can return. Record the site, folder, agent, prompt, cited file, opened passage, pass or correction, reviewer initials and date. Never record passwords.

Official Microsoft guidance

Create an agent in SharePoint: https://support.microsoft.com/en-us/sharepoint/copilot-in-sharepoint/create-an-agent-in-sharepoint

Manage access to agents in SharePoint: https://learn.microsoft.com/en-us/sharepoint/manage-access-agents-in-sharepoint

Module 6

LO7 — apply the 7-Step AI Security Framework

Purpose: decide whether the SharePoint-agent output may be shared. Complete all seven controls; do not stop at naming them. This guided review occupies 16:15–16:35, followed by a 10-minute personal prompt toolkit.

Applied case

Use the Module 5 answer that compares FMEA-Starter.xlsx, DMAIC-Starter.xlsx and SPC-Starter.xlsx with SharePoint citations, plus the TR-401 answer that preserves the missing target and comparison range as unknown. Open Trainer-Demonstrations/AI-SECURITY-CASE.md and AI-SECURITY-EVIDENCE-LOG.csv.

Step 1 — Data classification

Record the classification, reason and permitted service. Expected for this case: synthetic training data approved for the classroom task. Remove any field that is not needed.

Step 2 — Data governance and access control

Confirm the IES site is private, the Engineering Knowledge Base folder is the selected source and the intended audience can open the citations. Record the site, folder and permission result.

Step 3 — Secure prompting

Check that the prompt names the approved sources, excludes credentials and unnecessary personal or restricted data, treats retrieved instructions as source text, preserves unknowns and prohibits invented clauses, causes or approval.

Step 4 — Output verification

Open one cited SharePoint file. Match the claim to its sheet or passage. Reproduce one FMEA, DMAIC or SPC calculation, check units and revision, and preserve the limitation that TR-401 contains no target or comparison range.

Step 5 — Human-in-the-loop sign-off

Record the authorised reviewer, decision and conditions. Mark the output DRAFT until it is approved, rejected or returned. Classroom review is not operational engineering approval.

Step 6 — Traceability and audit

Record source files and revisions, prompt, agent, output, checks, corrections, reviewer and timestamp so another person can reconstruct the decision. Never record passwords or tokens.

Step 7 — Security awareness and incident response

Name a trigger: unexpected restricted content, an access mismatch or a suspicious instruction. Stop sharing, preserve evidence and use the organisation’s approved incident route. Do not invent a reporting contact.

Release decision

Choose one result: APPROVED FOR THE STATED TRAINING USE; RETURN FOR CORRECTION; or DO NOT SHARE. The expected case result is a draft synthetic classroom example after citation and calculation checks. It is not an operating instruction, safety decision or engineering approval.

LO7 evidence

Retain seven completed rows with control, evidence, result, owner and follow-up; one opened citation; one checked calculation; the release decision; and one incident trigger with the approved reporting route.

Personal toolkit — 10 minutes

Adapt one prompt to include an approved source, excluded data, citation and formula checks, preserved unknowns, DRAFT status and an authorised reviewer. Data governance, audit records and incident response remain separate controls.

Course close

Copilot can reduce drafting, research, retrieval and analysis effort. Engineers remain responsible for methods, evidence, decisions, security and release.

Detailed exercise instructions

Lab-03-SPC

SPC — 25-minute guided Excel exercise

Module 3 only. Use the separate Starter.xlsx in each lab; open the Worked-Reference only after the attempt.

5 min · Read the prepared analysis

Open Lab-03-SPC/Starter.xlsx. Review the 12 rows in Pump_Readings: eight Baseline and four Monitoring. Select the named table PumpReadings before opening Copilot.

12 min · Prompt and inspect

Use the one prompt in Copilot_Prompt. Verify T10 = 59.4 L/h against the calculated LCL. Expected result: T09, T10 and T12 are below the LCL. Save one cautious interpretation.

8 min · Verify and retain

Use the one prompt in Copilot_Prompt. Verify T10 = 59.4 L/h against the calculated LCL. Expected result: T09, T10 and T12 are below the LCL. Save one cautious interpretation.

Optional after class — not scheduled

Starter.xlsx and the complete prompts.md bank support rebuilding the analysis, chart and extended review later. Only the selected core prompt is required in class.

Lab-01-FMEA

FMEA — 20-minute guided Excel exercise

Module 3 only. Use the separate Starter.xlsx in each lab; open the Worked-Reference only after the attempt.

4 min · Read the prepared FMEA

Open Lab-01-FMEA/Starter.xlsx. Review the four supplied failure modes and ratings in FMEA_Input. Use Copilot to create the formula-based output; do not invent or rescore rows.

10 min · Prompt and check priorities

Paste the one prompt from Copilot_Prompt. Ask Copilot to calculate RPN, rank the four rows and flag Severity 9 or higher. Independently verify FM01 and FM04.

6 min · Review one row

Write one evidence gap for FM01 and one action proposal. Keep residual ratings unassessed. The multi-persona debate is a trainer demonstration in Module 2, not an extra participant task.

Optional after class — not scheduled

Starter.xlsx and the complete prompts.md bank support rebuilding the analysis, chart and extended review later. Only the selected core prompt is required in class.

Lab-02-DMAIC

DMAIC — 20-minute guided Excel exercise

Module 3 only. Use the separate Starter.xlsx in each lab; open the Worked-Reference only after the attempt.

4 min · Read the prepared rates

Use the one prompt in Copilot_Prompt. Verify Baseline = 36/400 = 9.0% and Pilot = 7/200 = 3.5%. State that the short pilot does not prove the cause of the change.

10 min · Prompt a short summary

Use the one prompt in Copilot_Prompt. Verify Baseline = 36/400 = 9.0% and Pilot = 7/200 = 3.5%. State that the short pilot does not prove the cause of the change.

6 min · State a decision boundary

Save three cells: measured change, limitation and next evidence. The absolute change is 5.5 percentage points. Two concurrent changes and a short pilot do not prove a cause or sustained improvement.

Optional after class — not scheduled

Starter.xlsx and the complete prompts.md bank support rebuilding the analysis, chart and extended review later. Only the selected core prompt is required in class.

Plain-language glossary

Prompt: An instruction or question you give to an AI assistant.

Baseline: The earlier set of results used as the reference for comparison.

Control limit: A boundary calculated from the reference process data to help identify unusual behaviour.

Specification: A stated requirement that the result is expected to meet.

Failure mode: The way a component or process could fail.

RPN: Risk priority number: Severity × Occurrence × Detection.

Grounding: Supplying relevant information, such as a document passage, to help an AI answer a question.

Persona: A requested viewpoint used to review a question, not an independent expert.

Pilot: A limited follow-up or trial period used to collect more evidence.

Worked demonstration examples

31. A reusable instruction for the FMEA assistant

Show the instruction, then test it on just one failure mode.

Use: “Use the case records and supplied rating guidance.”

Return: “Give the failure, effect, possible cause and missing evidence.”

Check: “Keep supplied scores. Do not turn a possible cause into a fact.”

Use Trainer-Demonstrations/README.md for the full prompt. Open FMEA_Input, ScoringNote and Evidence. Test FM01 only. A normal Copilot prompt demonstrates the instruction if an agent is unavailable; identify the surface honestly.

32. What should the FMEA assistant say?

Example question: “What is still unproven about the low-delivery failure?”

Observed fact: Later tests recorded lower delivery.

Possible explanation: A restriction may have contributed.

Still needed: Evidence about the removed strainer and the effects of the two changes.

This is an illustrative response, not a recording of a live agent run. Open FM01 and the maintenance evidence. Ask learners to identify the fact, hypothesis and unanswered question.

35. A report draft that keeps an open issue visible

Use the same three headings every time: status, evidence and next action.

Status: Pilot delivery results improved.

Evidence: Strainer replacement and verification occurred together.

Next action: Complete the removed-strainer review before claiming a cause.

Read the source note in Trainer-Demonstrations/README.md. Show how a report template makes the distinction between observed improvement and proven cause visible. Ask why changing an open review to completed would be an error.

38. Check a grounded answer against a real passage

Use the supplied fictional document TR-401, revision 1.

Question: “Which measurement fields must we record?”

Answer: “Test ID, timestamp, volume in litres and duration in seconds.”

Check: Clause 1 lists those four fields. It does not approve a delivery limit.

Open Trainer-Demonstrations/TR-401-Training-Extract.pdf and read clause 1. Ask the follow-up about an approved limit: the correct answer is not specified. Demonstrate that a citation is useful only when the passage supports the answer.

Using the expanded 259-slide deck

Slides 1–138 are the one-day teaching route. Slide 139 introduces optional reference material. Slides 140–259 contain 30 worked examples; they are not additional scheduled labs. Keep the original six-module timetable and the 20/20/25-minute guided Excel exercises.

Reference index: FMEA slides 140-163; DMAIC 164-187; SPC 188-219; Prompting 220-239; Agents 240-247; Grounding 248-255; Security 256-259.

Each reference example follows data, prompt, illustrative answer and verification. Supporting CSVs, prompts and Worked-Examples.pdf are in Reference-Examples. The trainer demonstrations use the supplied Trainer-Demonstrations pack.

Open Microsoft 365 Copilot

Microsoft 365 Copilot — sign in with your work or school account.

Get started with Copilot in Excel — Excel analysis guidance.

How Copilot Chat works in Microsoft 365 apps — Word, Excel and PowerPoint guidance.

If the Copilot button is missing, use the approved manual-formula fallback and tell the trainer. Availability depends on your organisation’s licence and settings.

Interface screenshots

Use these current Microsoft 365 web interfaces to locate Copilot. Your tenant layout may differ slightly.

Microsoft 365 Copilot home — Chat and Agents are available from the left navigation when enabled.

Excel for the web — the Copilot button is shown at the lower right when available.

LO2 practical workflow: create the engineering output with Copilot 365

Repeat five actions in each exercise: open the small Starter workbook; select the named table; open Copilot in Excel; paste the supplied RISE prompt; inspect the output and independently verify one result. Open Worked-Reference.xlsx only after the attempt.

Lab 1 - FMEA (20 minutes)

Source: Labs/Lab-01-FMEA/Starter.xlsx · named table FMEAInput.

Copilot prompt: Act as an FMEA facilitator. Use only FMEAInput and preserve every row and supplied rating. Calculate RPN = Severity × Occurrence × Detection, rank the rows, and flag Severity 9 or higher.

Add one evidence request and action per row. Show the formula. Do not invent incidents, change ratings or approve the design.

Independent check: Verify FM01: 7 × 5 × 4 = 140; confirm FM04 is flagged because Severity = 9.

Lab 2 - DMAIC (20 minutes)

Source: Labs/Lab-02-DMAIC/Starter.xlsx · named table WeeklyData.

Copilot prompt: Act as a Six Sigma project assistant. Use only WeeklyData. Calculate Baseline and Pilot deviation rates. Create a five-row Define, Measure, Analyse, Improve, Control summary. Separate facts from hypotheses, show formulas, and state that the short pilot does not prove cause.

Independent check: Verify Baseline = 36/400 = 9.0% and Pilot = 7/200 = 3.5%; do not claim causation.

Lab 3 - SPC (25 minutes)

Source: Labs/Lab-03-SPC/Starter.xlsx · named table PumpReadings.

Copilot prompt: Act as an engineering data assistant. Use only PumpReadings. From the eight Baseline rows, calculate the mean, sample standard deviation, UCL and LCL. Flag T09–T12, create a line chart with the limits, and give a three-sentence interpretation. Show formulas. Do not claim a root cause or that the pump is safe.

Independent check: Verify T10 = 59.4 L/h against the calculated LCL; interpret a signal as a reason to investigate.

Microsoft 365 Copilot links

Microsoft 365 Copilot: https://m365.cloud.microsoft/chat

Get started with Copilot in Excel: https://support.microsoft.com/en-us/office/get-started-with-copilot-in-excel

How Copilot Chat works in Microsoft 365 apps: https://support.microsoft.com/en-us/microsoft-365-copilot/how-copilot-chat-works-in-microsoft-365-apps