

Lab 11 - Prompt and Specification Pack

Captions, Overlays, Safe Areas and Export Profiles Generative AI for Image and Video Creation
(TGS-2020505925) | Version v11.0 | 6 September 2026

Export is where a good asset gets ruined quietly. This pack is the delivery specification, the caption style rules and the acceptance checklist that make the constraints testable.

Currency note. Model identifiers and API parameters quoted anywhere in this pack were verified against the official vendor documentation on 6 September 2026. Model IDs change; re-verify before relying on one. Identifiers known to be deprecated are marked as such rather than quietly removed, so you can recognise them in older material.

Delivery ladder specification

```
{
  "ladder": "NQ-HARBOUR-AW26",
  "source": {"width": 1920, "height": 1080, "fps": 25, "duration_s": 12},
  "profiles": [
    {"name": "16x9", "width": 1920, "height": 1080, "reframe": "none",
      "safe_inset": 0.05, "min_cap_height_px": 34, "max_bytes": 12000000},
    {"name": "1x1", "width": 1080, "height": 1080, "reframe": "centre_crop",
      "safe_inset": 0.06, "min_cap_height_px": 30, "max_bytes": 9000000},
    {"name": "9x16", "width": 1080, "height": 1920, "reframe": "centre_crop",
      "safe_inset": 0.08, "min_cap_height_px": 36, "max_bytes": 12000000}
  ],
  "rule": "caption plate and logo must lie ENTIRELY inside the safe rectangle in every profile;
  verify, do not assume"
}
```

Caption style rules

1. Every caption sits on an opaque plate. Never bare text over picture.
2. Measured H-glyph height is at least the profile minimum AND at least 3% of frame height.
3. Plate-to-text luminance ratio at least 4:1, measured, not judged.
4. One line where possible; two maximum; never three.
5. A cue is on screen for at least 1.2 s regardless of how short the text is.
6. Cues never overlap. Verify programmatically before rendering.
7. Caption origin is computed from the safe rectangle, never a fixed offset.

Reframing decision record

PROFILE: 9x16
 DECISION: centre crop
 LOSES: 68.36% of the source width (the boardwalk on both sides)
 REASON: the subject occupies the central third in every shot, and a letterbox would leave about 68.36% of a phone screen as bars. The lost boardwalk is context, not product.
 ALTERNATIVE CONSIDERED: letterbox - rejected on screen-use grounds.
 RE-SHOOT NOTE: shots 2 and 3 should be framed with a 9:16 protect area next time.

Export acceptance checklist

- [] Three renditions exist at the specified dimensions.
- [] Each rendition duration equals the source duration to within one frame.
- [] Every caption cue verified inside the safe rectangle, per profile.
- [] Logo verified inside the safe rectangle, per profile.
- [] Achieved H-glyph height recorded in px and as % of frame height, per profile.
- [] Plate-to-text luminance ratio measured and recorded.
- [] File size and bit-rate recorded against the profile limit, PASS or FAIL stated.
- [] Any size failure reported WITH the lever that would fix it - not hidden by a silent re-encode.
- [] Provenance label inherited from the source and present on every derivative.

© 2026 Tertiary Infotech Academy Pte Ltd. UEN: 201200696W. Course material for TGS-2020505925, version v11.0.