Lab 11 - Blocks, Attributes and Part Lists

Course: WSQ Technical Drawing with AutoCAD (TGS-2021005538) | Topic 04: Organizing Objects

Objective: LO3 - create part lists using AutoCAD (A4, K4)

Goal

Inspect a reusable block library and a drawing containing dynamic blocks, then define a part-tag block with attributes and prepare its data for the part list.

You'll produce

A BALLOON block with PART_NO / DESC / QTY attributes, plus evidence that one library block and one dynamic-block state can be inserted and edited correctly.

Commands / tools: BLOCK, WBLOCK, DesignCenter, ATTDEF, INSERT, ATTEDIT, dynamic-block grips, DATAEXTRACTION

Files in this lab

- title-block.dwg - AutoCAD drawing file
- architecture-library.dwg - AutoCAD drawing file
- new-office-dynamic-blocks.dwg - AutoCAD drawing file

Step-by-step

1. Open architecture-library.dwg in DesignCenter and insert one reusable symbol into a new drawing

```
ADCENTER → Folders → architecture-library.dwg → Blocks → Insert
```

2. Open new-office-dynamic-blocks.dwg and change one dynamic block's grip or visibility state

```
OPEN new-office-dynamic-blocks.dwg → select dynamic block → grip / Properties
```

3. Open title-block.dwg and draw the balloon symbol (circle + leader stub)

```
C → radius 5
```

4. Define attributes PART_NO, DESC and QTY with prompts and default values

```
ATTDEF → tag/prompt/default
```

5. Create the block BALLOON from the circle plus its attribute definitions

```
B → name BALLOON → select objects
```

6. Insert the balloon against each component and fill in the attribute values

```
I → BALLOON → answer prompts
```

7. Edit one balloon attribute, then preview the data extraction used by the Lab 14 part list

```
ATTEDIT / EATTEDIT → DATAEXTRACTION
```

Check your work

The library block inserts at the correct scale, the dynamic state changes without exploding, and Data Extraction lists one row per BALLOON with the values you entered.