

Lab 07: Standardise Errors and Request Logs

Maps to: A5, A7

Objective: Create predictable error responses and trace a request from status to log event.

Build: error envelope and request-ID middleware

Tools: HTTPException, logging, middleware, OpenAI Python SDK

Lab asset inventory

- ai_vibe.py - OpenAI Python SDK runner with Pydantic structured output and safe generated-file paths
- mock-data.json - authorised synthetic scenario, route contract and test cases
- mock-database.sqlite - inspectable SQLite database seeded only with synthetic commerce and CRM records
- Prompts.pdf - learner-facing first-run, refinement and review prompts
- Prompts.md - copyable source used by the SDK runner
- working-files/ - complete FastAPI, SQLite, HTML/CSS/JavaScript project, including VS Code REST Client requests

AI vibe-coding control loop

Prompts.pdf → ai_vibe.py → Responses API → CodeBundle → working-files/generated/ → pytest + human review

Detailed procedure

Step 1 - Read Prompts.pdf and identify the role, context, constraints, target files and verification checks.

1. Perform the action exactly as stated: Read Prompts.pdf and identify the role, context, constraints, target files and verification checks.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 2 - Inspect mock-data.json; remove any personal, confidential or live credential data before prompting.

1. Perform the action exactly as stated: Inspect mock-data.json; remove any personal, confidential or live credential data before prompting.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 3 - Run python ai_vibe.py --dry-run to validate and preview the exact SDK request without using API credits.

1. Perform the action exactly as stated: Run python ai_vibe.py --dry-run to validate and preview the exact SDK request without using API credits.
2. Observe the resulting file, HTTP response, log or browser state.

3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 4 - Set OPENAI_API_KEY in the shell and choose an available OPENAI_MODEL; never paste either value into source files.

1. Perform the action exactly as stated: Set OPENAI_API_KEY in the shell and choose an available OPENAI_MODEL; never paste either value into source files.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 5 - Run python ai_vibe.py and inspect the typed CodeBundle written under working-files/generated/.

1. Perform the action exactly as stated: Run python ai_vibe.py and inspect the typed CodeBundle written under working-files/generated/.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 6 - Review the generated diff and copy only accepted changes into the working application.

1. Perform the action exactly as stated: Review the generated diff and copy only accepted changes into the working application.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 7 - Add request-ID middleware that accepts or creates X-Request-ID.

1. Perform the action exactly as stated: Add request-ID middleware that accepts or creates X-Request-ID.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 8 - Log method, path, status and elapsed time without logging secrets.

1. Perform the action exactly as stated: Log method, path, status and elapsed time without logging secrets.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 9 - Raise 404 for missing products and 409 for duplicate titles.

1. Perform the action exactly as stated: Raise 404 for missing products and 409 for duplicate titles.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.

4. Save one evidence item before continuing.

Step 10 - Add an exception handler for the public error envelope.

1. Perform the action exactly as stated: Add an exception handler for the public error envelope.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 11 - Trigger each error and match the response request_id to the log.

1. Perform the action exactly as stated: Trigger each error and match the response request_id to the log.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 12 - Confirm stack traces are absent from public JSON.

1. Perform the action exactly as stated: Confirm stack traces are absent from public JSON.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 13 - Run pytest -q and the lab acceptance checks; refine the prompt with the observed failure evidence when needed.

1. Perform the action exactly as stated: Run pytest -q and the lab acceptance checks; refine the prompt with the observed failure evidence when needed.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 14 - Save the prompt, model name, generated bundle summary and test result as the lab evidence trail.

1. Perform the action exactly as stated: Save the prompt, model name, generated bundle summary and test result as the lab evidence trail.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Acceptance criteria

- 404 and 409 use the same envelope; each response request ID locates one log trace; secrets are absent.
- Evidence names the lab number and the mapped codes: A5, A7.
- The saved SDK evidence records the prompt, model, assumptions, generated file list and verification result.
- mock-database.sqlite contains synthetic seed data only; no .env, live credential, virtual environment or runtime northstar.db is submitted.

Evidence checklist

- ☐ Prompts.pdf reviewed and dry run captured
- ☐ mock-data.json contains synthetic data only
- ☐ mock-database.sqlite opens in VS Code SQLite Viewer
- ☐ SDK CodeBundle saved under working-files/generated/
- ☐ Generated diff reviewed before applying
- ☐ Working artifact
- ☐ Request/response or test output
- ☐ One failure diagnosis
- ☐ Acceptance criterion confirmed