

Lab 10: Implement SQLite CRUD and Orders Safely

Maps to: A3, A4, A5

Objective: Connect product, customer and order operations to parameterized SQL and atomic transactions.

Build: repository.py with catalog, CRM and order transaction functions

Tools: sqlite3, FastAPI, pytest, OpenAI Python SDK

Lab asset inventory

- ai_vibe.py - OpenAI Python SDK runner with Pydantic structured output and safe generated-file paths
- mock-data.json - authorised synthetic scenario, route contract and test cases
- mock-database.sqlite - inspectable SQLite database seeded only with synthetic commerce and CRM records
- Prompts.pdf - learner-facing first-run, refinement and review prompts
- Prompts.md - copyable source used by the SDK runner
- working-files/ - complete FastAPI, SQLite, HTML/CSS/JavaScript project, including VS Code REST Client requests

AI vibe-coding control loop

Prompts.pdf → ai_vibe.py → Responses API → CodeBundle → working-files/generated/ → pytest + human review

Detailed procedure

Step 1 - Read Prompts.pdf and identify the role, context, constraints, target files and verification checks.

1. Perform the action exactly as stated: Read Prompts.pdf and identify the role, context, constraints, target files and verification checks.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 2 - Inspect mock-data.json; remove any personal, confidential or live credential data before prompting.

1. Perform the action exactly as stated: Inspect mock-data.json; remove any personal, confidential or live credential data before prompting.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 3 - Run python ai_vibe.py --dry-run to validate and preview the exact SDK request without using API credits.

1. Perform the action exactly as stated: Run python ai_vibe.py --dry-run to validate and preview the exact SDK request without using API credits.

2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 4 - Set OPENAI_API_KEY in the shell and choose an available OPENAI_MODEL; never paste either value into source files.

1. Perform the action exactly as stated: Set OPENAI_API_KEY in the shell and choose an available OPENAI_MODEL; never paste either value into source files.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 5 - Run python ai_vibe.py and inspect the typed CodeBundle written under working-files/generated/.

1. Perform the action exactly as stated: Run python ai_vibe.py and inspect the typed CodeBundle written under working-files/generated/.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 6 - Review the generated diff and copy only accepted changes into the working application.

1. Perform the action exactly as stated: Review the generated diff and copy only accepted changes into the working application.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 7 - Implement create_product with placeholders and return the inserted row.

1. Perform the action exactly as stated: Implement create_product with placeholders and return the inserted row.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 8 - Implement list_products with bounded limit/offset and optional status filter.

1. Perform the action exactly as stated: Implement list_products with bounded limit/offset and optional status filter.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 9 - Implement create_customer and reject duplicate email addresses.

1. Perform the action exactly as stated: Implement create_customer and reject duplicate email addresses.
2. Observe the resulting file, HTTP response, log or browser state.

3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 10 - Implement create_order as one transaction that checks stock, inserts order rows and decrements stock.

1. Perform the action exactly as stated: Implement create_order as one transaction that checks stock, inserts order rows and decrements stock.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 11 - Implement dynamic PATCH SQL from a validated allow-list of fields.

1. Perform the action exactly as stated: Implement dynamic PATCH SQL from a validated allow-list of fields.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 12 - Implement delete_product and inspect rowcount.

1. Perform the action exactly as stated: Implement delete_product and inspect rowcount.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 13 - Run CRUD and injection-shaped-input tests against a temporary database.

1. Perform the action exactly as stated: Run CRUD and injection-shaped-input tests against a temporary database.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 14 - Run pytest -q and the lab acceptance checks; refine the prompt with the observed failure evidence when needed.

1. Perform the action exactly as stated: Run pytest -q and the lab acceptance checks; refine the prompt with the observed failure evidence when needed.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.
4. Save one evidence item before continuing.

Step 15 - Save the prompt, model name, generated bundle summary and test result as the lab evidence trail.

1. Perform the action exactly as stated: Save the prompt, model name, generated bundle summary and test result as the lab evidence trail.
2. Observe the resulting file, HTTP response, log or browser state.
3. If the expected state is absent, compare the request contract, status code and latest log entry.

4. Save one evidence item before continuing.

Acceptance criteria

- Catalog/CRM CRUD and order tests pass, insufficient stock rolls back fully, missing IDs map to 404 and SQL values are parameter-bound.
- Evidence names the lab number and the mapped codes: A3, A4, A5.
- The saved SDK evidence records the prompt, model, assumptions, generated file list and verification result.
- mock-database.sqlite contains synthetic seed data only; no .env, live credential, virtual environment or runtime northstar.db is submitted.

Evidence checklist

- ☐ Prompts.pdf reviewed and dry run captured
- ☐ mock-data.json contains synthetic data only
- ☐ mock-database.sqlite opens in VS Code SQLite Viewer
- ☐ SDK CodeBundle saved under working-files/generated/
- ☐ Generated diff reviewed before applying
- ☐ Working artifact
- ☐ Request/response or test output
- ☐ One failure diagnosis
- ☐ Acceptance criterion confirmed