

Activity 04 acceptance checklist

EtherChannel and STP resilience

TGS-2023037854 | v7.0 | 100 minutes

Learner: _____ Date: _____

- ☐ 1. I built the compulsory simulator topology using the exact models, named ports and endpoint addresses.
- ☐ 2. I installed every peer baseline configuration and saved the CONFIGURED healthy baseline.
- ☐ 3. I observed the baseline traffic matrix on the simulator and captured actual show output.
- ☐ 4. I introduced the specified controlled fault and proved the affected and unaffected flows.
- ☐ 5. I applied the narrow repair and repeated the allowed, denied and failure/recovery tests where specified.
- ☐ 6. I rehearsed rollback from the saved healthy baseline and observed recovered traffic.
- ☐ 7. I calculated the relevant addressing, cost, tuple or policy results before editing fixtures.
- ☐ 8. I captured the original faulty fixture FAIL controls and explained their cause.
- ☐ 9. The corrected JSON fixture passes every contract; self-test rejects faulty and corrupted controls.
- ☐ 10. I distinguished fixture calculations from actual simulator results and recorded unsupported advanced features honestly.
- ☐ 11. I submitted the verified .pkt file, actual show/traffic evidence, corrected case.json and diagnosis.

Evidence note

The core simulator construction is compulsory. Separately labelled unsupported extensions may be evidence-only. Fixture PASS does not prove live forwarding, authentication or deployment.

Trainer / peer review: _____

Actual simulator acceptance tests

S1/S2 show etherchannel summary: Po1(SU), both Fa0/23 and Fa0/24 show (P). show spanning-tree vlan 10: S1 is root. The configured Po1 STP cost3 is lower than Gi0/1 cost4. Therefore S2 Po1 root forwarding, Gi0/1 alternate. PC1 ping PC2 succeeds. After Po1 shutdown Gi0/1 becomes forwarding. Measure actual simulated interruption; offline 2.1s is a synthetic example, not your measured result.

☐ Healthy baseline observed ☐ Controlled fault observed ☐ Repair verified

Observed outcomes / differences: _____

Fixture acceptance controls

- ☐ LACP initiation
- ☐ channel member consistency
- ☐ intended STP root
- ☐ one redundant alternate
- ☐ alternate takes over within budget