

Activity 05 acceptance checklist

Wireless WLAN and policy mapping

TGS-2023037854 | v7.0 | 90 minutes

Learner: _____ Date: _____

- ☐ 1. I built the compulsory simulator topology using the exact models, named ports and endpoint addresses.
- ☐ 2. I installed every peer baseline configuration and saved the CONFIGURED healthy baseline.
- ☐ 3. I observed the baseline traffic matrix on the simulator and captured actual show output.
- ☐ 4. I introduced the specified controlled fault and proved the affected and unaffected flows.
- ☐ 5. I applied the narrow repair and repeated the allowed, denied and failure/recovery tests where specified.
- ☐ 6. I rehearsed rollback from the saved healthy baseline and observed recovered traffic.
- ☐ 7. I calculated the relevant addressing, cost, tuple or policy results before editing fixtures.
- ☐ 8. I captured the original faulty fixture FAIL controls and explained their cause.
- ☐ 9. The corrected JSON fixture passes every contract; self-test rejects faulty and corrupted controls.
- ☐ 10. I distinguished fixture calculations from actual simulator results and recorded unsupported advanced features honestly.
- ☐ 11. I submitted the verified .pkt file, actual show/traffic evidence, corrected case.json and diagnosis.

Evidence note

The core simulator construction is compulsory. Separately labelled unsupported extensions may be evidence-only. Fixture PASS does not prove live forwarding, authentication or deployment.

Trainer / peer review: _____

Actual simulator acceptance tests

W1 GUI > Wireless > Basic Wireless Settings: SSID CCNA-Staff, channel6; Save Settings. Wireless Security: WPA2 Personal, AES, create a training-only passphrase of at least12 characters; Save Settings. On each laptop Desktop > PC Wireless > Connect choose CCNA-Staff and enter that phrase; Desktop > IP Configuration > DHCP. Expect 192.168.20.100+ leases with gateway192.168.20.1. L1/L2 ping 192.168.20.1 and ADMIN192.168.20.10 should succeed. Wrong PSK association must fail. Capture SSID/security/channel and DHCP evidence without showing the passphrase.

☐ Healthy baseline observed ☐ Controlled fault observed ☐ Repair verified

Observed outcomes / differences: _____

Fixture acceptance controls

- ☐ staff enterprise and VLAN20
- ☐ clients match WLAN subnet
- ☐ 2.4GHz plan 1 6 11
- ☐ CAPWAP control and local data
- ☐ guest isolation