

Activity 06 acceptance checklist

Static routing and IPv6

TGS-2023037854 | v7.0 | 100 minutes

Learner: _____ Date: _____

- ☐ 1. I built the compulsory simulator topology using the exact models, named ports and endpoint addresses.
- ☐ 2. I installed every peer baseline configuration and saved the CONFIGURED healthy baseline.
- ☐ 3. I observed the baseline traffic matrix on the simulator and captured actual show output.
- ☐ 4. I introduced the specified controlled fault and proved the affected and unaffected flows.
- ☐ 5. I applied the narrow repair and repeated the allowed, denied and failure/recovery tests where specified.
- ☐ 6. I rehearsed rollback from the saved healthy baseline and observed recovered traffic.
- ☐ 7. I calculated the relevant addressing, cost, tuple or policy results before editing fixtures.
- ☐ 8. I captured the original faulty fixture FAIL controls and explained their cause.
- ☐ 9. The corrected JSON fixture passes every contract; self-test rejects faulty and corrupted controls.
- ☐ 10. I distinguished fixture calculations from actual simulator results and recorded unsupported advanced features honestly.
- ☐ 11. I submitted the verified .pkt file, actual show/traffic evidence, corrected case.json and diagnosis.

Evidence note

The core simulator construction is compulsory. Separately labelled unsupported extensions may be evidence-only. Fixture PASS does not prove live forwarding, authentication or deployment.

Trainer / peer review: _____

Actual simulator acceptance tests

PC1 ping 10.10.20.20 and ping 2001:db8:20::20; PC2 ping 10.10.10.10 and ping 2001:db8:10::10. All repeated baseline/repair pings succeed. R1/R2 show ip route and show ipv6 route show S routes; show ipv6 neighbors shows fe80 peer on Gi0/1. Add host route on R1: ip route 10.10.20.20 255.255.255.255 10.0.0.2; show ip route 10.10.20.20 chooses /32. Add a floating static with distance200 to the SAME next hop and inspect that distance1 wins; it is not a physically diverse backup. Use the independent offline two-next-hop fixture to verify real backup selection under route withdrawal.

☐ Healthy baseline observed ☐ Controlled fault observed ☐ Repair verified

Observed outcomes / differences: _____

Fixture acceptance controls

- ☐ host route longest match
- ☐ floating distance greater
- ☐ backup selected after withdrawal
- ☐ IPv6 link-local scope