

Activity 07 acceptance checklist

OSPF and gateway failover

TGS-2023037854 | v7.0 | 120 minutes

Learner: _____ Date: _____

- ☐ 1. I built the compulsory simulator topology using the exact models, named ports and endpoint addresses.
- ☐ 2. I installed every peer baseline configuration and saved the CONFIGURED healthy baseline.
- ☐ 3. I observed the baseline traffic matrix on the simulator and captured actual show output.
- ☐ 4. I introduced the specified controlled fault and proved the affected and unaffected flows.
- ☐ 5. I applied the narrow repair and repeated the allowed, denied and failure/recovery tests where specified.
- ☐ 6. I rehearsed rollback from the saved healthy baseline and observed recovered traffic.
- ☐ 7. I calculated the relevant addressing, cost, tuple or policy results before editing fixtures.
- ☐ 8. I captured the original faulty fixture FAIL controls and explained their cause.
- ☐ 9. The corrected JSON fixture passes every contract; self-test rejects faulty and corrupted controls.
- ☐ 10. I distinguished fixture calculations from actual simulator results and recorded unsupported advanced features honestly.
- ☐ 11. I submitted the verified .pkt file, actual show/traffic evidence, corrected case.json and diagnosis.

Evidence note

The core simulator construction is compulsory. Separately labelled unsupported extensions may be evidence-only. Fixture PASS does not prove live forwarding, authentication or deployment.

Trainer / peer review: _____

Actual simulator acceptance tests

R1/R2 show ip ospf neighbor: FULL adjacency on Gi0/1; R2/R3 FULL on their transit link. R1 show ip route ospf includes 10.10.20.0/24; R2 learns 10.10.10.0/24 through equal advertised LAN paths according to cost. show standby brief: R1 Active, R3 Standby, VIP 10.10.10.254. PC1 ping 10.10.20.20 succeeds. After R1 isolation R3 Active and PC1 remote ping recovers using unchanged gateway. Capture before/failure/recovery route and HSRP outputs.

☐ Healthy baseline observed ☐ Controlled fault observed ☐ Repair verified

Observed outcomes / differences: _____

Fixture acceptance controls

- ☐ unique router IDs
- ☐ compatible adjacency
- ☐ lowest OSPF path cost
- ☐ single virtual gateway owner
- ☐ refresh OSPFv3 IPv6 adjacency
- ☐ refresh VRRP unique master