

Activity 08 acceptance checklist

NAT DHCP DNS and time

TGS-2023037854 | v7.0 | 100 minutes

Learner: _____ Date: _____

- ☐ 1. I built the compulsory simulator topology using the exact models, named ports and endpoint addresses.
- ☐ 2. I installed every peer baseline configuration and saved the CONFIGURED healthy baseline.
- ☐ 3. I observed the baseline traffic matrix on the simulator and captured actual show output.
- ☐ 4. I introduced the specified controlled fault and proved the affected and unaffected flows.
- ☐ 5. I applied the narrow repair and repeated the allowed, denied and failure/recovery tests where specified.
- ☐ 6. I rehearsed rollback from the saved healthy baseline and observed recovered traffic.
- ☐ 7. I calculated the relevant addressing, cost, tuple or policy results before editing fixtures.
- ☐ 8. I captured the original faulty fixture FAIL controls and explained their cause.
- ☐ 9. The corrected JSON fixture passes every contract; self-test rejects faulty and corrupted controls.
- ☐ 10. I distinguished fixture calculations from actual simulator results and recorded unsupported advanced features honestly.
- ☐ 11. I submitted the verified .pkt file, actual show/traffic evidence, corrected case.json and diagnosis.

Evidence note

The core simulator construction is compulsory. Separately labelled unsupported extensions may be evidence-only. Fixture PASS does not prove live forwarding, authentication or deployment.

Trainer / peer review: _____

Actual simulator acceptance tests

PC1 ipconfig shows 10.10.10.21+ /24 gateway 10.10.10.1 DNS 192.0.2.50. PC1 ping 192.0.2.50 succeeds. Browser http://app.example.test returns the PT server page. R1 show ip dhcp binding shows the leased client; show ip nat translations during traffic shows inside local 10.10.10.x mapped to inside global 10.0.0.1; show ntp associations/status should show synchronized peer if the PT NTP model supports it. In Simulation inspect DHCP DORA, DNS question/answer and NAT address rewrite.

☐ Healthy baseline observed ☐ Controlled fault observed ☐ Repair verified

Observed outcomes / differences: _____

Fixture acceptance controls

- ☐ PAT tuple disambiguation
- ☐ DHCP scope and options
- ☐ DNS forward and refresh records
- ☐ NTP selected synchronized source
- ☐ secure transfer integrity