

Activity 10 acceptance checklist

Layer2 and wireless security

TGS-2023037854 | v7.0 | 90 minutes

Learner: _____ Date: _____

- ☐ 1. I built the compulsory simulator topology using the exact models, named ports and endpoint addresses.
- ☐ 2. I installed every peer baseline configuration and saved the CONFIGURED healthy baseline.
- ☐ 3. I observed the baseline traffic matrix on the simulator and captured actual show output.
- ☐ 4. I introduced the specified controlled fault and proved the affected and unaffected flows.
- ☐ 5. I applied the narrow repair and repeated the allowed, denied and failure/recovery tests where specified.
- ☐ 6. I rehearsed rollback from the saved healthy baseline and observed recovered traffic.
- ☐ 7. I calculated the relevant addressing, cost, tuple or policy results before editing fixtures.
- ☐ 8. I captured the original faulty fixture FAIL controls and explained their cause.
- ☐ 9. The corrected JSON fixture passes every contract; self-test rejects faulty and corrupted controls.
- ☐ 10. I distinguished fixture calculations from actual simulator results and recorded unsupported advanced features honestly.
- ☐ 11. I submitted the verified .pkt file, actual show/traffic evidence, corrected case.json and diagnosis.

Evidence note

The core simulator construction is compulsory. Separately labelled unsupported extensions may be evidence-only. Fixture PASS does not prove live forwarding, authentication or deployment.

Trainer / peer review: _____

Actual simulator acceptance tests

PC1/PC2 get 10.10.10.100+ leases; ping 10.10.10.1 succeeds. S1 show port-security interface FastEthernet0/1 displays secure-up/max1 and violation counter; show port-security address displays PC1 MAC. show ip dhcp snooping shows VLAN10 and only Fa0/24 trusted; show ip dhcp snooping binding shows clients if supported by PT. DAI/storm-control/RA Guard may be absent on the selected PT model; test core snooping and port security, then inspect extension fixture separately.

☐ Healthy baseline observed ☐ Controlled fault observed ☐ Repair verified

Observed outcomes / differences: _____

Fixture acceptance controls

- ☐ untrusted endpoints
- ☐ trusted infrastructure uplink
- ☐ DAI binding matches ARP
- ☐ refresh RA guard at edge
- ☐ refresh storm threshold bounded
- ☐ enterprise AES no embedded PSK