

Lab 22 - Expected verification output

Run from the lab directory:

```
bash verification/checks.sh
```

Honesty note

checks.sh is read-only: it creates, patches and deletes nothing. It is a live check - it queries your cluster with kubectl, so it can only pass after you have actually worked through the procedure in README.md.

The transcript below is the shape of a fully passing run. Counts of ready replicas and endpoint addresses depend on how far through the lab you are.

Fully passing run

```
== Namespace isolation
PASS namespace kcna-lab22 exists
PASS Pod Security Admission enforce=baseline

== Part 1 - content ConfigMap sourced from data/
PASS configmap/depot-portal-content exists
PASS configmap key 'index.html' is populated
PASS configmap key 'ready.html' is populated

== Part 2 - depot-portal probes
PASS deployment/depot-portal exists
PASS readinessProbe configured (path=/ready.html)
PASS livenessProbe configured (path=/index.html)
PASS readiness and liveness target DIFFERENT paths (/ready.html vs /index.html)
PASS container image is pinned (nginx:1.27-alpine)
PASS depot-portal has 2 ready replica(s)

== Part 3 - Service backends via EndpointSlice
PASS service/depot-portal exists
PASS EndpointSlice carries 2 backend address(es)

== Part 4 - manifest-indexer startup probe
PASS deployment/manifest-indexer exists
PASS startupProbe present (failureThreshold=24 x periodSeconds=5s = 120s budget)
PASS startup budget 120s exceeds the app's ~40s boot time
PASS manifest-indexer reached Ready with 0 restarts

== Part 6 - failure injection cleaned up
PASS injected deployment manifest-indexer-outage removed

== Worksheet
PASS worksheet present at data/probe-tuning-worksheet.csv
PASS worksheet header intact

== Blast-radius guard
PASS no lab-22 objects in kube-system

SUMMARY: 18 passed, 0 failed
```

Exit code 0.

Common partial runs and what they mean

You ran the checks before Part 4

```
== Part 4 - manifest-indexer startup probe
  FAIL deployment/manifest-indexer missing - see Step 4.1

SUMMARY: 14 passed, 1 failed
```

Exit code 1. Apply manifests/20-manifest-indexer-startup.yaml and re-run.

You ran the checks during Part 6, before cleanup

```
== Part 6 - failure injection cleaned up
  FAIL manifest-indexer-outage still present - see Step 6.10

SUMMARY: 17 passed, 1 failed
```

This is expected mid-lab. Complete Step 6.10 and re-run.

You ran the checks in the 40-second startup window

```
FAIL depot-portal has no ready replicas yet - wait, then re-run
```

Not a defect - you are inside the probe's grace window. Wait ~45 seconds and re-run. If it never clears, work through the Troubleshooting table in README.md.

Manual observations the script cannot make for you

The script can confirm configuration and end state. It cannot confirm that you watched the transition happen, which is the actual learning objective. Before you sign off, be sure you personally observed all four:

#	Observation	Where
1	An address leaving the EndpointSlice within ~13 s of deleting ready.html	Step 3.7
2	RESTARTS remaining at 0 while the Pod was 0/1	Step 3.8
3	Five consecutive successful requests through the degraded Deployment	Step 3.10
4	Killing ... failed liveness probe, will be restarted in the injected Deployment's events	Step 6.4