



RUST

AI VIBE CODING

COURSE SLIDES · WSQ

AI Vibe Coding with Rust


WSQ Course Code: TGS-2023039924

Conducted by Tertiary Infotech Academy Pte Ltd · UEN 201200696W

Trainer: Dr Alfred Ang

Version 3.0 · 27 September 2026

© 2026 Tertiary Infotech Academy Pte Ltd. All rights reserved. · www.tertiarycourses.com.sg



Course illustration: Activity 1 code and its real cargo test result

Digital Attendance (Mandatory)

1

TRAQOM / SSG

Take the digital attendance through the Singpass app when the trainer displays the QR code.

2

AM, PM and assessment

Attendance is taken for each session and separately for the assessment.

3

75% minimum

At least 75% attendance is required for assessment eligibility and funding.

4

Your own record

Use only your own Singpass; tell the trainer if the course title or code does not match.

About the Trainer



General Trainer

Complete before delivery

NAME

DESIGNATION

QUALIFICATIONS

EXPERTISE

INDUSTRY / TRAINING EXPERIENCE

CONTACT

About the Trainer



Dr Alfred Ang

Founder / Trainer, Tertiary Infotech
Academy

COURSE

AI Vibe Coding with Rust

FOCUS

AI-assisted software development, programming and software design

TRAINING APPROACH

Specification first, vibe-coded drafts, compiler + tests as the gate

CONTACT

enquiry@tertiaryinfotech.com

Learner Introduction

1

Your name and role

What do you do at work today?

2

Programming background

Any language: Python, JavaScript, C, none yet?

3

AI coding tools

Which assistant have you tried: Copilot, Claude, ChatGPT?

4

Your goal

One tool or service you would like to build in Rust.

Ground Rules

1

Your code, your call

AI drafts; you accept only what you can explain.

2

Evidence over opinion

cargo test, clippy and fmt decide "done", not the AI.

3

Privacy

Never paste passwords, keys, personal data or assessment answers into AI tools.

4

Respect

Phones on silent; ask questions early; help without giving answers.

Course Outline

1

Topic 1

Rust Programming Fundamentals and Software Components

2

Topic 2

AI Vibe Coding for Rust Application Development

3

Topic 3

Rust Programming Controls, Functions and Features

4

Topic 4

Testing, Debugging and Integrating Rust Components

5

Topic 5

AI-Assisted Rust Software Design and Documentation

6

Assessment

Written Assessment + Practical Performance

Lesson Plan / two days

Time	Day 1	Day 2
Morning	9:30-11:30 Topic 1 / 2h; 11:30-12:30 Topic 2 / 1h	9:30-12:30 Topic 4 / 3h
12:30-1:30 PM	Lunch / 1 hour	Lunch / 1 hour
Afternoon	1:30-3:30 Topic 2 / 2h; 3:30-6:30 Topic 3 / 3h	1:30-4:30 Topic 5 / 3h
Assessment	No assessment on Day 1	WA 4:30-5:30 PM / PP 5:30-6:30 PM

WHEN IT MATTERS Topic durations 2/3/3/3/3 hours. Day 1: 8 training hours. Day 2: 6 training hours + 2 assessment hours. Lunch excluded.

Learning Outcomes

1

LO1

Determine basic software components using programming methodologies to meet functional specifications

2

LO2

Apply programming methodologies and tools for software creation

3

LO3

Select essential programming controls and features to meet software design requirements

4

LO4

Examine the interoperability and functionality of programming components

5

LO5

Generate programming design documentation aligned with user specifications

Briefing for Assessment

1

Instruments

Written Assessment: 5 open-ended questions.
Practical Performance: 5 hands-on tasks.

2

What is assessed

Components, tools, controls/features,
testing/integration and documentation.

3

Conditions

Open book, individual. AI only where a PP task
explicitly allows a reviewed draft.

4

Evidence

Keep your crates, cargo output and records; upload
as instructed.

Assessment & Funding

Written Assessment

- Day 2, 4:30-5:30 PM
- 60 minutes / 5 questions
- K1-K5 / open book


Practical Performance

- Day 2, 5:30-6:30 PM
- 60 minutes / 5 tasks
- A1-A5 / Rust crates + evidence

Result and funding

- All items attempted individually
- Competent (C) or NYC
- Funding requires 75% attendance + C


Assessment Flow



ORDER OF THE DAY

Written Assessment (K1-K5) 4:30-5:30 PM, then Practical Performance (A1-A5) 5:30-6:30 PM on Day 2. Follow the assessor's submission instructions.

Download course material from the LMS



Screenshot of the live LMS sign-in page (lms-tms.tertiaryinfotech.com), captured September 2026.

1. Sign in

Open lms-tms.tertiaryinfotech.com and sign in with your email (OTP) or password.

2. Open this course

AI Vibe Coding with Rust (TGS-2023039924).

3. Download

Learner slides PDF, Learner Guide and the Activities link.

4. Assessment

Question papers open on the assessment day; upload your answers there.

[Open the LMS](#)

Get the Hands-On Activities

Course repository

- 14 activity folders
- starter/ + solution/ crates
- Data files and prompts

<https://github.com/tertiarycourses/TGS-2023039924-AI-Vibe-Coding-with-Rust>

Get a working copy

- git clone, or
- Download ZIP from GitHub
- Open a folder in VS Code

Toolchain check

- rustc --version
- cargo --version
- cargo test in solution/

HOW WE WORK

Your AI Vibe Coding workbench

The screenshot displays the AI Vibe Coding workbench interface. On the left is a code editor with a dark theme, showing Rust code for a function `line_total`. The code includes comments and a `cargo test` command at the bottom. The output of the test shows 5 tests passed and 0 failed. To the right of the editor is an 'AI coding assistant' panel. It contains a prompt from the user to implement `line_total` with specific constraints. Below the prompt is the AI's response, which includes a proposal using `checked_mul` and a list of tests. At the bottom of the panel are buttons for 'Prompt', 'Generate', 'Compile', 'Test', and 'Review'. A footer note states: 'The AI Vibe Coding loop: every draft passes the compiler and the tests.'

```
1 //! Activity 1: price one order line.
2
3 pub const MAX_QTY: u32 = 10_000;
4
5 /// Returns the line total in cents.
6 pub fn line_total(
7     unit_price_cents: u64,
8     qty: u32,
9 ) -> Option<u64> {
10     if qty == 0 || qty > MAX_QTY {
11         return None;
12     }
13     unit_price_cents
14         .checked_mul(u64::from(qty))
15 }
```

`$ cargo test`
`running 5 tests .....`
`test result: ok. 5 passed; 0 failed`

AI coding assistant

You: implement `line_total`. Keep the signature, no unwrap, `qty 1..=10,000`, refuse overflow. Add boundary tests.

AI: proposal uses `checked_mul` and returns `None` for 0 and 10,001.
Tests: 0, 1, 10,000, 10,001, `u64::MAX`.

Reviewer: accepted after cargo test.

Prompt Generate Compile Test Review

The AI Vibe Coding loop: every draft passes the compiler and the tests.

Editor

VS Code + rust-analyzer shows types and errors as you type.

AI assistant

Drafts code, tests and docs from a bounded prompt.

Cargo

Builds, tests, lints and formats: the objective gate.

You

Decide what is accepted, and record why.

Course illustration; the code and test result shown are from Activity 1 of this course.

TOPIC 1 / K1/A1

Rust Programming Fundamentals and Software Components

Activities 1-3 / concepts, contracts, failure modes and evidence

A specification becomes a component contract

Read the code, then the contract: what must always be true?

```
R1 price one order line in cents
R2 quantity must be 1..=10,000
R3 never wrap or lose money on overflow

component: fn line_total(
    unit_price_cents: u64,    // input
    qty: u32,                // input
) -> Option<u64>             // output or refusal
```

Requirement

Write the rule in business words before any code exists.

Input

Each input gets a type that already excludes invalid values (u32 is never negative).

Output

Option<u64> makes "refused" part of the signature, not a comment.

Evidence


Each requirement maps to at least one named test.

A specification becomes a component contract / contract

Contract field	Exact rule
Business rule	Totals are whole cents; quantity 1..=10,000; overflow is refused.
Rust types	u64 for money in cents, u32 for quantity, Option for refusal.
Component boundary	A pure function: no printing, no files, no global state.
Acceptance	Tests at 0, 1, 10,000, 10,001 and u64::MAX.

WHEN IT MATTERS Every requirement ID appears in a test name or a trace table row.

A specification becomes a component contract / failure



The Rust toolchain: rustup, cargo and rustc

Read the code, then the contract: what must always be true?

```
# install once (macOS/Linux; Windows uses rustup-init.exe)
curl https://sh.rustup.rs -sSf | sh
rustup component add clippy rustfmt

rustc --version      # the compiler
cargo --version      # build tool + package manager
cargo new stockpilot # create a package
cargo run            # build and run
cargo test           # build and run tests
```

rustup

Installs and updates Rust toolchains and components.

cargo

One command for new, build, run, test, fmt, clippy and doc.

rustc

The compiler; cargo calls it for you with the right flags.

stable


The course uses the stable channel; record the version as evidence.

The Rust toolchain: rustup, cargo and rustc / contract

Contract field	Exact rule
Install	rustup from rustup.rs; Windows also needs the MSVC build tools.
Editor	Visual Studio Code with the rust-analyzer extension.
Components	clippy (lints) and rustfmt (formatting) via rustup component add.
Evidence	rustc --version output is recorded in every verification record.

WHEN IT MATTERS rustc --version and cargo --version both print a version in the VS Code terminal.

The Rust toolchain: rustup, cargo and rustc / failure



Anatomy of a Cargo package

Read the code, then the contract: what must always be true?

```
activity01/  
  Cargo.toml      # name, edition, dependencies  
  Cargo.lock      # exact resolved versions  
  src/  
    lib.rs        # library crate: the logic  
    main.rs       # binary crate: thin entry point  
  tests/  
    acceptance.rs # integration tests (public API)  
  target/         # build output (never commit)
```

Cargo.toml

The manifest: package metadata and dependencies.

lib.rs

Holds the reusable, testable components.

main.rs

Only parses arguments, calls the library and prints results.

tests/


Each file is compiled as a separate crate that uses the public API.

Anatomy of a Cargo package / contract

Contract field	Exact rule
Package	One Cargo.toml; can contain one library and several binaries.
Crate	A compilation unit: lib.rs or main.rs and its modules.
Edition	edition = "2021" fixes the language rules the crate uses.
Build output	target/ is generated; add it to .gitignore.

WHEN IT MATTERS cargo test builds lib, bin and tests; tests only use pub items.

Anatomy of a Cargo package / failure



Variables are immutable by default

Read the code, then the contract: what must always be true?

```
let qty = 4;           // immutable binding
let mut stock = 10;    // mutable binding
stock -= qty;          // allowed: declared mut

const MAX_QTY: u32 = 10_000; // compile-time constant

let input = " 42 ";
let input: u32 = input.trim().parse().unwrap_or(0);
// shadowing: same name, new type and value
```

let

A binding cannot change unless you opt in with mut.

mut

Makes every place that changes state easy to find in review.

const

Named, typed constant; UPPER_SNAKE_CASE by convention.

Shadowing


Re-using a name with let creates a new variable, often of a new type.

Variables are immutable by default / contract

Contract field	Exact rule
Default	Immutable: accidental writes are compile errors (E0384).
Constants	Must have an explicit type; evaluated at compile time.
Naming	snake_case for variables and functions, CamelCase for types.
Review rule	Every mut should be necessary; clippy flags unused mut.

WHEN IT MATTERS The code compiles with no unused_mut warnings under clippy.

Variables are immutable by default / failure



Choose integer types deliberately

Read the code, then the contract: what must always be true?

```
let unit: u64 = 250;           // cents, never float
let qty: u32 = 4;              // cannot be negative
let total = unit * u64::from(qty); // widen, then multiply

u64::MAX.checked_mul(2)        // None
250u64.checked_mul(4)          // Some(1000)
3u32.checked_sub(5)            // None
(-4i64).abs()                  // 4
u32::try_from(-1i64)           // Err(..)
```

Money

Store cents in an integer; floats cannot represent 0.10 exactly.

Widening

`u64::from(qty)` converts losslessly before multiplying.

checked_*

Returns None instead of overflowing.

try_from


Narrowing conversions return Result because they can fail.

Choose integer types deliberately / contract

Contract field	Exact rule
u32	0..=4,294,967,295: quantities and counts.
u64	0..=18.4 quintillion: money in cents and large totals.
i64	Signed: adjustments that can be negative.
Overflow policy	Debug builds panic, release builds wrap: so use checked_* explicitly.

WHEN IT MATTERS Tests at u64::MAX and u32::MAX prove the overflow policy.

Choose integer types deliberately / failure



Functions: the signature is the contract

Read the code, then the contract: what must always be true?

```
pub fn line_total(
    unit_price_cents: u64,
    qty: u32,
) -> Option<u64> {
    if qty == 0 || qty > MAX_QTY {
        return None;           // early return
    }
    unit_price_cents.checked_mul(u64::from(qty))
    // last expression, no semicolon = return value
}
```

Parameters

Every parameter has an explicit type; nothing is inferred at the boundary.

Return type

The arrow type tells callers what they must handle.

Expression body

The final expression without ; is the value returned.

pub


Only pub functions are part of the crate API.

Functions: the signature is the contract / contract

Contract field	Exact rule
Inputs	unit_price_cents: u64, qty: u32.
Output	Some(total) or None, never a panic.
Side effects	None: no printing, files or globals.
Tests	Normal, zero, maximum, above maximum and overflow.

WHEN IT MATTERS Five boundary tests in Activity 1 pass.

Functions: the signature is the contract / failure



String and &str: owned text and borrowed text

Read the code, then the contract: what must always be true?

```
let owned: String = String::from("abc-1234");
let view: &str = &owned;           // borrow, no copy
let trimmed: &str = "  ABC-1234 ".trim();

fn is_valid_sku(code: &str) -> bool { /* reads */ }
fn normalise_sku(code: &str) -> Option<String> {
    let upper = code.trim().to_ascii_uppercase(); // new String
    is_valid_sku(&upper).then_some(upper)
}
```

String

Owns growable UTF-8 text on the heap.

&str

A borrowed view of text; the preferred parameter type.

Returning String

Needed only when the function creates new text.

UTF-8


Byte length and character count differ for non-ASCII text.

String and &str: owned text and borrowed text / contract

Contract field	Exact rule
Parameter	Accept &str so callers can pass literals or &String.
Return	String when new text is produced; &str when returning part of an input.
Validation	ASCII rules can use bytes safely; general text should use chars().
Tests	Include whitespace, lower case and a non-ASCII letter.

WHEN IT MATTERS Activity 2 tests pass, including "ÄBC-1234" being rejected.

String and &str: owned text and borrowed text / failure



Ownership moves; borrowing lends

Read the code, then the contract: what must always be true?

```
let items = vec![cable, charger];

let total = total_quantity(&items); // shared borrow
restock(&mut items[0], 3);          // exclusive borrow
let kept = in_stock(items);         // move: items is gone

// println!("{:?}", items);
// error[E0382]: borrow of moved value: `items`
```

Owner

Every value has exactly one owner; it is dropped when the owner goes out of scope.

&T

Any number of readers at once; nobody may change the value.

&mut T

Exactly one writer and no readers at the same time.

Move


Passing by value transfers ownership; the old name cannot be used.

Ownership moves; borrowing lends / contract

Contract field	Exact rule
Read only	<code>fn f(items: &[Item])</code> - caller keeps ownership.
Change in place	<code>fn f(item: &mut Item)</code> - caller sees the change.
Consume	<code>fn f(items: Vec<Item>) -> Vec<Item></code> - caller hands the value over.
Clone	An explicit copy; justify it in review because it costs memory and time.

WHEN IT MATTERS Activity 3 compiles with no clone() and all five tests pass.

Ownership moves; borrowing lends / failure



Compiler errors, failing tests and clippy warnings are evidence: read them, then act.

Turn a specification into a Rust function

ACTIVITY 1

Independent practice; full steps in the activity README and Learner Guide

StockPilot must price an order line. The specification limits quantity to 1..10,000 and forbids a silently wrapped total. You create the Cargo package, write the function and prove it with tests.

YOU'LL BUILD

labs/activity-01-line-total: complete starter/ against the tests


TOOLCHAIN

Rust stable / Cargo / VS Code + rust-analyzer / AI assistant

DONE WHEN

cargo test reports 5 passed; cargo run prints "4 x 250 cents = 1000 cents".

Turn a specification into a Rust function / workflow



EXACT CONTRACT

`line_total(unit_price_cents: u64, qty: u32) -> Option<u64>. qty 0 or above MAX_QTY (10,000) returns None; an overflowing product returns None; otherwise Some(total cents).`

Turn a specification into a Rust function / Rust

Reference solution: solution/src/lib.rs (formatted, tested, clippy-clean)

```
/// Returns the line total in cents.  
///  
/// Returns `None` when `qty` is outside `1..=MAX_QTY` or when the  
/// multiplication would overflow `u64`.  
pub fn line_total(unit_price_cents: u64, qty: u32) -> Option<u64> {  
    if qty == 0 || qty > MAX_QTY {  
        return None;  
    }  
    unit_price_cents.checked_mul(u64::from(qty))  
}
```

Specification

Quantity range and overflow policy are decided before any code is written.

Types

u64 cents avoid floating-point rounding; u32 quantity cannot be negative.

Option

None is an explicit, typed rejection that the caller must handle.

checked_mul

Overflow becomes None instead of wrapping or panicking.

Turn a specification into a Rust function / vibe-coding prompts

Plan before code

- Act as a senior Rust reviewer. Specification:
line_total(unit_price_cents: u64, qty: u32) -> Option<u64>. qty 0 or above MAX_QTY (10,000) returns None; an overflowing product returns None; otherwise Some(total cents). Before writing any code, list the public signatures, the edge cases and at least four boundary tests you would expect. Ask me about anything ambiguous.

Generate with AI

- Implement "Turn a specification into a Rust function" in starter/src so that the supplied tests pass. Keep the u64/u32 types and the Option return; use checked arithmetic only. Keep public signatures unchanged, use no unsafe code, and explain each design decision in one sentence.

Repair from evidence

- Here is my exact cargo output: <paste the first error or failing test>. Explain the cause in plain English, propose the smallest fix that keeps the specification, and add one regression test. Do not change expected values in existing tests.

Turn a specification into a Rust function / acceptance

✓ Expected result

cargo test reports 5 passed; cargo run prints "4 x 250 cents = 1000 cents". Starter before you begin: Every test that calls an unfinished function fails with "not yet implemented" from todo!().

IF IT DOESN'T WORK

Test fails

Compare expected vs actual; check the boundary and the type, never edit the expected value.

Does not compile

Read the first error and its code; rustc --explain E0XXX; ask the AI to explain before fixing.

clippy / fmt fails

Apply the suggested idiom or cargo fmt, then rerun cargo test.

Validate a product code with strings

ACTIVITY 2

Independent practice; full steps in the activity README and Learner Guide

Product codes arrive from scanners and spreadsheets with stray spaces and lower-case letters. StockPilot accepts only the SKU format AAA-9999 and normalises valid input to upper case.

YOU'LL BUILD

labs/activity-02-sku-validation: complete starter/ against the tests


TOOLCHAIN

Rust stable / Cargo / VS Code + rust-analyzer / AI assistant

DONE WHEN

cargo test reports 6 passed, including the non-ASCII and whitespace cases.

Validate a product code with strings / workflow



EXACT CONTRACT

`is_valid_sku(&str) -> bool`: after trimming, exactly 3 ASCII upper-case letters, "-", 4 ASCII digits. `normalise_sku(&str) -> Option<String>`: trimmed upper-case SKU when valid, else None.

Validate a product code with strings / Rust

Reference solution: solution/src/lib.rs (formatted, tested, clippy-clean)

```
/// Returns true when `code`, after trimming, has the form `AAA-9999`.
pub fn is_valid_sku(code: &str) -> bool {
    let bytes = code.trim().as_bytes();
    bytes.len() == 8
        && bytes[..3].iter().all(u8::is_ascii_uppercase)
        && bytes[3] == b'-'
        && bytes[4..].iter().all(u8::is_ascii_digit)
}
```

&str

The validator borrows text; it never needs to own or copy it.

trim

Returns a slice of the same text without leading or trailing whitespace.

Bytes

The format is ASCII, so byte positions are exact character positions.

String

normalise_sku returns an owned String because it creates new text.

Validate a product code with strings / vibe-coding prompts

Plan before code

- Act as a senior Rust reviewer. Specification: `is_valid_sku(&str) -> bool`: after trimming, exactly 3 ASCII upper-case letters, "-", 4 ASCII digits. `normalise_sku(&str) -> Option<String>`: trimmed upper-case SKU when valid, else None. Before writing any code, list the public signatures, the edge cases and at least four boundary tests you would expect. Ask me about anything ambiguous.

Generate with AI

- Implement "Validate a product code with strings" in `starter/src` so that the supplied tests pass. Borrow `&str` inputs, return an owned `String` only from `normalise_sku`, and do not use regex crates. Keep public signatures unchanged, use no unsafe code, and explain each design decision in one sentence.

Repair from evidence

- Here is my exact cargo output: `<paste the first error or failing test>`. Explain the cause in plain English, propose the smallest fix that keeps the specification, and add one regression test. Do not change expected values in existing tests.

Validate a product code with strings / acceptance

✓ Expected result

cargo test reports 6 passed, including the non-ASCII and whitespace cases. Starter before you begin: Every test that calls an unfinished function fails with "not yet implemented" from todo!().

IF IT DOESN'T WORK

Test fails

Compare expected vs actual; check the boundary and the type, never edit the expected value.

Does not compile

Read the first error and its code; rustc --explain E0XXX; ask the AI to explain before fixing.

clippy / fmt fails

Apply the suggested idiom or cargo fmt, then rerun cargo test.

Share inventory records with ownership and borrowing

ACTIVITY 3

Independent practice; full steps in the activity README and Learner Guide

Three StockPilot functions handle the same item list differently: one only reads it, one changes one item and one consumes the list. You choose the parameter types that express those intentions.

YOU'LL BUILD

labs/activity-03-ownership-borrowing:
complete starter/ against the tests


TOOLCHAIN

Rust stable / Cargo / VS Code + rust-
analyzer / AI assistant

DONE WHEN

cargo test reports 5 passed; the overflow
test proves the item is unchanged.

Share inventory records with ownership and borrowing / workflow



EXACT CONTRACT

Item { sku, name, qty: u32 }. total_quantity(&[Item]) -> u64 reads; restock(&mut Item, u32) -> Option<u32> changes one item and leaves it unchanged on overflow; in_stock(Vec<Item>) -> Vec<Item> consumes the list.

Share inventory records with ownership and borrowing / Rust

Reference solution: solution/src/lib.rs (formatted, tested, clippy-clean)

```
/// Borrows one item mutably and returns its new quantity.
///
/// On overflow the item is left unchanged and `None` is returned.
pub fn restock(item: &mut Item, amount: u32) -> Option<u32> {
    let new_qty = item.qty.checked_add(amount)?;
    item.qty = new_qty;
    Some(new_qty)
}
```

&[Item]

A shared borrow: many readers, no changes, caller keeps ownership.

&mut Item

An exclusive borrow: exactly one writer while the borrow lives.

Vec<Item>

Passing by value moves ownership; the caller can no longer use the list.

? on Option

checked_add(...) returns None early before the item is modified.

Share inventory records with ownership and borrowing / vibe-coding prompts

Plan before code

- Act as a senior Rust reviewer.
Specification: `Item { sku, name, qty: u32 }`. `total_quantity(&[Item]) -> u64` reads; `restock(&mut Item, u32) -> Option<u32>` changes one item and leaves it unchanged on overflow; `in_stock(Vec<Item>) -> Vec<Item>` consumes the list. Before writing any code, list the public signatures, the edge cases and at least four boundary tests you would expect. Ask me about anything ambiguous.

Generate with AI

- Implement "Share inventory records with ownership and borrowing" in `starter/src` so that the supplied tests pass. Choose `&`, `&mut` or by-value parameters to match each function's intent; avoid `clone()` unless you justify it. Keep public signatures unchanged, use no unsafe code, and explain each design decision in one sentence.

Repair from evidence

- Here is my exact cargo output: `<paste the first error or failing test>`. Explain the cause in plain English, propose the smallest fix that keeps the specification, and add one regression test. Do not change expected values in existing tests.

Share inventory records with ownership and borrowing / acceptance

✓ Expected result

cargo test reports 5 passed; the overflow test proves the item is unchanged. Starter before you begin: Every test that calls an unfinished function fails with "not yet implemented" from todo!().

IF IT DOESN'T WORK

Test fails

Compare expected vs actual; check the boundary and the type, never edit the expected value.

Does not compile

Read the first error and its code; rustc --explain E0XXX; ask the AI to explain before fixing.

clippy / fmt fails

Apply the suggested idiom or cargo fmt, then rerun cargo test.

TOPIC 2 / K2/A2

AI Vibe Coding for Rust Application Development

Activities 4-6 / concepts, contracts, failure modes and evidence

The vibe-coding loop for Rust

Read the code, then the contract: what must always be true?

```
1. intent      "parse add/remove/list commands"
2. contract    types, ranges, errors, tests
3. prompt      bounded request to the AI
4. generate     AI proposes code
5. compile     cargo build    (the first reviewer)
6. test        cargo test     (the specification)
7. review      read, question, accept or reject
8. record      decision + evidence
```

Intent

Describe the outcome in plain language, as a user would.

Contract

Pin down types, ranges and errors so the output can be judged.

Compiler + tests

Rust rejects many wrong programs before they run.

Human review


You own the code: accept only what you can explain.

The vibe-coding loop for Rust / contract

Contract field	Exact rule
Speed	AI drafts in seconds; the loop turns drafts into trusted code.
Iteration	Small prompts and small diffs are easier to review.
Stop rule	Never accept code that fails a gate or that you cannot explain.
Record	Keep prompt, proposal, decision and test result for each change.

WHEN IT MATTERS Each activity review record shows prompt, decision and the passing test result.

The vibe-coding loop for Rust / failure



Write a bounded prompt

Read the code, then the contract: what must always be true?

```
Role:      Act as a senior Rust reviewer.
Context:   StockPilot command parser, Rust 2021, std only.
Contract:  parse_command(&[&str]) -> Result<Command, String>
           list | add <sku> <qty> | remove <sku> <qty>
           qty: u32 and >= 1
Limits:    no new crates, no unsafe, no unwrap on input,
           keep the public signature.
Output:    code + 4 boundary tests + one-line reasons.
```

Role

Sets the expected quality bar and tone.

Contract

The exact signature and rules to satisfy.

Limits

What the AI must not do: crates, unsafe, signature changes.

Output


Ask for tests and reasons, not only code.

Write a bounded prompt / contract

Contract field	Exact rule
Include	Specification, relevant file, exact cargo output.
Exclude	Secrets, API keys, personal data, assessment answers.
Size	One function or one fix per prompt.
Follow-up	Ask "which edge case did you not test?" before accepting.

WHEN IT MATTERS The accepted proposal compiles, passes the tests and respects every limit.

Write a bounded prompt / failure



The compiler is your first reviewer

Read the code, then the contract: what must always be true?

```
error[E0382]: borrow of moved value: `items`
--> src/main.rs:9:22
5 |     let items = vec![cable, charger];
  |     ----- move occurs because `items` has type
  |         `Vec<Item>`, which does not implement Copy
7 |     let kept = in_stock(items);
  |               ----- value moved here
9 |     println!("{:?}", items);
  |                   ^^^^^ value borrowed here after move
```

Error code

E0382 can be looked up with `rustc --explain E0382`.

Spans

The arrows show where the value moved and where it was used.

Help lines

Often suggest the exact fix (borrow, clone, add mut).

AI use


Paste the full message; ask for the cause before the fix.

The compiler is your first reviewer / contract

Contract field	Exact rule
Read order	First error first; later errors are often consequences.
Explain	<code>rustc --explain E0XXX</code> gives a worked example.
Fix scope	Smallest change that keeps the contract.
Evidence	Record the error and the fix in the review record.

WHEN IT MATTERS cargo build reports zero errors and zero warnings.

The compiler is your first reviewer / failure



Review AI-generated Rust before accepting it

Read the code, then the contract: what must always be true?

```
// Red flags in a proposal
let qty: u32 = args[2].parse().unwrap(); // panics on bad input
unsafe { ... }                          // never needed here
let copy = items.clone();               // unjustified clone
use clap::Parser;                       // new crate, not allowed

// Accept when
cargo test                             # all pass
cargo clippy --all-targets -- -D warnings # clean
```

unwrap/expect

Acceptable in tests; in library code they turn bad input into a crash.

unsafe

Removes compiler guarantees; not needed for this course.

clone

Often hides an ownership question; ask why it is needed.

New crates


Add supply-chain risk; only with explicit approval.

Review AI-generated Rust before accepting it / contract

Contract field	Exact rule
Signatures	Public API unchanged unless the specification changed.
Errors	Invalid input returns Err/None, never panics.
Tests	Every boundary in the specification is tested.
Explainability	You can explain every line to a colleague.

WHEN IT MATTERS The review record lists at least one rejected or edited suggestion with a reason.

Review AI-generated Rust before accepting it / failure



Modules and visibility organise a crate

Read the code, then the contract: what must always be true?

```
// src/lib.rs
pub mod money;      // loads src/money.rs
pub mod report;     // loads src/report.rs

// src/report.rs
use crate::money::format_cents;

pub fn report_line(name: &str, qty: u32, unit: u64)
    -> Option<String> { /* ... */ }
fn helper() {}      // private to this module
```

mod

Declares a module; the file name matches the module name.

Privacy

Everything is private unless marked pub.

Paths

crate:: starts from the crate root; super:: goes up one level.

use


Brings a path into scope so it can be called by its short name.

Modules and visibility organise a crate / contract

Contract field	Exact rule
pub	Visible to other crates, including your tests/ folder.
pub(crate)	Visible inside this crate only.
Module per concern	money formats currency; report builds lines.
API check	Integration tests compile only against pub items.

WHEN IT MATTERS Activity 5 tests import activity05::money and activity05::report successfully.

Modules and visibility organise a crate / failure



Compiler errors, failing tests and clippy warnings are evidence: read them, then act.

Cargo dependencies and Cargo.lock

Read the code, then the contract: what must always be true?

```
# Cargo.toml
[dependencies]
serde = { version = "1", features = ["derive"] }
serde_json = "1"

cargo add serde --features derive # edits Cargo.toml
cargo build                       # downloads + locks
cargo tree                       # show dependency graph
cargo update                      # move within semver range
```

Semver

"1" means any compatible 1.x version.

Features

Opt-in capabilities such as serde's derive macros.

Cargo.lock

Exact versions used; commit it for applications and courses.

crates.io


The public registry; check downloads, docs and maintenance.

Cargo dependencies and Cargo.lock / contract

Contract field	Exact rule
Approval	Every new crate is a design decision recorded in review.
Reproducibility	Cargo.lock gives every learner the same versions.
Offline	cargo fetch downloads everything before class.
Audit	cargo tree shows what a crate pulls in.

WHEN IT MATTERS Activity 6 builds with serde 1.x recorded in Cargo.lock and 6 tests pass.

Cargo dependencies and Cargo.lock / failure



fmt and clippy encode team practice

Read the code, then the contract: what must always be true?

```
cargo fmt                # rewrite to house style
cargo fmt --check         # fail if not formatted
cargo clippy --all-targets -- -D warnings

warning: this `if` has identical blocks
warning: redundant clone
warning: missing documentation for a function
= help: for further information visit
       https://rust-lang.github.io/rust-clippy/...
```

rustfmt

One formatting style for everyone; no style debates in review.

clippy

Hundreds of lints for bugs, performance and idiom.

-D warnings

Treat warnings as errors so they cannot accumulate.

rustfmt.toml


Project settings, for example max_width = 80.

fmt and clippy encode team practice / contract

Contract field	Exact rule
Before commit	fmt --check, clippy -D warnings and test must all pass.
AI output	Run the same gates on generated code; no exceptions.
Allow a lint	Only with #[allow(...)] plus a reason in a comment.
CI	The same three commands can run in a pipeline.

WHEN IT MATTERS Every activity solution passes `fmt --check` and `clippy -D warnings`.

fmt and clippy encode team practice / failure



Set up VS Code for Rust vibe coding

Read the code, then the contract: what must always be true?

Extensions

<code>rust-analyzer</code>	types, errors, go-to-definition
(optional) <code>CodeLLDB</code>	step-through debugging
your AI assistant	Copilot / Claude / ChatGPT

Workspace habits

<code>open the crate folder</code>	(the one with <code>Cargo.toml</code>)
<code>inlay hints on</code>	see inferred types
<code>terminal: cargo test</code>	after every accepted change

rust-analyzer

Shows the same errors as the compiler while you type.

Inlay hints

Display inferred types, which helps review AI code.

Run/Test lenses

Click "Run Test" above a `#[test]` function.

AI panel


Keep prompts beside the code; paste exact errors.

Set up VS Code for Rust vibe coding / contract

Contract field	Exact rule
Folder	Open starter/ or solution/ so rust-analyzer finds Cargo.toml.
Save	Format on save can call rustfmt automatically.
Terminal	Use the integrated terminal for cargo commands.
Privacy	Do not paste secrets or assessment answers into AI tools.

WHEN IT MATTERS Hovering a variable shows its type and cargo test runs from the terminal.

Set up VS Code for Rust vibe coding / failure



Vibe-code a command parser

ACTIVITY 4

Independent practice; full steps in the activity README and Learner Guide

Store staff will type commands such as "add ABC-0001 5". You describe the command language to an AI assistant, review the generated parser, and keep only code that passes the acceptance tests.

YOU'LL BUILD

labs/activity-04-cli-commands: complete starter/ against the tests


TOOLCHAIN

Rust stable / Cargo / VS Code + rust-analyzer / AI assistant

DONE WHEN

cargo test reports 5 passed; cargo run --add ABC-0001 5 prints Add { sku: "ABC-0001", qty: 5 }.

Vibe-code a command parser / workflow



EXACT CONTRACT

`parse_command(&[&str]) -> Result<Command, String>`. Accepts exactly: `list | add <sku> <qty> | remove <sku> <qty>`. `qty` must parse as `u32` and be at least 1. Anything else returns `Err` with a usage or reason message.

Vibe-code a command parser / Rust

Reference solution: `solution/src/lib.rs` (formatted, tested, clippy-clean)

```
pub fn parse_command(args: &[&str]) -> Result<Command, String> {
    match args {
        ["list"] => Ok(Command::List),
        [verb @ ("add" | "remove"), sku, qty] => {
            let qty: u32 = qty
                .parse()
                .map_err(|_| format!("invalid quantity: {qty}"))?;
            if qty == 0 {
                return Err("quantity must be at least 1".to_string());
            }
            let sku = sku.to_string();
            if *verb == "add" {
                Ok(Command::Add { sku, qty })
            } else {
                Ok(Command::Remove { sku, qty })
            }
        }
    }
}
// ... full code: solution/src/lib.rs
```

Slice patterns

`match on [verb, sku, qty]` checks the word count and binds words at once.

Or-pattern

`"add" | "remove"` shares one arm; `verb @` keeps the matched word.

map_err

Turns a `ParseIntError` into a message staff can act on.

Exit code

main returns 2 for a usage error, so scripts can detect failure.

Vibe-code a command parser / vibe-coding prompts

Plan before code

- Act as a senior Rust reviewer.
Specification: `parse_command(&[&str]) -> Result<Command, String>`. Accepts exactly: `list | add <sku> <qty> | remove <sku> <qty>`. `qty` must parse as `u32` and be at least 1. Anything else returns `Err` with a usage or reason message. Before writing any code, list the public signatures, the edge cases and at least four boundary tests you would expect. Ask me about anything ambiguous.

Generate with AI

- Implement "Vibe-code a command parser" in `starter/src` so that the supplied tests pass. Generate the parser from the command grammar only; reject any suggestion that adds crates such as `clap`. Keep public signatures unchanged, use no unsafe code, and explain each design decision in one sentence.

Repair from evidence

- Here is my exact cargo output: `<paste the first error or failing test>`. Explain the cause in plain English, propose the smallest fix that keeps the specification, and add one regression test. Do not change expected values in existing tests.

Vibe-code a command parser / acceptance

✓ Expected result

cargo test reports 5 passed; cargo run -- add ABC-0001 5 prints Add { sku: "ABC-0001", qty: 5 }. Starter before you begin: Every test that calls an unfinished function fails with "not yet implemented" from todo!().

IF IT DOESN'T WORK

Test fails

Compare expected vs actual; check the boundary and the type, never edit the expected value.

Does not compile

Read the first error and its code; rustc -- explain E0XXX; ask the AI to explain before fixing.

clippy / fmt fails

Apply the suggested idiom or cargo fmt, then rerun cargo test.

Organise a crate into modules

ACTIVITY 5

Independent practice; full steps in the activity README and Learner Guide

The reporting code has grown. You split StockPilot formatting into a money module and a report module, expose only what callers need, and keep the behaviour identical under test.

YOU'LL BUILD

labs/activity-05-modules-visibility:
complete starter/ against the tests


TOOLCHAIN

Rust stable / Cargo / VS Code + rust-
analyzer / AI assistant

DONE WHEN

cargo test reports 4 passed; tests import
activity05::money and activity05::report.

Organise a crate into modules / workflow



EXACT CONTRACT

`money::format_cents(u64) -> String` renders "\$D.CC". `report::report_line(name, qty, unit_cents) -> Option<String>` renders "<name> x<qty> @ <unit> = <total>"; `report::report` joins lines with "\n" and fails wholly on overflow.

Organise a crate into modules / Rust

Reference solution: solution/src/report.rs (formatted, tested, clippy-clean)

```
/// Builds `"<name> x<qty> @ <unit> = <total>"`, or `None` on overflow.
pub fn report_line(name: &str, qty: u32, unit_cents: u64) -> Option<String> {
    let total = unit_cents.checked_mul(u64::from(qty))?;
    Some(format!(
        "{name} x{qty} @ {} = {}",
        format_cents(unit_cents),
        format_cents(total)
    ))
}
```

mod

`pub mod money`; loads `src/money.rs` as the module `crate::money`.

pub

Items are private by default; `pub` is a deliberate API decision.

use crate::

`report` imports `format_cents` by its full path inside the crate.

collect

Collecting `Option<Vec<_>>` stops at the first `None`.

Organise a crate into modules / vibe-coding prompts

Plan before code

- Act as a senior Rust reviewer.
Specification: `money::format_cents(u64) -> String` renders "\$D.CC".
`report::report_line(name, qty, unit_cents) -> Option<String>` renders "<name> x<qty> @<unit> = <total>"; `report::report` joins lines with "\n" and fails wholly on overflow. Before writing any code, list the public signatures, the edge cases and at least four boundary tests you would expect. Ask me about anything ambiguous.

Generate with AI

- Implement "Organise a crate into modules" in `starter/src` so that the supplied tests pass. Keep the two-module layout and public paths; do not merge modules to make tests pass. Keep public signatures unchanged, use no unsafe code, and explain each design decision in one sentence.

Repair from evidence

- Here is my exact cargo output: <paste the first error or failing test>. Explain the cause in plain English, propose the smallest fix that keeps the specification, and add one regression test. Do not change expected values in existing tests.

Organise a crate into modules / acceptance

✓ Expected result

cargo test reports 4 passed; tests import activity05::money and activity05::report. Starter before you begin: Every test that calls an unfinished function fails with "not yet implemented" from todo!().

IF IT DOESN'T WORK

Test fails

Compare expected vs actual; check the boundary and the type, never edit the expected value.

Does not compile

Read the first error and its code; rustc --explain E0XXX; ask the AI to explain before fixing.

clippy / fmt fails

Apply the suggested idiom or cargo fmt, then rerun cargo test.

Load inventory JSON with Cargo dependencies

ACTIVITY 6

Independent practice; full steps in the activity README and Learner Guide

The purchasing team exports inventory as JSON. You add `serde` and `serde_json` with Cargo, derive the data contract, and let the type system reject malformed records at the boundary.

YOU'LL BUILD

labs/activity-06-cargo-serde-json:
complete starter/ against the tests


TOOLCHAIN

Rust stable / Cargo / VS Code + rust-
analyzer / AI assistant

DONE WHEN

cargo test reports 6 passed; stock value
of data/inventory.json is 65,948 cents.

Load inventory JSON with Cargo dependencies / workflow



EXACT CONTRACT

```
Item { sku, name, qty: u32, unit_cents: u64 } derives Serialize and Deserialize. load_items(&str) -> Result<Vec<Item>, serde_json::Error>;  
to_json(&[Item]) -> Result<String, _>; stock_value(&[Item]) -> Option<u64>.
```

Load inventory JSON with Cargo dependencies / Rust

Reference solution: solution/src/lib.rs (formatted, tested, clippy-clean)

```
/// Parses a JSON array of items; missing or mistyped fields are errors.
pub fn load_items(json: &str) -> Result<Vec<Item>, serde_json::Error>
{
    serde_json::from_str(json)
}
```

Cargo.toml

serde with the derive feature and serde_json are declared dependencies.

derive

`#[derive(Deserialize)]` generates the parser from the struct definition.

Types as validation

qty: u32 makes -1 a parse error before business logic runs.

Cargo.lock

Records the exact resolved versions so every learner builds the same code.

Load inventory JSON with Cargo dependencies / vibe-coding prompts

Plan before code

- Act as a senior Rust reviewer.
Specification: `Item { sku, name, qty: u32, unit_cents: u64 }` derives `Serialize` and `Deserialize`. `load_items(&str) -> Result<Vec<Item>, serde_json::Error>`; `to_json(&[Item]) -> Result<String, _>`; `stock_value(&[Item]) -> Option<u64>`. Before writing any code, list the public signatures, the edge cases and at least four boundary tests you would expect. Ask me about anything ambiguous.

Generate with AI

- Implement "Load inventory JSON with Cargo dependencies" in `starter/src` so that the supplied tests pass. Use `serde` derive only; do not hand-write JSON parsing or add other crates. Keep public signatures unchanged, use no unsafe code, and explain each design decision in one sentence.

Repair from evidence

- Here is my exact cargo output: `<paste the first error or failing test>`. Explain the cause in plain English, propose the smallest fix that keeps the specification, and add one regression test. Do not change expected values in existing tests.

Load inventory JSON with Cargo dependencies / acceptance

✓ Expected result

cargo test reports 6 passed; stock value of data/inventory.json is 65,948 cents. Starter before you begin: Every test that calls an unfinished function fails with "not yet implemented" from todo!().

IF IT DOESN'T WORK

Test fails

Compare expected vs actual; check the boundary and the type, never edit the expected value.

Does not compile

Read the first error and its code; rustc --explain E0XXX; ask the AI to explain before fixing.

clippy / fmt fails

Apply the suggested idiom or cargo fmt, then rerun cargo test.

TOPIC 3 / K3/A3

Rust Programming Controls, Functions and Features

Activities 7-9 / concepts, contracts, failure modes and evidence

if and match are expressions

Read the code, then the contract: what must always be true?

```
let label = if qty == 0 { "out" } else { "in stock" };

let status = match qty {
    0 => "out of stock",
    1..=4 => "low",
    5..=99 => "ok",
    _ => "bulk",
};
```

Expression

if and match produce a value you can bind with let.

Same type

Every branch must return the same type.

Ranges

1..=4 matches 1, 2, 3 and 4 inclusive.

Wildcard


_ matches everything else; use it deliberately.

if and match are expressions / contract

Contract field	Exact rule
Boolean	Conditions must be bool; there is no truthy integer.
Exhaustive	match must cover every possible value.
Order	Arms are tried top to bottom; the first match wins.
Tests	Test each range boundary: 0, 1, 4, 5, 99, 100.

WHEN IT MATTERS Boundary tests cover every arm.

if and match are expressions / failure



enum + match model every case

Read the code, then the contract: what must always be true?

```
enum Movement { Receive(u32), Ship(u32), Adjust(i64) }

match movement {
    Movement::Receive(q) => stock.checked_add(q)
        .ok_or(StockError::Overflow),
    Movement::Ship(q) if q > stock => Err(Insufficient {..}),
    Movement::Ship(q) => Ok(stock - q),
    Movement::Adjust(d) => adjust(stock, d),
}
```

Variants with data

Each variant carries exactly the data it needs.

Guards

if q > stock refines an arm with a condition.

Compiler help

Adding a variant makes every incomplete match fail to compile.

Errors as enums


StockError names each failure for callers and tests.

enum + match model every case / contract

Contract field	Exact rule
Receive	checked_add; Overflow on u32 overflow.
Ship	Insufficient when requested > available.
Adjust	NegativeResult below zero; Overflow above u32.
Sequence	apply_all stops at the first error.

WHEN IT MATTERS Activity 7: six tests cover every variant and every error.

enum + match model every case / failure



Loops: for, while and loop

Read the code, then the contract: what must always be true?

```
for item in &items {                // iterate by reference
    total += u64::from(item.qty);
}

for (index, line) in text.lines().enumerate() { /* .. */ }

let mut attempts = 0;
let code = loop {                  // loop can return a value
    attempts += 1;
    if attempts == 3 { break "gave up"; }
};
```

for

Iterates over anything that implements IntoIterator.

&items

Borrows each element; items stays usable afterwards.

enumerate

Adds a 0-based index; add 1 for human line numbers.

loop/break


An infinite loop that can return a value with break.

Loops: for, while and loop / contract

Contract field	Exact rule
Preferred	for over iterators; no manual index bounds to get wrong.
while	When the stop condition is not a collection end.
continue	Skip blank lines and headers early.
Early exit	? inside a loop returns the first error from the function.

WHEN IT MATTERS Activity 10 numbers errors from 1 and skips header and blank lines.

Loops: for, while and loop / failure



Structs and impl blocks

Read the code, then the contract: what must always be true?

```
#[derive(Debug, Default)]
pub struct Inventory {
    stock: HashMap<String, u32>,    // private field
}

impl Inventory {
    pub fn new() -> Self { Self::default() }
    pub fn quantity(&self, sku: &str) -> u32 { .. }
    pub fn ship(&mut self, sku: &str, qty: u32)
        -> Result<u32, String> { .. }
}
```

Struct

Groups related data under one named type.

Private fields

Force every change through methods that keep the rules.

&self / &mut self

Methods declare whether they read or change the value.

derive


Debug, Clone, PartialEq, Default generated by the compiler.

Structs and impl blocks / contract

Contract field	Exact rule
Constructor	<code>new()</code> by convention; Default for empty values.
Readers	<code>&self</code> methods such as <code>quantity</code> and <code>low_stock</code> .
Writers	<code>&mut self</code> methods such as <code>receive</code> and <code>ship</code> .
Invariant	Stock never goes below zero because only <code>ship</code> can reduce it.

WHEN IT MATTERS Activity 8: callers cannot touch the `HashMap` directly and six tests pass.

Structs and impl blocks / failure



Collections: Vec and HashMap

Read the code, then the contract: what must always be true?

```
let mut skus: Vec<String> = Vec::new();
skus.push("ABC-0001".to_string());
skus.sort();

let mut stock: HashMap<String, u32> = HashMap::new();
*stock.entry("ABC-0001".into()).or_insert(0) += 5;
let level = stock.get("ABC-0001").copied().unwrap_or(0);

if let Some(q) = stock.get_mut("ABC-0001") { *q -= 1; }
```

Vec<T>

Growable, ordered list; index or iterate.

HashMap<K, V>

Key lookup in constant average time; no order.

entry API

Insert-or-update with a single lookup.

get returns Option


A missing key is a normal case, not a crash.

Collections: Vec and HashMap / contract

Contract field	Exact rule
Order	Sort before output because HashMap order is random.
Ownership	Keys are owned Strings; look up with &str.
Missing key	unwrap_or(0) or an explicit error, never map[key] panic.
Choice	Vec for sequences; HashMap for lookup by id.

WHEN IT MATTERS low_stock returns a sorted Vec so tests are deterministic.

Collections: Vec and HashMap / failure



Traits and generics share behaviour

Read the code, then the contract: what must always be true?

```
pub trait Priced {  
    fn unit_cents(&self) -> u64;  
    fn quantity(&self) -> u32;  
    fn line_cents(&self) -> Option<u64> {          // default  
        self.unit_cents().checked_mul(u64::from(self.quantity()))  
    }  
}  
  
impl Priced for Product { .. }  
impl Priced for Service { .. }  
  
fn order_total<T: Priced>(lines: &[T]) -> Option<u64>  
fn mixed_total(lines: &[&dyn Priced]) -> Option<u64>
```

Trait

A named set of methods a type promises to provide.

Default method

Written once, inherited by every implementor.

Generic T: Priced

One type per call, resolved at compile time (fast).

&dyn Priced


Different types in one list, resolved at run time.

Traits and generics share behaviour / contract

Contract field	Exact rule
Contract	Implementors supply unit_cents and quantity only.
Extension	A new type joins by implementing the trait; totals are unchanged.
Dispatch	Generics for speed; trait objects for mixed collections.
Tests	Test the default method once via any implementor.

WHEN IT MATTERS Activity 9 totals products, services and a mixed order.

Traits and generics share behaviour / failure



Closures and iterator chains

Read the code, then the contract: what must always be true?

```
let expensive: Vec<&str> = products
    .iter()
    .filter(|p| p.unit_cents >= 1_000)
    .map(|p| p.name.as_str())
    .collect();

let total = lines.iter().try_fold(0u64, |acc, line| {
    acc.checked_add(line.line_cents())?
});
```

Closure

`|p| ...` is an anonymous function that can capture variables.

Lazy

`filter` and `map` do nothing until `collect` or a fold consumes them.

collect

The target type (`Vec`, `String`, `Option<Vec>`) decides the result.

try_fold


A fold that stops at the first `None` or `Err`.

Closures and iterator chains / contract

Contract field	Exact rule
Readability	Each step names one transformation.
Safety	No manual indexes, so no out-of-bounds errors.
Performance	Compiles to the same machine code as a hand loop.
Order	Iterator chains keep input order unless you sort.

WHEN IT MATTERS `names_at_least` keeps input order; `try_fold` returns `None` on overflow.

Closures and iterator chains / failure



Compiler errors, failing tests and clippy warnings are evidence: read them, then act.

Option and Result are control features

Read the code, then the contract: what must always be true?

```
fn find(sku: &str) -> Option<u32>           // may be absent
fn ship(sku: &str, q: u32) -> Result<u32, String> // may fail

match find("ABC-0001") {
    Some(q) => println!("{q} on hand"),
    None => println!("unknown SKU"),
}
let q = find("ABC-0001").unwrap_or(0);
let left = ship("ABC-0001", 2)?;           // propagate
```

Option<T>

Some(value) or None: absence without null.

Result<T, E>

Ok(value) or Err(reason): failure without exceptions.

Combinators

map, and_then, ok_or, unwrap_or transform without match.

?


Returns early with the None/Err, otherwise unwraps the value.

Option and Result are control features / contract

Contract field	Exact rule
Absent	Use Option when there is no reason to report.
Failed	Use Result when the caller needs to know why.
Library code	Return Option/Result; let the caller decide.
Binaries	Convert errors to messages and exit codes at the edge.

WHEN IT MATTERS No unwrap() on input data remains in any solution crate.

Option and Result are control features / failure



Apply stock movements with enums and match

ACTIVITY 7

Independent practice; full steps in the activity README and Learner Guide

Stock changes through receipts, shipments and manual adjustments. An enum names every movement and match forces each one to be handled, including the failure cases.

YOU'LL BUILD

labs/activity-07-match-control-flow:
complete starter/ against the tests


TOOLCHAIN

Rust stable / Cargo / VS Code + rust-
analyzer / AI assistant

DONE WHEN

cargo test reports 6 passed, covering
every variant and every error.

Apply stock movements with enums and match / workflow



EXACT CONTRACT

`Movement::{Receive(u32), Ship(u32), Adjust(i64)}`. `apply(stock, movement) -> Result<u32, StockError>`: shipping more than available is `Insufficient`; results below zero are `NegativeResult`; above `u32` are `Overflow`. `apply_all` stops at the first error.

Apply stock movements with enums and match / Rust

Reference solution: `solution/src/lib.rs` (formatted, tested, clippy-clean)

```
pub fn apply(stock: u32, movement: Movement) -> Result<u32, StockError> {
    match movement {
        Movement::Receive(qty) => {
            stock.checked_add(qty).ok_or(StockError::Overflow)
        }
        Movement::Ship(qty) if qty > stock => Err(StockError::Insufficient {
            available: stock,
            requested: qty,
        }),
        Movement::Ship(qty) => Ok(stock - qty),
        Movement::Adjust(delta) => {
            let next = i64::from(stock)
                .checked_add(delta)
                .ok_or(StockError::Overflow)?;
            if next < 0 {
                return Err(StockError::NegativeResult);
            }
        }
    }
    // ... full code: solution/src/lib.rs
}
```

enum

Each movement kind is a variant that can carry its own data.

match

The compiler rejects a match that forgets a variant.

Guard

Ship(qty) if qty > stock is tested before the normal Ship arm.

? in a loop

apply_all returns the first Err without applying later moves.

Apply stock movements with enums and match / vibe-coding prompts

Plan before code

- Act as a senior Rust reviewer. Specification: `Movement::{Receive(u32), Ship(u32), Adjust(i64)}`. `apply(stock, movement) -> Result<u32, StockError>`: shipping more than available is `Insufficient`; results below zero are `NegativeResult`; above `u32` are `Overflow`. `apply_all` stops at the first error. Before writing any code, list the public signatures, the edge cases and at least four boundary tests you would expect. Ask me about anything ambiguous.

Generate with AI

- Implement "Apply stock movements with enums and match" in `starter/src` so that the supplied tests pass. Use `enum + match` with exhaustive arms; no wildcard `_` arm that hides future variants. Keep public signatures unchanged, use no unsafe code, and explain each design decision in one sentence.

Repair from evidence

- Here is my exact cargo output: `<paste the first error or failing test>`. Explain the cause in plain English, propose the smallest fix that keeps the specification, and add one regression test. Do not change expected values in existing tests.

Apply stock movements with enums and match / acceptance

✓ Expected result

cargo test reports 6 passed, covering every variant and every error. Starter before you begin: Every test that calls an unfinished function fails with "not yet implemented" from todo!().

IF IT DOESN'T WORK

Test fails

Compare expected vs actual; check the boundary and the type, never edit the expected value.

Does not compile

Read the first error and its code; rustc --explain E0XXX; ask the AI to explain before fixing.

clippy / fmt fails

Apply the suggested idiom or cargo fmt, then rerun cargo test.

Track stock in a HashMap

ACTIVITY 8

Independent practice; full steps in the activity README and Learner Guide

StockPilot needs fast lookup by SKU. You wrap a HashMap in an Inventory type so every change goes through methods that enforce the stock rules.

YOU'LL BUILD

labs/activity-08-hashmap-inventory:
complete starter/ against the tests


TOOLCHAIN

Rust stable / Cargo / VS Code + rust-
analyzer / AI assistant

DONE WHEN

cargo test reports 6 passed; low_stock(5)
returns AAA-0001 and BBB-0002 only.

Track stock in a HashMap / workflow



EXACT CONTRACT

`Inventory::receive(&mut self, sku, qty) -> Option<u32>` (None on overflow, unchanged); `ship -> Result<u32, String>` (unknown SKU or insufficient stock is Err, unchanged); `quantity(sku) -> u32` (0 when unknown); `low_stock(threshold) -> Vec<(String, u32)>` strictly below threshold, sorted by SKU.

Track stock in a HashMap / Rust

Reference solution: solution/src/lib.rs (formatted, tested, clippy-clean)

```
/// Removes units; unknown SKUs and shortages are errors.
pub fn ship(&mut self, sku: &str, qty: u32) -> Result<u32, String> {
    let level = self
        .stock
        .get_mut(sku)
        .ok_or_else(|| format!("unknown SKU {sku}"))?;
    if qty > *level {
        return Err(format!("only {level} of {sku} available"));
    }
    *level -= qty;
    Ok(*level)
}
```

Encapsulation

The HashMap field is private; callers can only use the methods.

entry API

entry(..).or_insert(0) creates a missing key in one lookup.

get_mut

A mutable reference into the map lets ship change the level in place.

Sorting

HashMap order is random, so low_stock sorts before returning.

Track stock in a HashMap / vibe-coding prompts

Plan before code

- Act as a senior Rust reviewer. Specification: `Inventory::receive(&mut self, sku, qty) -> Option<u32>` (None on overflow, unchanged); `ship -> Result<u32, String>` (unknown SKU or insufficient stock is Err, unchanged); `quantity(sku) -> u32` (0 when unknown); `low_stock(threshold) -> Vec<(String, u32)>` strictly below threshold, sorted by SKU. Before writing any code, list the public signatures, the edge cases and at least four boundary tests you would expect. Ask me about anything ambiguous.

Generate with AI

- Implement "Track stock in a HashMap" in starter/src so that the supplied tests pass. Keep the HashMap private and the method signatures unchanged; no `unwrap()` on lookups. Keep public signatures unchanged, use no unsafe code, and explain each design decision in one sentence.

Repair from evidence

- Here is my exact cargo output: `<paste the first error or failing test>`. Explain the cause in plain English, propose the smallest fix that keeps the specification, and add one regression test. Do not change expected values in existing tests.

Track stock in a HashMap / acceptance

✓ Expected result

cargo test reports 6 passed; low_stock(5) returns AAA-0001 and BBB-0002 only. Starter before you begin: Every test that calls an unfinished function fails with "not yet implemented" from todo!().

IF IT DOESN'T WORK

Test fails

Compare expected vs actual; check the boundary and the type, never edit the expected value.

Does not compile

Read the first error and its code; rustc --explain E0XXX; ask the AI to explain before fixing.

clippy / fmt fails

Apply the suggested idiom or cargo fmt, then rerun cargo test.

Price mixed order lines with traits and iterators

ACTIVITY 9

Independent practice; full steps in the activity README and Learner Guide

Orders can contain products and services (for example, device set-up hours). A Priced trait gives both one pricing contract, and iterator chains total and filter them without manual index loops.

YOU'LL BUILD

labs/activity-09-traits-iterators: complete starter/ against the tests


TOOLCHAIN

Rust stable / Cargo / VS Code + rust-analyzer / AI assistant

DONE WHEN

cargo test reports 5 passed; the mixed order totals 14,297 cents.

Price mixed order lines with traits and iterators / workflow



EXACT CONTRACT

```
trait Priced { unit_cents, quantity, line_cents (default, checked) }. order_total<T: Priced>(&[T]) and mixed_total(&[&dyn Priced]) return Option<u64> (None on overflow; empty is Some(0)). names_at_least(&[Product], min_cents) -> Vec<&str> in input order.
```

Price mixed order lines with traits and iterators / Rust

Reference solution: solution/src/lib.rs (formatted, tested, clippy-clean)

```
/// Totals lines of one type (static dispatch).
pub fn order_total<T: Priced>(lines: &[T]) -> Option<u64> {
    lines
        .iter()
        .try_fold(0u64, |total, line| total.checked_add(line.line_cents()?))
}
```

Trait

Priced is a contract: any type that implements it can be totalled.

Default method

line_cents is written once and reused by Product and Service.

Generic vs dyn

T: Priced is resolved at compile time; &dyn Priced at run time.

try_fold

Accumulates a total and stops at the first overflow (None).

Price mixed order lines with traits and iterators / vibe-coding prompts

Plan before code

- Act as a senior Rust reviewer. Specification: trait Priced { unit_cents, quantity, line_cents (default, checked) }. order_total<T: Priced>(&[T]) and mixed_total(&[&dyn Priced]) return Option<u64> (None on overflow; empty is Some(0)). names_at_least(&[Product], min_cents) -> Vec<&str> in input order. Before writing any code, list the public signatures, the edge cases and at least four boundary tests you would expect. Ask me about anything ambiguous.

Generate with AI

- Implement "Price mixed order lines with traits and iterators" in starter/src so that the supplied tests pass. Implement with iterator adaptors (iter, filter, map, try_fold); no index-based for loops. Keep public signatures unchanged, use no unsafe code, and explain each design decision in one sentence.

Repair from evidence

- Here is my exact cargo output: <paste the first error or failing test>. Explain the cause in plain English, propose the smallest fix that keeps the specification, and add one regression test. Do not change expected values in existing tests.

Price mixed order lines with traits and iterators / acceptance

✓ Expected result

cargo test reports 5 passed; the mixed order totals 14,297 cents. Starter before you begin: Every test that calls an unfinished function fails with "not yet implemented" from todo!().

IF IT DOESN'T WORK

Test fails

Compare expected vs actual; check the boundary and the type, never edit the expected value.

Does not compile

Read the first error and its code; rustc --explain E0XXX; ask the AI to explain before fixing.

clippy / fmt fails

Apply the suggested idiom or cargo fmt, then rerun cargo test.

END OF DAY 1

Day 1 recap: the compiler and tests are the gate.

You built typed components, organised them in a crate, and used AI drafts only after they compiled, passed and made sense.

TOPIC 4 / K4/A4

Testing, Debugging and Integrating Rust Components

Activities 10-12 / concepts, contracts, failure modes and evidence

Unit tests live beside the code

Read the code, then the contract: what must always be true?

```
pub fn needs_reorder(on_hand: u32, point: u32) -> bool {
    on_hand <= point
}

#[cfg(test)]
mod tests {
    use super::*;
    #[test]
    fn boundary_is_inclusive() {
        assert!(needs_reorder(80, 80));
        assert!(needs_reorder(81, 80));
    }
}
```

`#[test]`

Marks a function that cargo test runs.

`#[cfg(test)]`

Compiled only for tests; not shipped in the binary.

`use super::*`

Unit tests can reach private items of their module.

`assert_eq!`


Shows left and right values when it fails.

Unit tests live beside the code / contract

Contract field	Exact rule
Name	Describe the rule: boundary_is_inclusive, not test1.
One behaviour	Each test checks one rule so failures are specific.
Boundaries	Test at, just below and just above every limit.
Speed	Unit tests run in milliseconds; run them constantly.

WHEN IT MATTERS cargo test lists each test by name with ok.

Unit tests live beside the code / failure



Integration tests check components together

Read the code, then the contract: what must always be true?

```
tests/integration.rs    # separate crate, public API only

use activity11::{parse_lines, summarise, Summary};
const SAMPLE: &str = include_str!("../data/stock.csv");

#[test]
fn end_to_end_summary() {
    assert_eq!(summarise(SAMPLE, 5), Ok(Summary {
        lines: 4, total_cents: 52_655,
        low_stock: vec!["ABC-0003".into()] }));
}
```

tests/ folder

Each file is compiled like an external user of the crate.

Fixtures

include_str! embeds a data file at compile time.

End to end

Parse, calculate and report are checked together.

Public API


If a test needs a private item, the API may be incomplete.

Integration tests check components together / contract

Contract field	Exact rule
Unit	One function, fast, may use private items.
Integration	Several components through the public API.
Process	Run the real binary (Activity 12).
Data	Fixture files live in data/ and are versioned.

WHEN IT MATTERS Activity 11: the end-to-end test fixes the expected total at 52,655 cents.

Integration tests check components together / failure



Custom errors and the ? operator

Read the code, then the contract: what must always be true?

```
#[derive(Debug, PartialEq)]
pub enum ParseError {
    FieldCount(usize),
    EmptySku,
    BadNumber { field: &'static str, value: String },
}
impl fmt::Display for ParseError { .. }
impl std::error::Error for ParseError {}

let qty = number("qty", fields[1])?; // early return on Err
```

Error enum

Each failure is a named, testable variant.

Display

Human-readable message for logs and operators.

Error trait

Lets the error work with Box<dyn Error> and ?.

?


Stops at the first bad field and returns its error.

Custom errors and the ? operator / contract

Contract field	Exact rule
Recoverable	Bad input is Result, not panic.
Context	Include the field and the offending value.
Aggregation	parse_all keeps good lines and numbered errors.
Tests	assert_eq! on the exact error variant and message.

WHEN IT MATTERS Activity 10 reports errors on lines 3, 4 and 6 with readable messages.

Custom errors and the ? operator / failure



Read a failing test like a detective

Read the code, then the contract: what must always be true?

```
---- total_includes_the_first_line stdout ----  
thread 'total_includes_the_first_line' panicked at  
tests/integration.rs:13:5:  
assertion `left == right` failed  
  left: Some(16695)  
 right: Some(52655)  
  
52655 - 16695 = 35960 = 40 x 899 -> first line missing
```

Test name

Tells you which rule is broken.

left / right

Actual value versus expected value.

Arithmetic

The difference often identifies the missing or extra data.

Location


File and line of the failing assertion.

Read a failing test like a detective / contract

Contract field	Exact rule
Reproduce	Run one test: cargo test total_includes
Backtrace	RUST_BACKTRACE=1 cargo test shows the call path.
Isolate	Check each component with its own test.
Fix	Change the code, never the expected value.

WHEN IT MATTERS After the fix, the same test passes and stays as a regression test.

Read a failing test like a detective / failure



Debug with dbg!, focused tests and AI

Read the code, then the contract: what must always be true?

```
let total = dbg!(total_cents(&lines)); // prints file:line + value

cargo test low_stock -- --nocapture      # one test, show output
RUST_BACKTRACE=1 cargo test

Prompt: "Here is the failing test and total_cents().
Explain why the actual value is 16695, point to the line,
and propose the smallest fix. Do not change the test."
```

dbg!

Prints the expression, its value and where it ran; returns the value.

Filter

cargo test <name> runs only matching tests.

--nocapture

Shows println!/dbg! output from passing tests too.

AI


Ask for a diagnosis first, then a minimal patch.

Debug with dbg!, focused tests and AI / contract

Contract field	Exact rule
Hypothesis	State what you think is wrong before changing code.
One change	Change one thing, rerun, observe.
Cleanup	Remove dbg! before committing; clippy can flag it.
Record	Symptom, cause, fix and test in the review record.

WHEN IT MATTERS Activity 11 ends with 6 passed and a written defect record.

Debug with dbg!, focused tests and AI / failure



Interoperability: arguments, files, exit codes

Read the code, then the contract: what must always be true?

```
$ stockpilot data/stock.csv 13
ITEMS 4
TOTAL $526.55
LOW STOCK ABC-0002, ABC-0003, ABC-0004
$ echo $?          # 0

$ stockpilot          # usage error -> stderr, exit 2
$ stockpilot nope.csv # cannot read -> stderr, exit 1
```

Arguments

`std::env::args()`; validate count and types.

Files

`std::fs::read_to_string` returns `Result`.

stdout/stderr

Data to `stdout`, diagnostics to `stderr`.

ExitCode


`main` returns `ExitCode` so scripts can react.

Interoperability: arguments, files, exit codes / contract

Contract field	Exact rule
0	Success: report printed.
1	Data problem: unreadable file or malformed row.
2	Usage problem: wrong arguments.
Tests	Process tests run the binary via CARGO_BIN_EXE_<name>.

WHEN IT MATTERS Activity 12 process tests check stdout, stderr and exit codes 0, 1 and 2.

Interoperability: arguments, files, exit codes / failure



Serde: typed data at the boundary

Read the code, then the contract: what must always be true?

```
#[derive(Serialize, Deserialize, Debug, PartialEq)]
pub struct Item {
    pub sku: String,
    pub name: String,
    pub qty: u32,          // -1 in JSON -> error
    pub unit_cents: u64,
}

let items: Vec<Item> = serde_json::from_str(json)?;
let text = serde_json::to_string_pretty(&items)?;
```

Derive

Serialize/Deserialize are generated from the struct.

Validation

Types reject wrong shapes before business logic runs.

Round trip

Serialise then parse must give equal values.

Errors


serde_json::Error reports line, column and cause.

Serde: typed data at the boundary / contract

Contract field	Exact rule
Missing field	Error unless <code>#[serde(default)]</code> is chosen.
Unknown field	Ignored unless <code>#[serde(deny_unknown_fields)]</code> .
Numbers	Out-of-range or negative values for <code>u32</code> are errors.
Contract	The struct is the documented JSON schema.

WHEN IT MATTERS Activity 6 rejects a missing field and a negative quantity.

Serde: typed data at the boundary / failure



Parse CSV records with Result and custom errors

ACTIVITY 10

Independent practice; full steps in the activity README and Learner Guide

Stock files arrive with typos. Instead of crashing, StockPilot must report exactly which line is wrong and why, while still importing every valid line.

YOU'LL BUILD

labs/activity-10-error-handling: complete starter/ against the tests


TOOLCHAIN

Rust stable / Cargo / VS Code + rust-analyzer / AI assistant

DONE WHEN

cargo test reports 5 passed;
data/stock.csv yields 2 records and errors on lines 3, 4 and 6.

Parse CSV records with Result and custom errors / workflow



EXACT CONTRACT

`parse_record(&str) -> Result<Record, ParseError>` with `ParseError::`{`FieldCount(n)`, `EmptySku`, `BadNumber{field, value}`} and a Display message for each. `parse_all(&str)` skips blank lines and the header, returning valid records and (1-based line number, error) pairs.

Parse CSV records with Result and custom errors / Rust

Reference solution: [solution/src/lib.rs](#) (formatted, tested, clippy-clean)

```
/// Parses `sku,qty,unit_cents`; surrounding spaces are ignored.
pub fn parse_record(line: &str) -> Result<Record, ParseError> {
    let fields: Vec<&str> = line.split(',').map(str::trim).collect();
    if fields.len() != 3 {
        return Err(ParseError::FieldCount(fields.len()));
    }
    if fields[0].is_empty() {
        return Err(ParseError::EmptySku);
    }
    Ok(Record {
        sku: fields[0].to_string(),
        qty: number("qty", fields[1])?,
        unit_cents: number("unit_cents", fields[2])?,
    })
}
```

Result

Every caller must decide what to do with Ok and Err.

Custom error

An enum names each failure so tests can match on it exactly.

Display

Separate, human-readable messages for operators and logs.

?

Returns the error early, converting it where From allows.

Parse CSV records with Result and custom errors / vibe-coding prompts

Plan before code

- Act as a senior Rust reviewer. Specification: `parse_record(&str) -> Result<Record, ParseError>` with `ParseError::`{`FieldCount(n)`, `EmptySku`, `BadNumber{field, value}`} and a `Display` message for each. `parse_all(&str)` skips blank lines and the header, returning valid records and (1-based line number, error) pairs. Before writing any code, list the public signatures, the edge cases and at least four boundary tests you would expect. Ask me about anything ambiguous.

Generate with AI

- Implement "Parse CSV records with Result and custom errors" in `starter/src` so that the supplied tests pass. Return `Result` everywhere; no `unwrap()`, `expect()` or `panic!` in library code. Keep public signatures unchanged, use no unsafe code, and explain each design decision in one sentence.

Repair from evidence

- Here is my exact cargo output: `<paste the first error or failing test>`. Explain the cause in plain English, propose the smallest fix that keeps the specification, and add one regression test. Do not change expected values in existing tests.

Parse CSV records with Result and custom errors / acceptance

✓ Expected result

cargo test reports 5 passed; data/stock.csv yields 2 records and errors on lines 3, 4 and 6. Starter before you begin: Every test that calls an unfinished function fails with "not yet implemented" from todo!().

IF IT DOESN'T WORK

Test fails

Compare expected vs actual; check the boundary and the type, never edit the expected value.

Does not compile

Read the first error and its code; rustc --explain E0XXX; ask the AI to explain before fixing.

clippy / fmt fails

Apply the suggested idiom or cargo fmt, then rerun cargo test.

Debug a failing integration with tests

ACTIVITY 11

Independent practice; full steps in the activity README and Learner Guide

The nightly stock summary is wrong: the total is too low and a correctly stocked item is flagged. The starter crate contains two real defects. You reproduce them with tests, diagnose them with the help of an AI assistant, fix them and keep regression tests.

YOU'LL BUILD

labs/activity-11-debug-integration:
complete starter/ against the tests


TOOLCHAIN

Rust stable / Cargo / VS Code + rust-
analyzer / AI assistant

DONE WHEN

Starter: 4 of 6 tests fail. After both fixes
cargo test reports 6 passed.

Debug a failing integration with tests / workflow



EXACT CONTRACT

`summarise(csv, threshold) -> Result<Summary, String>` where `Summary { lines, total_cents, low_stock }`. Every line counts towards the total; low stock is strictly below the threshold, sorted by SKU; malformed lines are `Err("line N: ...")`.

Debug a failing integration with tests / Rust

Reference solution: solution/src/lib.rs (formatted, tested, clippy-clean)

```
/// Total value of every line, or `None` on overflow.
pub fn total_cents(lines: &[Line]) -> Option<u64> {
    lines.iter().try_fold(0u64, |total, line| {
        total.checked_add(line.unit_cents.checked_mul(u64::from(line.qty)))
    })
}
```

Reproduce

A failing test pins the defect with exact input and expected output.

Diagnose

Compare expected and actual values; 16,695 vs 52,655 means a line is missing.

Fix minimally

Change the defect, never the expected values in the test.

Regress

Keep the test so the defect cannot silently return.

Debug a failing integration with tests / vibe-coding prompts

Plan before code

- Act as a senior Rust reviewer.
Specification: `summarise(csv, threshold) -> Result<Summary, String>` where `Summary { lines, total_cents, low_stock }`. Every line counts towards the total; low stock is strictly below the threshold, sorted by SKU; malformed lines are `Err("line N: ...")`. Before writing any code, list the public signatures, the edge cases and at least four boundary tests you would expect. Ask me about anything ambiguous.

Generate with AI

- Implement "Debug a failing integration with tests" in `starter/src` so that the supplied tests pass. Give the AI the failing test output and the function only; ask for a diagnosis before any code change. Keep public signatures unchanged, use no unsafe code, and explain each design decision in one sentence.

Repair from evidence

- Here is my exact cargo output: `<paste the first error or failing test>`. Explain the cause in plain English, propose the smallest fix that keeps the specification, and add one regression test. Do not change expected values in existing tests.

Debug a failing integration with tests / acceptance

✓ Expected result

Starter: 4 of 6 tests fail. After both fixes cargo test reports 6 passed. Starter before you begin: Four of the six tests fail because the starter contains two real defects; the other two pass.

IF IT DOESN'T WORK

Test fails

Compare expected vs actual; check the boundary and the type, never edit the expected value.

Does not compile

Read the first error and its code; rustc --explain E0XXX; ask the AI to explain before fixing.

clippy / fmt fails

Apply the suggested idiom or cargo fmt, then rerun cargo test.

Integrate components into a tested command-line tool

ACTIVITY 12

Independent practice; full steps in the activity README and Learner Guide

Operations staff will run StockPilot from a terminal and from scheduled scripts. You connect the library to a binary that reads a file, prints a report and returns exit codes that other programs can rely on.

YOU'LL BUILD

labs/activity-12-cli-integration: complete starter/ against the tests


TOOLCHAIN

Rust stable / Cargo / VS Code + rust-analyzer / AI assistant

DONE WHEN

cargo test reports 7 passed; cargo run -- ../data/stock.csv prints ITEMS 4, TOTAL \$526.55, LOW STOCK ABC-0003.

Integrate components into a tested command-line tool / workflow



EXACT CONTRACT

`run(csv, threshold) -> Result<String, String>` returns "ITEMS n\nTOTAL \$D.CC\nLOW STOCK a, b | none". The binary takes `<file> [threshold=5]`; exit 0 on success, 1 for unreadable or invalid data, 2 for usage errors.

Integrate components into a tested command-line tool / Rust

Reference solution: `solution/src/lib.rs` (formatted, tested, clippy-clean)

```
pub fn run(csv: &str, threshold: u32) -> Result<String, String> {
    let mut count = 0usize;
    let mut total = 0u64;
    let mut low = Vec::new();
    for (index, raw) in csv.lines().enumerate() {
        let raw = raw.trim();
        if raw.is_empty() || raw.starts_with("sku,") {
            continue;
        }
        let fields: Vec<&str> = raw.split(',').map(str::trim).collect();
        let [sku, qty, unit] = fields.as_slice() else {
            return Err(format!("line {}: expected 3 fields", index + 1));
        };
        let qty: u32 = qty
            .parse()
            .map_err(|_| format!("line {}: bad qty", index + 1))?;
        // ... full code: solution/src/lib.rs
    }
}
```

Thin main

main handles arguments, files and exit codes; the library holds the logic.

Exit codes

0 success, 1 bad data, 2 usage: a contract for scripts and schedulers.

CARGO_BIN_EXE

Integration tests run the real compiled binary as a separate process.

stdout vs stderr

Reports go to stdout; errors go to stderr so pipes stay clean.

Integrate components into a tested command-line tool / vibe-coding prompts

Plan before code

- Act as a senior Rust reviewer. Specification: `run(csv, threshold) -> Result<String, String>` returns "ITEMS\n\nTOTAL \$D.CC\nLOW STOCK a, b | none". The binary takes `<file> [threshold=5]`; exit 0 on success, 1 for unreadable or invalid data, 2 for usage errors. Before writing any code, list the public signatures, the edge cases and at least four boundary tests you would expect. Ask me about anything ambiguous.

Generate with AI

- Implement "Integrate components into a tested command-line tool" in `starter/src` so that the supplied tests pass. Keep main thin; put every rule in `lib.rs` where the library tests can reach it. Keep public signatures unchanged, use no unsafe code, and explain each design decision in one sentence.

Repair from evidence

- Here is my exact cargo output: `<paste the first error or failing test>`. Explain the cause in plain English, propose the smallest fix that keeps the specification, and add one regression test. Do not change expected values in existing tests.

Integrate components into a tested command-line tool / acceptance

✓ Expected result

cargo test reports 7 passed; cargo run -- ../data/stock.csv prints ITEMS 4, TOTAL \$526.55, LOW STOCK ABC-0003.
Starter before you begin: Every test that calls an unfinished function fails with "not yet implemented" from todo!().

IF IT DOESN'T WORK

Test fails

Compare expected vs actual; check the boundary and the type, never edit the expected value.


Does not compile

Read the first error and its code; rustc -- explain E0XXX; ask the AI to explain before fixing.

clippy / fmt fails

Apply the suggested idiom or cargo fmt, then rerun cargo test.

Activity 11 fixture: stock value by SKU (cents)



WHAT THE DATA SHOWS

Correct total 52,655. The defective starter reported 16,695: exactly the total without ABC-0001 (35,960). The arithmetic points straight at the skipped first line.

TOPIC 5 / K5/A5

AI-Assisted Rust Software Design and Documentation

Activities 13-14 / concepts, contracts, failure modes and evidence

Doc comments become documentation

Read the code, then the contract: what must always be true?

```
#![ Reorder-point calculations for StockPilot.    (crate docs)
#![deny(missing_docs)]

/// Calculates the reorder point in units.
///
/// `point = daily_usage x lead_days + safety_stock` (R1).
/// Returns `None` instead of wrapping on overflow (R2).
pub fn reorder_point(daily_usage: u32, lead_days: u32,
                    safety_stock: u32) -> Option<u32>

cargo doc --no-deps --open
```

///

Documents the enclosing item: the crate or module.

///

Documents the next item: function, struct, field.

Markdown

Headings, lists, code and links render in cargo doc.

deny(missing_docs)


An undocumented public item fails the build.

Doc comments become documentation / contract

Contract field	Exact rule
Summary line	One sentence saying what it does.
Units and ranges	State units (cents, days) and limits.
Failure	Say what None/Err means, or add # Panics / # Errors.
Trace	Reference requirement IDs such as R1.

WHEN IT MATTERS cargo doc builds and clippy -D warnings reports no missing docs.

Doc comments become documentation / failure



Doctests keep examples honest

Read the code, then the contract: what must always be true?

```
/// # Examples
///
/// ```
/// use activity13::reorder_point;
/// assert_eq!(reorder_point(12, 5, 20), Some(80));
/// ```
pub fn reorder_point(..) -> Option<u32> { .. }

$ cargo test
  Doc-tests activity13
test src/lib.rs - reorder_point (line 12) ... ok
```

Doctest

A code block in docs is compiled and run by cargo test.

Honesty

If behaviour changes, the stale example fails the build.

Users first

Examples show how to call the API correctly.

AI drafts


AI-written examples must pass as doctests before acceptance.

Doctests keep examples honest / contract

Contract field	Exact rule
Location	Under a # Examples heading in /// comments.
Imports	Doctests use the crate like an external user.
Hidden lines	Lines starting with # are compiled but not shown.
Evidence	The Doc-tests section of cargo test output.

WHEN IT MATTERS Activity 13: 3 unit tests and 3 doctests pass.

Doctests keep examples honest / failure



Compiler errors, failing tests and clippy warnings are evidence: read them, then act.

Trace requirements to code and tests

Read the code, then the contract: what must always be true?

ID	Requirement	Test (tests/acceptance.rs)
R1	point = usage*lead+safe	r1_r3_below_the_point...
R2	above point: no order	r2_above_the_point...
R3	order up to 7-day target	r2_exactly_at_the_point...
R4	overflow item skipped	r4_overflow_is_skipped...

Code: reorder_suggestions() in src/lib.rs

```

R1 checked_mul(..)?.checked_add(..)?
R2 if item.on_hand > point { return None; }
R3 point + cover - on_hand, kept only if > 0
R4 ? after every checked_* call
  
```

Trace matrix

Each user requirement links to code and a named test.

Coverage gap

An empty cell is a missing test or feature.

Change impact

Changing R3 shows exactly which code and tests to update.

Audit


Reviewers can verify claims without reading all code.

Trace requirements to code and tests / contract

Contract field	Exact rule
Requirement ID	Stable identifiers R1..Rn used in docs, tests and commits.
Code	Function or line that implements it.
Test	Exact test name; the result must be ok.
Status	Passed, failed or not yet run: never assumed.

WHEN IT MATTERS Activity 14 design.md traces R1-R4 to named, passing tests.

Trace requirements to code and tests / failure



Architecture and module maps

Read the code, then the contract: what must always be true?

```

+-----+
CSV/JSON ->| parse      |-- Result<Vec<Line>, Error>
+-----+
      |
+-----+ +-----+
| inventory |---->| report  |--> stdout
+-----+ +-----+
      |
+-----+
| reorder   |--> Vec<Suggestion>
+-----+

```

Components

One box per module with a single responsibility.

Data flow

Arrows labelled with the Rust types that cross them.

Boundaries

I/O at the edges; pure logic in the middle.

Mermaid


Diagrams as text in Markdown, versioned with the code.

Architecture and module maps / contract

Contract field	Exact rule
Module	Name, responsibility, public functions.
Interface	Input type, output type, error type.
External	Files, arguments, exit codes, crates.
Owner	Who maintains it and where its tests live.

WHEN IT MATTERS Every box in design.md exists as a module or function in the crate.

Architecture and module maps / failure



Record design decisions

Read the code, then the contract: what must always be true?

```
Decision: Skip items whose arithmetic overflows (R4).
Context: Planning data can contain bad usage values.
Options: 1. panic 2. saturate at u32::MAX 3. skip item
Chosen: 3 - skip; wrong orders are worse than none.
Consequences:
  + no crash, no absurd order quantities
  - skipped items must be visible in a report (future)
Evidence: test r4_overflow_is_skipped_without_panic
```

Decision

What was decided, in one sentence.

Options

Alternatives considered, so reviewers see the trade-off.

Consequences

Benefits and costs, including follow-up work.

Evidence


The test that demonstrates the decision.

Record design decisions / contract

Contract field	Exact rule
When	Any choice a maintainer would question later.
Where	docs/design.md next to the code.
AI role	AI may list options; you choose and justify.
Update	Supersede, do not delete, old decisions.

WHEN IT MATTERS design.md contains at least one complete decision record.

Record design decisions / failure



AI-assisted documentation, human-verified

Read the code, then the contract: what must always be true?

```
Prompt: "Draft rustdoc for reorder_suggestions using ONLY  
this code and R1-R4. Include units, a # Examples doctest  
and a requirement list. Mark anything you are unsure of."
```

Verify:

```
cargo test          # doctest compiles and passes  
cargo doc --no-deps # renders  
compare every claim with code and tests
```

Grounding

Give the AI the code and requirements, nothing else.

Hallucination

AI may describe behaviour the code does not have.

Doctests

Executable examples catch false claims automatically.

Ownership


You sign off the documentation, not the AI.

AI-assisted documentation, human-verified / contract

Contract field	Exact rule
Accept	Claims that match code and a passing test.
Correct	Wrong units, ranges or missing failure cases.
Reject	Invented functions, options or performance claims.
Record	Section, what was verified, what was changed.

WHEN IT MATTERS The AI review table in design.md lists verified and corrected sections.

AI-assisted documentation, human-verified / failure



Hand over: README and maintenance notes

Read the code, then the contract: what must always be true?

```
README.md
What it does      (one paragraph)
Build and test    cargo test / clippy / fmt
Usage            stockpilot <file> [threshold]
Requirements trace link to docs/design.md
Known limits      e.g. skipped overflow items
Change procedure  update code + docs + tests together
```

Audience

Written for the maintainer who joins next month.

Commands

Exact commands that prove the system still works.

Limits

Honest list of what is not handled yet.

Procedure


How to make a change safely.

Hand over: README and maintenance notes / contract

Contract field	Exact rule
Build	Toolchain version and commands.
Interfaces	Inputs, outputs, exit codes and data formats.
Quality gates	fmt, clippy -D warnings, test, doc.
Contacts	Owner and where decisions are recorded.

WHEN IT MATTERS A classmate can build, test and explain the capstone from its README and design.md.

Hand over: README and maintenance notes / failure



Document an API with rustdoc and doctests

ACTIVITY 13

Independent practice; full steps in the activity README and Learner Guide

The maintenance team will own the reorder calculation. The starter code works but has no documentation. You write rustdoc comments whose examples are compiled and run as tests, and trace them to requirements.

YOU'LL BUILD

labs/activity-13-rustdoc-doctests:
complete starter/ against the tests


TOOLCHAIN

Rust stable / Cargo / VS Code + rust-
analyzer / AI assistant

DONE WHEN

cargo test runs 3 tests and 3 doctests;
cargo doc --no-deps builds; clippy -D
warnings is clean.

Document an API with rustdoc and doctests / workflow



EXACT CONTRACT

`reorder_point(daily_usage, lead_days, safety_stock) -> Option<u32> = daily_usage x lead_days + safety_stock (R1), None on overflow (R2).`
`needs_reorder(on_hand, point)` is true at or below the point (R3). Every public item is documented; cargo clippy with `-D warnings` enforces `missing_docs`.

Document an API with rustdoc and doctests / Rust

Reference solution: solution/src/lib.rs (formatted, tested, clippy-clean)

```
/// Calculates the reorder point in units.  
///  
/// `reorder point = daily_usage x lead_days + safety_stock` (R1).  
///  
/// # Examples  
///  
/// ```  
/// ... (full docs in the source file)  
pub fn reorder_point(  
    daily_usage: u32,  
    lead_days: u32,  
    safety_stock: u32,  
) -> Option<u32> {  
    daily_usage  
        .checked_mul(lead_days)?  
        .checked_add(safety_stock)  
}
```

///

Outer doc comments document the next item; //! documents the crate.

Examples

Code blocks in docs are compiled and run by cargo test as doctests.

missing_docs

deny(missing_docs) turns an undocumented public item into a build error.

Traceability

R1-R3 in the docs link each behaviour to a user requirement and a test.

Document an API with rustdoc and doctests / vibe-coding prompts

Plan before code

- Act as a senior Rust reviewer.
Specification: `reorder_point(daily_usage, lead_days, safety_stock) -> Option<u32> = daily_usage x lead_days + safety_stock (R1), None on overflow (R2).`
`needs_reorder(on_hand, point)` is true at or below the point (R3). Every public item is documented; cargo clippy with `-D warnings` enforces `missing_docs`. Before writing any code, list the public signatures, the edge cases and at least four boundary tests you would expect. Ask me about anything ambiguous.

Generate with AI

- Implement "Document an API with rustdoc and doctests" in `starter/src` so that the supplied tests pass. Ask the AI to draft docs from the code and requirements only; verify every example by running cargo test. Keep public signatures unchanged, use no unsafe code, and explain each design decision in one sentence.

Repair from evidence

- Here is my exact cargo output: `<paste the first error or failing test>`. Explain the cause in plain English, propose the smallest fix that keeps the specification, and add one regression test. Do not change expected values in existing tests.

Document an API with rustdoc and doctests / acceptance

✓ Expected result

cargo test runs 3 tests and 3 doctests; cargo doc --no-deps builds; clippy -D warnings is clean. Starter before you begin: cargo test passes because the logic already works, but cargo clippy --all-targets -- -D warnings fails with "missing documentation" errors.

IF IT DOESN'T WORK

Test fails

Compare expected vs actual; check the boundary and the type, never edit the expected value.

Does not compile

Read the first error and its code; rustc --explain E0XXX; ask the AI to explain before fixing.

clippy / fmt fails

Apply the suggested idiom or cargo fmt, then rerun cargo test.

Design and document a reorder feature with AI

ACTIVITY 14

Independent practice; full steps in the activity README and Learner Guide

Capstone: purchasing wants weekly reorder suggestions. You agree requirements R1-R4, implement the feature with an AI assistant, and hand over a design record that traces every requirement to code and tests.

YOU'LL BUILD

labs/activity-14-design-capstone:
complete starter/ against the tests


TOOLCHAIN

Rust stable / Cargo / VS Code + rust-
analyzer / AI assistant

DONE WHEN

cargo test reports 6 passed and 1
doctest; docs/design.md traces R1-R4 to
named tests.

Design and document a reorder feature with AI / workflow



EXACT CONTRACT

`reorder_suggestions(&[StockItem]) -> Vec<Suggestion>`. R1 point = usage x lead + safety; R2 items above the point are excluded; R3 order_qty = point + 7 days usage - on_hand, zero quantities excluded; R4 overflowing items are skipped, never wrapped. Output sorted by SKU.

Design and document a reorder feature with AI / Rust

Reference solution: `solution/src/lib.rs` (formatted, tested, clippy-clean)

```
pub fn reorder_suggestions(items: &[StockItem]) -> Vec<Suggestion> {
    let mut suggestions: Vec<Suggestion> = items
        .iter()
        .filter_map(|item| {
            let point = item
                .daily_usage
                .checked_mul(item.lead_days)?
                .checked_add(item.safety_stock)?;
            if item.on_hand > point {
                return None;
            }
            let cover = item.daily_usage.checked_mul(REVIEW_DAYS)?;
            let order_qty = point.checked_add(cover)? - item.on_hand;
            (order_qty > 0).then(|| Suggestion {
                sku: item.sku.clone(),
                order_qty,
            })
        })
    // ... full code: solution/src/lib.rs
}
```

Requirements first

R1-R4 are agreed before prompting, so AI output has a target.

filter_map

One pass: skip items (None) or produce a Suggestion (Some).

No underflow

`on_hand <= point <= target`, so the subtraction cannot underflow.

Design record

`docs/design.md` traces R1-R4 to code, tests and review decisions.

Design and document a reorder feature with AI / vibe-coding prompts

Plan before code

- Act as a senior Rust reviewer. Specification:
reorder_suggestions(&[StockItem]) -> Vec<Suggestion>. R1 point = usage x lead + safety; R2 items above the point are excluded; R3 order_qty = point + 7 days usage - on_hand, zero quantities excluded; R4 overflowing items are skipped, never wrapped. Output sorted by SKU. Before writing any code, list the public signatures, the edge cases and at least four boundary tests you would expect. Ask me about anything ambiguous.

Generate with AI

- Implement "Design and document a reorder feature with AI" in starter/src so that the supplied tests pass. Give the AI R1-R4 and the public types; require a trace table in its answer and verify each row against the tests. Keep public signatures unchanged, use no unsafe code, and explain each design decision in one sentence.

Repair from evidence

- Here is my exact cargo output: <paste the first error or failing test>. Explain the cause in plain English, propose the smallest fix that keeps the specification, and add one regression test. Do not change expected values in existing tests.

Design and document a reorder feature with AI / acceptance

✓ Expected result

cargo test reports 6 passed and 1 doctest; docs/design.md traces R1-R4 to named tests. Starter before you begin: Every test that calls an unfinished function fails with "not yet implemented" from todo!().

IF IT DOESN'T WORK

Test fails

Compare expected vs actual; check the boundary and the type, never edit the expected value.


Does not compile

Read the first error and its code; rustc --explain E0XXX; ask the AI to explain before fixing.

clippy / fmt fails

Apply the suggested idiom or cargo fmt, then rerun cargo test.

Every activity is verified: tests per reference crate



WHAT THE DATA SHOWS

All 14 solution crates pass cargo test (including doctests), clippy -D warnings and fmt --check. Every starter compiles and fails in the intended way until you complete it.

What You Achieved

1

LO1

Determine basic software components using programming methodologies to meet functional specifications

2

LO2

Apply programming methodologies and tools for software creation

3

LO3

Select essential programming controls and features to meet software design requirements

4

LO4

Examine the interoperability and functionality of programming components

5

LO5

Generate programming design documentation aligned with user specifications

PRACTICE EXAM

Practice Exam: keep practising AI-assisted development

Tertiary Exams | Practice Exams | Vendors | About Us | FAQ | Support | Sign in | [Get started](#)

All exams / Anthropic
Anthropic | CCDV-F | Foundational

Claude Certified Developer — Foundations (CCDV-F)

Practice bundle for the Claude Certified Developer — Foundations (CCDV-F) credential. 53 questions matching the official exam blueprint — agents and workflows, applications and integration, Claude Code, evals and debugging, model selection, prompt and context engineering, security, and tools and MCP servers. Aligned to the official Anthropic exam guide and the public documentation at docs.anthropic.com, docs.claude.com, and modelcontextprotocol.io.

Questions	Duration	Pass score
53	120 min	72%

Practice mode

See the correct answer and full explanation immediately after each question. Best for studying.

Exam mode

120-minute timer, no answer reveal until you submit. Auto-saves and auto-submits — like the real exam.

Domains covered	
Agents and Workflows	14.7%
Applications and Integration	33.1%
Claude Code	3.1%
Eval, Testing, and Debugging	2.6%
Model Selection and Optimization	16.8%
Prompt and Context Engineering	11%
Security and Safety	9.1%

2026 PRACTICE EXAM DETAILS

Exam code	CCDV-F
Level	Foundational
Duration	120 min
Pass score	72%
Question count	53

FREE

Try our free practice teaser
No credit card required.

[Start free practice exam](#)

PICK A PLAN

☒ Practice Exam	SGD \$20.00
--	-------------

[Sign in to buy](#)

[WhatsApp](#)

Where

exams.tertiaryinfotech.com - practice exams with exam and practice modes.

Recommended

Claude Certified Developer - Foundations (CCDV-F): AI coding tools, agents and debugging.

Free start

Try 10 questions free on any exam before deciding.


Not the WSQ test

Optional further practice; it is not this course's assessment and there is no Rust-specific exam.

[Open the practice exam](#)

Screenshot of exams.tertiaryinfotech.com (CCDV-F practice exam page), captured September 2026.

Download course material from the LMS



Screenshot of the live LMS sign-in page (lms-tms.tertiaryinfotech.com), captured September 2026.

1. Sign in

Open lms-tms.tertiaryinfotech.com and sign in with your email (OTP) or password.

2. Open this course

AI Vibe Coding with Rust (TGS-2023039924).

3. Download

Learner slides PDF, Learner Guide and the Activities link.

4. Assessment

Question papers open on the assessment day; upload your answers there.

[Open the LMS](#)

Assessment / final reminder

Written Assessment

- Day 2, 4:30-5:30 PM
- 60 minutes / 5 questions
- K1-K5 / open book


Practical Performance

- Day 2, 5:30-6:30 PM
- 60 minutes / 5 tasks
- A1-A5 / Rust crates + evidence

Result and funding

- All items attempted individually
- Competent (C) or NYC
- Funding requires 75% attendance + C

Assessment Flow



ORDER OF THE DAY

Written Assessment (K1-K5) 4:30-5:30 PM, then Practical Performance (A1-A5) 5:30-6:30 PM on Day 2. Follow the assessor's submission instructions.

Digital Attendance (Mandatory)

1

TRAQOM / SSG

Take the digital attendance through the Singpass app when the trainer displays the QR code.

2

AM, PM and assessment

Attendance is taken for each session and separately for the assessment.

3

75% minimum

At least 75% attendance is required for assessment eligibility and funding.

4

Your own record

Use only your own Singpass; tell the trainer if the course title or code does not match.

TERTIARY INFOTECH ACADEMY

Thank You

Keep the loop: specify, prompt, compile, test, review, record.
enquiry@tertiaryinfotech.com / +65 6100 0613