

# Create Monitoring Evidence and an Incident Pack

90 minutes · Mapped criteria A5, K2

## Purpose and work product

Create a log-based error metric and alert policy, trigger a synthetic fault and assemble escalation evidence.

**Submit:** alert-policy.json, incident timeline and filtered log bundle

## Safety, cost and privacy

Use only the assigned training project. Confirm the active account, project and region before every mutation. Never place credentials, payment details, access tokens or private keys in screenshots or submitted files. Stop billable resources and verify the final inventory.

## Files in this folder

| File                  | Purpose                                                  |
|-----------------------|----------------------------------------------------------|
| alert-policy.json     | Mock data, script or configuration used by this activity |
| incident_timeline.csv | Mock data, script or configuration used by this activity |

## Detailed procedure

### Step 1

Select one Activity 7 or 8 workload and define the expected signal, threshold, evaluation window and notification owner.

### Step 2

Create a log-based counter metric whose filter matches a unique synthetic error marker.

### Step 3

Create or review alert-policy.json; replace placeholders with the actual project resource name and notification channel.

### Step 4

Trigger one error and verify it appears in Cloud Logging with the correct resource labels.

### Step 5

Trigger enough errors to breach the threshold for the specified duration.

### Step 6

Confirm an incident opens and the notification reaches the test channel.

### Step 7

Collect the filtered log entries, metric chart and policy configuration without credentials.

### Step 8

Stop the errors and confirm the incident closes after the recovery window.

### Step 9

Complete incident\_timeline.csv with UTC timestamps and evidence filenames.

## Step 10

Write the escalation summary: impact, expected/observed behaviour, safe actions, remaining unknowns and owner.

## Verification record

Record expected and observed output. A successful command without the correct project, identity, scope or evidence is not an accepted result.

| Check              | Expected evidence                                      |
|--------------------|--------------------------------------------------------|
| Identity and scope | Active account, project ID, region or zone             |
| Configuration      | Resource description or policy output                  |
| Runtime result     | Test output with UTC timestamp                         |
| Failure test       | One controlled negative test and diagnosis             |
| Cleanup            | Final inventory and stopped/deleted billable resources |

## Troubleshooting sequence

Check the active identity and project first, then API enablement and IAM, then resource state, networking and quotas. Preserve the failed output before making a correction. If the issue remains, escalate with the exact command, timestamp, expected result, observed result and evidence files.

## Cleanup

Delete or stop resources as instructed. Re-open Billing and the relevant service inventory, then record the remaining resource names. Budget alerts do not stop charges.