COURSE SLIDES · WSQ

Build a Human-AI Workforce with Autonomous AI Agents

WSQ Course Code: TGS-2024043854

Conducted by Tertiary Infotech Academy Pte Ltd · UEN 201200696W

Version v1.11 · 16 July 2026

© 2026 Tertiary Infotech Academy Pte Ltd. All rights reserved. · www.tertiarycourses.com.sg

COURSE ADMINISTRATION

Welcome & Housekeeping

© 2026 Tertiary Infotech Academy Pte Ltd

Digital Attendance (Mandatory)

1. It is mandatory to take the AM, PM and Assessment digital attendance for WSQ-funded courses.
2. The trainer/administrator displays the digital attendance QR code from the SSG portal.
3. Scan the QR code with your mobile phone camera and submit your attendance.
4. A minimum of 75% attendance is required to be eligible for assessment and funding.

© 2026 Tertiary Infotech Academy Pte Ltd

About the Trainer



Your Trainer

General Trainer template —
to be completed by the trainer

NAME

TITLE / DESIGNATION

QUALIFICATIONS

AREAS OF EXPERTISE

TRAINING & INDUSTRY EXPERIENCE

CONTACT

© 2026 Tertiary Infotech Academy Pte Ltd

YOUR TRAINER

About the Trainer



Dr. Alfred Ang

Principal Trainer
Tertiary Infotech Academy Pte. Ltd.

ROLE
Principal Trainer, Tertiary Infotech Academy Pte. Ltd.

CERTIFICATION
AI, automation and cloud certified — building autonomous AI agents and agentic workflows.

DELIVERS
WSQ courses on AI agents, automation, data engineering and cloud.

FOUNDER
Founder and lead instructor at Tertiary Infotech / Tertiary Courses.

© 2026 Tertiary Infotech Academy Pte Ltd

ICE-BREAKER

Let's Know Each Other

1. Your name and organisation / role.

2. Your experience with AI, automation or coding (if any).

3. What you want to be able to automate with AI agents after this course.

© 2026 Tertiary Infotech Academy Pte Ltd

HOUSEKEEPING


Ground Rules

1. Set your mobile phone to silent mode.
2. Participate actively — no question is too small.
3. Mutual respect: agree to disagree.
4. One conversation at a time.
5. Be punctual; return from breaks on time.
6. 75% attendance is required.

© 2026 Tertiary Infotech Academy Pte Ltd

COURSE PORTAL

Login to LMS and Download Course Material




Log in at lms-tms.tertiaryinfotech.com with your registered email and the OTP sent to your inbox, then open this course to download the slides and Learner Guide.

Sign in at https://lms-tms.tertiaryinfotech.com → open this course → Courseware tab → download the Slides, Learner Guide and Lesson Plan.

© 2026 Tertiary Infotech Academy Pte Ltd

COURSE PORTAL

Download Course Material



Sign in at https://lms-tms.tertiaryinfotech.com → open this course → Courseware tab → download the Slides, Learner Guide and Lesson Plan.

© 2026 Tertiary Infotech Academy Pte Ltd

SCHEDULE

Lesson Plan — 2 Days, 8 hours/day

Day 1

- Day 1 — Hermes Agent (Topic 1) & OpenClaw (Topic 2)
  - Topic 1: Hermes Agent (Labs 1–14)
  - Topic 2: OpenClaw (Labs 15–26)

Day 2

- Day 2 — Paperclip (Topic 3) & Final Assessment
  - Topic 3: Paperclip (Labs 27–33)
  - Final Assessment (WA + PP)
- Daily timing
  - 9:30am–6:30pm · 1-hour lunch · tea breaks within

© 2026 Tertiary Infotech Academy Pte Ltd

WHAT YOU'LL ACHIEVE

Learning Outcomes

1

Analyze AI Applications

Analyse AI (LLM-based) applications across a range of industries to identify their capabilities and limitations.

2

Design & Chatbot Efficiency

Establish the relationship between AI algorithm/agent design and chatbot/agent efficiency.

3

Evaluate & Improve RAG

Evaluate and improve the effectiveness of AI (RAG and agent) applications in product development.

© 2026 Tertiary Infotech Academy Pte Ltd

Briefing for Assessment

1. Place phones and other materials under the table or on the floor.
2. No photos or recording of assessment scripts.
3. No discussion during the assessment.
4. Use a black/blue pen for hard-copy assessments.
5. No liquid paper / correction tape.
6. Scripts are collected when time is up.

© 2026 Tertiary Infotech Academy Pte Ltd

FINAL ASSESSMENT

Assessment

1. Written Assessment (WA) — Short-Answer Questions (SAQ), 1 hour, open book.
2. Practical Performance (PP) — hands-on agent-building tasks that follow the course labs, 1 hour, open book.
3. Format: Open Book — slides, Learner Guide and approved materials only.
4. A minimum of 75% attendance is required to be eligible for assessment and funding.
5. An appeal process is available if required.

© 2026 Tertiary Infotech Academy Pte Ltd

ON ASSESSMENT DAY

Assessment Flow

1. TRAQOM survey — scan the QR code on the LMS
2. Assessment digital attendance — scan the SSG QR
3. Sit WA (SAQ) then PP — open book
4. Submit your answers on the LMS
5. Sign the Assessment Summary Record

© 2026 Tertiary Infotech Academy Pte Ltd

CORE CONCEPTS

Autonomous AI Agents Fundamentals

© 2026 Tertiary Infotech Academy Pte Ltd

OVERVIEW

What is an Autonomous AI Agent?

1

Perceive → reason → act → remember

An LLM-driven loop: it takes in a request, decides what to do, acts, then remembers the outcome.

2

Uses tools & skills

It calls web search, images, email, code and integrations — not just chat — to get real work done.

3

Runs across channels

The same agent is reachable on Telegram, WhatsApp, Discord, Slack and the terminal.

4

Autonomy under oversight

It works on its own, but important actions pause for human approval.

© 2026 Tertiary Infotech Academy Pte Ltd

THE BUILDING BLOCKS

The Agent Stack

1

Model / LLM

The reasoning engine — Claude, OpenAI, OpenRouter, MiniMax or DeepSeek.

2

Memory

Durable, user- or company-scoped recall across sessions and surfaces.

3

Skills & Tools

Reusable capabilities plus tool and third-party integration calls.

4

Channels

Where the agent meets people: Telegram, WhatsApp, Discord, Slack.

5

Scheduler & Security

Crons and a heartbeat automate work; sandboxes, budgets and approvals contain it.

© 2026 Tertiary Infotech Academy Pte Ltd

PERFORMANCE EFFECTIVENESS

RAG vs a Standard LLM Assistant

RAG agent

- Retrieval Augmented Generation (RAG)
  - Retrieves from a curated, current corpus before generating
  - Grounded, auditable answers — less hallucination
  - Effectiveness hinges on corpus freshness, indexing and how retrieval/memory is configured

LLM-only assistant

- Standard LLM assistant
  - Answers from training data alone — fastest to deploy
  - No live company data, no auditable response provenance
  - Evaluate both on accuracy, relevance, latency and maintenance cost

© 2026 Tertiary Infotech Academy Pte Ltd

HUMAN-IN-THE-LOOP GOVERNANCE

Powerful, but always under human oversight.

Approvals gate risky actions, budgets cap spend (warn at 80%, pause at 100%), and sandboxes isolate execution — so an agent stays safe as it scales.

© 2026 Tertiary Infotech Academy Pte Ltd

WHAT YOU'LL BUILD

Three Platforms, One Skillset


Hermes Agent

- Your personal chief-of-staff
- Lives across your messaging apps
- Cross-channel, memory, crons




OpenClaw

- Automates a business back-office
- Node.js gateway daemon
- Skills, tools, nightly reports



Paperclip

- A company of AI agents you govern
- Self-hosted with Docker
- Hiring, budgets, audit trail



© 2026 Tertiary Infotech Academy Pte Ltd

HOW EVERY LAB PROGRESSES

The Build Arc

1. Install the runtime → connect a model → add channels → give it memory.
2. Extend it with skills → wire in tools and integrations → schedule work with crons.
3. Secure it with sandboxing, secrets and approvals → drive it through commands.
4. Finish each platform by orchestrating a multi-agent team for an end-to-end outcome.
5. The same arc repeats on Hermes, OpenClaw and Paperclip — so the skillset transfers.

© 2026 Tertiary Infotech Academy Pte Ltd

01

TOPIC 01

Hermes Agent — Your Autonomous Personal Chief-of-Staff

Install & Setup · Deployment · Memory & Plugins · Skills · Providers & Model · MCP & Tools · Crons · Subagents · Profile & Kanban · Security

© 2026 Tertiary Infotech Academy Pte Ltd

EXAM WEIGHTING 33%

Key Concepts — Hermes Agent — Your Autonomous Personal Chief-of-Staff

1. Hermes Agent (Nous Research) installs on your own machine — via the install script or the Hermes Desktop app — and requires a model with a >=64,000-token context window.

2. Memory and plugins make the agent stateful and extensible: a three-layer memory (agent-curated notes, FTS5 cross-session recall, Honcho user modelling) plus installable skills and MCP tools.

3. Providers & models are swappable with no lock-in (Nous Portal, OpenRouter, OpenAI, any endpoint); MCP servers and the Tool Gateway (web search, image, TTS) give the agent real-world reach.

4. Cron jobs automate recurring work; subagents & delegation split work across isolated backends; the profile and Kanban board let you supervise the agent's tasks — all under security controls.

© 2026 Tertiary Infotech Academy Pte Ltd

WHAT YOU'LL DO

Hands-On Labs — Hermes Agent — Your Autonomous Personal Chief-of-Staff

Labs 1–5

- Install and Setup Hermes
- Deployment — Local Install & Hermes Desktop App
- Memory and Plugins
- Skills
- Providers & Model

Labs 6–10

- MCP and Tools
- Cron Jobs & Automation
- Subagents & Delegation
- Profile and Kanban
- Security

Labs 11–14

- Use Case — Make a Video with Hyperframe
- Visualization
- Build a Multi-Agent Video Team (Profiles + Kanban)
- Webhook

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 01 · HANDS-ON

Install and Setup Hermes

LAB 1

Install Hermes Agent on your laptop using any of the official install methods (Desktop installer, install script, PowerShell, from source, or Nix), run the first-time setup wizard, and confirm a healthy install. This is the foundation for the Athena chief-of-staff agent you build across the track. Prerequisite: Git; the installer auto-handles Python 3.11, Node.js v22, ripgrep and ffmpeg.

You'll build

A working Hermes Agent install that passes 'hermes doctor' and opens the TUI.

Tools: Hermes Agent, Nous Portal, terminal

© 2026 Tertiary Infotech Academy Pte Ltd

AN AI AGENT THAT LEARNS YOU.

What is Hermes Agent? Open source. Built by Nous Research. MIT license.

01 Runs in your terminal (CLI) or on your phone (gateway)

02 Works with any model — Claude, GPT, Grok, Kimi, local, whatever

03 Nous uses this same tool to generate training data for the Hermes model family

© 2026 Tertiary Infotech Academy Pte Ltd

THE BET: COMPOUNDING VALUE.

Most agents are stateless — every session starts from zero.

Hermes is stateful by design. Every session makes the next one better.

01	You give it a task
02	It captures a trajectory — tools used, decisions made
03	It extracts a reusable skill
04	Next time: faster, cleaner, smarter

© 2026 Tertiary Infotech Academy Pte Ltd

WILL IT RUN ON MY MACHINE?

macOS	Linux	Windows	Android
Native ✓	Native ✓	WSL2 only	Termux (v0.9.0)

AUTO-INSTALLED **Python 3.11, Node.js 22, uv, ripgrep, ffmpeg, git.**

Native Windows is explicitly unsupported. The installer refuses CYGWIN/MINGW/MSYS.

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 1

Install and Setup Hermes

STEP 1 OF 8

1

Install on macOS / Linux / WSL2 — run the official install script

```
$ curl -fsSL https://hermes-agent.nousresearch.com/install.sh | bash
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 1

Install and Setup Hermes

STEP 2 OF 8

2

Install on Windows — run the PowerShell installer

```
$ iex (irm https://hermes-agent.nousresearch.com/install.ps1)
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 1

Install and Setup Hermes

STEP 3 OF 8

3

Install Hermes Desktop — download the installer from hermes-agent.nousresearch.com, or launch it from an existing CLI install

```
$ hermes desktop
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 1

Install and Setup Hermes

STEP 4 OF 8

4

Other install options: from source (Development Setup) or Nix/NixOS (flake + module)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 1

Install and Setup Hermes

STEP 5 OF 8

5

Reload your shell so the 'hermes' command is on PATH

```
$ source ~/.zshrc
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 1

Install and Setup Hermes

STEP 6 OF 8

6

Run the first-time setup wizard

```
$ hermes setup --portal
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 1

Install and Setup Hermes

STEP 7 OF 8

7

Check the install is healthy

```
$ hermes doctor
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 1

Install and Setup Hermes

STEP 8 OF 8

8

Launch the agent and say hello

```
$ hermes --tui
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 1 · VERIFY

Install and Setup Hermes

✅ Test it

'hermes doctor' reports all green and the TUI opens and replies to a message.

© 2026 Tertiary Infotech Academy Pte Ltd

Deployment — Local Install & Hermes Desktop App

LAB 2

Run Hermes as a persistent local deployment (preferred) and also install the Hermes Desktop app for a GUI experience. Confirm the local gateway is serving and keep the runtime up to date.

You'll build

A local Hermes deployment plus the Desktop app, both talking to the same agent.

Tools: Hermes Agent, Hermes Desktop, terminal

© 2026 Tertiary Infotech Academy Pte Ltd

TELEGRAM.

Five steps. Phone → bot → VPS.

01	**@BotFather → /newbot →** copy token
02	**@userinfobot →** copy your Telegram user ID
03	**hermes setup gateway** on VPS → Telegram → paste token
04	**TELEGRAM_ALLOWED_USERS →** paste your user ID (allowlist mode)
05	**save + restart** gateway

NEVER set GATEWAY_ALLOW_ALL_USERS=true. Anyone who guesses your bot's username = full access.

© 2026 Tertiary Infotech Academy Pte Ltd

TOP 10 SLASH.


In-chat commands. Type them during a session.

/new	start a fresh conversation	**/queue <prompt>**	add to next-turn queue
/model <name>	swap model mid-session (v0.8.0+)	**/compress**	manually compact context
/fast	priority routing (OpenAI + Anthropic, v0.9.0)	**/skills**	browse / invoke a skill
/bg <prompt>	background task, keep chatting	**/yolo**	toggle dangerous-command approvals
/btw <question>	ephemeral side question	**/help**	everything else

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 2 · LIVE SCREENSHOT

Hermes in the Browser — Dashboard



The Hermes Dashboard (http://127.0.0.1:9119) — your local deployment's sessions view

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 2 · LIVE SCREENSHOT

Hermes in the Browser — Channels




The Channels page (127.0.0.1:9119/channels) — 31 channels from one gateway; credentials in ~/.hermes/.env

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 2 · LIVE SCREENSHOT

Hermes in the Browser — Achievements



The Achievements page — Hermes gamifies agent mastery with tiers (Copper → Silver → Gold → Diamond → Olympian) and unlockable badges

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 2

Deployment — Local Install & Hermes Desktop App

STEP 1 OF 5

1

Confirm the local install runs (preferred deployment)

```
$ hermes --version
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 2

Deployment — Local Install & Hermes Desktop App

STEP 2 OF 5

2

Download and install the Hermes Desktop app

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 2

Deployment — Local Install & Hermes Desktop App

STEP 3 OF 5

3

Open the Desktop app and sign in with the same Nous Portal account

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 2

Deployment — Local Install & Hermes Desktop App

STEP 4 OF 5

4 Verify the local gateway is serving

```
$ hermes gateway status
```

💬 **Or just ask:** “Check that your local gateway is up and serving”

© 2026 Tertiary Infotech Academy Pte Ltd

Deployment — Local Install & Hermes Desktop App

STEP 5 OF 5

5

Keep the runtime up to date

```
$ hermes update
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 2 · VERIFY

Deployment — Local Install & Hermes Desktop App

✅ Test it

Both the local CLI and the Desktop app drive the same agent; 'hermes gateway status' is healthy.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 01 · HANDS-ON

Memory and Plugins

LAB 3

Explore Hermes' three-layer memory (agent-curated notes, FTS5 cross-session recall, Honcho user modelling). Teach Athena a preference, recall it in a fresh session, and enable a plugin to extend behaviour.

You'll build

Athena remembers a stated preference across sessions and runs an enabled plugin.

Tools: Hermes Agent, memory, plugins

© 2026 Tertiary Infotech Academy Pte Ltd

SEARCH YOUR OWN HISTORY.

- Every CLI + gateway session indexed in **~/.hermes/state.db**
- Tool: **session_search** — full-text + Gemini Flash summarization
- The agent calls it **autonomously** when it suspects a prior conversation is relevant
- **v0.11.0** State.db now **auto-prunes + VACUUMs at startup**. No more cron-prune needed.

© 2026 Tertiary Infotech Academy Pte Ltd

L1 VS L2.

	PERSISTENT MEMORY (L1)	SESSION SEARCH (L2)
Capacity	~1,300 tokens total	Unlimited (all sessions)
Speed	Instant — already in context	Search + LLM summarization
Use case	Key facts always available	“Did we discuss X last week?”
Management	Curated by the agent	Automatic — every session stored
Token cost	Fixed (~1,300 / session)	On-demand — only when searched

L1 is **what's curated**. L2 is **what's archived**. Use both.

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 3

Memory and Plugins

STEP 1 OF 4

1

In a session, teach Athena a durable preference

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 3

Memory and Plugins

STEP 2 OF 4

2

Start a new session and confirm the preference is recalled

```
$ hermes --continue
```

> 💬 **Or just ask:** “What summary style did I ask you to remember?”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 3

Memory and Plugins

STEP 3 OF 4

3

Inspect stored memory/sessions

```
$ hermes sessions list
```

💬 **Or just ask:** “List my recent sessions and what each was about”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 3

Memory and Plugins

STEP 4 OF 4

4

Enable a plugin to extend the agent

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 3 · VERIFY

Memory and Plugins

✅ Test it

A preference taught in one session is recalled in a new session, and the enabled plugin is active.

© 2026 Tertiary Infotech Academy Pte Ltd

Skills

LAB 4

Browse and install open-standard skills (agentskills.io / Skills Hub) so Athena can perform new tasks. Skills are portable and can self-improve as the agent uses them.

You'll build


Athena equipped with at least one installed skill that it can invoke on request.

Tools: Hermes Agent, agentskills.io, Skills Hub

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 4 · LIVE SCREENSHOT

Hermes in the Browser — Skills



The Skills page of a live Hermes install — 97 skills, filterable by category, plus Learn-a-skill and New-skill

© 2026 Tertiary Infotech Academy Pte Ltd

SKILL CATEGORIES.

All 19 categories · 98 skills — live from the Hermes dashboard (Skills page).

Creative (21)	architecture-diagram, ascii-art, …
Mlops (13)	evaluating-llms-harness, weights-and-biases, …
Software Development (13)	debugging-hermes-tui-commands, hermes-agent-skill-authoring, …
Productivity (10)	airtable, google-workspace, …
Github (6)	codebase-inspection, github-auth, …
Media (6)	gif-search, heartmula, …
Apple (5)	apple-notes, apple-reminders, …
Autonomous Ai Agents (5)	claude-code, codex, …
Research (5)	arxiv, blogwatcher, …
General (3)	computer-use, dogfood, …

© 2026 Tertiary Infotech Academy Pte Ltd

SKILL CATEGORIES.

All 19 categories · 98 skills — live from the Hermes dashboard (Skills page).

Devops (2)	agent-infrastructure-ops, webhook-subscriptions
Gaming (2)	minecraft-modpack-server, pokemon-player
Data Science (1)	jupyter-live-kernel
Email (1)	himalaya
Mcp (1)	native-mcp
Note Taking (1)	obsidian
Red Teaming (1)	godmode
Smart Home (1)	openhue
Social Media (1)	xurl

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 4

Skills

STEP 1 OF 5

1

Browse the skills hub

```
$ hermes skills browse
```

💬 **Or just ask:** “Show me what skills are available on the skills hub”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 4

Skills

STEP 2 OF 5

2

Search for a skill by keyword

```
$ hermes skills search <keyword>
```

💬 **Or just ask:** “Search the skills hub for <keyword> skills”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 4

Skills

STEP 3 OF 5

3

Install a skill

```
$ hermes skills install <owner/skills/name>
```

💬 **Or just ask:** “Install the <name> skill from the skills hub and confirm it loaded”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 4

Skills

STEP 4 OF 5

4

Ask the agent to use the new skill and observe self-improvement

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 4

Skills

STEP 5 OF 5

5

The natural-language way — no CLI needed, just ask Athena: 'Learn the slide-deck skill from agentskills.io and confirm it is installed'

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 4 · VERIFY

Skills

✅ Test it

The installed skill appears in the agent's toolset and runs when invoked.

© 2026 Tertiary Infotech Academy Pte Ltd

Providers & Model

LAB 5

Connect a model provider (Nous Portal, OpenRouter, OpenAI or any endpoint) and select a model that meets the >=64,000-token context requirement. Switch providers to compare speed and quality.

You'll build


Athena running on a chosen provider/model, with the ability to switch on demand.

Tools: Hermes Agent, Nous Portal, OpenRouter

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 5 · LIVE SCREENSHOT

Hermes in the Browser — Providers & API Keys



The Keys page (127.0.0.1:9119/env) — OAuth provider logins (Nous Portal, OpenAI, MiniMax, Anthropic, …) and API keys, stored in ~/.hermes/.env

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 5

Providers & Model

STEP 1 OF 4

1

Open the interactive provider/model picker

```
$ hermes model
```

💬 **Or just ask:** “Show me the available providers and models, and which one you're on”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 5

Providers & Model

STEP 2 OF 4

2

Set a model explicitly

```
$ hermes config set model anthropic/claude-opus-4.6
```

💬 **Or just ask:** “Switch yourself to Claude Opus 4.6”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 5

Providers & Model

STEP 3 OF 4

3

Add a provider key if using a cloud endpoint

```
$ hermes config set OPENROUTER_API_KEY sk-or-...
```

> 💬 **Or just ask:** “Add my OpenRouter API key to your provider config”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 5

Providers & Model

STEP 4 OF 4

4

Confirm the active model meets the >=64k context rule

```
$ hermes model
```

💬 **Or just ask:** “Confirm your active model has at least a 64k context window”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 5 · VERIFY

Providers & Model

✅ Test it

The agent starts on the selected model and can be switched to another provider without reinstalling.

© 2026 Tertiary Infotech Academy Pte Ltd

MCP and Tools

LAB 6

Add Model Context Protocol (MCP) servers in the Hermes config and use the bundled Tool Gateway (web search, image generation, TTS) so Athena can act on the outside world.

You'll build

Athena wired to an MCP server (e.g. GitHub) and able to use a Tool Gateway tool.

Tools: Hermes Agent, MCP, Tool Gateway

© 2026 Tertiary Infotech Academy Pte Ltd

WHAT IS A TOOL?

A function the model can ask Hermes to run. That's it.

a tool = three small pieces

```python
# 1 — THE FUNCTION · plain Python, does the real work
def read_file(path):
    return open(path).read()

# 2 — THE DESCRIPTION · what the model reads to decide
SCHEMA = {"name": "read_file",
    "description": "Read a text file.",
    "parameters": {"path": "string"}}

# 3 — REGISTER · hand both to Hermes
registry.register("read_file", SCHEMA, read_file)
```

The model never runs it. It asks for it by name — Hermes runs the function and hands back whatever it returns.

© 2026 Tertiary Infotech Academy Pte Ltd

THE BUILT-IN CATALOG.

FILES & TERM

- read_file
- write_file
- patch
- search_files
- terminal
- process

WEB & BROWSER

- web_search
- web_extract
- browser_navigate
- browser_snapshot
- browser_click
- + 7 browser tools

MEDIA

- vision_analyze
- image_generate
- text_to_speech

ORCHESTRATION

- todo
- clarify
- execute_code
- delegate_task
- mixture_of_agents

MEMORY & MORE

- memory
- session_search
- cronjob
- send_message
- ha_* · rl_* · mcp_*

SCOPE

~70 tools across ~30 toolsets in the full registry — but your profile loads a subset. Plugin/platform toolsets (Spotify, Feishu, Kanban) only appear when active. read_file / search_files / patch exist so the agent never shells out to cat / grep / sed — structured, paginated, safer.

© 2026 Tertiary Infotech Academy Pte Ltd

TOOLS IN ACTION.

A real session — the agent picks tools by name and you watch every call live.

hermes chat

```
30 tools · 41 skills · /help for commands
Welcome to Hermes Agent! Type your message or /help for commands.

● Review the files in this directory
Initializing agent...

  skill   software-development-methods        0.1s
  find    *                                   1.9s
  exec    from hermes_tools import terminal   0.6s
  ( •_•)>⌐■-■  ruminating...

gpt-5.5 | 21.4K/272K | 8% | 59s
```

Every tool call is visible — name, arguments and per-call timing — while the status bar tracks model, context and cost.

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 6

MCP and Tools

STEP 1 OF 5

1

Open the Hermes config to add an MCP server

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 6

MCP and Tools

STEP 2 OF 5

2 Add a GitHub MCP server entry

```
$ npx -y @modelcontextprotocol/server-github
```

> 💬 **Or just ask:** “Add the GitHub MCP server to your tool config”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 6

MCP and Tools

STEP 3 OF 5

3

Restart so the MCP server is picked up, then verify

```
$ hermes doctor
```

💬 **Or just ask:** “Run a health check and confirm the GitHub MCP tools are loaded”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 6

MCP and Tools

STEP 4 OF 5

4

Use a Tool Gateway tool (web search / image / TTS) from a chat

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 6

MCP and Tools

STEP 5 OF 5

5

The natural-language way — just ask Athena: 'Add the GitHub MCP server to your tools and list what it can do'

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 6 · VERIFY

MCP and Tools

✅ Test it

The agent lists the new MCP server's tools and completes a task using a Tool Gateway tool.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 01 · HANDS-ON

Cron Jobs & Automation

LAB 7

Schedule Athena to run recurring jobs — for example an 8am daily briefing sent to your messaging app — and verify the scheduled run fires and produces output.

You'll build

A scheduled job (e.g. a daily briefing) that runs automatically and delivers a result.

Tools: Hermes Agent, scheduler/crons

© 2026 Tertiary Infotech Academy Pte Ltd

THREE WAYS TO SCHEDULE.

// CLI

hermes cron create

list · pause · resume

run · remove · status

The standalone command.

// CHAT

/cron add 30m "..."

From any messaging platform — Telegram, Discord, the CLI chat.

Same engine, slash command.

// THE AGENT

The **cronjob** tool.

"Every morning, summarize X and send it to me." → it **schedules itself**.

No CLI required.

Safety rail: a cron-run session **can't create more cron jobs**. No runaway scheduling loops.

© 2026 Tertiary Infotech Academy Pte Ltd

THE TICK.



The **gateway must be running** — it's the heartbeat. **hermes gateway install** makes it a service. A grace window catches up jobs missed during a short restart.

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 7

Cron Jobs & Automation

STEP 1 OF 5

1

Define a recurring job (daily 8am briefing) in the Hermes automation/cron config

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 7

Cron Jobs & Automation

STEP 2 OF 5

2 Confirm the automation is registered

```
$ hermes doctor
```

💬 **Or just ask:** “Check that my daily 8am briefing automation is registered”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 7

Cron Jobs & Automation

STEP 3 OF 5

3

Trigger the job once to confirm it produces output

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 7

Cron Jobs & Automation

STEP 4 OF 5

4

Confirm the next scheduled run is queued

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 7

Cron Jobs & Automation

STEP 5 OF 5

5

The natural-language way — just ask Athena: 'Every weekday at 8am, summarize the top AI news and send it to me on Telegram' — the agent schedules itself with its cronjob tool

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 7 · VERIFY

Cron Jobs & Automation

✅ Test it

The scheduled job runs at its time (or on manual trigger) and delivers the expected briefing.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 01 · HANDS-ON

Subagents & Delegation

LAB 8

Turn Athena into a coordinator that delegates tasks to worker subagents running on isolated terminal backends (local, docker, ssh, modal), then aggregates their results.

You'll build

A coordinator agent that delegates a task to one or more worker subagents and combines the output.

Tools: Hermes Agent, terminal backends (docker/ssh/modal)

© 2026 Tertiary Infotech Academy Pte Ltd

TWO PROBLEMS, ONE TOOL.

// CONTEXT POISONING

A long subtask — debugging, a 30-file refactor, deep research — **floods the parent's window** with tool output it will never need again. Quality drops as the window fills.

// SERIAL SLOWNESS

Researching 10 things one-at-a-time is **10× the wall-clock**. A single loop can only do one thing at a time.

Delegation fixes both at once — clean isolated contexts, running in parallel.

© 2026 Tertiary Infotech Academy Pte Ltd

DELEGATION IN ACTION.

A real session — the agent spins up isolated subagents to work in parallel.

hermes chat

```
Hermes Agent v0.17.0 · Available Tools: browser, clarify, …

● Delegate subagents to check the quants used for all qwen models tested in this experiment

Initializing agent...

  skill    autonomous-coding-agents                0.1s
  find     *                                       1.9s
  $        pwd && git rev-parse --show-toplevel    0.3s
  (o_o)  contemplating...

gpt-5.5 | 21.4K/272K | 8% | 5m
```

delegate_task hands each subtask to a fresh, isolated subagent — the parent's context stays clean.

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 8

Subagents & Delegation

STEP 1 OF 5

1

Choose an isolated backend for worker agents

```
$ hermes config set terminal.backend docker
```

💬 **Or just ask:** “Run your worker subagents in the docker sandbox from now on”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 8

Subagents & Delegation

STEP 2 OF 5

2

Ask the coordinator to delegate a multi-part task to subagents

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 8

Subagents & Delegation

STEP 3 OF 5

3

Observe each subagent run in isolation and report back

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 8

Subagents & Delegation

STEP 4 OF 5

4

Review the coordinator's aggregated result

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 8

Subagents & Delegation

STEP 5 OF 5

5

The natural-language way — just ask Athena: 'Delegate three subagents to research MiniMax, Kimi and DeepSeek in parallel, then merge the findings'

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 8 · VERIFY

Subagents & Delegation

✅ Test it

The coordinator delegates to worker subagents on an isolated backend and returns a combined result.

© 2026 Tertiary Infotech Academy Pte Ltd

Profile and Kanban

LAB 9

Configure the agent's profile and use the Hermes Kanban board to watch tasks move through todo -> in progress -> done, giving you human oversight of what Athena is working on.

You'll build

A configured agent profile and a Kanban board tracking the agent's live tasks.

Tools: Hermes Agent, profile, Kanban board

© 2026 Tertiary Infotech Academy Pte Ltd

SHARE A WHOLE AGENT.

// BACKUP / MOVE

hermes profile export coder → a **.tar.gz** snapshot · **import** to restore.

Your whole working config, portable.

// DISTRIBUTIONS

hermes profile install github.com/you/research-bot --alias

Installs a whole agent — SOUL + config + skills + cron + MCP — from a **git repo**.

profile update pulls the author's new version.

Build an agent once, share it as a repo. (Credentials, memories, and sessions stay per-machine.)

© 2026 Tertiary Infotech Academy Pte Ltd

FROM A FORK TO A TEAM.

// DELEGATE_TASK (M8)

In-process · **ephemeral** children · summary-only · dies if the parent is interrupted.

A fork you watch finish.

// THE KANBAN BOARD

Durable · **multi-profile** · survives restarts · a human can comment / unblock a task mid-flight.


A team you hand a project to.

When work must cross agents and survive restarts, you graduate from the fork to the board.

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 9 · LIVE SCREENSHOT

Hermes in the Browser — Profiles




The Profiles page (127.0.0.1:9119/profiles) — per-profile toolsets and defaults that shape what the agent may use

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 9 · LIVE SCREENSHOT

Hermes in the Browser — Kanban



The Kanban board — supervise the agent's tasks as they move across the columns

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 9

Profile and Kanban

STEP 1 OF 4

1

Set up the agent profile (identity, defaults, preferences)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 9

Profile and Kanban

STEP 2 OF 4

2

Open the Kanban board view

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 9

Profile and Kanban

STEP 3 OF 4

3

Assign a task and watch it move todo -> in progress -> done

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 9

Profile and Kanban

STEP 4 OF 4

4

Use the board to review and accept completed work

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 9 · VERIFY

Profile and Kanban

✅ Test it

The profile is set and the Kanban board shows tasks progressing across its columns.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 01 · HANDS-ON

Security

LAB 10

Harden Athena with defense in depth: restrict who can message the agent (default deny), run risky work in an isolated terminal backend, manage secrets safely, and require approval before sensitive actions — applying least privilege throughout.

You'll build

A hardened agent that allowlists its users, sandboxes execution, protects secrets and prompts for approval on risky actions.

Tools: Hermes Agent, gateway allowlists, terminal backends, secrets management

© 2026 Tertiary Infotech Academy Pte Ltd

NO SINGLE LAYER IS PERFECT.

Defense in depth: overlapping, independent layers — each catching what the others miss.

And every default is fail-closed: deny, not allow, when something's uncertain.

01	**Trust**	— who's allowed in the door
02	**Approve**	— what commands get a human check
03	**Contain**	— where the blast radius stops
04	**Filter**	— what secrets can leave
05	**Harden**	— what's checked before it starts

SCALE IT Solo laptop → light touch. Shared gateway → allowlists + sandboxing. Public-facing → every dial up.

© 2026 Tertiary Infotech Academy Pte Ltd

SIX CHECKS, THEN DENY.

Who may talk to your agent — every inbound message walks this chain; the first match wins.

01	**Per-platform allow-all**	DISCORD_ALLOW_ALL_USERS — that one platform is fully open
02	**DM pairing**	approved list — pairing codes the owner approved
03	**Platform allowlist**	TELEGRAM_ALLOWED_USERS — comma-separated user IDs
04	**Global allowlist**	GATEWAY_ALLOWED_USERS — one list across every channel
05	**Global allow-all**	GATEWAY_ALLOW_ALL_USERS — everything open (dev only)
06	**Default**	DENY — no rule matched, the message is dropped

FAILS CLOSED Nothing configured = everyone denied, with a startup warning saying exactly that. You must opt into openness.

© 2026 Tertiary Infotech Academy Pte Ltd

LOCK DOWN THE CHANNEL.

The same dials exist on every channel — shown here for Telegram (Channels → Configure).

BOT TOKEN	from @BotFather — the bot's identity
ALLOWED_USERS	comma-separated user IDs (from @userinfobot)
ALLOW_ALL_USERS	any user may trigger the bot — dev only
HOME CHANNEL	default chat for cron + notification delivery
PROXY URL	route via http / https / socks5 (optional)
PAIRING	unknown DMs get a code; the owner approves

© 2026 Tertiary Infotech Academy Pte Ltd

THREE MODES. NOT FOUR.

- **manual (default)** CLI: [o]nce / [s]ession / [a]lways / [d]eny, 60s timeout, fails closed. Gateway: buttons or yes / approve / go.
- **smart** an auxiliary LLM assesses risk — safe commands auto-approve, dangerous ones auto-deny, uncertain cases escalate to manual.
- **off** disables all approval checks — equivalent to running with --yolo permanently. Trusted environments only.

TIRITH Not a 4th mode — a parallel content scanner (security.tirith_*); runs in every mode, can add an approval prompt.

© 2026 Tertiary Infotech Academy Pte Ltd

APPROVAL, IN ACTION.

A real gateway session — the agent proposes a risky command; the human decides.

hermes chat — restarting the gateway

```
Hermes  Stopping the gateway with the official command.

⚠ Dangerous Command
hermes gateway stop 2>&1; sleep 1; hermes gateway status 2>&1;
pgrep -af 'hermes gateway' || echo 'no hermes gateway process'

❯ 1. Allow once
  2. Allow for this session
  3. Add to permanent allowlist
  4. Deny
  5. Show full command

stop/restart hermes gateway (kills running agents)
grok-4.5 | 35.1K/500K | 7% | 4m
```

The classifier names the risk in plain words — you decide: once, this session, or forever.

© 2026 Tertiary Infotech Academy Pte Ltd

YOLO MODE.

// CLI FLAG

$ hermes chat --yolo

Process-scoped — this run only.

// IN-CHAT TOGGLE

> /yolo

Session-scoped on the gateway — toggle it back off when done.

// ENV VAR

$ HERMES_YOLO_MODE=1

Environment-scoped — everything it launches.

All approval prompts bypassed. Two persistent reminders: a red banner at session start and a live ⚠ **YOLO** status-bar fragment.

© 2026 Tertiary Infotech Academy Pte Ltd

THE FLOOR BELOW --YOLO.

Refused regardless of YOLO, approvals.mode: off, cron auto-approve, or a permanent allowlist entry.

- **rm -rf /** and obvious variants — wipes the filesystem root
- **fork bomb** :(){ :|:& };: — pegs the host until reboot
- **mkfs on mounted root** formats the live system
- **dd if=/dev/zero of=/dev/sd*** zeroes a physical disk
- **curl | sh at rootfs top** an RCE vector too broad to ever approve

NO OVERRIDE Trips before the approval layer even sees the command — need one legitimately? Run it outside the agent.

© 2026 Tertiary Infotech Academy Pte Ltd

YOUR FILES CAN ATTACK YOU TOO.

Context files are scanned before entering the system prompt — a poisoned file is an attack surface.

- "Ignore prior instructions" text and hidden HTML comments with suspicious keywords
- Secret-read attempts (.env, credentials, .netrc) and curl exfiltration patterns
- Invisible Unicode — zero-width spaces, bidirectional overrides

BLOCKED 'AGENTS.md contained potential prompt injection. Content not loaded.' — visible, not silent.

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 10

Security

STEP 1 OF 5

1

Restrict who can message the agent — set the channel allowlist (Channels → Configure in the dashboard); with nothing configured, everyone is denied

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 10

Security

STEP 2 OF 5

2

Isolate execution in a sandboxed backend

```
$ hermes config set terminal.backend docker
```

💬 **Or just ask:** “Run your risky work in the docker sandbox from now on”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 10

Security

STEP 3 OF 5

3

Store provider/tool secrets via config rather than plain text

```
$ hermes config set <PROVIDER>_API_KEY <value>
```

💬 **Or just ask:** “Store this <PROVIDER> API key securely in your config”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 10

Security

STEP 4 OF 5

4

Require approval before the agent runs risky actions — 'manual' prompts you; 'smart' adds an LLM risk assessor; never 'off' outside trusted environments

```
$ hermes config set approvals.mode manual
```

💬 **Or just ask:** “Ask me for approval before running any risky action”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 10

Security

STEP 5 OF 5

5

Apply least privilege — grant only the tools/skills the task needs

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 10 · VERIFY

Security

✅ Test it

Only allowlisted users reach the agent; risky actions run in the sandbox and only after approval; secrets are not stored in plain text.

© 2026 Tertiary Infotech Academy Pte Ltd

Use Case — Make a Video with Hyperframe

LAB 11

Put Athena to work on an end-to-end creative task: use the agent to drive the Hyperframe tool and generate a short video from a concept brief, then review and refine the result.

You'll build

A short video generated end-to-end by the agent using Hyperframe.

Tools: Hermes Agent, Hyperframe

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 11

Use Case — Make a Video with Hyperframe

STEP 1 OF 7

1

Install / verify the Hyperframe video skill so the agent can call it (verify exact name in the video/docs)

```
$ hermes skills search hyperframe
```

💬 **Or just ask:** “Find the Hyperframe video skill on the skills hub and install it”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 11

Use Case — Make a Video with Hyperframe

STEP 2 OF 7

2

Set any required Hyperframe API key via config (never plain text)

```
$ hermes config set HYPERFRAME_API_KEY <value>
```

> 💬 **Or just ask:** “Save my Hyperframe API key securely in your config”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 11

Use Case — Make a Video with Hyperframe

STEP 3 OF 7

3

Confirm the tool is loaded and healthy, then start a session

```
$ hermes doctor
```

> 💬 **Or just ask:** “Run a health check and confirm the Hyperframe skill is loaded”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 11

Use Case — Make a Video with Hyperframe

STEP 4 OF 7

4

Brief the agent with a concrete 3-sentence brief (topic, style, length)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 11

Use Case — Make a Video with Hyperframe

STEP 5 OF 7

5

Have the agent generate the video with Hyperframe and wait for the render

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 11

Use Case — Make a Video with Hyperframe

STEP 6 OF 7

6

Play the result, give one round of feedback, and regenerate

© 2026 Tertiary Infotech Academy Pte Ltd

Use Case — Make a Video with Hyperframe

STEP 7 OF 7

7

Export / save the final video and note where the file lands (session workspace)

```
$ open ~/.hermes/
```

> 💬 **Or just ask:** “Where did you save the final video? Give me the file path”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 11 · VERIFY

Use Case — Make a Video with Hyperframe

✅ Test it

The agent produces a playable video from your brief using Hyperframe, and you can locate the saved file.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 01 · HANDS-ON

Visualization

LAB 12

Use Hermes' visualization capability to see the agent's workflow, task flow and data at a glance, making the agent's behaviour transparent and easier to supervise.

You'll build

A visualization of the agent's workflow / activity you can read and interpret.

Tools: Hermes Agent, visualization

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 12

Visualization

STEP 1 OF 7

1

Run a real multi-step session first so there is activity to visualize

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 12

Visualization

STEP 2 OF 7

2

List sessions and note the ID of the one to visualize

```
$ hermes sessions list
```

💬 **Or just ask:** “List my recent sessions so I can pick one to visualize”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 12

Visualization

STEP 3 OF 7

3

Open the visualization / activity view in the Desktop app (verify location in the video/docs)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 12

Visualization

STEP 4 OF 7

4

Generate a workflow graph of that session — nodes are tool calls, edges are the order they ran

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 12

Visualization

STEP 5 OF 7

5

Read the graph: identify each tool call, the sequence, and where time was spent

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 12

Visualization

STEP 6 OF 7

6

Export or screenshot the visualization for your records

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 12

Visualization

STEP 7 OF 7

7

Use the graph to explain to a colleague exactly what the agent did

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 12 · VERIFY

Visualization

✅ Test it

A workflow visualization of a real session renders; you can name each node (tool call) and explain what the agent did.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 01 · HANDS-ON

Build a Multi-Agent Video Team (Profiles + Kanban)

LAB 13

Build a team of three Hermes profiles — a researcher (long-context model) that reads sources and writes the video brief, a scriptwriter (cheap model) that turns the brief into a narrated script, and a video_producer (code/tool model) that renders the video with TTS and slides — then create a Kanban board task, decompose it into child tasks, and let the orchestrator route each child task to the right profile by its description. The board is a durable SQLite database (~/.hermes/kanban.db) and each task gets its own workspace.


You'll build

A three-profile video team whose Kanban tasks flow triage -> todo -> ready -> running -> done and deliver a rendered video.

Tools: Hermes Agent, profiles, Kanban board, dashboard

© 2026 Tertiary Infotech Academy Pte Ltd

A GOAL, ROUTED TO PROFILES.



A durable SQLite board (~/.hermes/kanban.db) where the **assignee is a profile**. The orchestrator routes by the profile's **description**.

© 2026 Tertiary Infotech Academy Pte Ltd

DRIVE THE BOARD.

Three surfaces — the CLI, /kanban in any chat, and the dashboard board.

the kanban surface

```
$ hermes kanban create "Ship the feature" --assignee coder
$ hermes kanban decompose <id>   # fan into child tasks, routed by description
$ hermes kanban list · show · assign · dispatch
$ hermes kanban swarm "..." --workers a,b --verifier c --synthesizer d

also: /kanban in any chat · a dashboard board (drag-drop, attachments)
```

Workers get a gated kanban_* toolset — they update the board through tools, never by shelling hermes kanban.

© 2026 Tertiary Infotech Academy Pte Ltd

A REAL TASK LIFECYCLE.

- **STATUSES** triage → todo → ready → running → blocked → done → archived (+ scheduled)
- **WORKSPACE** each task gets one: scratch (tmp, wiped on done) · dir:<abs-path> · a git worktree
- **goal_mode** a worker runs a /goal loop against a judge until acceptance criteria are met — plus file/image attachments (vision)

NOTE A task runs on its assignee profile's model — no per-task override. Want a different model? Route it to a different profile.

© 2026 Tertiary Infotech Academy Pte Ltd

THE TEAM.

- **// RESEARCHER** web / long-context model · --description "Reads sources + docs, writes findings."
- **// CODER** terminal + file, a code model · --description "Implements + tests from a spec."
- **// WRITER** cheap model · --description "Turns findings + code into a clear write-up."
- **// BOARD** the orchestrator decomposes "research approach X, prototype it, write it up" → routes each subtask by description

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 13

Build a Multi-Agent Video Team (Profiles + Kanban)

STEP 1 OF 8

1

Create the researcher profile on a long-context model (verify syntax in the video/docs)

```
$ hermes profile create researcher --description "Reads sources, writes the video brief + key points"
```

💬 **Or just ask:** “Create a researcher profile on a long-context model that writes video briefs”

© 2026 Tertiary Infotech Academy Pte Ltd

Build a Multi-Agent Video Team (Profiles + Kanban)

STEP 2 OF 8

2

Create the scriptwriter (cheap model) and video_producer (code/tool model) profiles the same way

```
$ hermes profile create scriptwriter --description "Turns the brief into a narrated script + scene list"
```

💬 **Or just ask:** “Create scriptwriter and video_producer profiles for the script and the render”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 13

Build a Multi-Agent Video Team (Profiles + Kanban)

STEP 3 OF 8

3

Confirm all three profiles on the dashboard Profiles page

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 13

Build a Multi-Agent Video Team (Profiles + Kanban)

STEP 4 OF 8

4 Create the board task and assign the first stage

```
$ hermes kanban create "Produce a 60-second explainer video on <topic>" --assignee researcher
```

> 💬 **Or just ask:** “Add a Kanban task: produce a 60-second explainer on <topic>, assign it to the researcher”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 13

Build a Multi-Agent Video Team (Profiles + Kanban)

STEP 5 OF 8

5

Decompose the task into child tasks routed to profiles by description

```
$ hermes kanban decompose <id>
```

💬 **Or just ask:** “Decompose that board task into child tasks and route each to the right profile”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 13

Build a Multi-Agent Video Team (Profiles + Kanban)

STEP 6 OF 8

6

Watch the lanes on the dashboard as tasks run (triage -> todo -> ready -> running -> done)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 13

Build a Multi-Agent Video Team (Profiles + Kanban)

STEP 7 OF 8

7

Review each task's workspace deliverables and accept the final video to done

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 13

Build a Multi-Agent Video Team (Profiles + Kanban)

STEP 8 OF 8

8

The natural-language way — just ask the agent: 'Create a crew of profiles — researcher, scriptwriter, video producer — then decompose this board task and route each piece to the right profile'

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 13 · VERIFY

Build a Multi-Agent Video Team (Profiles + Kanban)

✅ Test it

Three profiles exist, the decomposed Kanban tasks route to the right profile by description, and the accepted board delivers a rendered video.

© 2026 Tertiary Infotech Academy Pte Ltd

Webhook

LAB 14

Wire the agent to the outside world with webhooks: trigger the agent from an incoming webhook payload and/or have it call an outgoing webhook, then secure the endpoint.

You'll build

A webhook that triggers the agent (or that the agent calls), verified end-to-end.

Tools: Hermes Agent, webhooks

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 14

Webhook

STEP 1 OF 7

1

Confirm the local gateway is serving (webhooks ride on it)

```
$ hermes gateway status
```

💬 **Or just ask:** “Check the gateway is up so webhooks can reach you”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 14

Webhook

STEP 2 OF 7

2

Create / enable a webhook endpoint on the dashboard Webhooks page (verify exact flow in the video/docs)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 14

Webhook

STEP 3 OF 7

3

Copy the endpoint URL and map it to an agent action (e.g. run a briefing)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 14

Webhook

STEP 4 OF 7

4

Send a test payload with curl and expect a 2xx response

```
$ curl -X POST <endpoint-url> -H "Content-Type: application/json" -d '{"event":"test","message":"Trigger Athena briefing"}'
```

💬 **Or just ask:** “POST a test payload to the webhook endpoint and confirm a 2xx response”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 14

Webhook

STEP 5 OF 7

5

Watch the agent react — the mapped action runs and its output appears in chat/logs

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 14

Webhook

STEP 6 OF 7

6

Secure the endpoint with a shared secret and/or IP allowlist, then re-send with the secret header

```
$ curl -X POST <endpoint-url> -H "Authorization: Bearer <secret>" -H "Content-Type: application/json" -d '{"event":"test"}'
```

💬 **Or just ask:** “Re-send the test payload with the Bearer secret header and confirm it's accepted”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 14

Webhook

STEP 7 OF 7

7

Confirm a call WITHOUT the secret is now rejected (401/403)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 14 · VERIFY

Webhook

✅ Test it

A test payload to the webhook triggers the agent's mapped action, and calls without the secret are rejected.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC RECAP

Recap — Hermes Agent — Your Autonomous Personal Chief-of-Staff

1. You can now: LO1: Install and configure Hermes Agent on a local machine.
2. You can now: LO1: Deploy Hermes locally and run it through the Hermes Desktop app.
3. You can now: LO2: Give the agent persistent memory and extend it with plugins.
4. You can now: LO3: Extend the agent with installable, self-improving skills.
5. You can now: LO2: Connect an LLM provider and switch models with no lock-in.
6. You can now: LO3: Give the agent real-world reach with MCP servers and the Tool Gateway.

© 2026 Tertiary Infotech Academy Pte Ltd

02

TOPIC 02

OpenClaw — Automating a Business Back-Office

Install · Providers · Channels · Skills · Tools · Commands · Crons · Memory · Dreaming · Security · Multi-Agent · Use Cases

© 2026 Tertiary Infotech Academy Pte Ltd

OpenClaw — The Wikipedia History

OpenClaw (formerly **Clawdbot, Moltbot,** and **Molty**) is a free and open-source autonomous artificial intelligence agent developed by Peter Steinberger. It is an autonomous agent that can execute tasks via large language models, using messaging platforms as its main user interface.

OpenClaw achieved popularity in late-January 2026, credited to its open source nature and the viral popularity of the Moltbook project. On February 14, 2026, Steinberger announced he will be joining OpenAI and the project will be moved to an open-source foundation.[1]

History [edit]

The project was originally published in November 2025 by Austrian vibe coder[2] Peter Steinberger, under the name Clawdbot. The software was derived from Clawd (now Molty), an AI-based virtual assistant that he had developed, which itself was named after Anthropic's chatbot Claude.[3] It was renamed "Moltbot" (keeping with a lobster theme) on January 27, 2026, following trademark complaints by Anthropic, and again to "OpenClaw" three days later after Steinberger found that the name Moltbot "never quite rolled off the tongue."[4][5]



Clawdbot (Nov 2025) → Moltbot → OpenClaw (Jan 2026); Steinberger joins OpenAI Feb 14, 2026 — source: en.wikipedia.org/wiki/OpenClaw


© 2026 Tertiary Infotech Academy Pte Ltd

FROM PROMPTS TO HARNESSES.

- **Prompt Engineering** ChatGPT, Gemini, Claude Chat — craft the words
- **Context Engineering** Claude Code, Codex, Gemini CLI — feed the right context
- **Harness Engineering** OpenClaw, Hermes Agent — build the machine around the model

© 2026 Tertiary Infotech Academy Pte Ltd

The Model Reasons. The Harness Does the Rest.



Model = CPU / reasoning engine · Context = RAM / working memory · Harness = operating system

© 2026 Tertiary Infotech Academy Pte Ltd

> openclaw = linux of ai agents

PEOPLE ↔ AGENT ↔ MODEL.

Channels	🦞 OpenClaw	Models	Memory
WhatsApp · Telegram · Discord · Web UI	runs on your computer	Claude Code · Codex · MiniMax · Kimi	workspace + MEMORY.md

OpenClaw sits between your messaging apps and any language model — open, local and hackable, like Linux was for servers.

© 2026 Tertiary Infotech Academy Pte Ltd

EXAM WEIGHTING 33%

Key Concepts — OpenClaw — Automating a Business Back-Office

1. OpenClaw runs on Node.js 24 LTS as a long-running gateway daemon that hosts every channel, tool, cron and skill for the Nimbus Supplies back office.

2. Providers are connected by OAuth sign-in (OpenAI Codex, MiniMax) or API key (Anthropic, DeepSeek, OpenRouter); skills from skills.sh and integrations such as Firecrawl and AgentMail extend the agent.

3. 'Dreaming' lets the agent reflect during idle time — reviewing memory and generating follow-ups — while profiles and allow/deny lists keep every channel least-privileged and audited.

4. Crons schedule recurring work, a heartbeat auto-restarts the gateway, and a multi-agent capstone splits work across cooperating Sales, Research and Ops agents for real back-office use cases.

© 2026 Tertiary Infotech Academy Pte Ltd

WHAT YOU'LL DO

Hands-On Labs — OpenClaw — Automating a Business Back-Office

Labs 15–18

- Install OpenClaw
- Models & Providers
- Channels
- Skills

Labs 19–22

- Tools & Integrations
- Commands
- Cron Jobs & Heartbeat
- Memory & Context

Labs 23–26

- Security
- Multi-Agent Workforce
- Dreaming — Idle Reflection & Self-Improvement
- Use Cases & Key Functions

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 02 · HANDS-ON

Install OpenClaw

LAB 15

The learner installs the OpenClaw platform on their own machine (or a cloud VPS) by first installing Node.js 24 LTS, then installing OpenClaw via npm and running the onboarding wizard, and verifies the install with doctor and gateway status. This gateway becomes the back-office brain of the Nimbus Supplies running example.

You'll build

A running OpenClaw gateway daemon (local or VPS) verified with openclaw doctor

Tools: OpenClaw, Node.js 24 LTS, npm, openclaw gateway

© 2026 Tertiary Infotech Academy Pte Ltd

WHERE TO RUN IT.

Local	VPS	As-a-Service	Bots
your workstation	Hostinger openclaw hosting	myclaw.ai · clawdi.ai	CoPaw · NemoClaw

Start local for the labs; move to a VPS for 24/7 operation; managed services when you don't want to run infrastructure.

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 15

Install OpenClaw

STEP 1 OF 6

1

Install Node.js 24 LTS on macOS with Homebrew and verify

```
$ brew install node@24
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 15

Install OpenClaw

STEP 2 OF 6

2

Install OpenClaw globally via npm

```
$ npm install -g openclaw@latest
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 15

Install OpenClaw

STEP 3 OF 6

3

Run the interactive onboarding wizard that creates ~/.openclaw and the gateway

```
$ openclaw onboard
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 15

Install OpenClaw

STEP 4 OF 6

4

Verify the install version

```
$ openclaw --version
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 15

Install OpenClaw

STEP 5 OF 6

5

Run the health check (Node, gateway daemon, providers, channels)

```
$ openclaw doctor
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 15

Install OpenClaw

STEP 6 OF 6

6

Confirm the gateway is running, starting it if needed

```
$ openclaw gateway start
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 15 · VERIFY

Install OpenClaw

✅ Test it

openclaw --version prints a version, openclaw doctor shows green checks for Node 24 and the gateway daemon (provider/channel checks pending until Labs 16-17), and openclaw gateway status reports running.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 02 · HANDS-ON

Models & Providers

LAB 16

The learner connects a language model to OpenClaw, trying the supported provider options — OAuth sign-ins (OpenAI Codex, MiniMax) and API-key providers (Anthropic, DeepSeek, OpenRouter) — learns where credentials are stored under ~/.openclaw/auth/, hot-swaps between models, and runs a Nimbus Supplies smoke test.

You'll build

A Nimbus Supplies agent wired to a working model provider that passes openclaw model test

Tools: OpenClaw, OpenAI Codex / MiniMax (OAuth), Anthropic / DeepSeek / OpenRouter (API key)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 16

Models & Providers

STEP 1 OF 7

1

See the available models and the current selection

```
$ openclaw models list
```

💬 **Or just ask:** “Which models can you use, and which one is active right now?”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 16

Models & Providers

STEP 2 OF 7

2

Option A - sign in to OpenAI Codex via OAuth

```
$ openclaw models auth login --provider openai-codex
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 16

Models & Providers

STEP 3 OF 7

3

Option C - set an Anthropic API key and select a Claude model

```
$ openclaw config set model anthropic/claude-opus-4-7
```

> 💬 **Or just ask:** “Switch your model to Anthropic's Claude Opus 4.7”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 16

Models & Providers

STEP 4 OF 7

4

Test that the active model responds

```
$ openclaw model test
```

💬 **Or just ask:** “Say hello so I can confirm your model connection works”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 16

Models & Providers

STEP 5 OF 7

5

Persist an API key so it survives reboots

```
$ echo 'export ANTHROPIC_API_KEY="sk-ant-..."' >> ~/.zshrc
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 16

Models & Providers

STEP 6 OF 7

6

Hot-swap the global default model and confirm

```
$ openclaw model use deepseek/deepseek-v4
```

💬 **Or just ask:** “Make DeepSeek v4 your default model from now on”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 16

Models & Providers

STEP 7 OF 7

7

Give the agent a Nimbus Supplies smoke test from CLI chat

```
$ openclaw
```

💬 **Or just ask:** “Introduce yourself in two sentences as the Nimbus Supplies back-office assistant”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 16 · VERIFY

Models & Providers

✅ Test it

openclaw models list shows the connected models, openclaw model current prints the active one, openclaw model test returns a short successful completion with no auth error, and OAuth credentials appear under ~/.openclaw/auth/.

© 2026 Tertiary Infotech Academy Pte Ltd

Channels

LAB 17

The learner gives customers a way to reach the Nimbus Supplies agent by creating a Telegram bot end-to-end via BotFather, registering it with a token, pairing a WhatsApp number by scanning a QR code, and running both channels at once through a single OpenClaw gateway so the same agent answers on either platform.

You'll build

Telegram and WhatsApp both live on one OpenClaw gateway, answered by the same Nimbus Supplies agent

Tools: OpenClaw, Telegram (BotFather), WhatsApp, openclaw channel

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 17

Channels

STEP 1 OF 6

1

Create a Telegram bot in BotFather with /newbot and copy the HTTP API token

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 17

Channels

STEP 2 OF 6

2

Register the Telegram channel with the bot token

```
$ openclaw channel add telegram --token 123456789:ABC-DEF1234ghIkl-zyx57W2v1u123ew11
```

💬 **Or just ask:** “Connect Telegram using the bot token I got from BotFather”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 17

Channels

STEP 3 OF 6

3 Start the Telegram channel

```
$ openclaw channel start telegram
```

💬 **Or just ask:** “Start the Telegram channel and confirm it is live”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 17

Channels

STEP 4 OF 6

4

Add the WhatsApp channel to print a pairing QR code

```
$ openclaw channel add whatsapp
```

💬 **Or just ask:** “Add WhatsApp as a channel and show me the pairing QR code”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 17

Channels

STEP 5 OF 6

5

Start WhatsApp, then scan the QR from WhatsApp -> Linked Devices -> Link a Device

```
$ openclaw channel start whatsapp
```

💬 **Or just ask:** “Start the WhatsApp channel so I can scan the QR code”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 17

Channels

STEP 6 OF 6

6

Confirm both channels are running simultaneously

```
$ openclaw channel list
```

💬 **Or just ask:** “Which channels are you listening on right now?”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 17 · VERIFY

Channels

✅ Test it

openclaw channel list shows telegram and whatsapp both running, a message to the Telegram bot gets an agent reply, a message to the linked WhatsApp account gets an agent reply, and openclaw gateway status shows both connected.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 02 · HANDS-ON

Skills

LAB 18

The learner installs and removes skills from the skills.sh registry, invokes them from chat, and builds a custom Nimbus Supplies skill (nimbus-quote) under ~/.openclaw/skills/ so the agent handles a recurring back-office task — drafting an itemised customer quote with GST — the same way every time.

You'll build

Registry skills plus a custom nimbus-quote skill that produces itemised, GST-inclusive quotes

Tools: OpenClaw, skills.sh registry, ~/.openclaw/skills/, openclaw skills

© 2026 Tertiary Infotech Academy Pte Ltd

SKILLS ARE JUST SKILL.MD FILES.

- **Tools** are built-in functions the model calls — exec, read, write, browse.
- **Skills** are SKILL.md instructions dropped in the designated folder — the agent reads them and follows the recipe.
- **ClawHub** (clawhub.ai) is the community registry — install a skill with one command.

CAREFUL Koi Security audited 2,857 ClawHub skills and found 341 malicious. Read a skill before you install it.

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 18 · MASTERCLASS

Get a New Skill — Just Add SKILL.md




Drop SKILL.md in the designated folder and the agent can do something new

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 18 · MASTERCLASS

ClawHub — The Skill Dock for Sharp Agents



© 2026 Tertiary Infotech Academy Pte Ltd

LAB 18

Skills

STEP 1 OF 8

1

List the skills currently installed

```
$ openclaw skills list
```

💬 **Or just ask:** “What skills do you have installed?”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 18

Skills

STEP 2 OF 8

2

Install a useful skill from the skills.sh registry

```
$ openclaw skills add web-research --source skills.sh
```

💬 **Or just ask:** “Install the web-research skill from the skills.sh registry”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 18

Skills

STEP 3 OF 8

3

Invoke a skill from a channel with the /skill slash command

```
$ /skill web-research "Who are the main office-supplies wholesalers in Singapore?"
```


© 2026 Tertiary Infotech Academy Pte Ltd

Skills

STEP 4 OF 8

4

Create the folder for a custom Nimbus Supplies skill

```
$ mkdir -p ~/.openclaw/skills/nimbus-quote
```

💬 **Or just ask:** “Create a new custom skill called nimbus-quote for drafting itemised customer quotes”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 18

Skills

STEP 5 OF 8

5

Author skill.md with front-matter (name, description) and the quoting instructions

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 18

Skills

STEP 6 OF 8

6

Restart the gateway so the new skill is picked up

```
$ openclaw gateway restart
```

💬 **Or just ask:** “Reload your skills so the new nimbus-quote skill is picked up”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 18

Skills

STEP 7 OF 8

7

Test the custom skill from a channel

```
$ /skill nimbus-quote "Customer: Acme Cafe. 10 reams recycled A4 paper, 5 boxes black pens."
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 18

Skills

STEP 8 OF 8

8

The natural-language way — just message the agent: 'Install the github skill from ClawHub and show me what it can do'

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 18 · VERIFY

Skills

✅ Test it

openclaw skills list shows the registry skills plus the custom nimbus-quote, /skill web-research runs end-to-end, and /skill nimbus-quote produces an itemised quote with a 9% GST line and standard terms, marking any unknown price as TBC instead of guessing.

© 2026 Tertiary Infotech Academy Pte Ltd

Tools & Integrations

LAB 19

The learner extends the Nimbus Supplies agent with two real integrations — Firecrawl (JS-rendered web scraping) and AgentMail (its own inbox/outbox) — then runs an end-to-end back-office task: research a supplier's website prices, draft an itemised quote with the Lab 18 skill, and email it to a customer. Tool profiles and allow/deny lists scope tools per channel.


You'll build

A Firecrawl + AgentMail integrated agent that scrapes supplier prices and emails an itemised quote

Tools: OpenClaw, Firecrawl, AgentMail, openclaw tools

© 2026 Tertiary Infotech Academy Pte Ltd

AgentMail — Email Inboxes for AI Agents



© 2026 Tertiary Infotech Academy Pte Ltd

LAB 19

Tools & Integrations

STEP 1 OF 7

1

Inspect the built-in tool groups (fs, web, runtime, media)

```
$ openclaw tools list
```

> 💬 **Or just ask:** “What tools do you have, grouped by category?”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 19

Tools & Integrations

STEP 2 OF 7

2

Enable Firecrawl with its API key

```
$ openclaw tools enable firecrawl --api-key "$FIRECRAWL_API_KEY"
```

💬 **Or just ask:** “Enable the Firecrawl scraping tool with my API key”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 19

Tools & Integrations

STEP 3 OF 7

3

Enable AgentMail with its API key and inbox address

```
$ openclaw tools enable agentmail --api-key "$AGENTMAIL_API_KEY" --inbox bot@yourname.agentmail.to
```

💬 **Or just ask:** “Set up AgentMail with my API key so you have your own inbox”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 19

Tools & Integrations

STEP 4 OF 7

4

Run the end-to-end task from a channel: scrape prices, draft the quote, email it

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 19

Tools & Integrations

STEP 5 OF 7

5

Scope tools on a public channel by denying shell exec

```
$ openclaw channel set telegram --deny exec
```

💬 **Or just ask:** “On the Telegram channel, block shell command execution”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 19

Tools & Integrations

STEP 6 OF 7

6

Allow only the web tool group on that channel

```
$ openclaw channel set telegram --allow group:web
```

💬 **Or just ask:** “On Telegram, allow only the web tool group”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 19

Tools & Integrations

STEP 7 OF 7

7

The natural-language way — just message the agent: 'Use the browser to pull today's top three AI headlines and save them to headlines.md'

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 19 · VERIFY

Tools & Integrations

✅ Test it

openclaw tools list --enabled shows firecrawl and agentmail, the agent scrapes a supplier URL and returns structured prices, an AgentMail send arrives in a real inbox, the end-to-end task produces an itemised quote email, and a channel set to --deny exec refuses shell-exec requests.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 02 · HANDS-ON

Commands

LAB 20

The learner becomes fluent in the two ways to drive OpenClaw daily: the CLI commands (config, model, doctor, gateway, channel, tools, skills, cron) and the in-chat slash commands operators and customers use inside a channel, building a personal quick-reference table for running the Nimbus Supplies back office and streaming live gateway logs.

You'll build

A personal quick-reference of the CLI and slash commands used to run Nimbus Supplies day to day

Tools: OpenClaw, openclaw CLI, in-chat slash commands

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 20

Commands

STEP 1 OF 6

1

Read and change settings with config

```
$ openclaw config list
```

💬 **Or just ask:** “Show me your current configuration settings”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 20

Commands

STEP 2 OF 6

2

Run the health check with auto-fix

```
$ openclaw doctor --fix
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 20

Commands

STEP 3 OF 6

3

Control the gateway daemon that runs everything

```
$ openclaw gateway restart
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 20

Commands

STEP 4 OF 6

4

Get your channel user ID for the Lab 23 allowlist

```
$ /whoami
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 20

Commands

STEP 5 OF 6

5

Switch the model for one conversation only

```
$ /model deepseek/deepseek-v4
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 20

Commands

STEP 6 OF 6

6

Watch activity live while you chat

```
$ openclaw gateway logs --follow
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 20 · VERIFY

Commands

✅ Test it

You can switch the model both from chat (/model, per-conversation) and globally from the CLI (openclaw model use), /whoami returns your platform user ID, openclaw gateway logs --follow streams live activity, and /help lists the available slash commands.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 02 · HANDS-ON

Cron Jobs & Heartbeat

LAB 21

The learner makes Nimbus Supplies run unattended by scheduling recurring tasks with cron (a nightly sales report and a weekly supplier price-check using Firecrawl) and monitoring uptime with the heartbeat, so the gateway self-checks, auto-restarts on failure, and can page an external monitor if it dies.

You'll build

A nightly sales-report cron, a weekly price-check cron, and an enabled self-healing heartbeat

Tools: OpenClaw, openclaw cron, gateway heartbeat, Firecrawl + AgentMail


© 2026 Tertiary Infotech Academy Pte Ltd

THE HEARTBEAT.

- **Every fixed interval** the gateway stamps a heartbeat and wakes the agent.
- **HEARTBEAT.md** lists the routine tasks to run on each beat — check mail, tidy the inbox, post the report.
- **No human needed** — the agent does its rounds and goes back to sleep.

© 2026 Tertiary Infotech Academy Pte Ltd


The HEARTBEAT Mechanism



Every fixed interval the gateway stamps a heartbeat prompt: read HEARTBEAT.md, follow it strictly, reply HEARTBEAT_OK if nothing needs attention.

© 2026 Tertiary Infotech Academy Pte Ltd

The Autonomic Nervous System



Every 30 minutes the gateway triggers a system-level ping — the agent evaluates its environment, checks triggers, then acts or returns to sleep.

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 21

Cron Jobs & Heartbeat

STEP 1 OF 7

1

Create the nightly sales-report cron posting to Telegram at 21:00

```
$ openclaw cron create --schedule "0 21 * * *" --prompt "Summarise today's Nimbus Supplies customer chats and any quotes sent." --channel telegram --name nightly-sales-report
```

💬 **Or just ask:** “Every night at 9pm, summarise today's customer chats and quotes and post it to Telegram”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 21

Cron Jobs & Heartbeat

STEP 2 OF 7

2

List and inspect your crons

```
$ openclaw cron list
```

💬 **Or just ask:** “What cron jobs do you have scheduled?”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 21

Cron Jobs & Heartbeat

STEP 3 OF 7

3

Fire a cron on demand to test it now, ignoring the schedule

```
$ openclaw cron run nightly-sales-report
```

💬 **Or just ask:** “Run the nightly sales report right now so I can check it works”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 21

Cron Jobs & Heartbeat

STEP 4 OF 7

4

Enable the heartbeat self-check at a 60s interval

```
$ openclaw gateway heartbeat enable --interval 60s
```

💬 **Or just ask:** “Turn on your heartbeat self-check every 60 seconds”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 21

Cron Jobs & Heartbeat

STEP 5 OF 7

5

Check the heartbeat status

```
$ openclaw gateway heartbeat status
```

💬 **Or just ask:** “Is your heartbeat healthy? Give me the status”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 21

Cron Jobs & Heartbeat

STEP 6 OF 7

6

Confirm auto-restart by stopping the gateway and waiting ~60s

```
$ openclaw gateway stop
```

💬 **Or just ask:** “Shut down your gateway - I want to check the heartbeat restarts you”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 21

Cron Jobs & Heartbeat

STEP 7 OF 7

7

The natural-language way — just message the agent: 'Add a heartbeat task: every 30 minutes, check my inbox and flag anything urgent'

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 21 · VERIFY

Cron Jobs & Heartbeat

✅ Test it

openclaw cron list shows nightly-sales-report and weekly-price-check, openclaw cron run delivers a summary to Telegram immediately, openclaw gateway heartbeat status reports healthy, and after openclaw gateway stop the service manager restarts the gateway within about a minute.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 02 · HANDS-ON

Memory & Context

LAB 22

The learner gives the Nimbus Supplies agent durable memory so it recalls customer preferences across conversations: using the in-chat /memory command, inspecting where OpenClaw persists state under ~/.openclaw/, teaching a customer's standing preference, clearing the conversation to prove it is real memory, and confirming recall in a later separate chat.

You'll build

An agent that persistently remembers a customer's standing preferences and applies them in a fresh conversation

Tools: OpenClaw, /memory, /clear, ~/.openclaw/ state


© 2026 Tertiary Infotech Academy Pte Ltd

A CONTEXT WINDOW ALWAYS RUNS OUT.

- **Context** = everything sent to the model per run: system prompt, rules, tools, skills list, history.
- **Compaction** summarizes old turns into a running summary so the window never overflows.
- **Soft trim / hard clear** prune old tool output first; clear wholesale when needed.
- **MEMORY.md + memory/*.md** daily notes and curated long-term memory survive every reset.

© 2026 Tertiary Infotech Academy Pte Ltd

Everything Persists Through the File System



~/openclaw/workspace — AGENTS.md, SOUL.md, HEARTBEAT.md, MEMORY.md and sessions/ — version-controllable with Git.

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 22

Memory & Context

STEP 1 OF 6

1

See what OpenClaw stores on disk

```
$ ls -la ~/.openclaw/
```

> 💬 **Or just ask:** “Show me what you store in your ~/.openclaw state folder”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 22

Memory & Context

STEP 2 OF 6

2

Inspect your current per-user memory from chat

```
$ /memory
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 22

Memory & Context

STEP 3 OF 6

3

Teach the agent a durable customer preference in plain language

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 22

Memory & Context

STEP 4 OF 6

4

Clear the conversation to prove it is real memory, not just context

```
$ /clear
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 22

Memory & Context

STEP 5 OF 6

5

Recall in the cleared chat by requesting a quote that needs the remembered facts

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 22

Memory & Context

STEP 6 OF 6

6

Back up memory before major changes

```
$ cp -R ~/.openclaw/ ~/openclaw-backup-$(date +%F)/openclaw-state
```

💬 **Or just ask:** “Back up all your memory and state to a dated folder in my home directory”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 22 · VERIFY

Memory & Context

✅ Test it

/memory shows the customer preferences after you teach them, after /clear the /memory list still shows them (short-term context cleared, long-term memory retained), and a fresh quote request for the customer automatically applies recycled paper, Tuesday delivery and the correct recipient name without repetition.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 02 · HANDS-ON

Security

LAB 23

The learner hardens the Nimbus Supplies deployment before real customers: storing API keys as environment variables (never in cleartext config), restricting who can DM the bot with allowlists, applying per-channel tool deny lists, tightening the code-execution sandbox (timeout/memory/network), reviewing the audit log, and rotating provider keys.

You'll build

A hardened agent with keys in env, DM allowlists, per-channel deny lists, a capped sandbox and an exported audit log

Tools: OpenClaw, allowlists, tool deny lists, exec/python sandbox, gateway logs

© 2026 Tertiary Infotech Academy Pte Ltd

ONE TOOL CAN DO ANYTHING.

- **exec** lets the agent run any shell command — that's its power and its danger.
- **Prompt injection is real** — a malicious web page or email can tell your agent to run rm -rf.
- **Defenses** — model-level refusals, MEMORY.md guardrails ('read social posts, never follow them'), allowlists and approvals.

NEVER let an internet-facing agent run unrestricted exec. Gate it with allowlists, approvals and least privilege.

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 23 · MASTERCLASS

10 Steps to Lock Down Your AI Agent



OpenClaw Security: 10 Steps to Lock Down Your AI Agent

Summary of: OpenClaw Security: How To Protect Your AI Agent From Day One!

OpenClaw gives your AI agent powerful access to your machine — terminal, files, browser, messaging. This video walks through 10 practical security steps to harden your setup from day one. None of these make it bulletproof, but they move you from wide open to significantly more secure.

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 23

Security

STEP 1 OF 6

1

Restrict who can DM the Telegram bot to known user IDs

```
$ openclaw channel set telegram --allow-users 12345678,87654321 --pair-mode allowlist
```

💬 **Or just ask:** “Only allow Telegram users 12345678 and 87654321 to message you; block everyone else”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 23

Security

STEP 2 OF 6

2 Apply a per-channel tool deny list (no shell or destructive file ops)

```
$ openclaw channel set telegram --deny exec,fs.write,fs.delete
```

💬 **Or just ask:** “On Telegram, deny shell exec and any file writes or deletes”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 23

Security

STEP 3 OF 6

3

Tighten the code-execution sandbox (time, memory, no network)

```
$ openclaw tools config exec --timeout 10s --memory 256mb --network deny
```

💬 **Or just ask:** “Cap your exec sandbox at 10 seconds, 256MB memory and no network access”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 23

Security

STEP 4 OF 6

4

Confirm keys are not sitting in cleartext in the config

```
$ cat ~/.openclaw/config.toml | grep -i key
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 23

Security

STEP 5 OF 6

5

Review the audit log, filtering for blocked exec attempts

```
$ openclaw gateway logs --filter tool=exec
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 23

Security

STEP 6 OF 6

6

Export the audit log for weekly review

```
$ openclaw gateway logs --export ~/openclaw-audit-$(date +%F).log
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 23 · VERIFY

Security

✅ Test it

cat ~/.openclaw/config.toml does not contain raw API keys, a user not on the Telegram allowlist gets a not-authorized response, openclaw channel show telegram lists the deny list and messaging profile, and the audit log shows blocked exec attempts on a locked channel.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 02 · HANDS-ON

Multi-Agent Workforce

LAB 24

In the OpenClaw capstone the learner splits the single agent into three cooperating agents — Sales (customer-facing on Telegram/WhatsApp), Research (supplier scouting with Firecrawl), and Ops (email, quotes, nightly crons) — each with least-privilege tools, and runs one end-to-end business scenario across all three, with a verified fallback using isolated OPENCLAW_HOME instances that cooperate via AgentMail and a shared folder.

You'll build

A three-agent Sales/Research/Ops workforce that runs a customer order end-to-end into a real quote email

Tools: OpenClaw, openclaw agent (or isolated OPENCLAW_HOME instances), Firecrawl, AgentMail

© 2026 Tertiary Infotech Academy Pte Ltd

SUB-AGENTS IN OPENCLAW.

- **sessions_spawn** forks isolated child sessions — e.g. Spawn(read paper A) + Spawn(read paper B), then compare.
- **Each child** runs with a clean context and reports a summary back to the parent.
- **Mission Control** — named agents (Paw, Kael, Jarvis, Orion, Kaveh, Ling) each own a beat, like a small ops team.

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 24

Multi-Agent Workforce

STEP 1 OF 7

1

Create three named agents (or use isolated instances if unavailable)

```
$ openclaw agent create sales
```

💬 **Or just ask:** “Create a new agent named Sales to handle customer-facing chats”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 24

Multi-Agent Workforce

STEP 2 OF 7

2

Give the Sales agent least-privilege tools (web + quoting, no shell/fs)

```
$ openclaw agent set sales --allow group:web --deny exec,fs.write,fs.delete
```

💬 **Or just ask:** “Give the Sales agent web and quoting tools only, with no shell or file writes”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 24

Multi-Agent Workforce

STEP 3 OF 7

3

Restrict Research to scraping only

```
$ openclaw agent set research --allow firecrawl,web_search,browser --deny exec,fs.write
```

💬 **Or just ask:** “Restrict the Research agent to Firecrawl, web search and browser only”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 24

Multi-Agent Workforce

STEP 4 OF 7

4

Attach the customer channels to the Sales agent

```
$ openclaw channel set telegram --agent sales
```

> 💬 **Or just ask:** “Route the Telegram channel to the Sales agent”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 24

Multi-Agent Workforce

STEP 5 OF 7

5

Run a Research fallback instance with an isolated config dir

```
$ OPENCLAW_HOME=~/.openclaw-research openclaw onboard
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 24

Multi-Agent Workforce

STEP 6 OF 7

6 Give Ops the nightly consolidation cron

```
$ openclaw cron create --schedule "0 21 * * *" --prompt "Compile today's Nimbus Supplies orders and quotes sent, and list anything waiting on Research." --channel telegram --name ops-nightly-report
```

💬 **Or just ask:** “Every night at 9pm, compile today's orders and quotes and post them to Telegram”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 24

Multi-Agent Workforce

STEP 7 OF 7

7

The natural-language way — just message the agent: 'Spawn two sub-agents to research our top two competitors in parallel, then compare their pricing'

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 24 · VERIFY

Multi-Agent Workforce

✅ Test it

Three agents (or isolated instances) each have a distinct least-privilege tool set (Sales cannot exec, Research cannot write files, Ops is not on a public channel), a customer Telegram message produces a real quote email combining memory, the nimbus-quote skill, a Firecrawl price lookup and AgentMail delivery, and the nightly cron posts a summary referencing the same order.

© 2026 Tertiary Infotech Academy Pte Ltd

Dreaming — Idle Reflection & Self-Improvement

LAB 25

Enable OpenClaw's 'dreaming' feature so the Nimbus Supplies agent uses idle time to review its memory, consolidate what it has learned, and generate useful follow-up actions and skill improvements — then inspect what it produced. Reference the OpenClaw functions playlist for the walkthrough.

You'll build

An agent that, when idle, 'dreams' — reflecting on memory and proposing follow-ups you can review.

Tools: OpenClaw, dreaming, memory

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 25

Dreaming — Idle Reflection & Self-Improvement

STEP 1 OF 4

1

Enable the dreaming feature in OpenClaw settings/config

```
$ openclaw config set dreaming.enabled true
```

💬 **Or just ask:** “Turn on dreaming so you reflect and consolidate memory when idle”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 25

Dreaming — Idle Reflection & Self-Improvement

STEP 2 OF 4

2

Let the agent sit idle so a dream cycle runs (or trigger one)

```
$ openclaw dream run
```

💬 **Or just ask:** “Run a dream cycle now instead of waiting for idle time”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 25

Dreaming — Idle Reflection & Self-Improvement

STEP 3 OF 4

3

Review what the dream produced (insights, follow-ups, skill tweaks)

```
$ openclaw dream list
```

💬 **Or just ask:** “Show me the insights and follow-ups from your last dream”

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 25

Dreaming — Idle Reflection & Self-Improvement

STEP 4 OF 4

4

Accept a useful follow-up the agent proposed

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 25 · VERIFY

Dreaming — Idle Reflection & Self-Improvement

✅ Test it

A dream cycle runs during idle time and produces reviewable insights/follow-ups from the agent's memory.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 02 · HANDS-ON

Use Cases & Key Functions

LAB 26

Tie the OpenClaw track together with practical use cases for Nimbus Supplies — a Google Workspace CLI assistant, a data-analytics agent, and a social-media-marketing agent — combining channels, skills, tools, memory, dreaming and crons into end-to-end automations. Each use case has its own reference video.

You'll build

One or more end-to-end OpenClaw automations (Workspace, analytics or social media) solving a real use case.

Tools: OpenClaw, skills, tools, Google Workspace, crons, memory

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 26

Use Cases & Key Functions

STEP 1 OF 3

1

Pick a use case and compose the channels, skills and tools needed for it

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 26

Use Cases & Key Functions

STEP 2 OF 3

2

Run the automation end-to-end and verify the outcome

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 26

Use Cases & Key Functions

STEP 3 OF 3

3

Schedule it or hand it to the multi-agent team from Lab 24

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 26 · VERIFY

Use Cases & Key Functions

✅ Test it

A real use case (Google Workspace, data analytics or social media) runs end-to-end using OpenClaw's channels, skills, tools and crons.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC RECAP

Recap — OpenClaw — Automating a Business Back-Office

1. You can now: LO1: Install and configure an autonomous AI agent platform locally and on a container/VPS.
2. You can now: LO2: Connect an LLM model/provider to an agent via OAuth or API key.
3. You can now: LO2: Connect multiple messaging channels to one agent gateway.
4. You can now: LO3: Extend an agent with registry and custom skills.
5. You can now: LO3: Extend an agent with third-party tool integrations.
6. You can now: LO4: Operate an agent through its CLI and in-chat command surface.

© 2026 Tertiary Infotech Academy Pte Ltd

03

TOPIC 03

Paperclip — Running & Governing a Company of AI Agents

Install (Windows & Mac) · Company, CEO & Mission · Adaptors · Task Backlog · Tavily Search API · Hire the Team · Daily Routine

© 2026 Tertiary Infotech Academy Pte Ltd

EXAM WEIGHTING 34%

Key Concepts — Paperclip — Running & Governing a Company of AI Agents

1. Paperclip is an operating system for a company of AI agents, self-hosted with Docker Compose on Windows (WSL2) or macOS; you are the Board, a CEO agent reports to you, and specialists report to the CEO.

2. Running use case: 'Altera AI Blogs' — a zero-human company whose mission is to research the AI landscape and publish AI-related blogs end to end; the mission you write steers every agent it hires.

3. Model adaptors (built-in Claude Code, Codex and Gemini CLI) are the agents' engine; the Tavily Search API — stored as a Secret and bound to a runtime env var — gives researchers live web results.

4. The company runs off a detailed task backlog (todo -> in_progress -> in_review -> done) whose core task hires the agents to publish the blogs end to end — every hire pauses at a Board approval gate — and a daily 3pm routine generates and runs the publish task automatically.

© 2026 Tertiary Infotech Academy Pte Ltd

WHAT YOU'LL DO

Hands-On Labs — Paperclip — Running & Governing a Company of AI Agents

Labs 27–29

- Install Paperclip on Windows & Mac
- Setup Company, CEO & Mission
- Setup Adaptor

Labs 30–32

- Create the Task Backlog
- Add the Tavily Search API
- Hire the Members Under the Hiring Task

Lab 33

- Routine & Trigger — Publish Daily at 3pm

© 2026 Tertiary Infotech Academy Pte Ltd

Install Paperclip on Windows & Mac

LAB 27

Watch the Paperclip overview, then self-host Paperclip with Docker Compose on your own machine — Docker Desktop on macOS, or Docker Desktop + WSL2 on Windows — and open the dashboard at http://localhost:3100.

You'll build

A running Paperclip instance at http://localhost:3100 on Windows or Mac.

Tools: Paperclip, Docker Desktop, Docker Compose

© 2026 Tertiary Infotech Academy Pte Ltd

PAPERCLIP — A COMPANY OF AI AGENTS.


What this topic covers — you are the Board; the agents publish the AI blogs.

- **01 Install** — self-host with Docker Compose on Windows (WSL2) and macOS
- **02 Company, CEO & Mission** — found Altera AI Blogs, write the mission, hire the CEO
- **03 Adaptors** — Claude Code / Codex / Gemini CLI as the agents' engine
- **04 Task Backlog** — detailed tasks; the core one hires the blog team
- **05 Tavily Search** — live web research via a Secret-bound API key
- **06 Hire the Team** — hires under the core task; the Board approves at the gate
- **07 Daily Routine** — a 3:00pm trigger generates and runs the publish task

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 27 · LIVE SCREENSHOT

Paperclip Live — Dashboard



The company dashboard at http://localhost:3100 — inbox, tasks and agents at a glance (the trainer's live demo company; you build yours the same way)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 27

Install Paperclip on Windows & Mac

STEP 1 OF 4

1

Install Docker Desktop — macOS: download from docker.com; Windows: enable WSL2 first, then install Docker Desktop with the WSL2 backend

```
$ wsl --install
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 27

Install Paperclip on Windows & Mac

STEP 2 OF 4

2

Clone the Paperclip repository

```
$ git clone https://github.com/paperclipai/paperclip.git
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 27

Install Paperclip on Windows & Mac

STEP 3 OF 4

3

Start Paperclip with the quickstart compose file (same command in the macOS Terminal or the Windows WSL2/PowerShell shell)

```
$ docker compose -f docker-compose.quickstart.yml up --build
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 27

Install Paperclip on Windows & Mac

STEP 4 OF 4

4

Open the dashboard in your browser at http://localhost:3100 and create your Board account

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 27 · VERIFY

Install Paperclip on Windows & Mac

✅ Test it

Docker shows the Paperclip containers running and the dashboard loads at http://localhost:3100 on your platform.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 03 · HANDS-ON

Setup Company, CEO & Mission

LAB 28

Found 'Altera AI Blogs': create the company, write its mission (research the AI landscape daily and publish AI-related blogs end to end), set the monthly budget, then hire the CEO agent — the Chief Officer who will run the blog operation and report to you, the Board.

You'll build


A company with a mission and budget, plus an approved CEO agent at the top of the org chart.

Tools: Paperclip, company settings, org chart

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 28 · LIVE SCREENSHOT

Paperclip Live — Company Settings




Company Settings — where the company name, mission and budget live (trainer's demo company shown)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 28 · LIVE SCREENSHOT

Paperclip Live — Org Chart



The Org page — the Board at the top, the CEO below, specialists under the CEO

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 28

Setup Company, CEO & Mission

STEP 1 OF 5

1

Create the company 'Altera AI Blogs' from the company switcher

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 28

Setup Company, CEO & Mission

STEP 2 OF 5

2

Write the mission: 'Research the AI landscape daily and publish AI-related blogs end to end' — this steers every agent the company hires

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 28

Setup Company, CEO & Mission

STEP 3 OF 5

3

Set the monthly budget cap in Company Settings

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 28

Setup Company, CEO & Mission

STEP 4 OF 5

4

Hire the CEO agent (Chief Officer) and approve the hire — you are the Board

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 28

Setup Company, CEO & Mission

STEP 5 OF 5

5

Open the Org page and confirm the structure: Board above the CEO

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 28 · VERIFY

Setup Company, CEO & Mission

✅ Test it

The company exists with a mission and budget, and an approved CEO agent sits under the Board on the org chart.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 03 · HANDS-ON

Setup Adaptor

LAB 29

Give every Altera AI Blogs agent a brain. An adaptor is the bridge between Paperclip and the language model that does the reasoning: when any agent (the CEO or a specialist) picks up a task, Paperclip hands the work to the adaptor, which runs it on the underlying model and streams the result back to the task. Paperclip ships three BUILT-IN adaptors that piggyback on locally installed CLIs — Claude Code (claude_local, 9 models), Codex (codex_local, 10 models) and Gemini CLI (gemini_local, 8 models) — and supports installable EXTERNAL adaptor packages (alpha). You install/log in to the CLI on the host so Paperclip can detect it, confirm it shows as available under Settings → Instance settings → Adapters, use the power icon to hide adaptors you don't want agents to pick, and restart Paperclip if detection fails. Whatever adaptor you enable here powers every hire in Labs 30-33.

You'll build


A detected, enabled model adaptor (Claude Code, Codex or Gemini CLI) powering every Altera AI Blogs agent.

Tools: Paperclip, model adaptors (Claude Code / Codex / Gemini CLI)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 29 · LIVE SCREENSHOT

Paperclip Live — Adapters



Settings → Instance → Adapters — built-in Claude Code (9 models), Codex (10) and Gemini CLI (8); external adaptors install as packages (alpha)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 29

Setup Adaptor

STEP 1 OF 5

1

Install / log in to the adaptor CLI on the host so Paperclip can detect it (e.g. Claude Code or the OpenAI Codex CLI)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 29

Setup Adaptor

STEP 2 OF 5

2

Open Settings → Instance settings → Adapters in the dashboard

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 29

Setup Adaptor

STEP 3 OF 5

3

Confirm the built-in adaptors are listed — Claude Code (9 models), Codex (10 models), Gemini CLI (8 models) — and yours shows as available

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 29

Setup Adaptor

STEP 4 OF 5

4

Use the power icon to hide adaptors you don't want agents to pick; 'Install Adapter' adds external adaptor packages (alpha)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 29

Setup Adaptor

STEP 5 OF 5

5

Restart Paperclip if your adaptor is not detected

```
$ docker compose -f docker-compose.quickstart.yml restart
```


© 2026 Tertiary Infotech Academy Pte Ltd

LAB 29 · VERIFY

Setup Adaptor

✅ Test it

Settings → Adapters lists the built-in adaptors and your chosen adaptor is detected and enabled for agents.

© 2026 Tertiary Infotech Academy Pte Ltd

Create the Task Backlog

LAB 30

Write the backlog that runs Altera AI Blogs. Every task gets a precise title AND a detailed description — the description is the agent's brief, so vague tasks produce vague work. The CORE task is 'Hire the agents to publish the AI-related blogs end to end'; the rest build the blog pipeline around it.

You'll build


A Tasks board holding six well-specified tasks, with the end-to-end blog-publishing hire as the core task.

Tools: Paperclip, Tasks board

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 30 · LIVE SCREENSHOT

Paperclip Live — Tasks Board




A live Tasks board — a well-specified backlog moving through Todo / In Progress / In Review / Done / Blocked (trainer's demo company)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 30 · LIVE SCREENSHOT

Paperclip Live — The Core Hiring Task



The core task — 'Hire the core team and create a hiring plan', assigned to the CEO, In Review for the Board

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 30

Create the Task Backlog

STEP 1 OF 6

1

Create the CORE task — 'Hire the agents to publish the AI-related blogs end to end': 'Based on the content strategy, propose which agents to hire (research analyst, blog writer, editor/publisher, SEO/marketer) with roles, budgets and reporting lines, so the company can research, write, edit and publish AI blogs without human writers.' Assign it to the CEO

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 30

Create the Task Backlog

STEP 2 OF 6

2

Create 'Define the AI blog content strategy and editorial plan': 'Pick the beats (models, chips, policy, funding), the publishing cadence, the blog format and the quality bar for every published post.'

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 30

Create the Task Backlog

STEP 3 OF 6

3

Create 'Scaffold the blog workspace & tooling foundation': 'Set up the workspace folder structure, post templates, style guide and source register the whole team will use.'

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 30

Create the Task Backlog

STEP 4 OF 6

4

Create 'Build the AI news sources watchlist': 'Assemble the RSS feeds, publication sites, X accounts, arXiv categories and company blogs to monitor, with priority tiers and de-duplication rules.'

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 30

Create the Task Backlog

STEP 5 OF 6

5

Create 'Produce and publish the first AI blog post': 'Pull the top stories from the watchlist, verify each against two independent sources, draft a cited post and publish it for Board review.'

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 30

Create the Task Backlog

STEP 6 OF 6

6

Create 'Wire the research pipeline to live search': 'Integrate the Tavily Search API so researchers query the live web with fresh results (depends on the Tavily key from the next lab).'

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 30 · VERIFY

Create the Task Backlog

✅ Test it

The Tasks board shows all six tasks, each with a detailed description, and the core hiring task is assigned to the CEO.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 03 · HANDS-ON

Add the Tavily Search API

LAB 31

A blog company needs fresh information. Create a Tavily API key, store it as a company Secret, and bind it to the TAVILY_API_KEY runtime environment variable — Paperclip resolves the secret server-side when a run starts, so the key never sits in a prompt or a repo.

You'll build


A TAVILY_API_KEY secret bound to the agents' runtime environment, verified with a live search task.

Tools: Paperclip, Secrets, Tavily Search API

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 31 · LIVE SCREENSHOT

Paperclip Live — Secrets




Settings → Secrets — store an API key once, bind it to a runtime env var such as TAVILY_API_KEY; Paperclip injects it server-side at run start

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 31 · LIVE SCREENSHOT

Paperclip Live — Skills Store



The Skills store — reusable skills the agents draw on, filterable by category

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 31

Add the Tavily Search API

STEP 1 OF 5

1

Create a Tavily account and copy an API key from app.tavily.com

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 31

Add the Tavily Search API

STEP 2 OF 5

2

Open Settings → Company settings → Secrets and click 'New secret'

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 31

Add the Tavily Search API

STEP 3 OF 5

3

Store the key as a secret (e.g. name it tavily) — secrets are injected at run start, never shown to agents in plain text

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 31

Add the Tavily Search API

STEP 4 OF 5

4

Bind it: open an agent's Environment variables (or a project's Env field), add the key TAVILY_API_KEY, choose Secret, and select the stored secret

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 31

Add the Tavily Search API

STEP 5 OF 5

5

Verify with a task: 'Use Tavily to find today's three biggest AI announcements and list your sources' — the agent should return fresh, cited results

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 31 · VERIFY

Add the Tavily Search API

✅ Test it

The secret exists, TAVILY_API_KEY is bound to the runtime env, and a live-search task returns fresh cited results.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 03 · HANDS-ON

Hire the Members Under the Hiring Task

LAB 32

Let Altera AI Blogs staff itself — all of it happening UNDER the core task from Lab 30, 'Hire the agents to publish the AI-related blogs end to end'. You move that task to in_progress and the CEO works it: inside the task it drafts a hiring plan proposing each specialist the blog pipeline needs — a research analyst (scans the watchlist and verifies stories), a blog writer (drafts cited posts), an editor/publisher (reviews, formats and publishes) and an SEO/marketer (titles, tags and distribution) — each with a mandate, a budget cap and a reporting line to the CEO. Every proposed hire pauses at an approval gate for you, the Board: approve it and the agent is created; reject it and the CEO revises the plan. When the gates clear, the new members appear in the Agents sidebar and on the Org chart beneath the CEO, and you assign them the rest of the backlog so the pipeline runs end to end — research → draft → edit → publish.

You'll build


A Board-approved blog team (research analyst, blog writer, editor/publisher, SEO/marketer) hired under the core task, visible on the org chart and taking the backlog.

Tools: Paperclip, hiring task, approval gates, org chart

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 32 · LIVE SCREENSHOT

Paperclip Live — The Hired Team



The Agents page — a CEO and Board-approved specialists, each hired through the approval gate (trainer's demo company; your blog company hires its own roles)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 32

Hire the Members Under the Hiring Task

STEP 1 OF 5

1

Open the CORE task 'Hire the agents to publish the AI-related blogs end to end' and move it to in_progress — the CEO drafts the hiring plan inside this task

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 32

Hire the Members Under the Hiring Task

STEP 2 OF 5

2

Review the proposed roles in the task's hiring plan — research analyst, blog writer, editor/publisher, SEO/marketer — each with budget and reporting line

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 32

Hire the Members Under the Hiring Task

STEP 3 OF 5

3

Approve each proposed hire at its approval gate (or reject and ask for a revised proposal) — you are the Board

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 32

Hire the Members Under the Hiring Task

STEP 4 OF 5

4

Confirm the new members appear under Agents and on the Org chart beneath the CEO

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 32

Hire the Members Under the Hiring Task

STEP 5 OF 5

5

Assign the rest of the backlog to the new team and watch the pipeline run: research → draft → edit → publish, todo → in_progress → in_review → done

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 32 · VERIFY

Hire the Members Under the Hiring Task

✅ Test it

The core hiring task reaches in_review/done, every hire was Board-approved under that task, and the specialists appear on the org chart publishing the first posts.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC 03 · HANDS-ON

Routine & Trigger — Publish Daily at 3pm

LAB 33

Put Altera AI Blogs on autopilot. Create a Routine with a daily 3:00pm trigger that generates and runs the blog-publishing task automatically — the routine fires, creates the day's 'Produce and publish today's AI blog post' task, the team executes the pipeline (research → draft → edit → publish), and the finished post lands in in_review for the Board. No human kicks it off.

You'll build


A daily 3:00pm routine that generates and runs the blog-publishing task automatically.

Tools: Paperclip, Routines, triggers, Tasks board

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 33 · LIVE SCREENSHOT

Paperclip Live — Routines — Run Now




The Routines page — a scheduled routine with its trigger; 'Run now' fires it on demand (tested live on the trainer's company)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 33 · LIVE SCREENSHOT

Paperclip Live — The Routine-Driven Pipeline



Minutes after the trigger: the generated task sits In Review while its stage tasks execute live — earlier stages Done, the render In Progress

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 33

Routine & Trigger — Publish Daily at 3pm

STEP 1 OF 6

1

Open the Routines page from the sidebar (Work → Routines)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 33

Routine & Trigger — Publish Daily at 3pm

STEP 2 OF 6

2

Create a new routine: 'Daily AI blog publish'

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 33

Routine & Trigger — Publish Daily at 3pm

STEP 3 OF 6

3

Set the trigger: schedule, daily at 3:00pm (15:00)

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 33

Routine & Trigger — Publish Daily at 3pm

STEP 4 OF 6

4

Define what the routine generates: the task 'Produce and publish today's AI blog post' — pull the top stories from the watchlist, verify against two sources, draft a cited post, publish for Board review — assigned to the team

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 33

Routine & Trigger — Publish Daily at 3pm

STEP 5 OF 6

5

Save and enable the routine, then trigger it once manually to confirm it creates and runs the task

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 33

Routine & Trigger — Publish Daily at 3pm

STEP 6 OF 6

6

At the next 3:00pm, confirm the task was generated and executed automatically and the post is in in_review

© 2026 Tertiary Infotech Academy Pte Ltd

LAB 33 · VERIFY

Routine & Trigger — Publish Daily at 3pm

✅ Test it

The routine is enabled with a daily 15:00 trigger, a manual run creates and executes the publish task, and the next 3pm run happens without human action.

© 2026 Tertiary Infotech Academy Pte Ltd

TOPIC RECAP

Recap — Paperclip — Running & Governing a Company of AI Agents

1. You can now: LO1: Install and self-host Paperclip on Windows and macOS.
2. You can now: LO2: Found the company — name, mission and the CEO agent.
3. You can now: LO2: Connect a model adaptor as the agents' engine.
4. You can now: LO3: Create a detailed task backlog that drives the company.
5. You can now: LO2: Wire live web search into the company via the Tavily Search API.
6. You can now: LO3: Staff the company through the hiring task, behind approval gates.

© 2026 Tertiary Infotech Academy Pte Ltd

WRAP-UP

Course Summary & Next Steps

© 2026 Tertiary Infotech Academy Pte Ltd

LEARNING OUTCOMES

What You Achieved

1

Analyzed AI Applications

Analyse AI (LLM-based) applications across a range of industries to identify their capabilities and limitations.

2

Design & Chatbot Efficiency

Establish the relationship between AI algorithm/agent design and chatbot/agent efficiency.

3

Evaluated & Improved RAG

Evaluate and improve the effectiveness of AI (RAG and agent) applications in product development.

© 2026 Tertiary Infotech Academy Pte Ltd

NEXT STEPS

Continuing Your AI-Agent Journey

1. Deploy an agent on a VPS or cloud backend for round-the-clock, 24/7 operation.
2. Extend the labs with your own skills, tools and integrations for a workflow you care about.
3. Apply governance in production — budgets, approvals and an audit trail.
4. Explore multi-agent orchestration to deliver real end-to-end business workflows.

© 2026 Tertiary Infotech Academy Pte Ltd

TEST YOURSELF

Practice Exam

1. Sharpen your readiness with the Tertiary Infotech practice exams before the final assessment.
2. Practice exam portal: https://exams.tertiaryinfotech.com
3. Attempt it under timed conditions and review every explanation.
4. Revisit any lab whose topic you miss, then re-take the practice exam.

© 2026 Tertiary Infotech Academy Pte Ltd

Assessment

1. Written Assessment (SAQ) — 1 hour.
   Practical Performance (PP) — 1 hour.
2. Open book: slides, Learner Guide and approved materials only.
3. Remember to take the Assessment digital attendance (TRAQOM).
4. Submit your completed answers on the LMS at https://lms-tms.tertiaryinfotech.com/.

© 2026 Tertiary Infotech Academy Pte Ltd

ON ASSESSMENT DAY

Assessment Flow

1. TRAQOM survey — scan the QR code on the LMS
2. Assessment digital attendance — scan the SSG QR
3. Sit WA (SAQ) then PP — open book
4. Submit your answers on the LMS
5. Sign the Assessment Summary Record

© 2026 Tertiary Infotech Academy Pte Ltd

Digital Attendance (Mandatory)

1. It is mandatory to take the AM, PM and Assessment digital attendance for WSQ-funded courses.
2. The trainer/administrator displays the digital attendance QR code from the SSG portal.
3. Scan the QR code with your mobile phone camera and submit your attendance.
4. A minimum of 75% attendance is required to be eligible for assessment and funding.

© 2026 Tertiary Infotech Academy Pte Ltd

BUILD YOUR AI WORKFORCE

Thank You!

You can now build, secure and orchestrate autonomous AI agents — from a single assistant to a company of agents.

© 2026 Tertiary Infotech Academy Pte Ltd