

CHEATSHEET · QUICK REFERENCE

Lab 24 — Patch and Update Management

Separate security from feature updates, snapshot-then-test, apply with change-management discipline, configure security auto-apply and plan rollbacks.

Inventory and classify

```
apt list --upgradable 2>/dev/null | head -20
Pre-patch baseline

apt-get -s dist-upgrade | grep -i security
Identify security-only updates

debsecan --suite "$(lsb_release -cs)" --format detail
CVE-aware audit
```

Test, apply, restart

```
lvcreate -L 200M -s -n pre_patch_$(date +%F) /dev/vg_data/lv_root
Snapshot before patching

DEBIAN_FRONTEND=noninteractive apt -y upgrade
Apply in the maintenance window

needrestart -b
Which services need a restart

[ -f /var/run/reboot-required ] && cat /var/run/reboot-required
Reboot decision
```

Security auto-apply + rollback

```
Unattended-Upgrade::Allowed-Origins { "${distro_id}:${distro_codename}-security"; };
Auto-apply security only

apt install -y --allow-downgrades nginx=1.18.0-6ubuntu14.4
Version-pin rollback

apt-mark hold nginx
Hold a package
```

Cluster-aware patch order

Step	Action
1	Drain node from the LB
2	Verify remaining nodes carry load
3	Patch, reboot, smoke-test
4	Re-enable; watch one health interval
5	Repeat per node - never in parallel