WSQ COURSE • TGS-2025052468

Version 21.0 · 29 Oct 2026

Agentic AI Applications with Claude Code

Tertiary Infotech Academy Pte Ltd
UEN: 201200696W

www.tertiarycourses.com.sg | enquiry@tertiaryinfotech.com | +65 6100 0613

© Tertiary Infotech Academy Pte Ltd

HOUSEKEEPING

Digital Attendance



Attendance is mandatory for SSG funding.

Take AM, PM and Assessment digital attendance for every session.

Use the SSG / TMS QR code provided by your trainer.

Minimum 75% attendance required

© Tertiary Infotech Academy Pte Ltd

About the Trainer



[Trainer Name]

[Title / Role]



Qualifications: _____



Expertise: _____




Experience: _____



Contact / Profile: _____

© Tertiary Infotech Academy Pte Ltd

About the Trainer



PhD-qualified trainer specialising in AI, software engineering and developer tooling.

Hands-on experience building agentic AI applications with Claude Code.

Trains professionals across Singapore on practical, project-based AI skills.

Certifications: Claude Certified Associate (Foundations),
PMP, AWS, Microsoft, CompTIA, CKA, CKAD.

linkedin.com/in/angchewhoe

github.com/alfredang

© Tertiary Infotech Academy Pte Ltd

INTRODUCTION

Let's Know Each Other

Take a minute to introduce yourself to the class:



Your name & role



What you do day to day



Your coding experience



What you want from this course

© Tertiary Infotech Academy Pte Ltd

HOUSEKEEPING

Ground Rules

Phones on silent

Step out quietly for calls or breaks.

Participate actively

No question is stupid — ask freely.

Mutual respect

Agree to disagree; one conversation at a time.

Be punctual

Return from breaks on time.

75% attendance

Required for funding eligibility.

Stay hands-on

Follow along with every activity.

© Tertiary Infotech Academy Pte Ltd

ROADMAP

Course Outline

1

Claude Code Fundamentals

- Setup & the Agentic Loop
- Context, Memory & Sessions
- Permissions & Scheduled Tasks
- **Activity: Build & deploy a website**

2

Tools and Commands

- Custom Commands
- MCP Tools
- Playwright MCP
- **Activities: /gitpush + MCP screenshot**

3

Skills, Agents & Hooks

- Agent Skills
- Sub Agents
- Hooks
- **Key Concepts Summary**

© Tertiary Infotech Academy Pte Ltd

ROADMAP · HANDS-ON

Lab Materials

Four labs, each in its own folder. They build on one another — Lab 1 creates the website that every later lab extends.

Lab 1

Topic 1

The 7-step build workflow — goal, plan, execute, /init, GitHub, Pages, CI/CD.

`labs/lab1-seven-steps/`

Lab 1b

Topic 2

A /publish custom command + Playwright MCP screenshots into the README.

`labs/lab1b-commands-mcp/`

Lab 2

Topic 3

Install 3 skills — cybersecurity, kanban, UI/UX — and revamp the site.

`labs/lab2-skills/`

Lab 3

Topic 3

Hooks, sub agents and /loop — the event, delegation and schedule triggers.

`labs/lab3-hooks/`

TIP Every step gives you the exact prompt to paste, what you should see, and a checkpoint before moving on.

© Tertiary Infotech Academy Pte Ltd

ROADMAP

Lesson Plan (9:00 AM – 6:00 PM)

Time	Session
9:00 – 9:30	Welcome, admin, attendance (AM), introductions, ground rules
9:30 – 10:30	Topic 1.1: agentic loop & tools, setup, permission modes
10:30 – 10:40	*Morning break*
10:40 – 11:20	Topic 1.2: context, memory, sessions, scheduled tasks, /goal
11:20 – 12:30	Activity 1: Build & deploy a website
12:30 – 1:15	*Lunch break*
1:15 – 1:45	Topic 2: Custom commands · Activity 2: /gitpush
1:45 – 2:45	Topic 2: MCP tools · Activity 3: Playwright screenshot + form test
2:45 – 2:55	*Afternoon break*
2:55 – 3:40	Topic 3: Agent skills · Activity 4: frontend-design & SEO
3:40 – 4:25	Topic 3: Sub agents & hooks · Activity 5: security + UX agents
4:25 – 4:50	Activities 6–7 · hooks, testing, optimisation & deployment
4:50 – 5:00	Summary, Q&A, attendance (PM)
5:00 – 6:00	Final Assessment: 30 min WA + 30 min PP (on the LMS)

© Tertiary Infotech Academy Pte Ltd

ASSESSMENT

Briefing for Assessment

Clear your space

Place phones and other materials under the table or on the floor.

No recording

No photos or recording of assessment materials.

Open book

Only slides, learner guide and approved materials are allowed.

Work individually

Complete the assessment on your own; no discussion.

Manage your time

Written Assessment then Practical Performance — watch the clock.

Appeals

An appeal process is available if you disagree with the outcome.

© Tertiary Infotech Academy Pte Ltd

ASSESSMENT

Assessment & Funding



Final Assessment

- Written Assessment (WA) — 30 min, starts 5:00 PM
- Practical Performance (PP) — 30 min
- Format: Open book — class ends 6:00 PM
- Allowed: slides, learner guide & approved materials only
- Appeal process available



Criteria for Funding

Minimum 75% attendance

Based on SSG digital attendance records.


Assessed as 'Competent'

Complete and pass both assessment components.

© Tertiary Infotech Academy Pte Ltd

COURSE PORTAL

Login to LMS and Download Course Material



Log in at lms-tms.tertiaryinfotech.com with your registered email and the OTP sent to your inbox, then open this course to download the slides and Learner Guide.

© Tertiary Infotech Academy Pte Ltd

LEARNING MANAGEMENT SYSTEM

Courseware & Assessment on the LMS

Download the courseware


Get the slides and learner guide from the LMS for the open-book assessment.

Take the assessment

Complete the Written Assessment and Practical Performance on the LMS.

Log in

Use your enrolled account to access the course materials and assessment.



LMS: https://lms-tms.tertiaryinfotech.com/

© Tertiary Infotech Academy Pte Ltd

TOPIC 1

Claude Code Fundamentals

1 Overview of Claude Code

2 The Agentic Loop

3 Context Engineering

4 Activity: Build a website

© Tertiary Infotech Academy Pte Ltd

The Claude Product Family

Anthropic offers several Claude products — here's how they differ so you know which is which.

Claude (Chat + Cowork)

Chat + Cowork in one app — web, desktop & mobile.

Claude Code

The agentic tool for building — terminal, IDE & web.

Claude Design

Polished UI, prototypes & front-end designs.

Claude for Microsoft

Claude inside Excel, PowerPoint, Word & Outlook.

Claude for Chrome

Browser agent that clicks & fills forms in Chrome.

Claude for Science

Speeds up research workflows for scientists and labs.

TIP *All are powered by the same Claude models — they differ in where they run and who they're for.*

© Tertiary Infotech Academy Pte Ltd

Claude (Chat + Cowork) and Claude Code

Chat and Cowork are now one app: Claude. Claude Code is the agentic tool for building — the one we use in this course.



Claude (Chat + Cowork)

- Chat: ask, draft, analyse and research with web search.
- Cowork: plans and runs multi-step tasks on your files.
- Connectors & skills: Drive, Gmail, Calendar, Microsoft 365.
- For everyone — web, desktop and mobile apps.




Claude Code

- Agentic tool for building software, sites and automations.
- Runs in the terminal, VS Code, desktop app and web.
- Edits files, runs commands and calls MCP tools for you.
- Extend with CLAUDE.md, skills, sub agents and hooks.

© Tertiary Infotech Academy Pte Ltd

A Brief History of AI, 2023–2026



From wording one prompt → curating context → engineering the harness → AI agents that work around the clock.


© Tertiary Infotech Academy Pte Ltd

What is Harness Engineering?

A harness is the system built around the model — the agentic loop, tools, context management, verification and guardrails — that turns a capable model into an agent which can complete long-running tasks. Harness engineering is designing that scaffolding (and stripping it back as models improve).

A harness provides:

- The agentic loop
- Tool access (files, shell, MCP)
- Context & memory management
- Verification & guardrails



TIP *Build the simplest harness that works — and re-examine it with every new, more capable model.*

© Tertiary Infotech Academy Pte Ltd

The Agentic Loop

Every Claude Code task runs the same repeating cycle. Understanding this loop is the key to working effectively with an agent.



1. Gather Context

Read files, run searches, use tools to understand the task.



2. Take Action

Edit code, run commands, call MCP tools to make progress.



3. Verify Work

Run tests, lint, view output — check the result is correct.



4. Repeat

Feed results back as new context and loop until the goal is met.

Goal in → context → action → verification → repeat → goal met

© Tertiary Infotech Academy Pte Ltd

Why the loop matters



Give direction, not micro-steps

State the goal and constraints clearly; let the loop figure out the steps.



Verification is everything

An agent is only as good as its ability to check its own work — provide tests, linters, screenshots.



Steer mid-loop

Review the plan, interrupt, and course-correct rather than waiting for a wrong final answer.



Context is the fuel

What the agent can see determines what it can do — leading us to context engineering.

© Tertiary Infotech Academy Pte Ltd

Built-in Tools

Tools are what make Claude Code agentic. Each tool use returns information that feeds the next decision in the loop.



File ops

Read, edit, create, rename and reorganise files.



Search

Find files by pattern, grep content, explore code.



Execution

Run shell commands, tests, builds and git.



Web

Search the web and fetch docs or error messages.

TIP *Plus subagents, code intelligence and your configured extensions (MCP, skills, hooks).*

© Tertiary Infotech Academy Pte Ltd

The Agentic Loop in Action

You: *"Build a responsive software-dev website with an enquiry form, then test it."*



1. Gather context

Reads the folder & CLAUDE.md to understand the existing site and conventions.



2. Plan

Drafts the approach — hero, testimonials and enquiry form sections — for you to approve.



3. Take action

Writes index.html, styles.css and script.js with form validation.



4. Verify work

Opens the page via Playwright MCP and submits the form to test it.



5. Repeat

Spots a validation bug, fixes script.js, re-tests — then reports done.

© Tertiary Infotech Academy Pte Ltd

What is Claude Code?

Claude Code is an agentic coding tool that lives in your terminal. You describe a goal in plain English, and Claude plans, writes, runs and verifies the work — editing files, running commands and using tools on your behalf.



Terminal-native

Runs where you already work — no heavy IDE required.



Agentic

Plans multi-step tasks and acts, not just autocompletes.



Tool-using

Reads/writes files, runs bash, calls MCP servers.



Extensible

Custom commands, skills, sub-agents and hooks.

© Tertiary Infotech Academy Pte Ltd

What Claude Code Can Do

Claude Code handles real engineering tasks end to end — describe the outcome and it does the work.



Build

Create features, apps and whole projects from a prompt.



Debug & fix

Find and fix errors; read logs and stack traces.



Refactor

Improve, restructure and document existing code.



Automate

Run git, tests, deployment and CI/CD workflows.

Common use cases: marketing sites & landing pages · internal web tools · full-stack apps · mobile apps · scripts & automations · data tasks.

© Tertiary Infotech Academy Pte Ltd

Setup Claude Code

The same agentic loop runs everywhere — choose the interface that fits how you work.

Terminal

Install the CLI, then run `claude` in any project.
Mac/Linux: curl -fsSL claude.ai/install.sh | bash

IDE (VS Code)

Install the Claude Code extension (also Cursor & JetBrains): inline diffs, @-mentions, plan review.

Desktop App

A full GUI for parallel sessions, scheduled tasks and connectors — runs on your machine.

TIP *No CLI yet? In VS Code just ask Claude Code: "install claude cli in the terminal for me."*

© Tertiary Infotech Academy Pte Ltd

Setup Claude Code in VS Code

Add Claude Code to VS Code in five steps — from a clean install to signed in and ready to build.

1. **Install VS Code**
   Download from code.visualstudio.com/download and install it for your operating system.

2. **Open a project folder**
   Launch VS Code and open an empty folder to start a new project.

3. **Install the Claude Code extension**
   In the Extensions panel, search for “Claude Code” and click Install.

4. **Move it to the secondary side bar**
   Drag the Claude Code icon into the secondary side bar so it stays open beside your editor.

5. **Sign in with your subscription**
   Click Sign in and log in with your Claude Pro or Max subscription — you’re ready to build.

TIP No CLI needed to start — the VS Code extension runs the same agentic loop. Ask it to “install the Claude CLI” anytime.

© Tertiary Infotech Academy Pte Ltd

Claude Code Pricing

Claude Code is included in the subscription plans (from Pro up) and is also available pay-as-you-go via the API.



Pro

$17/mo (annual) · $20 monthly. Claude Code included.



Max

From $100/mo — 5× or 20× more usage than Pro.



Team

$20/seat standard · $100/seat premium (5× usage).



Enterprise

$20/seat + usage at API rates. Contact sales.

API pay-as-you-go (per million tokens, input / output): Opus 4.8 $5 / $25 · Sonnet 4.6 $3 / $15 · Haiku 4.5 $1 / $5

TIP *A free plan is also available. Prices as of June 2026 — verify at claude.com/pricing.*

© Tertiary Infotech Academy Pte Ltd

7 Steps to Build an App with Claude Code

1

Goal & Features

Define what to build (draft the prompt with ChatGPT).

2

Plan Mode

Let Claude plan before coding (Shift+Tab).

3

Execute

Run the plan in Bypass Permissions mode.

4

Context (/init)

Generate CLAUDE.md to capture project context.

5

Commit to GitHub

Version-control and push your code.

6

Deployment

Publish the app (e.g. GitHub Pages).

7

CI/CD


Automate build & deploy with GitHub Actions.

TIP *We'll do steps 1–3 now (Activity 1a), then context engineering, then steps 4–7 (Activity 1b).*

© Tertiary Infotech Academy Pte Ltd

Install the Claude Code Extension

Before Step 1 — install the official Claude Code extension from the VS Code Marketplace.



1 Open Extensions
Click the Extensions icon or press Ctrl+Shift+X (Cmd+Shift+X on Mac).

2 Search “claude”
Type claude in the Marketplace search box.

3 Pick “Claude Code for VS Code”
Select the result published by Anthropic.

4 Check the publisher
Look for the blue verified tick and anthropic.com — skip look-alike extensions.

5 Install & keep it updated
Click Install and leave Auto Update ticked to get new features.


TIP An extension can read your whole codebase — install only the verified Anthropic one.

© Tertiary Infotech Academy Pte Ltd

Move Claude Code to the Secondary Side Bar

Next, dock Claude Code on the right, so files stay on the left and the editor stays in the middle.


1. **Right-click the Claude icon**
   Move To → Secondary Side Bar




2. **Files on the left**
   Explorer shows your project folder (kanban8).

3. **Claude Code on the right**
   Chat with Claude while files change in the editor.

4. **New session**
   + starts fresh; the clock reopens history.




5. **Prompt box**
   Ctrl+Esc to focus · / for commands · pick Plan & model.



© Tertiary Infotech Academy Pte Ltd

Or Use Claude Code in the Desktop App

Prefer a GUI? The Claude Desktop app runs the same Claude Code agent — open the Code tab and point it at a project folder.



1. **Open the Code tab**
   Click the </> icon at the top-left to switch from Chat to Claude Code.

2. **Choose your project folder**
   Pick a folder (here kanban8). Claude reads and edits files only inside it.

3. **Describe the task**
   Type your goal in plain English and press Enter — the same agentic loop as the CLI.

4. **Check folder, mode & model**
   The status bar shows the folder, permission mode (Plan) and model (Sonnet 5.5 · Medium).

5. **Sessions grouped by project**
   The sidebar lists past sessions under each project — click one to resume.

TIP "Import Claude Code CLI sessions" brings your terminal history into the Desktop app.

© Tertiary Infotech Academy Pte Ltd

Start With a Clear Prompt

- **Describe the goal & features**

The clearer the brief, the better the build.

- **Use ChatGPT to draft it**

Ask ChatGPT to expand your idea into a detailed prompt, then paste it into Claude Code.

- **Cover the essentials**

Goal · sections · behaviour · styling · deliverable.

Example prompt (software-dev website)

```
Build a single-page, responsive website
for a software development company
(HTML, CSS, vanilla JS — no frameworks).

Goal: market services + capture leads.

Sections: 1) Hero + CTA  2) 3 testimonial
cards  3) Enquiry form (JS validation,
console.log, commented fetch()).

Styling: mobile-first, CSS variables,
Google Font, smooth scroll, accessible.

Deliverable: runs by opening the file.
```

TIP *The full prompt is in your Learner Guide (Activity 1).*

© Tertiary Infotech Academy Pte Ltd

Permission Modes

Permission modes control how often Claude pauses to ask before editing files or running commands.



`default`

Reads freely; asks before edits and shell commands.



`acceptEdits`

Auto-approves file edits and common filesystem commands.



`plan`

Explores and proposes a plan without editing source.



`auto`

Runs with background safety checks (research preview).

TIP *Press Shift+Tab to cycle modes; the current mode shows in the status bar.*

© Tertiary Infotech Academy Pte Ltd

Bypass Permissions — Handle with Care



`bypassPermissions` / `--dangerously-skip-permissions`

- Skips all permission prompts and safety checks — tool calls run immediately.
- Offers NO protection against prompt injection or unintended actions.
- Use only in isolated containers / VMs without internet access.
- Refuses to start as root/sudo; cannot be entered mid-session.
- **Prefer auto mode for fewer prompts WITH background safety checks.**

© Tertiary Infotech Academy Pte Ltd

STEP 3 · EXECUTE

Bypass Permissions in VS Code

To let Claude build hands-free, enable bypass-permissions mode — use it only in a trusted, sandboxed project.

1. Open VS Code Settings → Extensions → Claude Code.
2. Enable “Allow dangerously skip permissions”.
3. In the prompt box, open the mode selector.
4. Choose “Bypass permissions”.
5. Give your build prompt — Claude runs without per-action prompts.

CLI equivalent

```
$ claude \
    --dangerously-skip-permissions
```


⚠ *No safety checks or prompt-injection protection. Sandboxed / trusted projects only — prefer auto mode otherwise.*

© Tertiary Infotech Academy Pte Ltd

Allow Bypass Permissions — VS Code & Desktop

Both apps hide Bypass mode until you allow it in Settings. Turn it on only for trusted, sandboxed projects.


VS CODE



1. **Gear icon**
   Bottom-left of VS Code.
2. **Settings**
   Or press Ctrl+, (Cmd+, on Mac).
3. **Search "Claude Code"**
   Tick "Allow dangerously skip permissions".
4. **Pick the mode**
   Prompt box mode menu → Bypass permissions.

⚠ **No safety checks or prompt-injection protection — sandbox only.**

CLAUDE DESKTOP



1 Settings → Claude Code **2** Allow bypass mode **3** Keep awake (optional)

© Tertiary Infotech Academy Pte Ltd

ACTIVITY 1A

Goal, Plan & Build (Steps 1–3)

1. Step 1 — Goal & Features: draft a detailed build prompt (use ChatGPT) for the software-dev website.
2. Step 2 — Plan Mode: have Claude plan the build (Shift+Tab) and review the plan.
3. Step 3 — Execute: approve the plan and build the site in Bypass Permissions mode.
4. Open index.html and check the hero, testimonials and enquiry form work.

TIP *Full website prompt is in your Learner Guide (Activity 1).*

© Tertiary Infotech Academy Pte Ltd

Context Engineering

Context engineering is the practice of curating exactly what Claude sees — instructions, files and tools — so it has the right information and nothing that wastes its limited context window.



`CLAUDE.md`

Project memory loaded every session. Run /init to generate it.



`@ mentions`

Pull specific files or folders into context on demand.



`/compact`

Summarise the conversation to reclaim context space.



`/clear`

Wipe the slate for a fresh, unrelated task.

© Tertiary Infotech Academy Pte Ltd

Managing Your Context

- **Keep CLAUDE.md tight**

Project overview, conventions, commands to run. Short and high-signal.

- **Pull only what's needed**

Use @file mentions instead of pasting whole folders.

- **Compact before it overflows**

Watch the context meter; /compact at natural breakpoints.

- **Clear between tasks**

Start fresh so old context doesn't bleed into new work.

CLAUDE.md

```
# My Web App

## Stack
Vanilla HTML, CSS, JS. No frameworks.

## Conventions
- Single index.html, mobile-first
- Use CSS variables for colors

## Commands
- Deploy: push to main (GH Pages)
```

© Tertiary Infotech Academy Pte Ltd

Example CLAUDE.md (/init)

Run /init to generate a CLAUDE.md so Claude remembers your project's structure and conventions every session.

CLAUDE.md

```
# CLAUDE.md

## What this is
Single-page marketing site. HTML + CSS + vanilla JS — no framework, no build step.

## Running
Open index.html directly in a browser. No dev server.

## Architecture
- index.html  — sections: #home, #services, #testimonials, #contact
- styles.css  — design tokens in :root variables; mobile-first
- script.js   — enquiry-form validation (one DOMContentLoaded handler)
```

TIP *Keep CLAUDE.md short and high-signal — see github.com/alfredang/softwaredevleopment.*

© Tertiary Infotech Academy Pte Ltd

The Context Window

Claude's context window holds everything it can see at once. As you work it fills up, so manage it deliberately.



What fills it

System prompt, CLAUDE.md, memory, conversation, file reads, tool output, skills.



/context

See what's using space; run /mcp for per-server token cost.



Auto-compaction

Near the limit, old tool outputs clear first, then history is summarised.



Stay lean

MCP schemas load on demand; subagents keep their own context.

TIP *Put persistent rules in CLAUDE.md — conversation detail can be lost during compaction.*

© Tertiary Infotech Academy Pte Ltd

Memory Files

Each session starts fresh. Two mechanisms carry knowledge across sessions.



CLAUDE.md

- You write it — instructions & rules.
- Generate with /init; keep under ~200 lines.
- Scopes: project, user, or organisation.
- Loaded in full every session.



Auto Memory

- Claude writes it — learnings & patterns.
- Stored in MEMORY.md per repository.
- First 200 lines / 25KB load each session.
- Browse & edit with /memory.

© Tertiary Infotech Academy Pte Ltd

Manage Sessions

A session is a saved conversation tied to a project directory. Resume, branch, name and switch between them.



`--continue`

Resume the most recent session in this directory.



`--resume`

Open the session picker to browse and search.



`/rename`

Name a session so it's findable later.



`/branch`

Fork the conversation to try another approach.

TIP *Sessions are saved locally; use /clear and /compact to manage context within one.*

© Tertiary Infotech Academy Pte Ltd

Scheduled Tasks

Scheduled tasks (Desktop Routines) start a new session automatically — for daily reviews, audits or briefings.

Create

Routines → New routine → Local; set name & instructions.

Schedule

Hourly, daily, weekdays or weekly — or describe it.

Runs locally

Fires while the app is open and your machine is awake.

Manage

Run now, pause, edit, and review run history.

TIP *Just ask: "set up a daily code review that runs every morning at 9am."*

© Tertiary Infotech Academy Pte Ltd

Keep Working Toward a Goal

/goal sets a completion condition. After each turn a fast model checks it, and Claude keeps working until it's met.

`/goal <cond>`

Set a verifiable end state, e.g. “all tests pass”.

`/goal`

Check status: turns, tokens and the latest reason.

`/goal clear`

Remove an active goal before it's met.

How

A Haiku evaluator judges the condition each turn.

TIP *Write conditions Claude can prove in the transcript — e.g. “npm test exits 0”.*

© Tertiary Infotech Academy Pte Ltd

ACTIVITY 1B

Context, Deploy & CI/CD (Steps 4–7)

1. Step 4 — Context: run /init to generate CLAUDE.md for your project.
2. Step 5 — Commit to GitHub: create an empty repo on github.com, then have Claude push your code.
3. Step 6 — Deployment: deploy to GitHub Pages via GitHub Actions; add a README.
4. Step 7 — CI/CD: confirm each push automatically rebuilds and redeploys the site.
5. Present your live GitHub Pages link: https://<username>.github.io/software-dev-site/


TIP *Share your deployed GitHub Pages URL with the class.*

© Tertiary Infotech Academy Pte Ltd

Create a GitHub Repository

Before Claude can push your code, create an empty repository on github.com to receive it.


1 Click New
github.com → Repositories → green New button.



2 Owner
Keep your own GitHub account.

3 Name the repository
e.g. software-dev-site — a green tick means it's free.

4 Description (optional)
One line about the project.




TIP Use lowercase-with-hyphens — the repo name becomes part of your GitHub Pages URL.

© Tertiary Infotech Academy Pte Ltd

Configure & Create the Repository

Keep the repository empty — your project already has its files, and Claude will push them in the next step.



1. **Visibility: Public**
   Free GitHub Pages hosting needs a public repository.
2. **No template**
   Start from a blank repository.
3. **README: Off**
   Leave it off — Claude writes the README in Step 6.
4. **No .gitignore, no license**
   Files created here would clash with your first push.
5. **Create repository**
   Click the green button to finish.


TIP An empty repo avoids the “rejected — fetch first” error on your first git push.

© Tertiary Infotech Academy Pte Ltd

STEP 5 · COMMIT TO GITHUB

Connect & Push Your Code

GitHub shows your repository URL and the git commands — copy the URL and let Claude Code do the push.




```
Prompt to Claude Code

Commit all files and push this project to
https://github.com/<username>/software-dev-site.git on the main
branch.
```

1. **Copy the HTTPS URL**
   Click the copy icon beside https://github.com/<you>/<repo>.git.

2. **The git commands**
   init → add → commit → branch -M main → remote add → push.

3. **Let Claude run them**
   Paste the prompt (left); Claude initialises git, commits and pushes.

4. **Sign in when asked**
   Approve the GitHub sign-in (or run gh auth login) the first time.

5. **Refresh the repo page**
   Your files appear — ready for Step 6, GitHub Pages.

© Tertiary Infotech Academy Pte Ltd

TOPIC 2

Tools and Commands

1 The .claude directory

2 Custom Commands

3 MCP Tools

4 Playwright MCP

© Tertiary Infotech Academy Pte Ltd

The .claude Directory

Claude Code keeps its configuration in two places: your user folder (applies everywhere) and the project folder (shared with your team via version control).

```
~/.claude/   (user — all projects)


settings.json    # settings, hooks
CLAUDE.md       # personal memory
agents/  skills/  commands/
projects/<p>/ # sessions + memory/
plugins/
~/.claude.json # MCP servers, config
```

```
<project>/.claude/   (team — in git)


settings.json          # shared settings
settings.local.json   # personal
CLAUDE.md  rules/ # memory & rules
commands/   # /slash commands
skills/<name>/SKILL.md
agents/<name>.md # sub agents
.mcp.json   # project MCP servers
```

TIP *User scope applies to every project; project scope is committed so your whole team shares it.*

© Tertiary Infotech Academy Pte Ltd

User Level vs Project Level

Every customisation — commands, MCP tools, skills, CLAUDE.md and hooks — can be stored at two levels. User level applies to ALL your projects; project level applies only to that ONE project.

User Level · ~/.claude/

APPLIES TO ALL PROJECTS

- **Commands** ~/.claude/commands/<name>.md
- **MCP Tools** ~/.claude.json · claude mcp add -s user …
- **Skills** ~/.claude/skills/<name>/SKILL.md
- **CLAUDE.md** ~/.claude/CLAUDE.md (your personal memory)
- **Hooks** ~/.claude/settings.json → "hooks"

Project Level · <project>/

THIS PROJECT ONLY

- **Commands** <project>/.claude/commands/<name>.md
- **MCP Tools** <project>/.mcp.json · claude mcp add -s project …
- **Skills** <project>/.claude/skills/<name>/SKILL.md
- **CLAUDE.md** <project>/CLAUDE.md (shared with the team)
- **Hooks** <project>/.claude/settings.json → "hooks"

TIP *Keep personal preferences at user level; commit team-shared rules, commands, skills and hooks at project level. Both levels load together — where they conflict, project settings take precedence.*

© Tertiary Infotech Academy Pte Ltd

Custom Slash Commands

Custom commands are reusable prompts saved as Markdown files. Type a slash command to run a multi-step workflow the same way every time.

- **Where they live**

.claude/commands/ in your project (or ~/.claude for personal).

- **How to make one**

Create name.md — the filename becomes /name.

- **Reload**

Restart Claude Code to pick up new commands.

- **Arguments**

Use $ARGUMENTS to pass input into the command.

```
.claude/commands/gitpush.md



Push all code to GitHub, then:
1. Create a README
2. Enable GitHub Pages
3. Update repo About + Pages link
4. Scan for secrets before publishing

Target: $ARGUMENTS
```

© Tertiary Infotech Academy Pte Ltd

ACTIVITY 2

Create a /gitpush Command

1. Create .claude/commands/gitpush.md in your project.
2. Step: push/update all code to GitHub.
3. Step: generate a README for the repository.
4. Step: create a GitHub Page via GitHub Actions.
5. Step: update the repo About section and add the GitHub Pages link.
6. Step: security scan so no sensitive data is published.

TIP *Restart Claude Code, then run /gitpush to execute the whole workflow.*

© Tertiary Infotech Academy Pte Ltd

What is MCP?

The Model Context Protocol (MCP) is an open standard that lets Claude Code connect to external tools and data sources through a common interface — like a USB-C port for AI.



MCP Server

Exposes tools/data (e.g. Playwright, GitHub, databases).



MCP Client

Claude Code connects to servers and calls their tools.



Transport

stdio or HTTP/SSE — transport-agnostic communication.



Tools

Each server publishes callable actions Claude can use.

© Tertiary Infotech Academy Pte Ltd

Connect an MCP Server

- **Add a server**

claude mcp add — register an HTTP or local stdio server.

- **Pick a scope**

local (this project), project (.mcp.json, shared), or user (all projects).

- **Verify & use**

claude mcp list to check status; /mcp to manage in-session.

terminal

```
# hosted server
$ claude mcp add --transport \
   http docs <url>

# local stdio server (project)
$ claude mcp add playwright \
   -s project -- npx -y \
   @playwright/mcp@latest

$ claude mcp list
```

TIP *Project-scoped servers live in .mcp.json — commit it so teammates get the same tools.*

© Tertiary Infotech Academy Pte Ltd

Playwright MCP

The Playwright MCP server lets Claude Code drive a real browser — open pages, click, fill forms and capture screenshots — perfect for testing the website you just built.

- **Install at project level**

Add the server to your project's MCP config.

- **Approve permissions**

Allow Claude to launch and control the browser.

- **Use the tools**

Ask Claude to open your site and take a screenshot.

```
terminal


$ claude mcp add playwright \
    npx @playwright/mcp@latest

> open my site and take a
  screenshot, then add it
  to the README
```

© Tertiary Infotech Academy Pte Ltd

ACTIVITY 3

Install & Use Playwright MCP



1. Install the Playwright MCP tool at the project level.
2. Approve the browser permissions for Claude Code.
3. Ask Claude to open your deployed website in the browser.
4. Capture a screenshot of the site using the Playwright MCP tool.
5. Add the screenshot to your README and push to GitHub.

TIP *Verify the screenshot renders correctly in your GitHub README.*

© Tertiary Infotech Academy Pte Ltd

ACTIVITY 3B

Test the Enquiry Form (Playwright)

1. Wire the enquiry form to send submissions to angch@tertiaryinfotech.com (e.g. Formspree or a fetch to your endpoint).
2. Ask Claude to use the Playwright MCP tool to open your deployed site.
3. Fill the form with test data (name, email, message) and submit it.
4. Confirm the success message appears and the data is captured in the console.
5. Check that the enquiry email actually arrives in the inbox.

TIP *Re-run after each change so every enquiry reliably reaches your email.*

© Tertiary Infotech Academy Pte Ltd

TOPIC 3

Skills, Agents & Hooks

1 Agent Skills

2 Sub Agents

3 Hooks

4 Key Concepts Summary

© Tertiary Infotech Academy Pte Ltd

Agent Skills

Skills are reusable folders of instructions (SKILL.md) plus optional scripts and resources that teach Claude how to do a specialised task. Claude loads a skill only when it's relevant.



SKILL.md

Name + description + instructions Claude follows on demand.



Project skills

.claude/skills/ — shared with your repo & team.



Install

npx skills add <repo> --skill <name>.



Customise

Edit the skill to fit your project's needs.

© Tertiary Infotech Academy Pte Ltd

SKILL.md vs CLAUDE.md

Both are Markdown instruction files — the difference is WHEN Claude loads them.

SKILL.md

Loaded ON DEMAND

Trigger	Claude reads the name + description, and loads it only when the task matches.
Scope	One specialised capability — a workflow, a format, a house standard.
Cost	Costs no context until it fires; you can keep dozens installed.
Lives in	.claude/skills/<name>/SKILL.md

CLAUDE.md

Loaded EVERY SESSION

Trigger	Read automatically at the start of every session — always in context.
Scope	Project-wide facts: stack, conventions, commands, do-nots.
Cost	Spends context on every turn, so keep it tight and high-value.
Lives in	CLAUDE.md at the project root (or ~/.claude/CLAUDE.md)

TIP *Put stable project facts in CLAUDE.md; put specialised, occasional procedures in a skill.*

© Tertiary Infotech Academy Pte Ltd

ACTIVITY 4

Install & Run Skills



1. Install frontend-design: npx skills add https://github.com/anthropics/skills --skill frontend-design
2. Customise the frontend design to appeal to software-dev clients.
3. Install seo-audit: npx skills add https://github.com/coreyhaines31/marketingskills --skill seo-audit
4. Run the seo-audit skill to optimise the website's SEO.
5. Commit the improvements and push to GitHub.

TIP *Both skills install into .claude/skills/ at the project level.*

© Tertiary Infotech Academy Pte Ltd

Sub Agents

Sub agents are specialised assistants with their own prompt, tools and context window. Delegate focused jobs — like security review or UX critique — to keep the main thread clean.

- **Create with /agents**

Choose Project to save under .claude/agents/.

- **Give it a clear role**

Describe purpose, tools and when to invoke it.

- **Isolated context**

Each sub agent runs in its own context window.

```
.claude/agents/security-scan.md

---
name: security-scan
description: Scan for vulns
  & hardening
---
You are a security reviewer...
```

© Tertiary Infotech Academy Pte Ltd

Why Use Sub Agents?

Reach for a sub agent when a side task would flood your main conversation with output you won't reference again.

Preserve context

Exploration & logs stay in the agent's own window — only the summary returns.

Enforce constraints

Limit exactly which tools the sub agent is allowed to use.

Reuse & specialise

Reuse configs across projects; focused prompts for each domain.

Control costs


Route narrow tasks to a faster, cheaper model.

TIP *Define a custom sub agent when you keep spawning the same kind of worker with the same instructions.*


© Tertiary Infotech Academy Pte Ltd

Sub Agents vs Agent Teams

Sub Agents



Agent Teams




Sub agents report back to one main agent · agent teams coordinate via a shared task list.

© Tertiary Infotech Academy Pte Ltd

ACTIVITY 5

Create Custom Sub Agents



1. Create a security-scan sub agent in .claude/agents/ to find vulnerabilities and harden the site.
2. Run it and apply the recommended fixes.
3. Install lead-magnets: npx skills add https://github.com/coreyhaines31/marketingskills --skill lead-magnets
4. Create a UI/UX review sub agent that uses lead-magnets to optimise for lead capture.
5. Apply improvements and push to GitHub.

TIP *Both agents live in .claude/agents/ at the project level.*

© Tertiary Infotech Academy Pte Ltd

Hooks

Hooks are shell commands that run automatically at defined points in Claude Code's lifecycle — letting you enforce rules, format code, or trigger actions without asking.



`PreToolUse`

Runs before a tool — validate or block an action.



`PostToolUse`

Runs after a tool — auto-format or test.



`Notification`

React when Claude needs input or finishes.



`Stop`

Run cleanup or checks when a task ends.

Configured in .claude/settings.json under "hooks".

© Tertiary Infotech Academy Pte Ltd

Automating with Hooks

- **Deterministic, not optional**

Hooks always run at their event — they don't rely on the model deciding to.

- **Common uses**

Auto-format after edits, run tests, block risky commands, send notifications.

- **Where**

Add a "hooks" block to .claude/settings.json (matchers + commands).

.claude/settings.json

```
{
  "hooks": {
    "PostToolUse": [{
      "matcher": "Edit|Write",
      "hooks": [{
        "type": "command",
        "command":
          "npx prettier --write ."
      }]
    }]
  }
}
```

TIP *Hooks receive event context on stdin as JSON — perfect for lint, format and guardrail scripts.*

© Tertiary Infotech Academy Pte Ltd

ACTIVITY 6

Hooks — Floating WhatsApp Widget

1. Add a floating WhatsApp widget to the bottom-right of the website from Activity 1.
2. Style it as a round WhatsApp button that expands into a chat panel on click.
3. Add a Claude Code hook that fires 10 seconds after page load to auto-open the widget.
4. On auto-open, prompt the user “Hi! How can I help you?” with suggested queries as quick-reply chips.
5. Add voice activation — let the visitor speak their question using the Web Speech API.
6. Use the Playwright MCP to test the 10-second auto-open, the suggested queries and the voice prompt.

TIP *Hooks live in .claude/hooks + .claude/settings.json; the widget behaviour lives in script.js.*

© Tertiary Infotech Academy Pte Ltd

ACTIVITY 7

Test, Optimise & Deploy

1. Use Playwright MCP to test the enquiry form end-to-end.
2. Ensure all enquiries are sent to angch@tertiaryinfotech.com.
3. Add a WhatsApp floating widget (bottom-right) with suggestive queries, linked to +65 9698 3731.
4. Run a final security scan and lead-magnet UX review.
5. Deploy the final version and verify the live site end-to-end.

TIP Record the live URL and the tests completed for your final verification.

© Tertiary Infotech Academy Pte Ltd

KEY CONCEPTS · SUMMARY

What Triggers What

Six ways to extend Claude Code — each one is loaded by a different trigger. Knowing which fires when is how you choose the right mechanism.

CLAUDE.md	EVERY SESSION	Project memory — read automatically at the start of every session, so it is always in context.
Skills	ON DEMAND	SKILL.md folders — Claude reads the name + description, and loads one when the task matches.
Tools / MCP	ON DEMAND	Built-in and MCP tools — invoked by Claude during the agentic loop whenever the job needs them.
Slash Commands	MANUALLY	Saved prompts in .claude/commands/ — they run only when you type /<name> yourself.
Hooks	BY EVENT	Shell commands in settings.json — fired deterministically by a lifecycle event, not by the model.
Sub Agents	BY DELEGATION	Specialised assistants with their own context — spawned when the main agent delegates a job.

TIP Always-on context is expensive — keep CLAUDE.md tight and push specialised, occasional procedures into skills, commands and sub agents.

© Tertiary Infotech Academy Pte Ltd

AI SECURITY

5 Principles of AI Security

Agents act on your behalf. These five controls keep what they can see and do safe, reviewable and accountable.

Data Control	WHAT AI CAN SEE	Classify your data (public, internal, confidential) and decide exactly which data the AI may access.
Permission Control	WHAT AI CAN DO	Grant only the rights needed — read, write, edit, delete. Ask before anything destructive.
Human in the Loop	WHO APPROVES	A person reviews and approves high-impact actions — deploys, deletions, payments, emails.
Traceability	WHAT HAPPENED	Log every prompt, tool call and change so actions can be audited, explained and rolled back.
Right-Sized Models	NOT THE MOST POWERFUL	Do not use the most powerful models by default — the smallest model that does the job has less autonomy and risk.

TIP In Claude Code: permission modes & allow/deny rules, hooks for guardrails & logs, plan mode for human review.

© Tertiary Infotech Academy Pte Ltd

WRAP UP

Summary & Q&A


Topic 1	The agentic loop and context engineering power everything Claude Code does.
Topic 2	Custom commands and MCP tools automate and extend your workflow.
Topic 3	Skills, sub agents and hooks make Claude a specialised teammate.
Integrated Build	You built, deployed, tested, secured and optimised a real website.

© Tertiary Infotech Academy Pte Ltd

ASSESSMENT

Assessment Flow

At the assessment stage, follow these five steps in order.



TIP *Courseware and the assessment are on the LMS: https://lms-tms.tertiaryinfotech.com/*

© Tertiary Infotech Academy Pte Ltd

BEFORE YOU GO

Certification & TRAQOM Survey



TRAQOM Survey (Mandatory)

Complete the certification & TRAQOM survey to receive your certificate.

ai-lms-tms.tertiaryinfo.tech



Digital Attendance

Remember to take AM, PM and Assessment digital attendance — required for your funding.

© Tertiary Infotech Academy Pte Ltd

Thank You!

Questions? We're here to help — during and after class.

enquiry@tertiaryinfotech.com | +65 6100 0613