Lab 14: rm -rf meets a hook, not a polite request

Topic 1: Agentic Architecture & Orchestration · Task 1.5: Apply Agent SDK hooks for tool call interception and data normalization

Runs on Simulator 4: Developer Productivity with Claude · Self-practice

Source: Built from exam guide task statement 1.5 (no practice question covers this angle)

Commit to an answer first

A developer's agent can run Bash. Someone asks it to tidy up, and it reaches for rm -rf. What should stop it?

A. A PreToolUse hook denies Bash commands containing rm -rf.

B. A CLAUDE.md line saying "be careful with deletes".

Simulate the solution

```
# In the browser: open Simulator 4, then Lab 14
cd labs
uv run serve.py

# In Claude Code, from the labs folder
/lab 14

# In a terminal, from simulators/simulator-4-developer-productivity/
uv run explorer.py --case UC-D6
```

What you should see

The hook denies the command, work/tests still exists, and the agent reports the policy.

The hook denies the command; tests/ still exists; the agent reports the policy.

Open `simulators/simulator-4-developer-productivity/evidence/` and find it yourself.

The answer

A. A PreToolUse hook denies Bash commands containing rm -rf.

Check yourself

- a blocked row for rm -rf appears in tool_log.jsonl
- work/tests still exists afterwards
- agent's final text acknowledges the block

Now change one thing

Edit the prompt_template in this lab's file under cases/, rerun with --case, and check tool_log.jsonl for what changed.