

HTTP, Caching, and CDNs

Web Applications and Services
Spring Term

Naercio Magaia



Overview

- Web and HTTP
- video streaming and content distribution networks

Web and HTTP

First, a quick review...

- web page consists of *objects*, each of which can be stored on different Web servers
- object can be HTML file, JPEG image, Java applet, audio file,...
- web page consists of *base HTML-file* which includes *several referenced objects, each* addressable by a *URL*, e.g.,

`www.someschool.edu/someDept/pic.gif`


host name

path name

HTTP overview

HTTP: hypertext transfer protocol

- Web's application-layer protocol
- client/server model:
 - *client*: browser that requests, receives, (using HTTP protocol) and “displays” Web objects
 - *server*: Web server sends (using HTTP protocol) objects in response to requests



HTTP overview (continued)

HTTP uses TCP:

- client initiates TCP connection (creates socket) to server, port 80
- server accepts TCP connection from client
- HTTP messages (application-layer protocol messages) exchanged between browser (HTTP client) and Web server (HTTP server)
- TCP connection closed

HTTP is “stateless”

- server maintains *no* information about past client requests

aside
protocols that maintain “state” are complex!

- past history (state) must be maintained
- if server/client crashes, their views of “state” may be inconsistent, must be reconciled

HTTP connections: two types

Non-persistent HTTP

1. TCP connection opened
2. at most one object sent over TCP connection
3. TCP connection closed

downloading multiple objects required multiple connections

Persistent HTTP

- TCP connection opened to a server
- multiple objects can be sent over *single* TCP connection between client, and that server
- TCP connection closed

Non-persistent HTTP: example

User enters URL: `www.someSchool.edu/someDepartment/home.index`
(containing text, references to 10 jpeg images)



1a. HTTP client initiates TCP connection to HTTP server (process) at `www.someSchool.edu` on port 80



1b. HTTP server at host `www.someSchool.edu` waiting for TCP connection at port 80 “accepts” connection, notifying client

2. HTTP client sends HTTP *request message* (containing URL) into TCP connection socket. Message indicates that client wants object `someDepartment/home.index`

3. HTTP server receives request message, forms *response message* containing requested object, and sends message into its socket

time



Non-persistent HTTP: example (cont.)

User enters URL: `www.someSchool.edu/someDepartment/home.index`
(containing text, references to 10 jpeg images)



5. HTTP client receives response message containing html file, displays html. Parsing html file, finds 10 referenced jpeg objects

6. Steps 1-5 repeated for each of 10 jpeg objects

4. HTTP server closes TCP connection.




Non-persistent HTTP: response time

RTT (definition): time for a small packet to travel from client to server and back

HTTP response time (per object):

- one RTT to initiate TCP connection
- one RTT for HTTP request and first few bytes of HTTP response to return
- object/file transmission time



Non-persistent HTTP response time = 2RTT + file transmission time

Persistent HTTP (HTTP 1.1)

Non-persistent HTTP issues:

- requires 2 RTTs per object
- OS overhead for *each* TCP connection
- browsers often open multiple parallel TCP connections to fetch referenced objects in parallel

Persistent HTTP (HTTP1.1):

- server leaves connection open after sending response
- subsequent HTTP messages between same client/server sent over open connection
- client sends requests as soon as it encounters a referenced object
- as little as one RTT for all the referenced objects (cutting response time in half)

HTTP request message

- two types of HTTP messages: *request, response*
- **HTTP request message:**
 - ASCII (human-readable format)


request line (GET, POST,
HEAD commands) →

/ carriage return character
/ line-feed character

carriage return, line feed →
at start of line indicates
end of header lines

* Check out the online interactive exercises for more
examples: http://gaia.cs.umass.edu/kurose_ross/interactive/

HTTP request message: general format



Other HTTP request messages

POST method:

- web page often includes form input
- user input sent from client to server in entity body of HTTP POST request message

GET method (for sending data to server):

- include user data in URL field of HTTP GET request message (following a '?'):

`www.somesite.com/animalsearch?monkeys&banana`


HEAD method:

- requests headers (only) that would be returned *if* specified URL were requested with an HTTP GET method.

PUT method:

- uploads new file (object) to server
- completely replaces file that exists at specified URL with content in entity body of POST HTTP request message

HTTP response message

status line (protocol  HTTP/1.1 200 OK
status code status phrase)

HTTP response status codes

- status code appears in 1st line in server-to-client response message.
- some sample codes:

200 OK

- request succeeded, requested object later in this message

301 Moved Permanently

- requested object moved, new location specified later in this message (in Location: field)

400 Bad Request

- request msg not understood by server

404 Not Found

- requested document not found on this server

505 HTTP Version Not Supported

Common Request Header Fields

Field name	Field purpose	Example
Accept-Charset	Character sets that are acceptable	Accept-Charset: utf-8
Accept-Encoding	List of acceptable encodings	Accept-Encoding: gzip, deflate
Accept-Language	List of acceptable human languages	Accept-Language: en-US
Authorization	Authentication credentials	Authorization: Basic QWxhZGRpbjpvcGVuIHNlc2FtZQ==
Cookie	A cookie previously sent by the server with Set-Cookie	Cookie: \$Version=1; Skin=new;
Content-Length	The length of the request body in octets	Content-Length: 348
Content-Type	The MIME type of the body of the request	Content-Type: application/x-www-form-urlencoded
Date	The date and time that the message was sent	Date: Tue, 15 Nov 1994 08:12:31 GMT
Host	The domain name of the server, and the listening TCP Port number	Host: en.wikipedia.org:8080 Host: en.wikipedia.org
If-Modified-Since	Allows a 304 Not Modified to be returned if content is unchanged	If-Modified-Since: Sat, 29 Oct 1994 19:43:31 GMT
If-Unmodified-Since	Only send the response if the entity has not been modified since a specific time	If-Unmodified-Since: Sat, 29 Oct 1994 19:43:31 GMT

Common Request Header Fields

Field name	Field purpose	Example
User-Agent	The user agent	User-Agent: Mozilla/5.0
Upgrade	Ask the server to upgrade to other protocol	Upgrade: websocket
Content-Encoding	The type of encoding used on the data	Content-Encoding: gzip
Content-Language	The language the content is in	Content-Language: da
Content-Length	The length of the response body in octets	Content-Length: 348
Content-Location	Alternate location for the returned data	Content-Location:/index.htm
Content-Type	MIME Type of this content	Content-Type: text/html;charset=utf-8
Date	Date and time that the message was sent	Date:Tue,15 Nov 1994 08:12
Expires	When the response is considered stale	Expires: Thu, 01 Dec 1994 16:00:00 GMT
Last-Modified	Last modified date for the object	Last-Modified: Tue, 15 Nov 1994 12:45:26 GMT
Location	Used in redirection, or when a new resource has been created (PUT)	Location: www.w3.org/pub/WWW/p.html
Server	A name for the server	Server: Apache/2.4.1 (Unix)
Set-Cookie	An HTTP Cookie	Set-Cookie: UserID=JohnDoe; Max-Age=3600; Version=1
Upgrade	Ask the client to upgrade to other protocol	Upgrade: websocket
WWW-Authenticate	Authentication scheme that should be used	WWW-Authenticate: Basic

Trying out HTTP (client side) for yourself

1. netcat to your favorite Web server:

```
% nc -C -v gaia.cs.umass.edu 80
```

- opens TCP connection to port 80 (default HTTP server port) at gaia.cs.umass.edu.
- anything typed in will be sent to port 80 at gaia.cs.umass.edu

2. type in a GET HTTP request:

```
GET /kurose_ross/interactive/index.php HTTP/1.1  
Host: gaia.cs.umass.edu
```

- by typing this in (hit carriage return twice), you send this minimal (but complete) GET request to HTTP server

3. look at response message sent by HTTP server!


(or use Wireshark to look at captured HTTP request/response)

Maintaining user/server state: cookies

Recall: HTTP GET/response interaction is *stateless*

- no notion of multi-step exchanges of HTTP messages to complete a Web “transaction”
 - no need for client/server to track “state” of multi-step exchange
 - all HTTP requests are independent of each other
 - no need for client/server to “recover” from a partially-completed-but-never-completely-completed transaction

a *stateful protocol*: client makes two changes to X , or none at all



Q: what happens if network connection or client crashes at t' ?

Maintaining user/server state: cookies

Web sites and client browser use *cookies* to maintain some state between transactions


four components:

- 1) cookie header line of HTTP *response* message
- 2) cookie header line in next HTTP *request* message
- 3) cookie file kept on user's host, managed by user's browser
- 4) back-end database at Web site

Example:

- Susan uses browser on laptop, visits specific e-commerce site for first time
- when initial HTTP requests arrives at site, site creates:
 - unique ID (aka “cookie”)
 - entry in backend database for ID
- subsequent HTTP requests from Susan to this site will contain cookie ID value, allowing site to “identify” Susan

Maintaining user/server state: cookies



HTTP cookies: comments

What cookies can be used for:

- authorization
- shopping carts
- recommendations
- user session state (Web e-mail)


Challenge: How to keep state?

- *at protocol endpoints:* maintain state at sender/receiver over multiple transactions
- *in messages:* cookies in HTTP messages carry state


- aside
- cookies and privacy:*
- cookies permit sites to *learn* a lot about you on their site.
 - third party persistent cookies (tracking cookies) allow common identity (cookie value) to be tracked across multiple web sites

Example: displaying a NY Times web page


- 1 GET base html file
- 2 from nytimes.com
- 4 fetch ad from
- 5 AdX.com
- 7 display composed page




Cookies: tracking a user's browsing behavior



Cookies: tracking a user's browsing behavior



Cookies: tracking a user's browsing behavior (one day later)



Cookies: tracking a user's browsing behavior

Cookies can be used to:

- track user behavior on a given website (**first party cookies**)
- track user behavior across multiple websites (**third party cookies**) without user ever choosing to visit tracker site (!)
- tracking may be *invisible* to user:
 - rather than displayed ad triggering HTTP GET to tracker, could be an invisible link

third party tracking via cookies:

- disabled by default in Firefox, Safari browsers
- to be disabled in Chrome browser in 2023

GDPR (EU General Data Protection Regulation) and cookies


“Natural persons may be associated with online identifiers [...] such as internet protocol addresses, cookie identifiers or other identifiers [...].

This may leave traces which, in particular when combined with unique identifiers and other information received by the servers, may be used to create profiles of the natural persons and identify them.”

GDPR, recital 30 (May 2018)



when cookies can identify an individual, cookies are considered personal data, subject to GDPR personal data regulations




User has explicit control over whether or not cookies are allowed

Web caches

Goal: satisfy client requests without involving origin server

- user configures browser to point to a (local) *Web cache*
- browser sends all HTTP requests to cache
 - *if* object in cache: cache returns object to client
 - *else* cache requests object from origin server, caches received object, then returns object to client



Web caches (aka proxy servers)

- Web cache acts as both client and server
 - server for original requesting client
 - client to origin server
- server tells cache about object's allowable caching in response header:

```
Cache-Control: max-age=<seconds>
```

```
Cache-Control: no-cache
```


Why Web caching?

- reduce response time for client request
 - cache is closer to client
- reduce traffic on an institution's access link
- Internet is dense with caches
 - enables “poor” content providers to more effectively deliver content

Browser caching: Conditional GET

Goal: don't send object if browser has up-to-date cached version

- no object transmission delay (or use of network resources)
- **client:** specify date of browser-cached copy in HTTP request
If-modified-since: <date>
- **server:** response contains no object if browser-cached copy is up-to-date:
HTTP/1.0 304 Not Modified



HTTP/2

Key goal: decreased delay in multi-object HTTP requests

HTTP1.1: introduced multiple, pipelined GETs over single TCP connection

- server responds *in-order* (FCFS: first-come-first-served scheduling) to GET requests
- with FCFS, small object may have to wait for transmission (**head-of-line (HOL) blocking**) behind large object(s)
- loss recovery (retransmitting lost TCP segments) stalls object transmission

HTTP/2


Key goal: decreased delay in multi-object HTTP requests

HTTP/2: [RFC 7540, 2015] increased flexibility at *server* in sending objects to client:

- methods, status codes, most header fields unchanged from HTTP 1.1
- transmission order of requested objects based on client-specified object priority (not necessarily FCFS)
- *push* unrequested objects to client
- divide objects into frames, schedule frames to mitigate HOL blocking

HTTP/2: mitigating HOL blocking


HTTP 1.1: client requests 1 large object (e.g., video file) and 3 smaller objects



objects delivered in order requested: O_2 , O_3 , O_4 wait behind O_1

HTTP/2: mitigating HOL blocking

HTTP/2: objects divided into frames, frame transmission interleaved



O₂, O₃, O₄ delivered quickly, O₁ slightly delayed

HTTP/2 to HTTP/3

HTTP/2 over single TCP connection means:

- recovery from packet loss still stalls all object transmissions
 - as in HTTP 1.1, browsers have incentive to open multiple parallel TCP connections to reduce stalling, increase overall throughput
- no security over vanilla TCP connection
- **HTTP/3** adds security, per object error- and congestion-control (more pipelining) over UDP

Video Streaming and CDNs: context


- stream video traffic: major consumer of Internet bandwidth
 - Netflix, YouTube, Amazon Prime: 80% of residential ISP traffic (2020)
- *challenge*: scale - how to reach ~1B users?
- *challenge*: heterogeneity
 - different users have different capabilities (e.g., wired versus mobile; bandwidth rich versus bandwidth poor)
- *solution*: distributed, application-level infrastructure



Multimedia: video

- video: sequence of images displayed at constant rate
 - e.g., 24 images/sec
- digital image: array of pixels
 - each pixel represented by bits
- coding: use redundancy *within* and *between* images to decrease # bits used to encode image
 - spatial (within image)
 - temporal (from one image to next)

spatial coding example: instead of sending N values of same color (all purple), send only two values: color value (*purple*) and number of repeated values (N)



frame i

temporal coding example: instead of sending complete frame at $i+1$, send only differences from frame i




frame $i+1$

Multimedia: video

- **CBR: (constant bit rate):** video encoding rate fixed
- **VBR: (variable bit rate):** video encoding rate changes as amount of spatial, temporal coding changes
- **examples:**
 - MPEG 1 (CD-ROM) 1.5 Mbps
 - MPEG2 (DVD) 3-6 Mbps
 - MPEG4 (often used in Internet, 64Kbps – 12 Mbps)

spatial coding example: instead of sending N values of same color (all purple), send only two values: color value (*purple*) and number of repeated values (N)



frame i


temporal coding example: instead of sending complete frame at $i+1$, send only differences from frame i



frame $i+1$

Streaming stored video


simple scenario:



Main challenges:


- server-to-client bandwidth will *vary* over time, with changing network congestion levels (in house, access network, network core, video server)
- packet loss, delay due to congestion will delay playout, or result in poor video quality

Streaming stored video




Streaming stored video: challenges

- **continuous playout constraint**: during client video playout, playout timing must match original timing
 - ... but **network delays are variable** (jitter), so will need **client-side buffer** to match continuous playout constraint
- other challenges:
 - client interactivity: pause, fast-forward, rewind, jump through video
 - video packets may be lost, retransmitted



Streaming stored video: playout buffering




- *client-side buffering and playout delay*: compensate for network-added delay, delay jitter

Streaming multimedia: DASH

*D*ynamic, *A*daptive
*S*treaming over *H*TTP

server:

- divides video file into multiple chunks
- each chunk encoded at multiple different rates
- different rate encodings stored in different files
- files replicated in various CDN nodes
- *manifest file*: provides URLs for different chunks




client:

- periodically estimates server-to-client bandwidth
- consulting manifest, requests one chunk at a time
 - chooses maximum coding rate sustainable given current bandwidth
 - can choose different coding rates at different points in time (depending on available bandwidth at time), and from different servers

Streaming multimedia: DASH

- “*intelligence*” at client: client determines
 - *when* to request chunk (so that buffer starvation, or overflow does not occur)
 - *what encoding rate* to request (higher quality when more bandwidth available)
 - *where* to request chunk (can request from URL server that is “close” to client or has high available bandwidth)



Streaming video = encoding + DASH + playout buffering

Content distribution networks (CDNs)

challenge: how to stream content (selected from millions of videos) to hundreds of thousands of *simultaneous* users?

- *option 1:* single, large “mega-server”
 - single point of failure
 - point of network congestion
 - long (and possibly congested) path to distant clients

....quite simply: this solution *doesn't scale*

Content distribution networks (CDNs)


challenge: how to stream content (selected from millions of videos) to hundreds of thousands of *simultaneous* users?

- *option 2:* store/serve multiple copies of videos at multiple geographically distributed sites (*CDN*)
 - *enter deep:* push CDN servers deep into many access networks
 - close to users
 - Akamai: 240,000 servers deployed in > 120 countries (2015)
 - *bring home:* smaller number (10's) of larger clusters in POPs near access nets
 - used by Limelight



Content distribution networks (CDNs)

- CDN: stores copies of content (e.g., MADMEN) at CDN nodes
- subscriber requests content, service provider returns manifest
 - using manifest, client retrieves content at highest supportable rate
 - may choose different rate or copy if network path congested



Content distribution networks (CDNs)



OTT challenges: coping with a congested Internet from the “edge”

- what content to place in which CDN node?
- from which CDN node to retrieve content? At which rate?

Next Lecture ...

- ✓ Introduction
- ✓ HTTP, Caching, and CDNs
- **Views**
 - Templates
 - Forms
 - Models
 - Security
- Transactions
- Remote Procedure Call
- Web Services
- Time
- Elections and Group Communication
- Coordination and Agreement