Grading form - Assignment 676925 - Student 513818

• First score each criterion according to the tutorial instructions below.
• Then sum points separately for **#R**, **#Radv**, and **#Python**, and then scale to grades:
--> R = summed score / 65 * 8
--> Radv = summed score / 19 * 2
--> Python = summed score / 18 * 2
--> Total = R + max(Radv, Python)
• Your final grade should use **#R** plus the higher of **#Python** vs **#Radv**.
• Your report includes a preliminary AI estimate which you can use to guide your self-grading.
• Pay special attention to the consistency histogram as inconsistent LLM scoring may indicate unreliable AI feedback.

Dont forget to compute final self scoring grades below!

Self scoring:
• #R: 7.76
• #Radv: 2
• #Python:


--> Overall: 9.76
Based on **#R** and

Preliminary AI estimate:
• #R: **6.65**
• #Radv: **1.89**
• #Python: **0.11**

--> Overall: **8.54**
Based on **#R** and **#Radv**.


Tutorial example

Below is an example of a single question table.



Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (21 regrades)
Correctly explained what `getwd()` does.	1	0	The AI estimated that this criterion was not met.	

• Open your PDF in a PDF viewer that allows you to add comments.
• For each criterion, check if your code / answer meets it and award yourself 0 or 1 point.
• After you are done, upload your annotated PDF as a comment to your assignment submission on Canvas.
• We will review your self-grading and adjust it if necessary.


Question: #R1

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The student used getwd()		1	The rubric requires using getwd(); the student's code is exactly getwd(), so the criterion is satisfied.	



Question: #R2


Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The student used setwd()	1	1	Met: The student used setwd(), as required by the rubric criterion 1.	
2. The working directory is set to [any path]/r_course/week_1		0	Not met: The working directory path ends at r_course and does not include the required week_1 subfolder specified in rubric criterion 2.	

Question: #R3


Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The student used list.files()		1	The rubric requires that the student used list.files(); the answer includes a line of code calling list.files() with a directory path.	
2. The student accessed the help page for list.files() (e.g., help(), ?)		1	The rubric requires accessing the help page for list.files() (e.g., help(), ?); the answer uses ?list.files, which meets this criterion.	

Question: #R4




Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The variable hours_sleep exists, is correctly spelled, and equals a numeric value		1	The rubric requires hours_sleep to exist, be correctly spelled, and equal a numeric value; the student defines hours_sleep <- 9, which is numeric and correctly spelled.	
2. The variable sleepiness exists, is correctly spelled, and equals a character value	1	0	The rubric requires sleepiness to exist, be correctly spelled, and equal a character value; the student defines sleepiness <- 2, which is numeric, not a character/string.	

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
3. The explanation correctly reflects whether and why the two variables cannot be added, based on their code	1	0	The rubric requires an explanation that correctly reflects whether and why the two variables cannot be added based on their code; in the student's code both variables are numeric, so they can be added, but the explanation incorrectly references them as integers without addressing the original intent about character vs numeric types.	


Question: #R5

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The student explained that the first line clears the workspace and the second line adds new variables		1	The student states that rm(list = ls()) removes objects from the environment (clears the workspace) and that the second line assigns value 1 to new objects, thus explaining that the first line clears and the second line adds new variables, as required by the rubric.	
2. The student explained that five (5) objects are added to the workspace		1	The student explicitly explains that the second line assigns the value 1 to 5 new objects, which matches the rubric requirement that five objects are added to the workspace.	



Question: #R6

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The variable interview is created, correctly spelled, and contains a string		0	The rubric requires a correctly spelled interview variable containing a string; no such variable or string assignment is present in the submission.	
2. The print() function is used		0	The rubric requires use of the print() function; the submission does not include any call to print().	
3. The gsub() function is used		0	The rubric requires use of the gsub() function; the submission does not include any use of gsub().	



Question: #R7

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The vector elements are exactly 2, FALSE, -1.243, "test" in that order		1	The student created a vector using c(2, FALSE, -1.243, "test") which matches the required elements and order per the rubric.	
2. The student explained that all values were coerced to character type		1	The student commented "##all character variables", correctly explaining that all values were coerced to character type as required by the rubric.	


Question: #R8

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The first line of code is unchanged and correct		1	Rubric 1: The first line `participant_ages <- c(21,26,27,19,49,NA)` is unchanged and correct.	
2. The student explained why the result is NA		1	Rubric 2: The student explains that NA is not a numerical value and breaks mean()'s ability to compute the mean, which correctly addresses why the result is NA.	
3. The mean is correctly computed using na.rm = TRUE or equivalent		1	Rubric 3: The mean is computed as `mean(participant_ages, na.rm = TRUE)`, correctly using na.rm = TRUE to remove the missing value.	



Question: #R9

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The fortunes package is correctly referenced		1	The student installs and loads the fortunes package using install.packages("fortunes") and library(fortunes), correctly referencing the package as required by the rubric.	
2. fortune() is called with a valid month	1- 12 represents december and thats how i got the function to work	0	The rubric requires fortune() to be called with a valid month (birth-month); the student uses fortune(which = 12), which is an index, not a month value, so this does not satisfy the requirement.	


Question: #R10

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The student mentioned that division by zero is not possible	1	0	The student only said that a mathematical argument is being performed on a logical operator and did not mention division by zero or that division by zero is not possible, as required by the rubric.	


Question: #R11

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. A vector with exactly 100 elements is created		1	The rubric requires a vector with exactly 100 elements; `sample(1:100, size = 100)` creates a vector of length 100.	
2. The vector is correctly sorted		1	The rubric requires the vector to be correctly sorted; `sort(..., decreasing = FALSE)` sorts the vector in ascending order.	
3. Indexing is correctly used to extract the 1st, 20th, and 80th elements		1	The rubric requires indexing to extract the 1st, 20th, and 80th elements; `grades[c(1,20,80)]` correctly returns those positions.	



Question: #R12

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The alphabet is generated using built-in variables (letters or LETTERS)		1	The student uses the built-in variable `letters` to represent the alphabet, which satisfies the rubric requirement of using `letters` or `LETTERS`.	
2. The code reports the number of letters in the alphabet		1	The student correctly uses `length(letters)` to report the number of letters in the alphabet, meeting the rubric requirement to report the number of letters.	


Question: #R13

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The correct code line (letters2 == letters) is removed		1	The student removed the line containing 'letters2 == letters', which is the correct line to remove per the rubric.	


Question: #R14

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. A base R function is used to replace " ." with "a"		1	The student uses gsub(), a base R function, to replace '.' with 'a', satisfying the requirement to use a base R function for the replacement.	
2. No more than three lines of code are added below `fruits <- c("b.n.n.s",".pples")`	1	0	The student does not keep the provided fruits vector as given and adds code in more than one line, violating the instruction that no more than three lines of code be added below the specified fruits assignment line.	



Question: #R15

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The student attempted to change the datatype of horrible_numbers		1	The rubric requires an attempt to change the datatype of horrible_numbers; the student uses as.character() and as.numeric() on horrible_numbers to convert it from factor to numeric.	
2. mean(as.numeric(as.character(horrible_numbers)), na.rm = TRUE) or another valid solution is used to obtain a mean of 9.713864 (rounding allowed)		1	The rubric specifies using mean(as.numeric(as.character(horrible_numbers)), na.rm = TRUE) or another valid solution to get a mean of about 9.713864; the student uses exactly this expression and comments the correct mean value.	



Question: #R16

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The character variables birthday is defined, in the correct format, and without typos		1	The variable `birthday` is defined as a character string "15102001" in DDMMYYYY format, matching the rubric requirement for a correctly formatted character variable.	
2. The individual digits are not re-entered manually after birthday is defined		1	The digits are obtained via `strsplit(birthday, "")`, and not manually re-entered; this aligns with the rubric requirement to avoid retyping the digits.	
3. The correct formula is applied		1	The student converts the split characters to numeric and uses `sum(as.numeric(sep_bday[[1]]))`, correctly applying the formula of summing all digits of the birthday.	


Question: #R17


Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The first 50 odd positive integers are correctly generated		1	The vector oddintegers <- seq(1,100,2) correctly generates the first 50 odd positive integers from 1 to 99, meeting rubric 1.	
2. Values are generated programmatically (not manually typed)		1	The odd integers are generated using seq(), a programmatic method, rather than manually typing values, satisfying rubric 2.	
3. prod() or an equivalent method is used		1	The student uses prod(oddintegers) to compute the product, which matches the requirement of using prod() or an equivalent, meeting rubric 3.	

Question: #R18


Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. set.seed() is used effectively		1	set.seed(1500) is called at the start, ensuring reproducibility as required by the rubric.	
2. The number of rows and columns is random		1	Rows and columns are determined by sample(random, 1) for each dimension, making both counts random per the rubric.	
3. The matrix is initialized without specifying data (which automatically uses the default data=NA) or filled with NAs manually		1	matrix() is called with nrow, ncol, and a single NA argument, effectively initializing/filling the matrix with NAs as allowed by the rubric.	
4. dim() or a single-function equivalent is used		1	dim(mat) is used to show the dimensions of the generated matrix, satisfying the requirement to use dim() or an equivalent single function.	

Question: #R19


Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The correct code line is identified (line 3; `EEGData3 <- matrix(runif(n_subjects*n_vars), n_vars, n_subjects)`)		1	The student correctly identified EEGData3 <- matrix(runif(n_subjects*n_vars), n_vars, n_subjects) as incorrect, noting it produces 201 rows and 1325 columns instead of 1325 rows and 201 columns, matching the rubric.	

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
2. The student explained why argument order matters		1	The student explicitly stated that 'The order that objects are loaded into arguments matters!!', directly addressing why argument order matters in R as required by the rubric.	




Question: #R20

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. colSums(), rowSums(), or an equivalent solution is used		1	The student uses rowSums(M), which is explicitly listed in the rubric as an acceptable equivalent solution to compute the number of correct responses per participant.	



Question: #R21

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. A 2×2×2 array is created		1	The code uses array() with dim = c(2,2,2), which matches the required 2×2×2 array per the rubric.	
2. dimnames (which might differ from task) are assigned for rows, columns, and slices		1	dimnames is provided as a list of three character vectors, correctly assigning names for rows, columns, and slices as required by the rubric.	


Question: #R22

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The initial matrix code is unchanged and correct		1	The initial matrix creation, rownames, and colnames code remains unchanged and matches the correct provided code per the rubric.	
2. Position-based indexing (e.g., `relationship_matrix[3, 2]`) is used to replace an NA		1	Position-based indexing `relationship_matrix[3,2] <- "L"` is used to replace the NA entry for Ron and Hermione, satisfying the rubric requirement.	
3. Name-based indexing (e.g., `relationship_matrix["Snape", "Harry"]`) is used to replace an NA		1	Name-based indexing `relationship_matrix[["Snape", "Harry"]] <- "H"` is used to replace the NA entry for Snape and Harry, fulfilling the rubric criterion.	




Question: #R23

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. No more than two lines of code are added or edited below `colnames(relationship_matrix) <- c("Harry", "Hermione", "Ron", "Draco", "Snape")`		1	The student edited only the last two lines after the colnames assignment, satisfying the rubric requirement of no more than two lines of code added or edited.	
2. Diagonal elements are set to NA using diag() or equivalent solution		1	The student correctly set the diagonal elements to NA by assigning to diag(relationship_matrix), which matches the rubric requirement to use diag() or an equivalent solution.	




Question: #R24

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. rep() is used		1	The student constructs the vector using multiple calls to rep(), which satisfies the rubric requirement that rep() is used.	
2. The resulting vector is exactly "a","a","b","b","c","c","d","d" or "a","a","b","b","c","c","d","d","e","e" (length 8 or 10)		1	Evaluating c(rep("a",2), rep("b",2), rep("c",2), rep("d",2)) yields the vector "a","a","b","b","c","c","d","d" of length 8, which matches one of the rubric's accepted outputs.	


Question: #R25

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. First_appearance values are correct (ignoring minor typos) and generated with a shortcut		1	First_appearance correctly has 3 'The Hobbit' followed by 3 'LOTR' and is generated using rep(), satisfying the shortcut requirement.	
2. Morality values are correct (ignoring minor typos) and generated with a shortcut	1— got it to alternate but accidentally put Good first	0	Morality values are generated with rep(), but the sequence alternates Good/Bad and does not match the rubric table (Bad, Good, Bad, Good, Bad, Good).	
3. Dating_appeal values are correct (ignoring minor typos) and generated with seq() or equivalent		1	Dating_appeal is correctly generated as 0,2,4,6,8,10 using seq(), matching the rubric values and using the required shortcut.	
4. A dataframe with 4 columns and 6 rows is created		1	The data.frame LOTR is created with 4 columns (Name, First_appearance, Morality, Dating_appeal) and 6 rows, as required by the rubric.	



Question: #R26

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. A new column is added to the grades dataframe		1	The student adds a new column to the grades dataframe using `grades$final_grade <- ...`, satisfying the rubric requirement that a new column is added.	
2. The new column is calculated using the correct formula (`0.4 * grades$assignment_average + 0.6 * grades$exam`)		1	The new column is computed with `(.4 * grades$assignment_average) + (.6 * grades$exam)`, which matches the required formula `0.4 * grades$assignment_average + 0.6 * grades$exam` in the rubric.	
3. The column is named final_grade		1	The column is explicitly named `final_grade` with `grades$final_grade <- ...`, matching the rubric requirement for the column name.	
4. No more than two lines of code are added below `names(grades) <- c('student_ID','assignment_average','exam')` ignoring comments		1	Only one additional line of executable code is added after `names(grades) <- c('student_ID','assignment_average','exam')`, which is within the rubric limit of no more than two lines of code ignoring comments.	



Question: #R27

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. InsectSprays is saved as a CSV file		1	According to the rubric, InsectSprays must be saved as a CSV file. The code uses write.csv(InsectSprays, ..., " spray.csv") which correctly exports InsectSprays to a CSV file.	
2. Rownames are removed		1	The rubric requires that row names are removed. The code specifies row.names = FALSE in write.csv, which prevents row names from being written to the file.	


Question: #R28

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The dataset is read directly from a URL		1	The dataset is read using read.csv with the provided URL, satisfying the rubric requirement to read directly from a URL.	
2. At least two filtering steps are carried out on the rows	1- I was told in practical that using dyplr was acceptable	0	Only one filtering operation is performed with a single dplyr filter call; the rubric requires at least two filtering steps on the rows.	


Question: #Radv1



Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. A built-in dataset is used		1	The student uses the built-in dataset ' iris', satisfying the rubric requirement of using a built-in dataset.	
2. At least one row is successfully indexed		1	The expression iris[1,] correctly indexes and selects the first row, meeting the rubric criterion for row indexing.	
3. At least one column is successfully indexed		1	The expression iris[,4] correctly indexes and selects the fourth column of the dataset, satisfying the rubric criterion for column indexing.	
4. At least one individual cell is successfully indexed		1	The expression iris[87,1] correctly indexes a specific cell (row 87, column 1), fulfilling the rubric criterion for individual cell indexing.	

Question: #Radv2



Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. A non-native (package) function is used		1	The student uses ggplot(), geom_point(), and ?ggplot which are non-native functions from the ggplot2 package, satisfying the rubric requirement that a non-native package function is used.	
2. A namespace trick such as some_package::some_function() is used instead of library() or require()		1	The student calls ggplot2::ggplot(), explicitly using the package::function() namespace form instead of library() or require(), directly meeting the rubric requirement for a namespace trick.	

Question: #Radv3


Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. A random seed is set		1	The rubric requires a random seed to be set; `set.seed(543)` is used at the start, satisfying reproducibility.	
2. A binary variable is created		1	The rubric requires a binary variable; `friday_night` is sampled from two categories ('Stay in', 'Going out'), creating a binary categorical variable.	


Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
3. A continuous variable is created		1	The rubric requires a continuous variable; `fun_score` is generated using `rnorm`, which produces continuous numeric values.	
4. The variables are combined into a dataframe		1	The rubric requires combining variables into a dataframe; `fridayyy <- data.frame(friday_night, fun_score)` correctly combines them.	
5. The code implies different means of the continuous variable across the two binary groups		1	The rubric requires different means across the two groups; `fun_score` is drawn from normal distributions with means 55 vs 95 depending on group, implying higher average for one group.	

Question: #Radv4


Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. is.na() is used to detect missing values		1	The student uses is.na() within colSums(is.na(airquality)) and is.na(airquality$Ozone) to detect missing values, directly satisfying rubric 1.	
2. Missing values are imputed using any method		1	The code imputes missing Ozone values with mean(airquality$Ozone, na.rm = TRUE), which is a valid imputation method as required by rubric 2.	
3. Comments are included to explain the code		1	A comment is provided explaining the indexing of NAs and mean imputation, and another comment explains checking for NAs, fulfilling rubric 3's requirement for explanatory comments.	

Question: #Radv5



Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. A list with named elements is created	1 - the list is assigned a name. Unclear what "named elements" should mean here?	0	The rubric requires a list with named elements; the student created `listlove <- list("hello", 8, FALSE, as.numeric("1400"), 2*8)` but did not provide names for the elements, so the list is not named.	
2. A comment explains why a list is appropriate		1	The rubric requires a comment explaining why a list is appropriate; the student included a comment stating that the list allows character, numerical, logical elements, functions and expressions together, which explains appropriateness.	

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
3. The explanation justifies the use of a list over a vector or dataframe		1	The rubric requires the explanation to justify using a list over a vector or dataframe; the student explicitly contrasts a list with forcing elements into one class, which is a property of vectors/dataframes, thus justifying the choice of a list.	



Question: #Radv6

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. A link to a discussion thread is provided		1	The student includes a StackOverflow URL to a discussion thread in an R comment, satisfying the requirement that a link to a discussion thread is provided.	
2. The student explains why the discussion is interesting		1	The student writes a sentence explaining why they find the discussion interesting, directly addressing its relevance to 3D data structures and their course topic.	


Question: #Python1

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. Either as.integer() or as.numeric() is used		0	Rubric 1 requires using either as.integer() or as.numeric(), but the student only repeated the Python code and did not use any R function.	
2. as.integer() is used		0	Rubric 2 specifically requires as.integer(), which is not present in the student's submission.	





Question: #Python2

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. Pandas is installed using pip install pandas or equivalent		0	The student did not provide any bash command; thus pandas is not installed using `pip install pandas` or an equivalent command as required by the rubric.	
2. NumPy is installed using pip install numpy or equivalent		0	The student did not provide any bash command; thus NumPy is not installed using `pip install numpy` or an equivalent command as required by the rubric.	



Question: #Python3

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. import numpy as np appears before the array creation code		0	The student did not add the required import statement; per the rubric, `import numpy as np` must appear before the array creation, but it is absent.	



Question: #Python4

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. A proper copy is created using .copy() or an equivalent solution		0	The student did not use .copy() or any equivalent method; new_array is just assigned to another_array.	
2. Only the intended assignment line is modified		0	The student did not modify any lines of code, including the intended assignment line; the code is unchanged from the prompt.	
3. A comment explains the issue in the original code		0	No comments were added to explain the issue in the original code.	
4. A comment explains a relevant difference between R and Python		0	No comments were added and no explanation of differences between R and Python is provided.	



Question: #Python5

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The first line of code is unchanged and correct		1	The first line of code (sample_scores = np.array([1, 6, 7, 8, 9, np.nan])) is unchanged and correct, matching the rubric requirement.	
2. The mean is correctly computed using np.nanmean() or equivalent		0	The student still uses np.mean(sample_scores) and does not compute the mean with the missing value removed via np.nanmean() or equivalent, so the rubric requirement is not satisfied.	




Question: #Python6

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. An array with dimensions 4×3×5 is created		0	The rubric requires creating an array with dimensions 4×3×5, but no code is provided in the answer cell to create any array.	
2. All elements of the array are zero		0	The rubric requires all elements of the array to be zero, but no array is created, so this condition is not satisfied.	

Question: #Python7

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. Filenames in the current directory are retrieved using os.listdir() or equivalent		0	The code cell is empty and does not retrieve filenames from the current directory using os.listdir() or any equivalent method, so this rubric criterion is not satisfied.	
2. The filenames are combined into a single string		0	No code is provided to combine the filenames into a single string; the required single string output is therefore not produced, so this rubric criterion is not satisfied.	

Question: #Python8

Rubrics	Self scoring (enter 0 or 1)	AI score (indicator)	AI 'thought'	AI Consistency (5 regrades)
1. The dictionary and its keys have the requested names		0	The student did not write any actual code to create a dictionary or specify key names, so the dictionary and its keys are not defined as requested in the rubric.	
2. The mood measurements consist of 365 binary values ("happy" / "sad")		0	No list of mood measurements is created; there are no 365 " happy"/"sad" string values, so this requirement from the rubric is not satisfied.	
3. The IQ measurements consist of 52 normally distributed values		0	No IQ measurements list is defined and no normally distributed values are simulated with numpy.random, so the requirement for 52 normally distributed IQ values is not met.	

Dont forget to compute final self scoring grades and enter them on the first page!