

RobotFramework_UDS

v. 0.2.0

Mai Minh Tri

23.02.2026

Contents

1	Introduction	1
2	Description	2
2.1	Overview	2
2.2	UDS Connector (DoIP)	2
2.3	Configuration	2
2.4	Supported UDS Services	2
2.5	Enhancements Usability with ODXTools Integration	2
2.6	Multiple Connections	4
2.7	Examples	5
3	DiagnosticServices.py	11
3.1	Class: DiagnosticServices	11
3.1.1	Method: convert_sub_param	11
3.1.2	Method: convert_request_data_type	11
3.1.3	Method: get_diag_service_by_name	12
3.1.4	Method: get_encoded_request_message	12
3.1.5	Method: get_decode_response_message	12
3.1.6	Method: get_full_positive_response_data	13
3.1.7	Method: get_did_codec	13
3.1.8	Method: get_param_value_base_on_param_type	13
3.2	Class: PDXCodec	13
3.2.1	Method: decode	13
3.2.2	Method: encode	13
3.3	Class: ServiceID	13
4	UDSKeywords.py	14
4.1	Class: UDSDeviceManager	14
4.1.1	Method: is_device_exist	14
4.2	Class: UDSDevice	14
4.3	Class: UDSKeywords	14
4.3.1	Method: connect_uds_connector	14
4.3.2	Method: create_uds_connector	14
4.3.3	Method: load_pdx	15
4.3.4	Method: create_config	16
4.3.5	Method: get_uds_device_config_by_keys	17
4.3.6	Method: update_uds_device_config_by_keys	17
4.3.7	Method: set_config	18

4.3.8	Method: connect	18
4.3.9	Method: disconnect	18
4.3.10	Method: access_timing_parameter	18
4.3.11	Method: clear_diagnostic_information	19
4.3.12	Method: communication_control	19
4.3.13	Method: control_dtc_setting	20
4.3.14	Method: diagnostic_session_control	20
4.3.15	Method: dynamically_define_did	21
4.3.16	Method: ecu_reset	21
4.3.17	Method: io_control	21
4.3.18	Method: link_control	22
4.3.19	Method: read_data_by_identifier	23
4.3.20	Method: read_dtc_information	23
4.3.21	Method: read_memory_by_address	24
4.3.22	Method: request_download	24
4.3.23	Method: request_transfer_exit	24
4.3.24	Method: request_upload	25
4.3.25	Method: routine_control	25
4.3.26	Method: security_access	25
4.3.27	Method: tester_present	26
4.3.28	Method: transfer_data	26
4.3.29	Method: write_data_by_identifier	26
4.3.30	Method: write_memory_by_address	27
4.3.31	Method: request_file_transfer	27
4.3.32	Method: authentication	28
4.3.33	Method: routine_control_by_name	29
4.3.34	Method: read_data_by_name	29
4.3.35	Method: get_encoded_request_message	30
4.3.36	Method: get_decoded_positive_response_message	30
4.3.37	Method: write_data_by_name	30
4.3.38	Method: io_control_by_name	31
4.3.39	Method: send_uds_request_by_name	31
4.3.40	Method: reconnect	32
5	__init__.py	33
6	Appendix	34
7	History	35

Chapter 1

Introduction

The library **RobotFramework-UDS** provides a set of **Robot Framework** keywords for sending UDS (Unified Diagnostic Services) requests and interpreting responses from automotive electronic control units (ECUs).

Whether you're testing diagnostic sessions, reading data, or controlling routines on an ECU, the UDS Library simplifies these tasks by offering specific keywords like `DiagnosticSessionControl` , `ReadDataByIdentifier` , and `RoutineControl` .

These keywords are designed to handle the complexity of UDS communication, enabling you to write efficient and reliable automated tests.

Moreover, you can now refer to UDS services by their readable names rather than hexadecimal IDs e.g `ReadDataByName` , `RoutineControlByName` . It helps to make your tests more intuitive and easier to maintain.

Chapter 2

Description

2.1 Overview

The **RobotFramework-UDS** is designed to interface with automotive ECUs using the UDS protocol over the DoIP (Diagnostic over IP) transport layer. This library abstracts the complexities of UDS communication, allowing users to focus on writing high-level test cases that validate specific diagnostic services and responses.

2.2 UDS Connector (DoIP)

Currently, the library supports the [DoIP](#) (Diagnostic over IP) transport layer, which is commonly used in modern vehicles for diagnostic communication. DoIP allows for faster data transfer rates and easier integration with network-based systems compared to traditional CAN-based diagnostics.

2.3 Configuration

In order to connect and send/receive message properly using the **RobotFramework-UDS** certain configurations must be set up:

- DoIP Configuration: The library requires the IP address and port of the ECU or the gateway through which the ECU is accessed.
- Data Identifiers and Codec: Define the Data Identifiers (DIDs) and corresponding codecs in the library's configuration. This enables correct encoding and decoding of data between the test cases and the ECU.
- Session Management: Some UDS services may require the ECU to be in a specific diagnostic session (e.g., extended diagnostics). The library should be configured to manage these session transitions seamlessly.

2.4 Supported UDS Services

The **RobotFramework-UDS** library supports almost UDS service as defined in [ISO 14229](#), providing comprehensive coverage for ECU diagnostics.

For detailed information on specific services and how to use them, please refer to the next section.

2.5 Enhancements Usability with ODXTools Integration

The **RobotFramework-UDS** library comes with [odxtools](#) fully integrated, allowing you to use readable service names instead of dealing with hex IDs.

You can now specify service names directly in your test cases, making them more readable and user-friendly.

The **RobotFramework-UDS** also supports automatic data type conversion for request parameters, enabling users to provide input values that are seamlessly converted into the correct data types required for UDS requests.

The **RobotFramework-UDS** library supports features such as Routine Control By Name, Read Data By Name, and Write Data By Name, enabling users to send requests to UDS using the service's name instead of its identifier.

The **RobotFramework-UDS** provides a versatile "Send UDS Request By Name" keyword that can send and receive UDS messages without requiring the command type specification (e.g., Read, Write, RoutineControl). This allows users to send requests without needing to know the specific UDS command type associated with a service, as the keyword automatically detects and handles it.

Examples

Send UDS Request By Name

```
Test user can send UDS request without needing to specify the command type
Log    Test user can send UDS request without needing to specify the command type

Log    readCPUClockFrequencies_Read
${service_name_list}=    Create List    readCPUClockFrequencies_Read
${responses}=    Send UDS Request By Name    ${service_name_list}
Log    ${responses}    console=True

FOR    ${request_id}    IN    @{responses.keys()}
Log    Key: ${request_id}, Value: ${responses["${request_id}"]}    console=True
${response}=    Set Variable    ${responses["${request_id}"]}
FOR    ${item}    IN    @{response.keys()}
Log    ${item} : ${response["${item}"]}    console=True
END
END

Log    CAM1PowerSupply_Set
${param_dict_input_output_control}=    Create Dictionary    mode=passiv
${response}=    Send UDS Request By Name    CAM1PowerSupply_Set    ↔
↪ ${param_dict_input_output_control}

Log    ${response}    console=True
FOR    ${item}    IN    @{response.keys()}
Log    ${item} : ${response["${item}"]}    console=True
END

Log    RealTimeClock_Write
${param_dict_write_data_by_name}=    Create Dictionary    Day=26    Month=September    ↔
↪ Year=2024    Hour=10    Second=45    Minute=0
${res}=    Send UDS Request By Name    RealTimeClock_Write    ↔
↪ ${param_dict_write_data_by_name}
Log    ${res}    console=True

Log    Routine Control By Name service: StartIperfServer_Start

${param_dict_routine_control_by_name}=    Create Dictionary    port=5101    ↔
↪ argument=-i 0.5 -B 192.168.1.
${response}=    Send UDS Request By Name    StartIperfServer_Start    ↔
↪ ${param_dict_routine_control_by_name}

Log    ${response}    console=True
FOR    ${item}    IN    @{response.keys()}
Log    ${item} : ${response["${item}"]}    console=True
END
```

Routine Control By Name

```
Test user can use Routine Control By Name service on ECU
Log    Routine Control By Name service: StartIperfServer_Start

${param_dict}=    Create Dictionary    port=5101    argument=-i 0.5 -B 192.168.1.
${response}=    Routine Control By Name    StartIperfServer_Start    ${param_dict}

Log    ${response}    console=True
FOR    ${item}    IN    @{response.keys()}
Log    ${item} : ${response["${item}"]}    console=True
END
```

Read Data By Name

```

Test user can use Read Data By Name service on ECU
Log    Use Read Data By Name service

Log    Use Read Data By Identifier - 25392

${list_identifiers}=    Create List    0x6330
${res}=    Read Data By Identifier    ${list_identifiers}
Log    ${res}    console=True
Log    ${res[0x6330]}    console=True

Log    readCPUClockFrequencies_Read

${service_name_list}=    Create List    readCPUClockFrequencies_Read
${responses}=    Read Data By Name    ${service_name_list}
Log    ${responses}    console=True

FOR    ${request_did}    IN    @${responses.keys()}
Log    Key: ${request_did}, Value: ${responses["${request_did}"]}    console=True
${response}=    Set Variable    ${responses["${request_did}"]}
FOR    ${item}    IN    @${response.keys()}
Log    ${item} : ${response["${item}"]}    console=True
END
END

Test Read List Services
${list_read_services}=    Create List    TestManager_SWVersion_Read
...                        CTSSWVersion_Read
...                        CPU_Load_Read

FOR    ${service_name}    IN    @${list_read_services}
Log    Read Data of ${service_name}    console=True
${list_service}=    Create List    ${service_name}
${res}=    Read Data By Name    ${list_service}
Log    ${res}    console=True
END

```

Write Data By Name

```

Test user can use Write Data By Name service on ECU
Log    Write Data By Name service

Log    RealTimeClock_Write
${PARAM_DICT}=    Create Dictionary    Day=26    Month=September    Year=2024    ↔
↔ Hour=10    Second=45    Minute=0
${res}=    Write Data By Name    RealTimeClock_Write    ${PARAM_DICT}
Log    ${res}    console=True

${DICT}=    Create Dictionary    ipAddress=155
${res}=    Write Data By Name    CTS_IPAddress_Write    ${DICT}
Log    ${res}    console=True

Log    Using service did instead service's name
${res}=    Write Data By Identifier    25382    ${PARAM_DICT}
Log    ${res}    console=True

```

2.6 Multiple Connections

The **RobotFramework-UDS** can be extended to manage multiple connections simultaneously. This is beneficial when working with complex vehicle systems or simultaneously testing multiple ECUs.

2.7 Examples

Single Connection

```

*** Settings ***
Library      RobotFramework_TestsuitesManagement    AS    testsuites
Library      RobotFramework_UDS

*** Variables ***
${SUT_IP_ADDRESS}=          SUT_IP_ADDRESS
${SUT_LOGICAL_ADDRESS}=     SUT_LOGICAL_ADDRESS
${TB_IP_ADDRESS}=           TB_IP_ADDRESS
${TB_LOGICAL_ADDRESS}=      TB_LOGICAL_ADDRESS
${ACTIVATION_TYPE}=         0
${DEVICE_NAME_1}=           UDS Connector 1
${FILE_1}=                  path/file.pdx
${VARIANT_1}=               variant

*** Test Cases ***
Test user can connect single UDS connection
    Log        Test user can connect single UDS connection
    Log        If no device_name is provided, it will default to 'default'

    Create UDS Connector    ecu_ip_address= ${SUT_IP_ADDRESS_1}
    ...                    ecu_logical_address= ${SUT_LOGICAL_ADDRESS_1}
    ...                    client_ip_address= ${TB_IP_ADDRESS_1}
    ...                    client_logical_address= ${TB_LOGICAL_ADDRESS_1}
    ...                    activation_type= ${ACTIVATION_TYPE_1}

    Connect UDS Connector
    Open UDS Connection
    Load PDX      ${FILE_1}      ${VARIANT_1}
    ${service_name_list}=    Create List    readCPUClockFrequencies_Read
    Read Data By Name    ${service_name_list}
    Close UDS Connection

```

Multiple Connections

```

*** Variables ***
${SUT_IP_ADDRESS_1}=          SUT_IP_ADDRESS_1
${SUT_LOGICAL_ADDRESS_1}=     SUT_LOGICAL_ADDRESS_1
${TB_IP_ADDRESS_1}=           TB_IP_ADDRESS_1
${TB_LOGICAL_ADDRESS_1}=      TB_LOGICAL_ADDRESS_1
${ACTIVATION_TYPE_1}=         0
${DEVICE_NAME_1}=             UDS Connector 1
${FILE_1}=                    path/file_1.pdx
${VARIANT_1}=                 VARIANT_1

${SUT_IP_ADDRESS_2}=          SUT_IP_ADDRESS_2
${SUT_LOGICAL_ADDRESS_2}=     SUT_LOGICAL_ADDRESS_2
${TB_IP_ADDRESS_2}=           TB_IP_ADDRESS_2
${TB_LOGICAL_ADDRESS_2}=      TB_LOGICAL_ADDRESS_2
${ACTIVATION_TYPE_2}=         0
${DEVICE_NAME_2}=             UDS Connector 2
${FILE_2}=                    path/file_2.pdx
${VARIANT_2}=                 VARIANT_2

${ERROR_STR}=    NegativeResponseException: ReadDataByIdentifier service execution ↵
    ↵ returned a negative response IncorrectMessageLengthOrInvalidFormat (0x13)

*** Test Cases ***
Test user can connect multiple UDS connection
    Log        Test user can connect multiple UDS connection
    Log        Connect to device 1
    Create UDS Connector    device_name= ${DEVICE_NAME_1}
    ...                    ecu_ip_address= ${SUT_IP_ADDRESS_1}
    ...                    ecu_logical_address= ${SUT_LOGICAL_ADDRESS_1}
    ...                    client_ip_address= ${TB_IP_ADDRESS_1}

```



```

...                client_logical_address= ${TB_LOGICAL_ADDRESS_1}
...                activation_type= ${ACTIVATION_TYPE_1}
Connect UDS Connector device_name= ${DEVICE_NAME_1}

Open UDS Connection device_name= ${DEVICE_NAME_1}
Load PDX    ${FILE_1}    ${VARIANT_1}    device_name= ${DEVICE_NAME_1}
${service_name_list_1}= Create List    readCPUClockFrequencies_Read
Read Data By Name    ${service_name_list_1}    device_name= ${DEVICE_NAME_1}

Log    Connect to device 2
Create UDS Connector    device_name= ${DEVICE_NAME_2}
...                ecu_ip_address= ${SUT_IP_ADDRESS_2}
...                ecu_logical_address= ${SUT_LOGICAL_ADDRESS_2}
...                client_ip_address= ${TB_IP_ADDRESS_2}
...                client_logical_address= ${TB_LOGICAL_ADDRESS_2}
...                activation_type= ${ACTIVATION_TYPE_2}
Connect UDS Connector    device_name= ${DEVICE_NAME_2}

Open UDS Connection    device_name= ${DEVICE_NAME_2}
Load PDX    ${FILE_2}    ${VARIANT_2}    device_name= ${DEVICE_NAME_2}
${service_name_list_2}= Create List    CPULoad_Read
Log    Expected device 2 cannot send readCPUClockFrequencies_Read service like ↩
↪ device 1
Run Keyword And Expect Error    ${ERROR_STR}    Read Data By Name    ↩
↪ ${service_name_list_1}    device_name= ${DEVICE_NAME_2}

Read Data By Name    ${service_name_list_2}    device_name= ${DEVICE_NAME_2}

Test user can connect multiple UDS connection but connect to the same ECU
Log    Test user can connect multiple UDS connection
Log    Connect to device 1
Create UDS Connector    device_name= ${DEVICE_NAME_1}
...                ecu_ip_address= ${SUT_IP_ADDRESS_1}
...                ecu_logical_address= ${SUT_LOGICAL_ADDRESS_1}
...                client_ip_address= ${TB_IP_ADDRESS_1}
...                client_logical_address= ${TB_LOGICAL_ADDRESS_1}
...                activation_type= ${ACTIVATION_TYPE_1}
Connect UDS Connector    device_name= ${DEVICE_NAME_1}

Log    Open uds connection
Open UDS Connection    device_name= ${DEVICE_NAME_1}
Load PDX    ${FILE_1}    ${VARIANT_1}    device_name= ${DEVICE_NAME_1}
${service_name_list_1}= Create List    readCPUClockFrequencies_Read
Read Data By Name    ${service_name_list_1}    device_name= ${DEVICE_NAME_1}

Log    Connect to device 2 but same IP as device 1
Log    The expected test case result in an error
Run Keyword And Expect Error    TimeoutError: ECU failed to respond in time    ↩
↪ Create UDS Connector    device_name= ${DEVICE_NAME_2}
...                ↩
↪                ecu_ip_address= ${SUT_IP_ADDRESS_1}                ↩
...                ↩
↪                ecu_logical_address= ${SUT_LOGICAL_ADDRESS_1}        ↩
...                ↩
↪                client_ip_address= ${TB_IP_ADDRESS_1}                ↩
...                ↩
↪                client_logical_address= ${TB_LOGICAL_ADDRESS_1}        ↩
...                ↩
↪                activation_type= ${ACTIVATION_TYPE_1}                ↩

Test users can reconnect to the closed ECU
Log    Connect to device 2
Create UDS Connector    device_name= ${DEVICE_NAME_2}
...                ecu_ip_address= ${SUT_IP_ADDRESS_2}
...                ecu_logical_address= ${SUT_LOGICAL_ADDRESS_2}
...                client_ip_address= ${TB_IP_ADDRESS_2}
...                client_logical_address= ${TB_LOGICAL_ADDRESS_2}
...                activation_type= ${ACTIVATION_TYPE_1}

```

```

Connect UDS Connector      device_name= ${DEVICE_NAME_2}

Open UDS Connection      device_name= ${DEVICE_NAME_2}
Load PDX      ${FILE_2}      ${VARIANT_2}      device_name= ${DEVICE_NAME_2}
${service_name_list_2}=    Create List      CPULoad_Read
Read Data By Name      ${service_name_list_2}      device_name= ${DEVICE_NAME_2}
Close UDS Connection      device_name= ${DEVICE_NAME_2}

Log      Connect to device 1
Create UDS Connector      device_name= ${DEVICE_NAME_1}
...      ecu_ip_address= ${SUT_IP_ADDRESS_1}
...      ecu_logical_address= ${SUT_LOGICAL_ADDRESS_1}
...      client_ip_address= ${TB_IP_ADDRESS_1}
...      client_logical_address= ${TB_LOGICAL_ADDRESS_1}
...      activation_type= ${ACTIVATION_TYPE_1}
Connect UDS Connector      device_name= ${DEVICE_NAME_1}

Open UDS Connection      device_name= ${DEVICE_NAME_1}
Load PDX      ${FILE_1}      ${VARIANT_1}      device_name= ${DEVICE_NAME_1}
${service_name_list_1}=    Create List      readCPUClockFrequencies_Read
Read Data By Name      ${service_name_list_1}      device_name= ${DEVICE_NAME_1}
Close UDS Connection      device_name= ${DEVICE_NAME_1}

Log      Re-open uds connection device 2
Open UDS Connection      device_name= ${DEVICE_NAME_2}
Read Data By Name      ${service_name_list_2}      device_name= ${DEVICE_NAME_2}

Log      Expected device 2 cannot send readCPUClockFrequencies_Read service like ↔
↔ device 1
Run Keyword And Expect Error      ${ERROR_STR}      Read Data By Name      ↔
↔ ${service_name_list_1}      device_name= ${DEVICE_NAME_2}
Close UDS Connection      device_name= ${DEVICE_NAME_2}

```

Routine Control By Name

```

Test user can use Routine Control By Name service on ECU
Log      Routine Control By Name service: StartIperfServer_Start

${param_dict}=    Create Dictionary      port=5101      argument=-i 0.5 -B 192.168.1.
${response}=      Routine Control By Name      StartIperfServer_Start      ${param_dict}

Log      ${response}      console=True
FOR      ${item}      IN      @${response.keys()}
    Log      ${item} : ${response["${item}"]}      console=True
END

Test user can use Routine Control By Name service if service have sub-service on ECU
Log      Routine Control By Name service: Routine_Control_Start, sub-service: ↔
↔ StartIperfServer_Start

${param_dict}=    Create Dictionary      port=5101      argument=-i 0.5 -B 192.168.1.
${response}=      Routine Control By Name      Routine_Control_Start      ${param_dict}      ↔
↔ sub_service=StartIperfServer

Log      ${response}      console=True
FOR      ${item}      IN      @${response.keys()}
    Log      ${item} : ${response["${item}"]}      console=True
END

```

Input Output Control By Name

```

Test user can use Input Output Control By Name service on ECU
Log      Input Output Control By Name service: CAM1PowerSupply_Set

${param_dict}=    Create Dictionary      mode=passiv
${response}=      Input Output Control By Name      CAM1PowerSupply_Set      ${param_dict}

```

```

Log      ${response}      console=True
FOR      ${item}      IN      @{response.keys()}
    Log      ${item} : ${response["${item}"]}      console=True
END

```

Test user can use Input Output Control By Name service if the service has sub-service on ECU

```

Log      Input Output Control By Name service: IOControl_Control, sub_service: ↵
↵ internalFan_PWM
${param_dict}=      Create Dictionary      pwm=10
${response}=      Input Output Control By Name      IOControl_Control      ${param_dict}      ↵
↵ sub_service=internalFan_PWM

```

```

Log      ${response}      console=True
FOR      ${item}      IN      @{response.keys()}
    Log      ${item} : ${response["${item}"]}      console=True
END

```

Read Data By Name

Test user can use Read Data By Name service on ECU

```

Log      Use Read Data By Name service

```

```

Log      Use Read Data By Identifier - 25392

```

```

${list_identifiers}=      Create List      0x6330
${res}=      Read Data By Identifier      ${list_identifiers}
Log      ${res}      console=True
Log      ${res[0x6330]}      console=True

```

```

Log      readCPUClockFrequencies_Read

```

```

${service_name_list}=      Create List      readCPUClockFrequencies_Read
${responses}=      Read Data By Name      ${service_name_list}
Log      ${responses}      console=True

```

```

FOR      ${request_id}      IN      @{responses.keys()}
    Log      Key: ${request_id}, Value: ${responses["${request_id}"]}      console=True
    ${response}=      Set Variable      ${responses["${request_id}"]}
    FOR      ${item}      IN      @{response.keys()}
        Log      ${item} : ${response["${item}"]}      console=True
    END
END

```

Test Read List Services

```

${list_read_services}=      Create List      TestManager_SWVersion_Read
...                          CTSSWVersion_Read
...                          CPULoad_Read

```

```

FOR      ${service_name}      IN      @{list_read_services}
    Log      Read Data of ${service_name}      console=True
    ${list_service}=      Create List      ${service_name}
    ${res}=      Read Data By Name      ${list_service}
    Log      ${res}      console=True
END

```

Test user can use Read Data By Name service if the services have sub-service on ECU

```

${list_read}=      Create List      Identification_Read
${sub_service}=      Create List      CTSSWVersion
${dict_sub_service}=      Create Dictionary      Identification_Read=${sub_service}

${responses}=      Read Data By Name      ${list_read}      parameters=${dict_sub_service}

Log      ${responses}      console=True

FOR      ${request_id}      IN      @{responses.keys()}
    Log      Key: ${request_id}, Value: ${responses["${request_id}"]}      console=True
    ${response}=      Set Variable      ${responses["${request_id}"]}
    FOR      ${item}      IN      @{response.keys()}

```

```

        Log    ${item} : ${response["${item}"]}    console=True
    END
END

Append To List    ${list_read}    readCPUClockFrequency_Read    ↵
↪ Temperature_Sensor_17_Read

${responses}=    Read Data By Name    ${list_read}    parameters=${dict_sub_service}

Log    ${responses}    console=True

FOR    ${request_id}    IN    @({responses.keys()})
    Log    Key: ${request_id}, Value: ${responses["${request_id}"]}    console=True
    ${response}=    Set Variable    ${responses["${request_id}"]}
    FOR    ${item}    IN    @({response.keys()})
        Log    ${item} : ${response["${item}"]}    console=True
    END
END

${read}=    Create List    readCPUClockFrequency_Read    Identification_Read
${s_service}=    Create List    CTSSWVersion
${dict_sub_service}=    Create Dictionary    Identification_Read=${s_service}
${responses}=    Read Data By Name    ${read}    parameters=${dict_sub_service}

Log    ${responses}    console=True

FOR    ${request_id}    IN    @({responses.keys()})
    Log    Key: ${request_id}, Value: ${responses["${request_id}"]}    console=True
    ${response}=    Set Variable    ${responses["${request_id}"]}
    FOR    ${item}    IN    @({response.keys()})
        Log    ${item} : ${response["${item}"]}    console=True
    END
END
END

```

Write Data By Name

```

Test user can use Write Data By Name service on ECU
Log    Write Data By Name service

Log    RealTimeClock_Write
${PARAM_DICT}=    Create Dictionary    Day=26    Month=September    Year=2024    ↵
↪ Hour=10    Second=45    Minute=0
${res}=    Write Data By Name    RealTimeClock_Write    ${PARAM_DICT}
Log    ${res}    console=True

${DICT}=    Create Dictionary    ipAddress=155
${res}=    Write Data By Name    CTS_IPAddress_Write    ${DICT}
Log    ${res}    console=True

Log    Using service did instead service's name
${res}=    Write Data By Identifier    25382    ${PARAM_DICT}
Log    ${res}    console=True

```

Get Encoded Request Message

```

Test Get Encoded Request Message - Simple request parameters
Log    Test Get Encoded Request Message - mainCPUSTressTest_Start
${service_name}=    Set Variable    mainCPUSTressTest_Start
${param_dict}=    Create Dictionary    cores=5    load=50
${res}=    Get Encoded Request Message    ${service_name}    ${param_dict}
Log    ${res}    console=True
Log    ${res.hex()}    console=True

Test Get Encoded Request Message - Complex request parameters
Load PDX    ↵
↪ C:/Users/MAR3HC/Desktop/UDS/robotframework-uds/test/pdx/XTS_MPCI_MaaS_1.23.45.pdx    ↵
↪ XTS_MPCI_MaaS

```

```

Log      Test Get Encoded Request Message - CAN_MasterSlaveEnduranceRun_Start
${service_name}=    Set Variable      CAN_MasterSlaveEnduranceRun_Start
${res}=    Get Encoded Request Message    ${service_name}    ${canConfig}
Log    ${res}    console=True
Log    ${res.hex()}    console=True

```

Get Decoded Request Message

```

Test Get Decoded Response Message
Log      Test Get Decoded Response Message
${service_name}=    Set Variable      StartIperfServer_Start
${response_str}=    Set Variable      \x012#\x00\x00\x18\x05H
${response_byte}=    Convert To Bytes    ${response_str}
${res}=    Get Decoded Response Message    ${service_name}    ${response_byte}
Log    ${res}    console=True

```

Send UDS Request By Name

```

Test user can send UDS request without needing to specify the command type
Log      Test user can send UDS request without needing to specify the command type

Log      readCPUClockFrequencies_Read
${service_name_list}=    Create List      readCPUClockFrequencies_Read
${responses}=    Send UDS Request By Name    ${service_name_list}
Log    ${responses}    console=True

FOR      ${request_id}    IN    @{responses.keys()}
Log      Key: ${request_id}, Value: ${responses["${request_id}"]}    console=True
${response}=    Set Variable    ${responses["${request_id}"]}
FOR      ${item}    IN    @{response.keys()}
Log      ${item} : ${response["${item}"]}    console=True
END
END

Log      CAM1PowerSupply_Set
${param_dict_input_output_control}=    Create Dictionary    mode=passiv
${response}=    Send UDS Request By Name    CAM1PowerSupply_Set    ↩
↪ ${param_dict_input_output_control}

Log    ${response}    console=True
FOR    ${item}    IN    @{response.keys()}
Log    ${item} : ${response["${item}"]}    console=True
END

Log      RealTimeClock_Write
${param_dict_write_data_by_name}=    Create Dictionary    Day=26    Month=September    ↩
↪ Year=2024    Hour=10    Second=45    Minute=0
${res}=    Send UDS Request By Name    RealTimeClock_Write    ↩
↪ ${param_dict_write_data_by_name}
Log    ${res}    console=True

Log      Routine Control By Name service: StartIperfServer_Start

${param_dict_routine_control_by_name}=    Create Dictionary    port=5101    ↩
↪ argument=-i 0.5 -B 192.168.1.
${response}=    Send UDS Request By Name    StartIperfServer_Start    ↩
↪ ${param_dict_routine_control_by_name}

Log    ${response}    console=True
FOR    ${item}    IN    @{response.keys()}
Log    ${item} : ${response["${item}"]}    console=True
END

```

Chapter 3

DiagnosticServices.py

3.1 Class: DiagnosticServices

3.1.1 Method: convert_sub_param

Recursive convert sub parameters in given request to correct data type

Arguments:

- `odx_param`
/ *Condition*: required / *Type*: object /
The ODX parameters.
- `req_sub_param`
/ *Condition*: required / *Type*: dict /
The dictionary of request parameter.

Returns:

- `req_sub_param`
/ *Type*: dict /
The dictionary of request parameters with the correct data types.

3.1.2 Method: convert_request_data_type

Convert given request parameters (dictionary) to correct data type

Arguments:

- `service`
/ *Condition*: required / *Type*: object /
The diagnostic service.
- `parameter_dict`
/ *Condition*: required / *Type*: dict /
The dictionary of request parameter.

Returns:

- `parameter_dict`
/ *Type*: dict /
The dictionary of request parameters with the correct data types.

3.1.3 Method: get_diag_service_by_name

Retrieve the list of diagnostic services from a PDX file using a specified list of service names.

Arguments:

- service_name_list
/ *Condition*: required / *Type*: list /
The list of service names

Returns:

- diag_service_list
/ *Type*: list /
The list of diagnostic services from a PDX file.

3.1.4 Method: get_encoded_request_message

Retrieve the encode request message from parameters dictionary.

Arguments:

- service_name
/ *Condition*: required / *Type*: str /
The service's names
- parameter_dict
/ *Condition*: required / *Type*: dict /
The dictionary of request parameter.

Returns:

- encode_message
/ *Type*: bytes /
The encoded message.

3.1.5 Method: get_decode_response_message

Retrieve the encode request message from parameters dictionary.

Arguments:

- service_name
/ *Condition*: required / *Type*: str /
The service's names
- raw_message
/ *Condition*: required / *Type*: bytes /
The raw message from the response.

Returns:

- decode_message
/ *Type*: bytes /
The decoded message.

3.1.6 Method: get_full_positive_response_data

Retrieve the complete byte data from the response, as the UDS removes the service ID.

Arguments:

- `service_name`
/ *Condition*: required / *Type*: str /
The service's names
- `data`
/ *Condition*: required / *Type*: bytes /
The raw message from the response.

Returns:

- `positive_response_data`
/ *Type*: bytes /
The complete byte data from the response.

3.1.7 Method: get_did_codec

Retrieves a dictionary of DID codecs for a given diagnostic service ID.

Arguments:

- `service_id`
/ *Condition*: required / *Type*: int /
The service's did

Returns:

- `did_codec`
/ *Type*: dict /
A dictionary where the keys are DIDs

3.1.8 Method: get_param_value_base_on_param_type

3.2 Class: PDXCodec

3.2.1 Method: decode

3.2.2 Method: encode

3.3 Class: ServiceID

Chapter 4

UDSKeywords.py

4.1 Class: UDSDeviceManager

4.1.1 Method: is_device_exist

4.2 Class: UDSDevice

4.3 Class: UDSKeywords

4.3.1 Method: connect_uds_connector

Connects a UDS connector for the specified device.

Arguments:

- `device_name`
/ *Condition*: optional / *Type*: str / *Default*: "default" /
Name of the device to connect to. If the device does not exist, a *ValueError* will be raised.
- `config`
/ *Condition*: optional / *Type*: dict / *Default*: `default_client_config` /
Configuration settings for the UDS client, applied if the device is not already available.
- `close_connection`
/ *Condition*: optional / *Type*: bool / *Default*: False /
Indicates whether to close the connection automatically when done.

Raises:

- `ValueError`
Raised if the specified device does not exist, suggesting the use of "Create UDS Connector" to create a new device.

Returns:

- `None`
No return value. The function initializes or updates the UDS connector for the specified device if not already available.

4.3.2 Method: create_uds_connector

Establishes a connection with an ECU.

Arguments:

- `communication_name`
/ Type: str / Condition: required /
 Specifies the type of communication to establish.
- `ecu_ip_address`
/ Type: str / Condition: required /
 The IP address of the ECU for establishing the connection. Should be a valid IPv4 (e.g., "192.168.1.1") or IPv6 address (e.g., "2001:db8::").
- `ecu_logical_address`
/ Type: any / Condition: required /
 The logical address of the ECU.
- `tcp_port`
/ Type: int / Condition: optional / Default: TCP_DATA_UNSECURED /
 TCP port used for unsecured data communication.
- `udp_port`
/ Type: int / Condition: optional / Default: UDP_DISCOVERY /
 UDP port used for ECU discovery.
- `activation_type`
/ Type: RoutingActivationRequest.ActivationType / Condition: optional / Default: ActivationTypeDefault /
 Specifies the activation type, which can be the default (`ActivationTypeDefault`) or a value based on application-specific settings.
- `protocol_version`
/ Type: int / Condition: optional / Default: 0x02 /
 The version of the protocol used for the connection.
- `client_logical_address`
/ Type: int / Condition: optional / Default: None /
 The logical address this DoIP client will use to identify itself. Per specification, this should be within the range 0x0E00 to 0x0FFF.
- `client_ip_address`
/ Type: str / Condition: optional / Default: None /
 If specified, binds to this IP as the source for UDP and TCP communication. Can be an IPv4 or IPv6 address, matching the type of `ecu_ip_address`.
- `use_secure`
/ Type: Union[bool, ssl.SSLContext] / Condition: optional / Default: False /
 Enables TLS if set to `True`. Uses a default SSL context by default; can be set to a preconfigured SSL context for more control. If enabled, consider changing `tcp_port` to 3496.
- `auto_reconnect_tcp`
/ Type: bool / Condition: optional / Default: False /
 Enables automatic reconnection of TCP sockets if closed by the peer.

4.3.3 Method: `load_pdx`

Load PDX file

Arguments:

- `pdx_file`
/ Type: str /
 PDX file path
- `variant`
/ Type: str /

4.3.4 Method: create_config

Creates a configuration for the UDS connector.

Arguments:

- `exception_on_negative_response : bool`
When set to True, raises a `NegativeResponseException` if the server responds with a negative response. If False, the Response's *positive* property will be set to False.
- `exception_on_invalid_response : bool`
When set to True, raises an `InvalidResponseException` if `interpret_response` encounters an invalid response. If False, the Response's *valid* property will be set to False.
- `exception_on_unexpected_response : bool`
When set to True, raises an `UnexpectedResponseException` if the server returns an unexpected response, such as an unmatched subfunction echo. If False, the Response's *unexpected* property will be set to True.
- `security_algo : Callable[[int, bytes, Any], bytes]`
Security algorithm function for the SecurityAccess service.
Signature: `security_algo(level, seed, params) -> bytes`
 - `level : int` — The requested security level.
 - `seed : bytes` — The seed provided by the server.
 - `params : Any` — Parameters provided by `security_algo_params`.
- `security_algo_params : object or dict`
Parameters passed to the security algorithm specified in `security_algo`.
- `data_identifiers : dict[int, Union[str, DidCodec]]`
A dictionary mapping data identifiers to a codec (string or `DidCodec`) for encoding/decoding values in services like `ReadDataByIdentifier`, `WriteDataByIdentifier`, etc.
- `input_output : dict[int, Union[str, DidCodec, dict]]`
Dictionary mapping IO data identifiers to a codec for `InputOutputControlByIdentifier` service. Supports composite codecs with sub-dictionaries specifying bitmasks.
- `tolerate_zero_padding : bool`
When True, ignores trailing zeros in response data to prevent `InvalidResponseException` if the protocol uses zero-padding.
- `ignore_all_zero_dtc : bool` For `ReadDTCInformation` service, skips DTCs with an ID of 0x000000, useful if the protocol uses zero-padding. See online documentation for further details.
- `server_address_format : int`
Specifies the `MemoryLocation` address format to use when not explicitly provided.
- `server_memorysize_format : int`
Specifies the `MemoryLocation` memory size format to use when not explicitly provided.
- `extended_data_size : dict[int, int]`
Specifies DTC extended data record sizes.

Example:

```
{
    0x123456: 45, # DTC 0x123456 has an extended data size of 45 bytes.
    0x123457: 23 # DTC 0x123457 has an extended data size of 23 bytes.
}
```

- `dtc_snapshot_did_size : int`
Number of bytes for encoding data identifiers in `ReadDTCInformation` (default: 2).

- `standard_version : int`
UDS standard version, valid values are 2006, 2013, or 2020 (default: 2020).
- `request_timeout : float`
Maximum wait time (in seconds) for a response after sending a request. Defaults to 5 seconds. Set to None to wait indefinitely.
- `p2_timeout : float`
Maximum wait time (in seconds) for a first response after sending a request, per ISO 14229-2:2013 (default: 1 second).
- `p2_star_timeout : float`
Maximum wait time (in seconds) after receiving a requestCorrectlyReceived-ResponsePending (0x78) response from the server (default: 5 seconds).
- `use_server_timing : bool`
When True, uses P2 and P2* timing values provided by the server for sessions with 2013 or later standards. Defaults to True.

4.3.5 Method: `get_uds_device_config_by_keys`

Retrieves the UDS device configuration for the specified keys.

Arguments:

- `keys`
/ *Condition*: optional / *Type*: list / A list of configuration keys to retrieve from the UDS device. If no keys are provided, the full configuration will be returned.
- `device_name`
/ *Condition*: optional / *Type*: str / *Default*: "default" / The name of the device for which the configuration should be retrieved.

Returns:

- `configs`
/ *Type*: dict / A dictionary containing the configuration values for the specified keys.

4.3.6 Method: `update_uds_device_config_by_keys`

Updates the UDS device configuration by multiple keys.

Arguments:

- `keys_dict`
/ *Condition*: required / *Type*: dict / A dictionary where keys are configuration keys and values are the new values to set for those keys.
- `device_name`
/ *Condition*: optional / *Type*: str / *Default*: "default" / The name of the device for which the configuration should be updated. If the device does not exist, a *ValueError* will be raised.

Returns:

- No return value. The method updates the configuration of the specified UDS device with the provided key-value pairs.

4.3.7 Method: set_config

This method sets the UDS config.

Arguments:

- `config`
/ *Type*: Configuration /
The configuration to set for the UDS client.
- `device_name`
/ *Condition*: optional / *Type*: str / *Default*: "default" / The name of the device for which the configuration should be set. If the device does not exist, a *ValueError* will be raised.

Returns:

- No return value. The method updates the configuration of the specified UDS device with the provided configuration.

4.3.8 Method: connect

Opens a UDS connection.

Arguments:

- `device_name`
/ *Condition*: optional / *Type*: str / *Default*: "default" / The name of the device for which the configuration should be set. If the device does not exist, a *ValueError* will be raised.

Returns:

- No return value. The method opens the UDS connection for the specified device.

4.3.9 Method: disconnect

Closes a UDS connection.

Arguments:

- No specific arguments for this method.

4.3.10 Method: access_timing_parameter

Sends a generic request for AccessTimingParameter service.

Arguments:

- `access_type`
/ *Condition*: required / *Type*: int /
The service subfunction:
 - readExtendedTimingParameterSet = 1
 - setTimingParametersToDefaultValues = 2
 - readCurrentlyActiveTimingParameters = 3
 - setTimingParametersToGivenValues = 4
- `timing_param_record`
/ *Condition*: optional / *Type*: bytes /
The parameters data. Specific to each ECU.

Returns:

- response
/ *Type*: Response /
The response from the AccessTimingParameter service request.

4.3.11 Method: clear_diagnostic_information

Requests the server to clear its active Diagnostic Trouble Codes.

Arguments:

- group
/ *Type*: int /
The group of DTCs to clear. It may refer to Powertrain DTCs, Chassis DTCs, etc. Values are defined by the ECU manufacturer except for two specific values:
 - 0x000000 : Emissions-related systems
 - 0xFFFFFFFF : All DTCs
- memory_selection
/ *Condition*: optional / *Type*: int /
MemorySelection byte (0-0xFF). This value is user-defined and introduced in the 2020 version of ISO-14229-1. Only added to the request payload when different from None. Default: None.

Returns:

- response
/ *Type*: Response /
The response from the server after attempting to clear the active Diagnostic Trouble Codes.

4.3.12 Method: communication_control

Switches the transmission or reception of certain messages on/off with CommunicationControl service.

Arguments:

- control_type
/ *Condition*: required / *Type*: int /
The action to request such as enabling or disabling some messages. This value can also be ECU manufacturer-specific:
 - enableRxAndTx = 0
 - enableRxAndDisableTx = 1
 - disableRxAndEnableTx = 2
 - disableRxAndTx = 3
 - enableRxAndDisableTxWithEnhancedAddressInformation = 4
 - enableRxAndTxWithEnhancedAddressInformation = 5
- communication_type
/ *Condition*: required / *Type*: CommunicationType<CommunicationType>, bytes, int /
Indicates what section of the network and the type of message that should be affected by the command. Refer to CommunicationType<CommunicationType> for more details. If an *integer* or *bytes* is given, the value will be decoded to create the required CommunicationType<CommunicationType> object.

- `node_id`

/ *Condition*: optional / *Type*: int /

DTC memory identifier (`nodeIdentificationNumber`). This value is user-defined and introduced in the 2013 version of ISO-14229-1. Possible only when control type is `enableRxAndDisableTxWithEnhancedAddressInformation` or `enableRxAndTxWithEnhancedAddressInformation`. Only added to the request payload when different from `None`. Default: `None`.

Returns:

- `response`

/ *Type*: `Response` /

The response from the `CommunicationControl` service request.

4.3.13 Method: `control_dtc_setting`

Controls some settings related to the Diagnostic Trouble Codes by sending a `ControlDTCSetting` service request. It can enable/disable some DTCs or perform some ECU-specific configuration.

Arguments:

- `setting_type`

/ *Condition*: required / *Type*: int /

Allowed values are from 0 to 0x7F:

- `on` = 1
- `off` = 2
- `vehicleManufacturerSpecific` = (0x40, 0x5F) # For logging purposes only.
- `systemSupplierSpecific` = (0x60, 0x7E) # For logging purposes only.

- `data`

/ *Condition*: optional / *Type*: bytes /

Optional additional data sent with the request called *DTCSettingControlOptionRecord*.

Returns:

- `response`

/ *Type*: `Response` /

The response from the `ControlDTCSetting` service request.

4.3.14 Method: `diagnostic_session_control`

Requests the server to change the diagnostic session with a `DiagnosticSessionControl` service request.

Arguments:

- `newsession`

/ *Condition*: required / *Type*: int /

The session to try to switch:

- `defaultSession` = 1
- `programmingSession` = 2
- `extendedDiagnosticSession` = 3
- `safetySystemDiagnosticSession` = 4

Returns:

- `response`

/ *Type*: `Response` /

The response from the `DiagnosticSessionControl` service request.

4.3.15 Method: dynamically_define_did

Defines a dynamically defined DID.

Arguments:

- `did`
/ *Type*: int /
The data identifier to define.
- `did_definition`
/ *Type*: `DynamicDidDefinition<DynamicDidDefinition>` or `MemoryLocation<MemoryLocation>` /
The definition of the DID. Can be defined by source DID or memory address. If a `MemoryLocation<MemoryLocation>` object is given, the definition will automatically be by memory address.

Returns:

- `response`
/ *Type*: `Response` /
The response from the request to define the dynamically defined DID.

4.3.16 Method: ecu_reset

Requests the server to execute a reset sequence through the ECUReset service.

Arguments:

- `reset_type`
/ *Condition*: required / *Type*: int /
The type of reset to perform:
 - `hardReset` = 1
 - `keyOffOnReset` = 2
 - `softReset` = 3
 - `enableRapidPowerShutDown` = 4
 - `disableRapidPowerShutDown` = 5

Returns:

- `response`
/ *Type*: `Response` /
The response from the ECUReset service request.

4.3.17 Method: io_control

Substitutes the value of an input signal or overrides the state of an output by sending an `InputOutputControlByIdentifier` service request.

Arguments:

- `did`
/ *Condition*: required / *Type*: int /
Data identifier to represent the IO.
- `control_param`
/ *Condition*: optional / *Type*: int /
Control parameters:

- returnControlToECU = 0
- resetToDefault = 1
- freezeCurrentState = 2
- shortTermAdjustment = 3

- values

/ Condition: optional / Type: list, dict, IOValues<IOValues> /

Optional values to send to the server. This parameter will be given to `DidCodec<DidCodec>.encode()` method. It can be:

- A list for positional arguments
- A dict for named arguments
- An instance of `IOValues<IOValues>` for mixed arguments

- masks

/ Condition: optional / Type: list, dict, IOMask<IOMask>, bool /

Optional mask record for composite values. The mask definition must be included in `config['input_output']`. It can be:

- A list naming the bit mask to set
- A dict with the mask name as a key and a boolean setting or clearing the mask as the value
- An instance of `IOMask<IOMask>`
- A boolean value to set all masks to the same value.

Returns:

- response

/ Type: dict /

The decoded response data.

4.3.18 Method: link_control

Controls the communication baudrate by sending a LinkControl service request.

Arguments:

- control_type

/ Condition: required / Type: int /

Allowed values are from 0 to 0xFF:

- verifyBaudrateTransitionWithFixedBaudrate = 1
- verifyBaudrateTransitionWithSpecificBaudrate = 2
- transitionBaudrate = 3

- baudrate

/ Condition: required / Type: Baudrate<Baudrate> /

Required baudrate value when `control_type` is either `verifyBaudrateTransitionWithFixedBaudrate` (1) or `verifyBaudrateTransitionWithSpecificBaudrate` (2).

Returns:

- response

/ Type: Response /

The response from the LinkControl service request.

4.3.19 Method: read_data_by_identifier

Requests a value associated with a data identifier (DID) through the ReadDataByIdentifier service.

Arguments:

- `data_id_list`
/ *Type*: int | list[int] /
The list of DIDs to be read.

Returns:

- `response`
/ *Type*: Response /
The response from the ReadDataByIdentifier service request.

4.3.20 Method: read_dtc_information

Performs a ReadDiagnosticInformation service request.

Arguments:

- `subfunction`
/ *Condition*: required / *Type*: int /
The subfunction for the ReadDiagnosticInformation service.
- `status_mask`
/ *Condition*: optional / *Type*: int /
Status mask to filter the diagnostic information.
- `severity_mask`
/ *Condition*: optional / *Type*: int /
Severity mask to filter the diagnostic information.
- `dtc`
/ *Condition*: optional / *Type*: int | Dtc /
The Diagnostic Trouble Code to query. Can be an integer or a Dtc object.
- `snapshot_record_number`
/ *Condition*: optional / *Type*: int /
Snapshot record number to specify the snapshot to read.
- `extended_data_record_number`
/ *Condition*: optional / *Type*: int /
Extended data record number to specify the extended data to read.
- `extended_data_size`
/ *Condition*: optional / *Type*: int /
Size of the extended data to read.
- `memory_selection`
/ *Condition*: optional / *Type*: int /
Memory selection to specify the memory to be accessed.

Returns:

- `response`
/ *Type*: Response /
The response from the ReadDiagnosticInformation service request.

4.3.21 Method: read_memory_by_address

Reads a block of memory from the server by sending a ReadMemoryByAddress service request.

Arguments:

- `memory_location`
/ *Condition*: required / *Type*: MemoryLocation<MemoryLocation> /
The address and the size of the memory block to read.

Returns:

- `response`
/ *Type*: Response /
The response from the ReadMemoryByAddress service request.

4.3.22 Method: request_download

Informs the server that the client wants to initiate a download from the client to the server by sending a RequestDownload service request.

Arguments:

- `memory_location`
/ *Condition*: required / *Type*: MemoryLocation<MemoryLocation> /
The address and size of the memory block to be written.
- `dfi`
/ *Condition*: optional / *Type*: DataFormatIdentifier<DataFormatIdentifier> /
Optional defining the compression and encryption scheme of the data. If not specified, the default value of 00 will be used, specifying no encryption and no compression.

Returns:

- `response`
/ *Type*: Response /
The response from the RequestDownload service request.

4.3.23 Method: request_transfer_exit

Informs the server that the client wants to stop the data transfer by sending a RequestTransferExit service request.

Arguments:

- `data`
/ *Condition*: optional / *Type*: bytes /
Optional additional data to send to the server.

Returns:

- `response`
/ *Type*: Response /
The response from the RequestTransferExit service request.

4.3.24 Method: request_upload

Inform the server that the client wants to initiate an upload from the server to the client by sending a RequestUpload service request.

Arguments:

- `memory_location`
/ Condition: required / Type: MemoryLocation<MemoryLocation> /
 The address and size of the memory block to be written.
- `dfi`
/ Condition: optional / Type: DataFormatIdentifier<DataFormatIdentifier> /
 Optional defining the compression and encryption scheme of the data. If not specified, the default value of 00 will be used, specifying no encryption and no compression.

Returns:

- `response`
/ Type: Response /
 The response from the RequestUpload service request.

4.3.25 Method: routine_control

Sends a generic request for the RoutineControl service.

Arguments:

- `routine_id`
/ Condition: required / Type: int /
 The 16-bit numerical ID of the routine.
- `control_type`
/ Condition: required / Type: int /
 The service subfunction. Valid values are:
 - `startRoutine` = 1
 - `stopRoutine` = 2
 - `requestRoutineResults` = 3
- `data`
/ Condition: optional / Type: bytes /
 Optional additional data to give to the server.

Returns:

- `response`
/ Type: Response /
 The response from the RoutineControl service request.

4.3.26 Method: security_access

Successively calls `request_seed` and `send_key` to unlock a security level with the SecurityAccess service. The key computation is done by calling `config['security_algo']`.

Arguments:

- `level`
/ *Condition*: required / *Type*: int /
The level to unlock. Can be the odd or even variant of it.
- `seed_params`
/ *Condition*: optional / *Type*: bytes /
Optional data to attach to the RequestSeed request (`securityAccessDataRecord`).

Returns:

- `response`
/ *Type*: Response /
The response from the SecurityAccess service request.

4.3.27 Method: tester_present

Sends a TesterPresent request to keep the session active.

Arguments:

- No specific arguments for this method.

Returns:

- `response`
/ *Type*: Response /
The response from the TesterPresent request.

4.3.28 Method: transfer_data

Transfers a block of data to/from the client to/from the server by sending a TransferData service request and returning the server response.

Arguments:

- `sequence_number`
/ *Condition*: required / *Type*: int /
Corresponds to an 8-bit counter that should increment for each new block transferred. Allowed values are from 0 to 0xFF.
- `data`
/ *Condition*: optional / *Type*: bytes /
Optional additional data to send to the server.

Returns:

- `response`
/ *Type*: Response /
The response from the TransferData service request.

4.3.29 Method: write_data_by_identifier

Requests to write a value associated with a data identifier (DID) through the WriteDataByIdentifier service.

Arguments:

- `did`
/ *Condition*: required / *Type*: int /
The DID to write its value.
- `value`
/ *Condition*: required / *Type*: dict /
Value given to the `DidCodec.encode` method. The payload returned by the codec will be sent to the server.

Returns:

- `response`
/ *Type*: Response /
The response from the `WriteDataByIdentifier` service request.

4.3.30 Method: write_memory_by_address

Writes a block of memory in the server by sending a `WriteMemoryByAddress` service request.

Arguments:

- `memory_location`
/ *Condition*: required / *Type*: `MemoryLocation<MemoryLocation>` /
The address and the size of the memory block to write.
- `data`
/ *Condition*: required / *Type*: bytes /
The data to write into memory.

Returns:

- `response`
/ *Type*: Response /
The response from the `WriteMemoryByAddress` service request.

4.3.31 Method: request_file_transfer

Sends a `RequestFileTransfer` request **Arguments:**

- `moop`
/ *Condition*: required / *Type*: int /
Mode of operation:
 - `AddFile` = 1
 - `DeleteFile` = 2
 - `ReplaceFile` = 3
 - `ReadFile` = 4
 - `ReadDir` = 5
 - `ResumeFile` = 6
- `path`
/ *Condition*: required / *Type*: str /
The path of the file or directory.
- `dfi`
/ *Condition*: optional / *Type*: `DataFormatIdentifier` /
DataFormatIdentifier defining the compression and encryption scheme of the data. Defaults to no compression and no encryption. Use for:

- AddFile = 1
- ReplaceFile = 3
- ReadFile = 4
- ResumeFile = 6

- filesize

/ *Condition*: optional / *Type*: int | Filesize /

The filesize of the file to write. If *Filesize*, uncompressed and compressed sizes will be encoded as needed. Use for:

- AddFile = 1
- ReplaceFile = 3
- ResumeFile = 6

Returns:

- response

/ *Type*: Response /

The response from the file operation.

4.3.32 Method: authentication

Sends an Authentication request introduced in 2020 version of ISO-14229-1. **Arguments:**

- authentication_task

/ *Condition*: required / *Type*: int /

The authentication task (subfunction) to use:

- deAuthenticate = 0
- verifyCertificateUnidirectional = 1
- verifyCertificateBidirectional = 2
- proofOfOwnership = 3
- transmitCertificate = 4
- requestChallengeForAuthentication = 5
- verifyProofOfOwnershipUnidirectional = 6
- verifyProofOfOwnershipBidirectional = 7
- authenticationConfiguration = 8

- communication_configuration

/ *Condition*: optional / *Type*: int /

Configuration about security in future diagnostic communication (vehicle manufacturer specific). Allowed values are from 0 to 255.

- certificate_client

/ *Condition*: optional / *Type*: bytes /

The certificate to verify.

- challenge_client

/ *Condition*: optional / *Type*: bytes /

Client challenge containing vehicle manufacturer-specific data or a random number.

- algorithm_indicator

/ *Condition*: optional / *Type*: bytes /

Algorithm used in Proof of Ownership (POWN). This is a 16-byte value containing the BER-encoded OID of the algorithm.

- `certificate_evaluation_id`
/ *Condition*: optional / *Type*: int /
Unique ID for evaluating the transmitted certificate. Allowed values are from 0 to 0xFFFF.
- `certificate_data`
/ *Condition*: optional / *Type*: bytes /
Certificate data for verification.
- `proof_of_ownership_client`
/ *Condition*: optional / *Type*: bytes /
Proof of Ownership of the challenge to be verified by the server.
- `ephemeral_public_key_client`
/ *Condition*: optional / *Type*: bytes /
Client's ephemeral public key for Diffie-Hellman key agreement.
- `additional_parameter`
/ *Condition*: optional / *Type*: bytes /
Additional parameter provided if required by the server.

Returns:

- `response`
/ *Type*: Response /
The server's response to the authentication request.

4.3.33 Method: `routine__control__by__name`

Sends a request for the RoutineControl service by routine name.

Arguments:

- param `routine_name` (required): Name of the routine
– type `routine_name`: str
- param `data` (optional): Optional additional data to give to the server
– type `data`: bytes

Returns:

- `response`
/ *Type*: Response /
The server's response to the RoutineControl request.

4.3.34 Method: `read__data__by__name`

Get diagnostic service list by a list of service names.

Arguments:

- param `service_name_list`: List of service names * type `service_name_list`: list[str]
- param `parameters`: Parameter list * type `parameters`: list[]

Returns:

- `response` / *Type*: Response / The server's response containing the diagnostic service list.

4.3.35 Method: get_encoded_request_message

Get diagnostic service encoded request (bytes value).

Arguments:

- param service_name: Diagnostic service's name * type service_name: string
- param parameters_dict: Parameter dictionary * type parameters_dict: dict

Returns:

- encoded_message / *Type*: bytes / The encoded message in bytes value.

4.3.36 Method: get_decoded_positive_response_message

Get diagnostic service decoded positive response message.

Arguments:

- param service_name: Diagnostic service's name * type service_name: string
- param response_data: Bytes data from the response * type parameters_dict: bytes
- param device_name: Name of the device * type device_name: string

Returns:

- decode_message / *Type*: dict / The decode message in dictionary.

4.3.37 Method: write_data_by_name

Requests to write a value associated with a name of service through the WriteDataByName service.

Arguments:

- service_name
/ *Condition*: required / *Type*: str /
The name to write its value.
- value
/ *Condition*: required / *Type*: dict /
Value given to the DidCodec.encode method. The payload returned by the codec will be sent to the server.
- sub_services / *Condition*: optional / *Type*: str /
A dictionary representing the sub-services of the main service, formatted as: { 'Name of main service': ['Name of sub-service'] }

Returns:

- response
/ *Type*: Response /
The response from the WriteDataByIdentifier service request.

4.3.38 Method: `io_control_by_name`

Sends a request for the IOControl service by name of input output control service.

Arguments:

- `io_control_name`
/ Condition: required / Type: str /
 Name of the input output control service
- `value`
/ Condition: optional / Type: dict /
 Optional additional data to give to the server
- `masks`
/ Condition: optional / Type: list, dict, IOMask<IOMask>, bool /
 Optional mask record for composite values. The mask definition must be included in `config['input_output']`. It can be:
 - A list naming the bit mask to set
 - A dict with the mask name as a key and a boolean setting or clearing the mask as the value
 - An instance of `IOMask<IOMask>`
 - A boolean value to set all masks to the same value.

Returns:

- `response`
/ Type: dict /
 The decoded response data.

4.3.39 Method: `send_uds_request_by_name`

Sends a UDS request by the name of the specified diagnostic service.

Arguments:

- `service_name`
/ Condition: optional / Type: str / Default: None /
 Name of the diagnostic service to request.
- `device_name`
/ Condition: optional / Type: str / Default: "default" /
 Name of the device to which the UDS request will be sent.
- `kwargs`
/ Condition: optional / Type: dict /
 Additional parameters specific to certain services. Possible values include:
 - `reset_type`: (int) Reset type for ECU reset services.
 - `parameters`: (dict) Parameters for `WRITE_DATA_BY_IDENTIFIER`, `INPUT_OUTPUT_CONTROL_BY_IDENTIFIER` and `ROUTINE_CONTROL` services.
 - `mask`: (any) Mask value for the `INPUT_OUTPUT_CONTROL_BY_IDENTIFIER` service.
 - `groups`: (int) Group identifiers for the `CLEAR_DIAGNOSTIC_INFORMATION` service (default: `0xFFFFFFFF`).
 - `memory_selection`: (any) Memory selection for the `CLEAR_DIAGNOSTIC_INFORMATION` service.
 - `control_type`: (int) Control type for `COMMUNICATION_CONTROL` service.
 - `communication_type`: (int) Communication type for `COMMUNICATION_CONTROL` service.

- node_id: (any) Node ID for COMMUNICATION_CONTROL service.
- setting_type: (int) Setting type for CONTROL_DTC_SETTING service.
- data: (any) Data for CONTROL_DTC_SETTING and TRANSFER_EXIT services.
- session_type: (int) Session type for DIAGNOSTIC_SESSION_CONTROL service.
- subfunction: (int) Subfunction for READ_DTC_INFORMATION service.
- status_mask: (any) Status mask for READ_DTC_INFORMATION service.
- severity_mask: (any) Severity mask for READ_DTC_INFORMATION service.
- dtc: (any) Diagnostic Trouble Code (DTC) for READ_DTC_INFORMATION service.
- snapshot_record_number: (any) Snapshot record number for READ_DTC_INFORMATION service.
- extended_data_record_number: (any) Extended data record number for READ_DTC_INFORMATION service.
- extended_data_size: (any) Extended data size for READ_DTC_INFORMATION service.
- memory_location: (any) Memory location for READ_MEMORY_BY_ADDRESS, REQUEST_DOWNLOAD, REQUEST_UPLOAD, and WRITE_MEMORY_BY_ADDRESS services.
- dfi: (any) Data Format Identifier (DFI) for REQUEST_DOWNLOAD and REQUEST_UPLOAD services.
- level: (any) Security level for SECURITY_ACCESS service.
- seed_params: (any) Seed parameters for SECURITY_ACCESS service.
- sequence_number: (int) Sequence number for TRANSFER_DATA service.
- data: (any) Data for TRANSFER_DATA and TRANSFER_EXIT services.

Returns:

- response
/ *Type*: Response /
The decoded response data from the service request.

4.3.40 Method: reconnect

Attempts to re-establish the connection.

Arguments:

- close_delay
/ *Condition*: optional / *Type*: float / *Default*: 2 second /
Time to wait between closing and re-opening socket
- device_name
/ *Condition*: optional / *Type*: str / *Default*: "default" /
Name of the device to which the UDS request will be sent.

Chapter 5

`__init__.py`

RobotFramework_UDS is a Robot Framework library aimed to provide UDP client to handle request/response.

Chapter 6

Appendix

About this package:

Table 6.1: Package setup

Setup parameter	Value
Name	RobotFramework-UDS
Version	0.2.0
Date	23.02.2026
Description	Robot Framework keywords for UDS (Unified Diagnostic Services) communication
Package URL	robotframework-uds
Author	Mai Minh Tri
Email	tri.maiMinh@vn.bosch.com
License	Apache-2.0
Python required	≥ 3.11

Chapter 7

History

0.1.0	09/2024
<i>Initial version</i>	
0.1.4	09/2024
<i>- Update Write Data By Name keyword to return response with given service name instead of did.</i>	
0.1.5	10/2024
<i>- Update Read Data By Name keyword to return response with given service name instead of did.</i> <i>- Update Get Encoded Request Message keyword to support convert string to proper data type for request parameters.</i> <i>- Update Get Decoded Response Message keyword to support decoded response data.</i>	
0.1.6	10/2024
<i>Temporary solution for encoding byte field param with dynamic length</i>	
0.1.7	10/2024
<i>Improve the encoding function for byte data</i>	
0.1.8	10/2024
<i>- Remove temporary solution for encoding byte field param with dynamic length</i> <i>- Update package requirements to use <code>odxtools</code> version greater than 8.2.1</i>	
0.1.9	10/2024
<i>Add Input Output Control By Name keyword</i>	
0.1.10	10/2024
<i>Add Send UDS Request By Name keyword</i>	
0.1.11	02/2025
<i>Fix the type error that occurs when user utilize string parameters in the Create UDS Connector keyword</i>	
0.1.12	02/2025
<i>Update Read/Write data by identifier keywords can be used without the need for PDX file</i>	
0.1.13	03/2025
<i>Support new pdx format using TABLE-KEY</i>	
0.1.14	03/2025

<i>Add the Reconnect keyword to enable users to attempt re-establishing the connection</i>	
0.1.15	05/2025
<i>Align Read data by name keyword's response to contain short name of service</i>	
0.1.16	08/2025
<i>Added keywords for managing UDS device configurations:</i> <i>- Get UDS Device Config By Keys</i> <i>- Update UDS Device Config By Keys</i>	
0.2.0	23.02.2026
<i>Usage of Setuptools replaced by usage of PIP/TOML/Setuptools</i>	