

Docgen

(Document Generator)

User Guide

version 1.8
May 22, 2024

Important Notice

『Freely available under the terms of the 3-Clause BSD License』

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)

HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Document Revision History

Doc Revision Number	Date	Description
1.8	May 22, 2024	add export file format(html, odt, rtf, xml, txt), and new template installation function
1.7	May 21, 2024	add Excel chart image reference and inline code expression
1.6	May 17, 2024	Markdown can be specified as the input source file
1.5	April 9, 2024	add lua snippet option on command line
1.4	February 5, 2024	add lua function call in paragraph
1.3	November 12, 2021	support excel table
1.2	July 3, 2021	add word's @<property> tag variable
1.1	April 2, 2020	add Visio page to picture & bookmark automation
1.0	February 4, 2019	Initial release

Table of Contents

1. INTRODUCTION	9
1.1 Main functions	9
1.2 Document automated creation process	9
1.3 How to run	10
1.3.1 Project creation example	12
1.4 Restrictions on use, licensing and prerequisites	12
1.4.1 Limitation	12
1.4.2 Licenses	12
1.4.3 Prerequisites	12
1.5 Known issues	13
1.5.1 Localization issue in Excel table	13
2. LUA EXPRESSION	14
2.1 docgen variables	15
2.1.1 Property object	15
2.2 AddRevision() function	17
2.3 AddTerm() function	18
2.4 AddParagraph() function	19
3. PARAGRAPH EXPRESSION	20
3.1 Title expression	20
3.2 Cataloging	20
3.3 Text expression	21
3.3.1 Bold text	21
3.3.2 Italic text	21
3.3.3 Underline	22
3.3.4 Strikethrough	22
3.3.5 Superscript	22
3.3.6 Subscript	22
3.3.7 Background color	23
3.3.8 Text color	23
3.3.9 Text size	23
3.3.10 Fixed font	23
3.3.11 Paragraph style	24
3.4 Cross-reference	24
3.4.1 Cross-reference in picture or table	24
3.4.2 Cross-reference in title	25
3.5 Property reference	25
3.6 Hyperlink	25
3.7 Math equation expression	26
3.8 Inline code block	27
3.9 Code block	27
3.10 Code execution	29
3.11 Page separation	30
3.12 horizontal line	30
3.13 Document activation	30
3.14 Lua function call	31
3.15 Picture insertion	31
3.16 Table insertion	34
3.16.1 Table insertion from excel file	34
3.16.2 Inserting table from Lua expressions	35

List of Tables

Table	Title	Page
Table 2-1.	docgen variables list	15
Table 3-1.	Excel table example.....	35
Table 3-2.	Insert only a caption without table content	35
Table 3-3.	Lua table example	36


List of Figures

Figure	Title	Page
Figure 1-1.	LaTeX setting.....	13
Figure 2-1.	Property tab in WORD	16
Figure 2-2.	AddRevision() function example.....	17
Figure 2-3.	AddTerm() function example	18
Figure 3-1.	WORD mathematical equation LaTeX conversion	27
Figure 3-2.	Donut image example.....	32
Figure 3-3.	SVG vector image example.....	32
Figure 3-4.	Visio vector image example.....	33
Figure 3-5.	Insert only a caption without picture content	33
Figure 3-6.	Excel chart example	33
Figure 3-7.	"media/table_sample.xlsx" Actual excel file	34

List of Terms

List	Description
TestDrive	TestDrive Profiling Master (https://testdrive-profiling-master.github.io/)
Lua	Lua script language (Wiki , Homepage)
WORD	Microsoft Office's word processor
Excel	Microsoft's spreadsheet editor
Visio	Microsoft Office's Visio - Diagramming and vector graphics application
PDF	Portable Document Format (Wiki)
markdown	Mark-up language (Wiki)
VBA	Microsoft's Visual Basic for Application

1. Introduction



docgen is a tool that refers to a template WORD (.docx) file and creates a new WORD (.docx) and various documents such as PDF/HTML/RTF through Markdown + HTML + Lua script.

NOTE: If you want to skip the introduction process and use it right away, please be sure to refer to '1.4.3. Prerequisites'. If you need new features or find improvements or bugs, please make suggestions to Hyunng-Ki Jeong(clonextop@gmail.com). Please note that this document was also written and created with docgen.

1.1 Main functions

docgen is a tool that automatically creates new WORD documents (.docx) and PDF documents (.pdf) by referring to template word (.docx) files.

Basically, CodeGen allows you to write documents in text format through a grammar compatible with the universal [Lua](#) programming environment and markdown. The main features are listed below.

- Supports various character modulation functions through Lua script
- Supports various document output formats such as WORD, ODT, PDF, and HTML files.
- Automated clause/caption/cross-reference creation function
- Picture, table, style formatting, code block, and mathematical equation expression functions
- Watermark insertion function
- Users can easily change various styles and apply consistent formatting based on Word template documents

1.2 Document automated creation process

The document automatedn creation process proceeds in the following steps.

1. Introduction

1. Open the template document (template.docx)
2. Apply content from user source (.md or .lua) document
3. Create Word(.docx), PDF(.pdf), DjVu(.djvu), OpenDocument(.odt), HTML(.html), XML(.xml), RichEdit(.rtf), Text(.txt) document

1.3 How to run

To run docgen, run as follows.

```
> docgen

Document Generator for TestDrive Profiling Master. v1.8
Usage: docgen [--help] [-t template] [-i template_desc] [-f format] [-l language]
[-r|--run=lua_code] input_file [output_file]

    --help                display this help and exit
    -t template            Document template name/file.
                        *** Installed docgen template list ***
                        testdrive      : TestDrive Profiling Master
                        (default : testdrive)
    -i template_desc       install new docgen template.
                        ex) docgen -t name -i "description" template.docx
    -f format              Extra output format.
                        - supported output format
                        djvu : DjVu image based document
                        html : Standard HTML format
                        odt  : OpenDocument Text format
                        pdf  : Portable Document Format
                        rtf  : Rich Text Format
                        txt  : Plain text format (unicode)
                        xml  : Extensible Markup Language format
                        (ex: -f pdf,html)
    -l language            Document language code string.
                        'docgen.language' variable in Lua
                        (default : 'en')
    -r, --run=lua_code     Run Lua snippet code
    input_file             input Lua or .md(markdown) file
    output_file            output Microsoft Word(.docx) file
```

command line : docgen **INPUT_LUA_FILE** **OUTPUT_DOCX_FILE**

In **INPUT_LUA_FILE**, set a Lua script or Markdown text file as the input source file. If **OUTPUT_DOCX_FILE** is not specified, it is automatically created appropriately by referring to the given property. The '-t' option specifies the template document that will be the base. If the template document is not specified, the default docgen_template.docx is specified, but various document types can be created by referencing/changing it.

The '-i' option allows adding a new template document. At this time, 'input_file' is the new template document source, and 'template' is the target template name to be specified.

The '-f' option specifies saving as a file other than .docx format. You can specify output in combination, such as '-f pdf,html'.

The '-l' option specifies an arbitrary language code. In Lua, you can check it with the 'docgen.language' variable, and in sentences, you can use the expression '**3.13. Document activation**' to select the desired language code.

The '-r' option specifies arbitrary preceding Lua code. This code can contain conditions for changing the document

1. Introduction

structure.

NOTE: The default setting is 'en' (english) and will have no effect on documents that do not use this 'language' setting.

1.3.1 Project creation example

아래와 같이 명령어를 입력하여, 간소화된 프로젝트를 생성하고 빌드 할 수 있습니다.

```
> create_project docgen_simplified example
*I: Create DocGen simplified project : 'example'
Run 'build.bat' to build document.

> cd example

> ls
build.bat  main.md  media

> build.bat
1. Introduction
   Main functions
2. first Contents
   media contents
*I: Link all bookmarks.
*I: Build document : Header_Name_userguide_rev1.0.docx
*I: Fields calculation & Saving to PDF output : Header_Name_userguide_rev1.0.pdf
```

1.4 Restrictions on use, licensing and prerequisites

1.4.1 Limitation

Since WORD's VBA is used, a Windows PC environment with WORD installed is required. (If it is Office 365 for the web, you need to install it as an App. version.) Additionally, in order to directly specify a Visio file (vsd/vsdX) in Picture insertion, Visio installation is required separately. And to use Excel charts, additional installation of Excel is required. Creation is possible on Linux, but functions such as updating entire document fields (can be updated manually by opening directly in WORD)/watermarking/PDF conversion are not performed.

1.4.2 Licenses

The source code implemented in docgen complies with the BSD license, and secondary works such as the user's individual scripts or images used to create the document are entirely owned by the user.

1.4.3 Prerequisites

Due to limitations in Microsoft Word's setting automation, the math equation expression is initially set to **Unicode**, the MS standard math equation expression. If you want to express this in "LaTeX", tab 'Equation/Conversions' on the ribbon menu (the menu below must be selected after creating the math equation with 'Insert/Equation' first) as in Figure 1-1. Select '**LaTeX**' instead of '**Unicode**'. A process is required.




Figure 1-1. LaTeX setting

NOTE: Microsoft currently does not provide an automatic change method in this area, and I do not know why the change function is blocked.

1.5 Knwon issues

1.5.1 Localization issue in Excel table

Regarding the expression of numeric data in Excel, the 'number format' of the default date format originally differs depending on the country setting.

예) For March 8, 2024

```
United state : number format("M/D/YYYY")
               -> '3/8/2024'
Korea        : number format("YYYY-M-D")
               -> 2024-3-8
```

As shown above, the year/month/day display order varies depending on the country setting, but only the US format is used here. If you want to use a different format, you must enter custom 'number format' directly in Excel, not the default format.

2. Lua expression

Lua scripts are very lightweight, fast, and simple, making them the preferred script language for non-programmers. There are examples of non-programmer game designers using it in various games such as 'Warcraft WoW' and 'Angry Birds'.

docgen is also written in Lua, and documents can be structured in more detail using Lua syntax in addition to the Markdown+HTML expression.

All functions added in codegen can be used for Lua functions, and the syntax below can be used additionally.

- External Lua-related links
 - [https://en.wikipedia.org/wiki/Lua_\(programming_language\)/Lua_wiki](https://en.wikipedia.org/wiki/Lua_(programming_language)/Lua_wiki)
 - docgen variables
 - AddRevision() function
 - AddTerm() function
 - AddParagraph() function

Here, only the features added to docgen are explained, and documents can be created with minimal template implementation without learning Lua.

2.1 docgen variables

Here is a list of variables available in Lua:

Table 2-1. docgen variables list

Variable	Type	Description
docgen.property	table	Document property variables table
docgen.contents_only	boolean	Document Title Remove all table of contents and leave only the text (default : false)
docgen.code_format	string	Inline code default format type Refer to. : "3.8. Inline code block" (default : "cpp")
docgen.code_bgcolor	string	Code block background color (24bit hex) (default : F7F7F7")
docgen.boarder_color	string	Table border color (24bit hex) (default : "AEAAAA")
docgen.fixed_font	string	Default fixed width font font name Refer to. : "3.3.10. Fixed font", "3.9. Code block", "3.8. Inline code block" (default : "Cascadia Mono")
docgen.language	string	Specify the document language Refer to. : "3.13. Document activation" (default : "en")

2.1.1 Property object

```
docgen.property["Document_Name"]      -- Document name
docgen.property["IP_Version"]          -- IP version (ex."1.00")
docgen.property["Main_Title"]          -- Main title name on the first page of
the document
docgen.property["Sub_Title"]           -- Sub title name on the first page of
the document (Can be skipped)
docgen.property["IP_Name_First_Page"]  -- Name of the first page of the
document
docgen.property["IP_Name_Header"]      -- Header and name on file
docgen.property["Ownership"]           -- Ownership name
docgen.property["Document_Name_Header"] -- header name (...)
docgen.property["Water_Mark"]          -- watermarking text (Can be skipped)
```

NOTE: Sentences starting with "--" is 'comment' notation in Lua. The above property names may vary across documents, the names listed above are examples used in the default TestDrive document and are not fixed names, except for "Water_Mark".

In Word, there is a 'Property' tab in the menu "File/Information" as like Figure 2-1.




Figure 2-1. Property tab in WORD

In this menu, you can add the `Field` property you want or change the existing `Property`, and the declared `property` is reflected in the `Field` information throughout the document.

Within the lua code, you can change the field value that already exists in the template document in the following way.

Alternatively, direct reference is possible within markdown sentences, such as Property reference.

ex) Example of field designation in this document

```
docgen.property["Document_Name"]      = "UserGuide"
docgen.property["IP_Version"]          = "1.00"
docgen.property["Main_Title"]          = "Document Generator"
docgen.property["IP_Name_First_Page"]  = "User Guide"
docgen.property["IP_Name_Header"]      = "document_generator"
docgen.property["Ownership"]           = "TestDrive"
docgen.property["Document_Name_Header"] = "userguide"
docgen.property["Water_Mark"]          = "TESTDRIVE CONFIDENTIAL"
```


2.2 AddRevision() function

Function prototype : AddRevision(version, year, month, day, description)

This is a function that manages the version information of a document. They can be listed in version order as shown in the example below, and **description** can use "3. Paragraph expression".

If you never use the AddRevision() function, the "Document Revision History" section is automatically removed.

ex)

```
AddRevision("1.0", 2022, 1, 14, "Initial Draft")
AddRevision("1.1", 2022, 2, 15, "Second release")
AddRevision("1.2", 2022, 3, 16, "Third release")
```

Result)

Document Revision History		
Doc Revision Number	Date	Description
1.2	March 16, 2022	Third release
1.1	February 15, 2022	Second release
1.0	January 14, 2022	Initial Draft

Figure 2-2. AddRevision() function example

2.3 AddTerm() function

Function prototype : AddTerm(**word**, **description**)

This function inserts a description of a word. It can be used as in the example below, and **Description** can use "**3. Paragraph expression**".

If you never use the AddTerm() function, the "List of Terms" clause is automatically removed.

```
AddTerm("TestDrive", "TestDrive Profiling Master (@<link:https://testdrive-  
profiling-master.github.io/>)")  
AddTerm("Lua", "Lua script language  
(<link:https://en.wikipedia.org/wiki/Lua_(programming_language);Wiki>,  
<link:http://www.lua.org/;Homepage>)" )
```

Result)

List of Terms	
List	Description
TestDrive	TestDrive Profiling Master (https://testdrive-profiling-master.github.io/)
Lua	Lua script language (Wiki , Homepage)

Figure 2-3. AddTerm() function example

2.4 AddParagraph() function

Function prototype : AddParagraph(sentence, [source_name])

You can fill in the actual document content, and **sentence** can use "3. Paragraph expression".

The contents of **sentence** can be directly described as a string, but the **sentence** can be converted to "[[file_name]]" refers to an external text file, and direct sentence notation is affected by the POSIX escape character notation, so users unfamiliar with soft programming can use "Example #2)" It is recommended to describe it in an external text file like.

source_name gives the sentence a name. This is used to identify the source when showing real-time status tracking. If the source name is not specified and a file is specified in the sentence, the source name is automatically assigned to the file name.

ex #1) Direct implementation

```
AddParagraph("#Title\  
Paragraph content 1\  
Paragraph content 2", "contents_1")
```

ex #2) External markdown expression text file implementation

```
AddParagraph("[[some.md]]")
```

ex #3) Implemented using the file read function

```
do  
    local txt_contents = String(nil)  
    txt_contents:ReadFile("some.md", false)  
    AddParagraph(txt_contents.s)  
end
```

ex #4) Lua application that checks the 'IsInsert' variable, reads several files,
changes all "%ABC%" expressions to "good", and inserts sentences.

```
if IsInsert == true then    -- directive check  
    local txt_contents     = String(nil)  
  
    txt_contents:Append(ReadText("some_1.md")) -- some_1.md added  
    txt_contents:Append(ReadText("some_2.md")) -- some_2.md added  
    txt_contents:Append(ReadText("some_3.md")) -- some_3.md added  
    txt_contents:Replace("%ABC%", "good", true) -- change all "%ABC%" to "good"  
  
    AddParagraph(txt_contents.s)    -- Apply to document  
end
```

3. Paragraph expression

Paragraph expression refers to how to describe the arguments **description** and **sentence** of the Lua functions of AddRevision, AddTerm, and AddParagraph. The notation method is a mixture of markdown and some html notation, and it additionally has its own grammar for versatility in expression. Additionally, each formula can be used equally wherever sentences are used, such as paragraphs and tables. To allow long sentences to be split into several shorter lines, paragraphs that end with " \" (space + '\') are automatically connected to the next line.

NOTE: If you have any suggestions for paragraph expressions or requests for improvement, please contact me at any time. (Refer to 1. Introduction.)

3.1 Title expression

Expression : # Main title

Sub title1

Sub title2

Sub title3

Sub title4

Sub title5

The document title is displayed by placing the '#' character at the beginning of the line, from **Main title** to **Sub title**. This is the same as markdown. If the '#' character is not at the beginning of the line, it is not recognized as a title and is affected by the "text style" of the WORD's template document. Up to 6 levels can be used.

3.2 Cataloging

Expression : * Element1

**** Element2**

***** Element3**

****** Element4**

******* Element5**

******* Element6**

Cataloging is similar to markdown, but there are some differences for more expressive functions. If the '*' character exists at the beginning of a line, it is displayed as a list, and the indentation is determined by the number of '*'s.

You can also use '>' after the '*' character listed for a number or special expression to remove the existing marker and use a different form of expression. Up to 6 levels can be used.

3. Paragraph expression

ex)

```
* first element
** second element
*** third element
**** fourth #1 element
**** fourth #2 element
**** >fourth #2 element extension
**** @<b>@<color:FF0000>Cataloging@</color>(目錄, List)@</b> refers to writing down
names of people, names of products, book titles, tables of contents, and items to be
checked in a certain standard and order to make them easier to read.
* >1). first number element
** >1-1). second number element
* >2). first number element
** >2-1). second number element
*** >Unmarked Element Extended element
```

Result)

- first element
 - second element
 - ◆ third element
 - fourth #1 element
 - fourth #2 element
 - fourth #2 element extension
 - **Cataloging(目錄, List)** refers to writing down names of people, names of products, book titles, tables of contents, and items to be checked in a certain standard and order to make them easier to read.
- 1). first number element
 - 1-1). second number element
- 2). first number element
 - 2-1). second number element
- Unmarked Element Extended element

3.3 Text expression

Text expressions can specify the color, thickness, italics, underline, size, superscript/subscript, etc. of the text. The scope of application is limited to one line, and multiple formula notations may be expressed overlapping.

3.3.1 Bold text

Expression : @expression@

Bold text is expressed by surrounding **Expression** with a 'b' tag, similar to HTML.

ex)

```
@<b>It's in bold.@</b> It's not in bold.
```

Result : **It's in bold.** It's not in bold.

3.3.2 Italic text

Expression : @<i>expression@</i>

3. Paragraph expression

Italic text is expressed by surrounding the **expression** with an 'i' tag, similar to HTML.

ex)

```
@<i>italic@</i> Non italic
```

Result : *italic* Non italic

3.3.3 Underline

Expression : @<u>expression**</u>**

The underlined text is expressed by surrounding **expression** with a 'u' tag, similar to HTML.

ex)

```
@<u>underlined text@</u>
```

Result : underlined text

3.3.4 Strikethrough

Expression : @<s>expression**</s>**

The strikethrough text is expressed by surrounding **expression** with 's' tags, similar to HTML.

ex)

```
@<s>Strikethrough text@</s>
```

Result : ~~Strikethrough text~~

3.3.5 Superscript

Expression : @^{expression**}**

Superscript text is expressed by surrounding **expression** with 'sup' tags, similar to HTML.

ex)

```
Text@<sup>Superscript@</sup>
```

Result : Text^{Superscript}

3.3.6 Subscript

Expression : @_{expression**}**

Subscript text is expressed by surrounding **expression** with 'sub' tags, similar to HTML.

ex)

```
Text@<sub>Subscript@</sub>
```

Result : Text_{Subscript}

3.3.7 Background color

Expression : @<bgcolor:color_value>expression@</bgcolor>

To change the background color, the expression is **expression** surrounded by 'bgcolor' tags similar to HTML, and the color is specified by **color_value** Expressed in 24bit RGB hexadecimal.

ex)

```
@<bgcolor:FF0000>Red background@</bgcolor> expression
```

Result : **Red background** expression

3.3.8 Text color

Expression : @<color:color_value>expression@</color>

To change the font color, the expression is **expression** surrounded by 'color' tags similar to HTML, and the color is specified by **color_value** Expressed in 24bit RGB hexadecimal.

ex)

```
@<color:FF0000>Red text@</color> expression
```

Result : **Red text** expression

3.3.9 Text size

Expression : @<size;font_size>expression@</size>

To change the font size, the expression is **expression** surrounded by 'size' tags similar to HTML, and the color is specified by **font_size** Specify it in point units.

ex)

```
@<size:30>Big text@</size> @<size:10>small text@</size>
```

Result : **Big text** small text

3.3.10 Fixed font

Expression : @<fixed>expression@</fixed>

To use fixed font, the **expression** is surrounded by 'fixed' tags similar to HTML.

NOTE: Fixed-width fonts can be specified with Lua's '**docgen.fixed_font**' variable, and the default font name is 'Casadia Mono'.

ex)

3. Paragraph expression

```
@<fixed>Fixed font@</fixed> expression.
```

Result : Fixed font expression.

3.3.11 Paragraph style

Expression : **:::style_name[,alignment]**

Change the paragraph style of the next line to 'style_name'. The style changes for only one line, and reverts to the original style formatting for the next line. Style formatting is implemented by referencing the style specified in the initial template WORD document, and can be changed or added by searching for 'text style' in WORD. Style names include tab characters, "/", "--", or ";" Anything after the character is ignored. It doesn't matter if you enter the style ID rather than the style name.

'alignment' can be one of 'left', 'right', 'center', and If omitted, basically it is considered as two-sided alignment. And you can also specify only 'alignment' without 'style_name'.

ex) Apply note style

```
:::NoteHeading      -- Additional explanation
Including both civilian and military deaths, an estimated 60 to 70 million \
people died as a result of World War II. \
In the aftermath of this war, collectivistic ideology, which had been \
the mainstream of society, declined in the Western world and individualistic \
ideology emerged, which continues to this day.
```

```
:::center
center alignment
:::right
right alignment
```

Result)

NOTE: Including both civilian and military deaths, an estimated 60 to 70 million people died as a result of World War II. In the aftermath of this war, collectivistic ideology, which had been the mainstream of society, declined in the Western world and individualistic ideology emerged, which continues to this day.

center alignment

right alignment

3.4 Cross-reference

Expression : **@<bookmark:target>**

Implement cross-referencing of titles, pictures, tables, etc.

Just write the caption or title of the figure or table in **target**.

3.4.1 Cross-reference in picture or table

ex)

```
@<bookmark:LaTeX setting>
```

Result : Figure 1-1

3. Paragraph expression

3.4.2 Cross-reference in title

In the case of titles, cross-references can be expressed in four ways depending on the presence or absence of a prefix, as shown below.

1. Reference to general sentences (expressed without a separate prefix)
: **target**
2. Page number reference
: **&target**
3. Chapter/section number reference
: **#target**
4. Chapter/section number and full sentence reference
: **@target**

The example below shows an actual usage example, and you can see that clicking on the sentence moves to the link to the current document.

ex) Reference to general sentences

```
@<bookmark:Restrictions on use, licensing and prerequisites>
```

Result : Restrictions on use, licensing and prerequisites

ex) Page number reference

```
@<bookmark:&Restrictions on use, licensing and prerequisites>
```

Result : 12

ex) Chapter/section number reference

```
@<bookmark:#Restrictions on use, licensing and prerequisites>
```

Result : 1.4

ex) Chapter/section number and full sentence reference

```
@<bookmark:@Restrictions on use, licensing and prerequisites>
```

Result : 1.4. Restrictions on use, licensing and prerequisites

3.5 Property reference

Expression : @<property:property_name>

You can create properties with various names using 'Property object' among 'Lua expression', and it provides a way to quote these in the text.

예)

```
@<property:Main_Title>, @<property:Ownership>
```

Result : Docgen, clonextop@gmail.com

3.6 Hyperlink

Expression : @<link:URL_target;display_text>

3. Paragraph expression

Hyperlinks are displayed as above, and `display_text` can be skipped.

ex) "https://testdrive-profiling-master.github.io/" hyperlink expression

```
@<link:https://testdrive-profiling-master.github.io/;TestDrive Profiling Master>
```

Result : [TestDrive Profiling Master](https://testdrive-profiling-master.github.io/)

3.7 Math equation expression

Expression : `$$math_formula$$`

In the case of mathematical formulas, the mathematical equation is displayed by surrounding it with "\$\$", as in markdown.

But, WORD's mathematical equation is initially set to the expression "**Unicode**". Therefore, if you want to use the equation "**LaTeX**", please note that you must change the settings by referring to "**1.4.3. Prerequisites**".

When a mathematical equation is expressed as a single expression, it is displayed centered, but when expressed in the middle of a sentence, the expression is automatically changed to match the sentence, and the example below is implemented in LaTeX expression, so if the result is notated incorrectly, it is the result of not attempting the "Prerequisites" above.

ex) 2 types of mathematical equation expressions

```
$$f\left(x\right)=a_0+\sum_{n=1}^{\infty}\left(a_n\cos\left\{\frac{n\pi}{L}x\right\}+b_n\sin\left\{\frac{n\pi}{L}x\right\}\right)$$
```

The expression in the sentence changes to

```
$$f\left(x\right)=a_0+\sum_{n=1}^{\infty}\left(a_n\cos\left\{\frac{n\pi}{L}x\right\}+b_n\sin\left\{\frac{n\pi}{L}x\right\}\right)$$.
```

Result :

$$f\left(x\right)=a_0+\sum_{n=1}^{\infty}\left(a_n\cos\left\{\frac{n\pi}{L}x\right\}+b_n\sin\left\{\frac{n\pi}{L}x\right\}\right)$$

The expression in the sentence changes to $f\left(x\right)=a_0+\sum_{n=1}^{\infty}\left(a_n\cos\left\{\frac{n\pi}{L}x\right\}+b_n\sin\left\{\frac{n\pi}{L}x\right\}\right)$.

WORD's mathematical equation can be changed by first creating the equation as shown in Figure 3-1 and then pressing the 'Linear format' button in the menu. You can write this string as a mathematical equation by adding the characters "\$\$" to both ends.




Figure 3-1. WORD mathematical equation LaTeX conversion

3.8 Inline code block

Expression : @<code[:**code_format**]>**inline_code**@</code>

Statement Represents inline code. 'code_format' can be omitted and, the default code format is 'cpp', and you can use the same code formats supported by 'Code block'.

NOTE: You can change the default code format in Lua by specifying 'docgen.code_format'.

ex)

Examples of output from C expressions is "@<code>printf("Hello world.");@</code>".

Result :

Examples of output from C expressions is "printf(**"Hello world."**);".

3.9 Code block

Expression : ```**code_format**
code_contents
```

In the case of **code\_format**, you can check the supported code formats by entering the "code\_highlighter -l" command as shown below.

```
> code_highlighter -l
*** Available current input code format(C:/Project/Profiles/Common/bin/source-
highlight-lang/lang.map) list

C, F77, F90, H, ac, ada, adb, am, applescript, asm
autoconf, awk, bash, bat, batch, bib, bison, c, caml, cbl
cc, changelog, clipper, cls, cobol, coffee, coffeescript, conf, cpp, cs
csh, csharp, css, ctp, cxx, d, desktop, diff, dmd, docbook
```

### 3. Paragraph expression

```
dtx, el, eps, erl, erlang, errors, f, f77, f90, feature
fixed-fortran, flex, fortran, free-fortran, glsl, go, groovy, h, haskell,
haxe
hh, hpp, hs, htm, html, hx, hxx, in, ini, ipxe
islisp, java, javalog, javascript, js, json, kcfg, kdevelop, kidl, ksh
l, lang, langdef, latex, ldap, ldif, lex, lgt, lhs, lilypond
lisp, ll, log, logtalk, lsm, lua, ly, m4, makefile, manifest
mf, ml, mli, moc, opa, outlang, oz, pas, pascal, patch
pc, perl, php, php3, php4, php5, pkgconfig, pl, pm, po
postscript, pot, prg, prolog, properties, proto, protobuf, ps, py, python
r, rb, rc, rs, ruby, s, scala, scheme, scm, scpt
sh, shell, sig, sl, slang, slsh, sml, spec, sql, sty
style, syslog, systemverilog, tcl, tcsh, tex, texi, texinfo, tk, tml
txt, ui, upc, v, vala, vbs, vbscript, verilog, vim, xhtml
xml, xorg, y, yacc, yaml, yml, yy, zsh
```

Below is an example of quoting verilog code. To use the string """" when quoting, you can quote it by writing "@`""". To insert a line number in the code, you can add '#' and quote it like this: "#code\_format".

ex) Verilog Code block with line numbers

```
```#verilog
`ifndef __TESTDRIVE_SRAM_SINGLE_V__
`define __TESTDRIVE_SRAM_SINGLE_V__
`timescale 1ns/1ns

module SRAM_Single #(
    parameter ADDR_WIDTH      = 4,
    parameter DATA_WIDTH    = 4
) (
    // System
    input          CLK,          // clock
    // SRAM interface
    input          nCE,          // Chip enable (active low)
    input          nWE,          // write enable (active low)
    input [(ADDR_WIDTH-1):0] ADDR, // address
    input [(DATA_WIDTH-1):0] DIN,  // input data
    output reg [(DATA_WIDTH-1):0] DOUT // output data
);
// synopsys template

// definition & assignment -----
reg [(DATA_WIDTH-1):0] mem[(2**ADDR_WIDTH)-1:0];

// implementation -----
always@(posedge CLK) begin
    if(!nCE) begin
        if(!nWE)
            mem[ADDR] <= DIN;
        DOUT <= mem[ADDR];
    end
end

endmodule

`endif//__TESTDRIVE_SRAM_SINGLE_V__
```
```

Result)

```
1: `ifndef __TESTDRIVE_SRAM_SINGLE_V__
2: `define __TESTDRIVE_SRAM_SINGLE_V__
3: `timescale 1ns/1ns
4:
5: module SRAM_Single #(
6: parameter ADDR_WIDTH = 4,
7: parameter DATA_WIDTH = 4
8:) (
9: // System
10: input CLK, // clock
11: // SRAM interface
12: input nCE, // Chip enable (active low)
13: input nWE, // write enable (active low)
14: input [(ADDR_WIDTH-1):0] ADDR, // address
15: input [(DATA_WIDTH-1):0] DIN, // input data
16: output reg [(DATA_WIDTH-1):0] DOUT // output data
17:);
18: // synopsys template
19:
20: // definition & assignment -----
21: reg [(DATA_WIDTH-1):0] mem[(2**ADDR_WIDTH)-1:0];
22:
23: // implementation -----
24: always@(posedge CLK) begin
25: if(!nCE) begin
26: if(!nWE)
27: mem[ADDR] <= DIN;
28: DOUT <= mem[ADDR];
29: end
30: end
31:
32: endmodule
33:
34: `endif//__TESTDRIVE_SRAM_SINGLE_V__
```

#### 3.10 Code execution

Expression : ``[code\_format]

code\_contents

``

It has a similar format to 'Code block', but if the "code format" is surrounded by "[ ]", the code content is executed.

The currently available code format supports only "lua".

ex)

```
``[lua]
property["Document_Name"] = "UserGuide"
property["IP_Version"] = "1.00"
``
```

#### 3.11 Page separation

##### Expression : `;;;`

If you enter at least three ';' characters at the beginning of a line, it will advance to the next page.

#### 3.12 horizontal line

##### Expression : `---`

If you enter at least three '-' characters at the beginning of a line, a horizontal line will be entered, just like in markdown.

ex)

```

```

Result)

---

#### 3.13 Document activation

##### Expression #1 : `%%% language_code`

##### Expression #2 : `%%% (Lua_code)`

Document activation determines whether the following statements will be applied to the actual document. The condition for document activation can be specified as a return value of "language\_code name" or "Lua\_code" enclosed in parentheses "()".

In the case of "language\_code", it is compared with the 'language code name' specified in the '-l' option. (Refer to '1.3. How to run'). If not equal, the next document content is ignored until the next document activation specified. This ensures that only sentences written in your desired language can be used in your document.

For "Lua\_code", it must be enclosed in parentheses "()". If the return value of Lua code execution is 'true'(boolean), then use the following document contents. If not same as 'true', the next document contents will be ignored.

If it ends with '%%%' without language code or Lua code definition, the document content is activated from the next line.

**NOTE:** Language code names are case-sensitive, and you can improve readability by listing '-', '=', or '%' characters after the language code name. The default value is 'en'. The language code can be used as the 'docgen.language' variable in Lua.

ex1)

```
%%% ko -----
한글 출력입니다.
%%% en -----
It's an english output.
%%% -----
```

### 3. Paragraph expression

---

It's all output.

Result) When using the '-l en' option.

It's an english output.

It's all output.

ex2)

[Lua code]

```
test_mode = true
```

[Markdown code]

```
%%% (test_mode == true)
test_mode is activated.
%%% (test_mode ~= false)
test_mode is inactivated.
%%%
```

Result)

```
test_mode is activated.
```

#### 3.14 Lua function call

##### Expression : @<lua:lua\_function>

Call a Lua function. If the returned value is in string type, it is applied to the next document content.

ex)

```
Lua variable 'docgen.language' is @<lua:docgen.language>
```

Result)

Lua variable 'docgen.language' is en

#### 3.15 Picture insertion

##### Expression : @<img:[#]filename;scale[;caption]>

Pictures support jpg, png, bmp, gif, tif, svg, wmf, and vsd/vsdX (Visio installation required), xls/xlsx(Excel installation required) formats. **file name** specifies the file name to display, if the picture requires an outline border, indicate it as "**#filename**". In the case of a Visio file, a separate page name can be specified as "**filename[page name]**", and if **page name** is not specified, it is considered the first page.

In the case of an Excel file, By specifying "**file\_name[sheet\_name:chart\_title]**", you can designate the chart of a specific sheet as an image. (The chart title can be omitted. If omitted, the first chart on the sheet is used.)

Additionally, in the case of **scale**, the maximum value based on the width of the paper is 1.0, and you can specify the size by entering a value between 0 and 1. If not specified, the default 1.0 is assumed.

**caption** literally specifies the caption content and can be used in '3.4. Cross-reference'. If not specified, the caption will not be inserted.

### 3. Paragraph expression

---

ex1) Illustration of a donut with border in size  $\frac{1}{4}$

```
@<img:#media/donut.jpg;0.25;Donut image example>
```

Result)



**Figure 3-2. Donut image example**

ex2) Borderless vector image

```
@<img:media/awesome_svg.svg;0.7;SVG vector image example>
```

Result)



**Figure 3-3. SVG vector image example**

ex3) Insert Visio specific page as vector image

```
@<img:media/test.vsd[test_sample];0.8;Visio vector image example>
```

Result)






Figure 3-4. Visio vector image example

ex4) Insert only a caption without a picture

```
@<img:nil;0;Insert only a caption without picture content>
```

Result)

Figure 3-5. Insert only a caption without picture content

ex5) Insert chart image from Excel

```
@<img:media/chart_sample.xlsx[chart_population:Population in the world];1.0;Excel chart example>
```

Result)




Figure 3-6. Excel chart example

#### 3.16 Table insertion

Tables support two expression methods: Excel and Lua script.

If the table is too long and you move to the next page, the header is automatically repeated.

##### 3.16.1 Table insertion from excel file

**Expression :** `@<tbl:[#]file_name;sheet_name[;caption]>`

In the case of inserting a table, you can move the content created in Excel, and the width will be the same as possible for the cells merged in Excel.

The first line of the table is the top title, and when you want to align lower data columns in the center, insert the character '\*' front of the title name.

**NOTE:** Figures or tables are basically grouped together with captions as one object so that they are not displayed separately from the caption. Therefore, when they cannot be displayed at once in the remaining page area, they are displayed on the next page. However, for very long tables, the extra blank space at the beginning can look awkward. In this case, you can prevent this by inserting the '#' character in front of the 'file\_name'.

ex1) Table from excel file : "media/table\_sample.xlsx"

```
@<tbl:media/table_sample.xlsx;Sheet1;Excel table example>
```

|   | A     | B            | C                                                   | D |
|---|-------|--------------|-----------------------------------------------------|---|
| 1 | Index | Name         | Description                                         |   |
| 2 | 0     | <u>Ace</u>   | description #0                                      |   |
| 3 | 1     | <i>Taro</i>  | <b>description #1 bold colored italic underline</b> |   |
| 4 |       | <b>Bison</b> | description #2                                      |   |
| 5 | 2     | <i>Toss</i>  | @<b>description @<color:FF0000>#3@</color>@</b>     |   |
| 6 | 3     | Gran         | description #4                                      |   |
| 7 | 4     | Mobi         | description #5                                      |   |
| 8 | 5     | Dose         | description #6                                      |   |
| 9 |       |              |                                                     |   |

Figure 3-7. "media/table\_sample.xlsx" Actual excel file

Result)

Table 3-1. Excel table example

| Index | Name         | Description                                         |
|-------|--------------|-----------------------------------------------------|
| 0     | <u>Ace</u>   | description #0                                      |
| 1     | Taro         | <b>description #1 bold colored italic underline</b> |
| 2     | <b>Bison</b> | description #2                                      |
|       | Toss         | <b>description #3</b>                               |
| 3     | Gran         | description #4                                      |
| 4     | Mobi         | description #5                                      |
| 5     | Dose         | description #6                                      |

ex2) Insert only captions without table content

```
@<tbl:nil;nil;Insert only a caption without table content>
```

Result)

Table 3-2. Insert only a caption without table content

#### 3.16.2 Inserting table from Lua expressions

**Expression : @<tbl:lua;table\_variable\_name;caption>**

Basically, since docgen is written based on Lua scripts, you can create a table with Lua variables and utilize it.

This is an example that utilizes the lua table already defined as shown below.

예) declared lua expression

```
lua_table_example = {
 HeaderCount = 2,
 {"Head A", merge={1,2}}, {"Head B", merge={3,1}}, {width=300,
style="TableTextCenter"}, "",
 {"", "Sub A", "Sub B", "Sub C"},
 {"index1", "a", "1", "aa"},
 {"index2", "b", "2", "bb"},
 {"index3", {"c", merge={2,1}}, "", "@<color:ff0000>cc@</color>"}
}
```

예) Expression within paragraph

```
@<tbl:lua;lua_table_example;Lua table example>
```

결과)

**Table 3-3. Lua table example**

| Head A | Head B |       |       |
|--------|--------|-------|-------|
|        | Sub A  | Sub B | Sub C |
| index1 | a      | 1     | aa    |
| index2 | b      | 2     | bb    |
| index3 | c      |       | cc    |

Lua tables are expressed with multiple braces, such as "{ { { ... }, ... }, ... }". The outer curly braces indicate the table, the next brace indicates Row, and the next brace indicates Column.

When expressing Column and Row, you can specify the following properties. In the case of Column, if you describe it only as a string, the braces can be omitted.

- Lua table Row properties
  - HeaderCount: Specifies the number of header lines. (Default: 1)
- Lua table Column properties
  - data : Specifies the string data of the cell. It is possible to omit "data=" and describe only as a string. However, if omitted, it must be the first attribute of the cell technology. (default : " ")
  - width : Specifies the horizontal length of one column. The final relative length is given by dividing it from the total length of all columns. This property is valid only for the Column described in the first Row. (Default: 100)
  - style : Specifies the text style name to apply to the column. The specified style is equally applied to the same child columns. (Default: "TableTextLeft", when specifying the style back to default, specify "" rather than nil.)
  - merge : It functions to merge multiple cells within a certain range starting from the current cell location. Range can be specified in properties as {width,height}.