

WebElement:-

#. Anything present on webpage is called as WebElement such as Textbox/Inputbox, Button, Link, Checkbox, RadioButton etc...

#. Web Elements are created using HTML (Hyper Text Markup Language)

#. Each HTML Contains TAG, ATTRIBUTE NAME, ATTRIBUTE VALUE, and Text

To see HTML code of Required WebElement:-

#. Right-click on that web element and select the option 'Inspect'.

#. If Right Click is disabled on the page, Then Press CTRL+SHIFT+I
or Press F12

#. It will display the "developer tool"

Example:-

```
<div id="d1"> Login</div>
```

In the above HTML code 'div' is the tag ,

"id" is the attribute name

d1 is the attribute value

and Login is the text.

Locaters:-

1. Id
2. Name
3. Class Name
4. Tag Name
5. Link Text
6. Partial Link Text
7. CSS Selector
8. Xpath

1. Application command

get() : open the application url

title : to capture the title of the current webpage.

current_url : to capture the current url of the web page

page_source: to capture source code of the webpage

2. Conditional Commands

is_displayed()

is_enabled()

is_selected()

3. Browser Commands

close() : close single browser window where driver is focused.

quit() : close multiple browser window.

Navigational Commands

back()

forward()

refresh()

wait command:-

time.sleep(time in seconds)

#. Simple to use.

Dis Advantages

#. The performance is very poor.

#. If the element is not available within the mentioned time, there is still getting exception

implicit wait

#. Single Statement

#. Performance will not be reduced (if the element is available within the time to execute further statements)

Dis Advantage

#. If the element is not available within the mentioned time .then there is a chance of getting exception

Explicit Wait:-

#. Wait for a specific condition before continuing ...

.