Before we heat

Semi-participatory JSA | Read the essentials, then show or say what is different today.

Location / asset: _____ **Date / time:** _____

Operator / unit: _____ **Site representative:** _____

Task / fluid: _____ **Contact / radio:** _____

Company safety lead and site representative must adapt and approve this draft against the actual unit manual, fluid SDS, site permits and emergency plan before use. Blank limits are not permission to operate.

Scope: truck-mounted hot-fluid circulation, paraffin removal or line/equipment heating. Describe the actual job. Tank entry, welding, chemical treatment and testing outside the approved service procedure require separate assessment.

01 What are we doing today?

READ: Confirm the work instruction, fluid/SDS, correct asset, flow path and return destination. Resolve conflicting work and required permits before setup. [S2, S3]

CREW CHECK: Operator describes the job. Site representative identifies the connection and return.
Today we are: _____

02 Where do we stand if something releases?

READ: Use the agreed separation and wind-aware layout. Keep escape clear; protect lines from traffic. Locate accessible extinguishers and emergency controls. [S1]

CREW CHECK: Point to the wind indicator, safe operator position and escape route.
Muster: _____ **Alarm / contact:** _____

03 What could the air do to us?

READ: Use site-required gas testing and monitoring. Confirm detectors and alarm response. Never rely on smell for H2S. Select PPE and respiratory protection through the site assessment. [S2, S4]

CREW CHECK: Say what the crew will do at an alarm. Identify today's gas/PPE requirement.
Hazard / control: _____

PREPARE CHECK: [ ] Scope agreed [ ] Permits resolved [ ] Layout accepted
[ ] Emergency plan understood. Any unresolved item means HOLD. Complete page 2 before starting.

Prove the controls

Short crew checks at the points where the risk changes.

04 Show the weak point before pressure does

READ: Check line condition, connections, rated restraints and exclusion areas. Verify testing and relief/check-valve arrangement. The lowest allowable rating governs. [S1, S5]

CREW CHECK: Identify the limiting component and where people must not stand.
Limit source: _____ **Pressure:** _____ psi **Temperature:** _____ deg F

05 Talk through the start - and the stop

READ: Use the unit's approved startup, heating and shutdown instructions. Verify fitted protection; never bypass it. Stop for leakage, abnormal conditions or lost flow/return. [S1-S3]

CREW CHECK: Point to emergency stop. Explain the safe response to a leak or alarm.
Flow range / unit procedure: _____

06 Prove it is safe before breaking a line

READ: Use approved cooldown and isolation. Use the intended bleed path; verify each trapped section is depressurized. Do not hammer live unions or check leaks by hand. Injection injury needs immediate medical attention. [S5, S6]

CREW CHECK: Who verifies isolation, zero pressure and safe temperature before disconnecting?
Responsible person: _____

FINAL GO / HOLD [ ] Ready [ ] Hold - correction required
One thing different today: _____
Extra control / owner: _____
Rebrief after changed fluid, connection, scope, crew, wind, equipment condition or an alarm. No answer is preselected.

Crew names / initials: _____ **Site representative:** _____

Closeout: capture residue, inspect/secure equipment, restore agreed valve status and hand back the site. [S2, S3]

Research basis - original synthesis, reviewed November 1, 2026

S1: OSHA - Hot oiling | S2: Sinopec Canada - 2022 handbook, section 7.8 | S3: OSHA - Hot work | S4: OSHA - H2S safety | S5: OSHA - Pressure-line controls, OSHA3763 | S6: UK HSE - Hydraulic injection injury

S2 is a hazard reference, not local law. S5 contributes pressure-line controls only; this is not a hydraulic-fracturing procedure. No source is adopted as the truck operating manual.