


Selenium WebDriver Training

List

Array Vs Collection

- An array is a collection of similar types of data.
- Limitation: Size is fixed.
- What if I do not know size of the data array upfront?
- What if I like to increase or decrease the size at runtime?
- That can be achieved using Collection (Dynamic Array)

Collection



- Interface (Sub Interface of Collection)
- Since List is an interface, we cannot create objects from it

- Interface (Sub Interface of Collection)
- Since List is an interface, we cannot create objects from it
- In order to use functionalities of the List interface, we can use any of the implementation classes like ArrayList

List Properties

- List interface is an ordered collection that allows us to store and access elements sequentially
- List allows duplicate values inside the collection



Syntax

```
List<String> mentors = new ArrayList<String>();
```

Syntax

```
List<String> mentors = new ArrayList<String>();
```



Interface

Syntax

```
List<String> mentors = new ArrayList<String>();
```



Generic (Type)

Syntax

```
List<String> mentors = new ArrayList<String>();
```



List Name

Syntax

```
List<String> mentors = new ArrayList<String>();
```



Cannot create object for List

Syntax

```
List<String> mentors = new ArrayList<String>();
```



The implementation class of List

```
List<String> mentors = new ArrayList<String>();
```

What happens here?

All the methods of ArrayList is not exposed in the mentors. **Only the methods of List is exposed (only showing the required implementation)**

List Methods

- `add()` - adds an element to a list

List Methods

- `add()` - adds an element to a list
- `addAll()` - adds all elements of one list to another

List Methods

- `add()` - adds an element to a list
- `addAll()` - adds all elements of one list to another
- `get()` - get particular element based on index

List Methods

- `add()` - adds an element to a list
- `addAll()` - adds all elements of one list to another
- `get()` - get particular element based on index
- `remove()` - removes an element from the list

List Methods

- `add()` - adds an element to a list
- `addAll()` - adds all elements of one list to another
- `get()` - get particular element based on index
- `remove()` - removes an element from the list
- `removeAll()` - removes all the elements from the list

List Methods

- `add()` - adds an element to a list
- `addAll()` - adds all elements of one list to another
- `get()` - get particular element based on index
- `remove()` - removes an element from the list
- `removeAll()` - removes all the elements from the list
- `clear()` - removes all the elements from the list

List Methods

- `add()` - adds an element to a list
- `addAll()` - adds all elements of one list to another
- `get()` - get particular element based on index
- `remove()` - removes an element from the list
- `removeAll()` - removes all the elements from the list
- `clear()` - removes all the elements from the list
- `size()` - returns the length of lists

List Methods

- `add()` - adds an element to a list
- `addAll()` - adds all elements of one list to another
- `get()` - get particular element based on index
- `remove()` - removes an element from the list
- `removeAll()` - removes all the elements from the list
- `clear()` - removes all the elements from the list
- `size()` - returns the length of lists
- `toArray()` - converts a list into an array

List Methods

- `add()` - adds an element to a list
- `addAll()` - adds all elements of one list to another
- `get()` - get particular element based on index
- `remove()` - removes a particular element from the list based on index
- `removeAll()` - removes all the elements from the list
- `clear()` - removes all the elements from the list
- `size()` - returns the length of lists
- `toArray()` - converts a list into an array
- `contains()` - returns true if list contains specified element

Activity: Create mentors List with duplicates !

- Demonstrate the index (order) and duplicates ..
- Also demonstrate to sort List !!

List Problem Solving in Selenium

- Get Link Count (Leafground)
- Get Dropdown values (Leafground)

Summary

- List – **interface** and implemented by **ArrayList**
- List can have **duplicated** and **ordered** collection
- Selenium Example: **findElements**

Classroom Exercise (Breakout)

- Go to <https://amazon.in>
- Type phones -> id: twotabsearchtextbox
- Print price of every phone -> class: a-price-whole
- Print the lowest price !

Hints:

- Look what is common locator for all price info of every phone.
- Use Collection sort to get the lowest price
- (make sure the stored values are in Integer to support sorting)
- Use Integer.parseInt to convert String to integer