
VOICEGUARD - MULTILAYER EMERGENCY SAFETY DEVICE

Discreet, clip-on device prototype for students, elderly, travelers and workers



VOICEGUARD

UNIVERSAL MULTILAYER EMERGENCY SAFETY DEVICE

“Because help should arrive even when every other system fails.”

---

1. THE PROBLEM

During an emergency, a victim may be unable to reach their phone, place a call, articulate their location, or maintain a reliable network connection. A single-point safety system inherently risks failure when needed most.

2. OUR SOLUTION & CONCEPT

VoiceGuard is a compact, discreet, gender-neutral clip-on safety device combining manual activation, voice analysis, fall detection, GPS tracking, local audio-visual alarms, and layered emergency communication into a single unified architecture.

3. AUTONOMOUS DETECTION LOGIC

Workflow: Trigger Detected → Threat Analysis → False-Alert Reduction → GPS Acquisition → Information Packaging → Layered Dispatch → Guardian Circle Notified

- **Manual SOS:** Recessed tactile emergency button.
- **AI Voice Analysis:** Dual Hindi + English voice recognition for distress wake-words.
- **Smart Fall Detection:** 6-axis IMU detects high-G impact and sudden orientation loss.
- **False-Alert Reduction:** Multi-sensor signal cross-validation prevents false alarms.

4. CORE SYSTEM FEATURES

🔴 **SOS Button:** Instant manual emergency trigger.

🎙️ **AI Distress Engine:** On-device voice classification.

📐 **6-Axis Motion Sensor:** Real-time fall impact analysis.

📍 **GPS Module:** Precise satellite coordinate locking.

🔊 **High-Decibel Siren:** Immediate localized deterrent.

💡 **Strobe Array:** High-visibility optical signaling.

👨‍👩‍👧 **Guardian Network:** Direct alerts to pre-configured contacts.

5. THREE-LAYER COMMUNICATION ARCHITECTURE

Layer 1 — Primary Mobile Network
Dedicated 4G/cellular module handles immediate location transmission and bidirectional voice/data alerts to emergency services and guardians.

Layer 2 — Smart Relay Fallback
If network connection drops, emergency logs are encrypted and buffered locally (SPI Flash), continually attempting delivery via alternative local pathways (Wi-Fi/BLE) or immediately upon network restoration.

Future Layer — Satellite (NTN Integration)
Planned support for Direct-to-Device Non-Terrestrial Network (NTN) satellite connectivity for remote areas without cellular coverage.

6. HARDWARE SPECIFICATION

The prototype strictly utilizes standard, commercially available hardware with believable 24mm clearance:

Core Stack: ESP32-S3 MCU + Dedicated Cellular Module + Ceramic Patch GPS + 6-Axis IMU + MEMS Microphone + High-dB Piezo Siren + Strobe LED + 500mAh Li-Po Battery + USB-C Power Management.

7. DESIGN REALISM & ROADMAP

- **Universal & Discreet:** Appears as a standard tech clip; gender-neutral and compact.
- **Affordable Prototyping:** Built using off-the-shelf development units prior to custom PCB consolidation.
- **Future Phase:** Ultra-low power sleep states, PCB shrink, and real-world pilot testing.

“VoiceGuard provides an intelligent, resilient layer of security that remains functional when smartphones or primary networks fail.”