PCB Name	Lighting LED Board
PCB Number	P26002A
Revision	1
Doc Number	S01BM90011

Reference	Manufacturer	Quantity	P/N	Package	Specification	Remark
R3, R15	Panasonic	2	ERJ-3BQFR91V	1608M(0603)	Thick Film Resistors, 910mOhms, ±1%, 1/4W	
R7, R9, R19, R22	KOA	4	RK73H1JTTD1000F	1608M(0603)	Thick Film Resistors, 100 Ohms, ±1%, 1/8W	
R28	KOA	1	RK73H1JTTD3001F	1608M(0603)	Thick Film Resistors, 3kOhms, ±1%, 1/8W	
R2, R16, R27	KOA	3	RK73H1JTTD1002F	1608M(0603)	Thick Film Resistors, 10kOhms, ±1%, 1/10W	
R13, R26	KOA	2	RK73H1JTTD1302F	1608M(0603)	Thick Film Resistors, 13kOhms, ±1%, 1/10W	
R12, R25	KOA	2	RK73H1JTTD1003F	1608M(0603)	Thick Film Resistors, 100kOhms, ±1%, 1/10W	
R11, R24	KOA	2	RK73H1JTTD1004F	1608M(0603)	Thick Film Resistors, 1MOhms, ±1%, 1/10W	
C7, C14	Murata	2	GCM1885C2A102JA16D	1608M(0603)	Ceramic Capacitor, 1000pF, ±5%, 100V, C0G	
C2, C3, C5, C9, C10, C12	Murata	6	GCM188R91E104KA37D	1608M(0603)	Ceramic Capacitor, 0.1uF, ±10%, 25V, X8R	
C6, C13	Murata	2	GCM188R71E105KA64D	1608M(0603)	Ceramic Capacitor, 1u, ±10%, 25V, X7R	
C1, C4, C8, C11	Murata	4	GRM21BR61E106KA73K	2012M(0805)	Ceramic Capacitor, 10u, ±10%, 25V, X5R	
L1, L4	Wurth Elektronik	2	74404032150	3.0x3.0x1.5mm	15uH, Semi-Shielded Drum Core, Wirewound Inductor, 730mA, 300mOhm	
L2, L3	Wurth Elektronik	2	782631141	1608M(0603)	Ferrite Bead, 120Ohms@100MHz, 2A, Power Line	
	Murata	2	BLM18PG121SN1D	1608M(0603)	Ferrite Bead, 120Ohms@100MHz, 2A, Power Line	Alternative
D1, D2	TOSHIBA	2	CUS05S40,H3F	USC	Schottky diode, IF=1A, VF=0.32V, VR=40V	
D3	Toshiba	1	DF2B7AFU,H3F	USC	TVS diode, 20V Clamp, 4A(8/20μs) Ipp	
LED1, LED2, LED3, LED4	Cree LED	4	JB2835BWT-N-U27EA0000-N000P001	3528M(1411)	LED Lighting J White, Warm 2700K 3-Step MacAdam Ellipse 2.7V 55mA 120°	
LED5, LED6, LED7, LED8	Cree LED	4	JB2835BWT-N-U65EA0000-N000P001	3528M(1411)	LED Lighting J White, Cool 6500K 3-Step MacAdam Ellipse 2.7V 55mA 120°	
LED9, LED10	Wurth Elektronik	2	150060VS75000	1608M(0603)	Green LED (570nm), VF=2V	
VA1, VA2	Wurth Elektronik	2	82556250	1608M(0603)	Varistor, 39V, 30A	
U1, U2	TI	2	TPS922052DYYR	14-SOT-23-THIN	LED Driver IC, 1 Output DC DC Regulator (Buck), Analog and PWM Dimming, 2A	
U3, U4, U5, U6, U7, U8, U9, U10, U11, U12	Worldsemi	10	WS2812B	5.0x5.0mm	Addressable Lighting (RGB), 5V	Option
	iPixel LED Light	10	SK6812RGB	5.0x5.0mm	Addressable Lighting (RGB), 5V	Alternative
	iPixel LED Light	10	SK6812RGBW-BW	5.0x5.0mm	Addressable Lighting (RGBW), Blue White(6000K-7000K), 5V	Option
	iPixel LED Light	10	SK6812RGBW-NW	5.0x5.0mm	Addressable Lighting (RGBW), Natural White(4000K-4500K), 5V	Option
	iPixel LED Light	10	SK6812RGBW-WS	5.0x5.0mm	Addressable Lighting (RGBW), Warm Sunlight(2700K-3000K), 5V	Option
	Wurth Elektronik	10	1315050930002	5.0x5.0mm	Addressable Lighting (RGB), 5V	Alternative, Note the mounting orientation
CN1	JST	1	S10B-PHDSS		Connector Header Through Hole, Right Angle, 10 position, 2.00mm	
TP1	MAC-8	1	HK-3-G	2.0x1.25mm	Surface-mount test terminals	
R1, R8, R14, R21	KOA	4	RK73Z1JTTD	1608M(0603)	Thick Film Resistors, 0 Ohm Jumper, 1A	DNF
R4, R5, R6, R10, R17, R18, R20, R23	KOA	8	RK73H1JTTD1002F	1608M(0603)	Thick Film Resistors, 10kOhms, ±1%, 1/10W	DNF