

Content of src/components/ui/badge.tsx

```
import * as React from "react"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@lib/utls"

const badgeVariants = cva(
  "inline-flex items-center rounded-full border px-2.5 py-0.5 text-xs font-semibold transition-colors focus:outline-none focus:ring-2 focus:ring-ring focus:ring-offset-2",
  {
    variants: {
      variant: {
        default:
          "border-transparent bg-primary text-primary-foreground hover:bg-primary/80",
        secondary:
          "border-transparent bg-secondary text-secondary-foreground hover:bg-secondary/80",
        destructive:
          "border-transparent bg-destructive text-destructive-foreground hover:bg-destructive/80",
        outline: "text-foreground",
      },
    },
    defaultVariants: {
      variant: "default",
    },
  }
)

export interface BadgeProps
  extends React.HTMLAttributes<HTMLDivElement>,
    VariantProps<typeof badgeVariants> {}

function Badge({ className, variant, ...props }: BadgeProps) {
  return (
    <div className={cn(badgeVariants({ variant }), className)} {...props} />
  )
}

export { Badge, badgeVariants }
```

Content of src/components/ui/button.tsx

```
import * as React from "react"
import { Slot } from "@radix-ui/react-slot"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@lib/utlis"

const buttonVariants = cva(
  "inline-flex items-center justify-center whitespace-nowrap rounded-md text-sm font-medium ring-offset-background transition-colors focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-ring focus-visible:ring-offset-2 disabled:pointer-events-none disabled:opacity-50",
  {
    variants: {
      variant: {
        default: "bg-primary text-primary-foreground hover:bg-primary/90",
        destructive:
          "bg-destructive text-destructive-foreground hover:bg-destructive/90",
        outline:
          "border border-input bg-background hover:bg-accent hover:text-accent-foreground",
        secondary:
          "bg-secondary text-secondary-foreground hover:bg-secondary/80",
        ghost: "hover:bg-accent hover:text-accent-foreground",
        link: "text-primary underline-offset-4 hover:underline",
      },
      size: {
        default: "h-10 px-4 py-2",
        sm: "h-9 rounded-md px-3",
        lg: "h-11 rounded-md px-8",
        icon: "h-10 w-10",
      },
    },
    defaultVariants: {
      variant: "default",
      size: "default",
    },
  },
)

export interface ButtonProps
  extends React.ButtonHTMLAttributes<HTMLButtonElement>,
    VariantProps<typeof buttonVariants> {
  asChild?: boolean
}

const Button = React.forwardRef<HTMLButtonElement, ButtonProps>(
  ({ className, variant, size, asChild = false, ...props }, ref) => {
    const Comp = asChild ? Slot : "button"
    return (
      <Comp
        className={cn(buttonVariants({ variant, size, className }))}
        ref={ref}
        {...props}
      />
    )
  }
)
```

```
    }  
  )  
  Button.displayName = "Button"  
  export { Button, buttonVariants }
```

Content of src/components/ui/checkbox.tsx

"use client"

```
import * as React from "react"
import { Check } from "lucide-react"
```

```
import { cn } from "@lib/Utils"
```

```
// B >Ct4C 5CÂ AC$>C' :Cä<Cô>CÔ5CÔB Checkbox, CÔ5 C,ACô>C' LCtCDò 1C,,1C'8CäBCT:D2 adix-ui/react-checkbo
```

```
export interface CheckboxProps extends React.InputHTMLAttributes<HTMLInputElement> {
  checked?: boolean;
  onCheckedChange?: (checked: boolean) => void;
}
```

```
export const Checkbox = React.forwardRef<HTMLDivElement, CheckboxProps>(
  ({ className, checked, onCheckedChange, ...props }, ref) => {
    const handleClick = () => {
      onCheckedChange?.(!checked);
    };

```

```
    return (
      <div
        ref={ref}
        className={cn(
          "peer h-4 w-4 shrink-0 rounded-sm border border-gray-400 ring-offset-background focus-
visible:outline-none focus-visible:ring-2 focus-visible:ring-ring focus-visible:ring-offset-2 disabled:cursor-
not-allowed disabled:opacity-50 flex items-center justify-center",
          checked && "bg-blue-500 border-blue-500 text-white",
          className
        )}
        onClick={handleClick}
      >
        {checked && <Check className="h-3 w-3 text-white" />}
        <input
          type="checkbox"
          checked={checked}
          onChange={(e) => onCheckedChange?.(e.target.checked)}
          className="sr-only"
          {...props}
        />
      </div>
    );
  }
);
Checkbox.displayName = "Checkbox"
```

Content of src/components/ui/dialog.tsx

"use client"

```
import * as React from "react"
import * as DialogPrimitive from "@radix-ui/react-dialog"
import { X } from "lucide-react"
```

```
import { cn } from "@lib/utls"
```

```
const Dialog = DialogPrimitive.Root
```

```
const DialogTrigger = DialogPrimitive.Trigger
```

```
const DialogPortal = ({
  ...props
}: DialogPrimitive.DialogPortalProps) => (
  <DialogPrimitive.Portal {...props} />
)
DialogPortal.displayName = DialogPrimitive.Portal.displayName
```

```
const DialogOverlay = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Overlay>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Overlay>
>(({ className, ...props }, ref) => (
  <DialogPrimitive.Overlay
    ref={ref}
    className={cn(
      "fixed inset-0 z-50 bg-black/70 backdrop-blur-sm data-[state=open]:animate-in data-
[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0",
      className
    )}
    {...props}
  />
))
DialogOverlay.displayName = DialogPrimitive.Overlay.displayName
```

```
const DialogContent = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Content>
>(({ className, children, ...props }, ref) => (
  <DialogPortal>
    <DialogOverlay />
    <DialogPrimitive.Content
      ref={ref}
      className={cn(
        "fixed left-[50%] top-[50%] z-50 grid w-full max-w-lg translate-x-[-50%] translate-y-[-50%] gap-4
border bg-background p-6 shadow-lg duration-200 data-[state=open]:animate-in data-
[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-
[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[state=closed]:slide-out-to-left-1/2 data-
[state=closed]:slide-out-to-top-[48%] data-[state=open]:slide-in-from-left-1/2 data-[state=open]:slide-in-
from-top-[48%] sm:rounded-lg md:w-full",
        className
      )}
      {...props}
    />
  />
))
```

```

    >
    {children}
    <DialogPrimitive.Close className="absolute right-4 top-4 rounded-sm opacity-70 ring-offset-
background transition-opacity hover:opacity-100 focus:outline-none focus:ring-2 focus:ring-ring focus:ring-
offset-2 disabled:pointer-events-none data-[state=open]:bg-accent data-[state=open]:text-muted-
foreground">
      <X className="h-4 w-4" />
      <span className="sr-only">Close</span>
    </DialogPrimitive.Close>
  </DialogPrimitive.Content>
</DialogPortal>
))
DialogContent.displayName = DialogPrimitive.Content.displayName

const DialogHeader = ({
  className,
  ...props
}): React.HTMLAttributes<HTMLDivElement> => (
  <div
    className={cn(
      "flex flex-col space-y-1.5 text-center sm:text-left",
      className
    )}
    {...props}
  />
)
DialogHeader.displayName = "DialogHeader"

const DialogFooter = ({
  className,
  ...props
}): React.HTMLAttributes<HTMLDivElement> => (
  <div
    className={cn(
      "flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2",
      className
    )}
    {...props}
  />
)
DialogFooter.displayName = "DialogFooter"

const DialogTitle = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Title>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Title>
>(({ className, ...props }, ref) => (
  <DialogPrimitive.Title
    ref={ref}
    className={cn(
      "text-lg font-semibold leading-none tracking-tight",
      className
    )}
    {...props}
  />
))
DialogTitle.displayName = DialogPrimitive.Title.displayName

```

```
const DialogDescription = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Description>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Description>
>(({ className, ...props }, ref) => (
  <DialogPrimitive.Description
    ref={ref}
    className={cn("text-sm text-muted-foreground", className)}
    {...props}
  />
))
DialogDescription.displayName = DialogPrimitive.Description.displayName

export {
  Dialog,
  DialogTrigger,
  DialogContent,
  DialogHeader,
  DialogFooter,
  DialogTitle,
  DialogDescription,
}
```

Content of src/components/ui/dropdown-menu.tsx

```
"use client"

import * as React from "react"
import * as DropdownMenuPrimitive from "@radix-ui/react-dropdown-menu"
import { Check, ChevronRight, Circle } from "lucide-react"

import { cn } from "@lib/utils"

const DropdownMenu = DropdownMenuPrimitive.Root

const DropdownMenuTrigger = DropdownMenuPrimitive.Trigger

const DropdownMenuGroup = DropdownMenuPrimitive.Group

const DropdownMenuPortal = DropdownMenuPrimitive.Portal

const DropdownMenuSub = DropdownMenuPrimitive.Sub

const DropdownMenuRadioGroup = DropdownMenuPrimitive.RadioGroup

const DropdownMenuSubTrigger = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.SubTrigger>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.SubTrigger> & {
    inset?: boolean
  }
>(({ className, inset, children, ...props }, ref) => (
  <DropdownMenuPrimitive.SubTrigger
    ref={ref}
    className={cn(
      "flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none focus:bg-
accent data-[state=open]:bg-accent",
      inset && "pl-8",
      className
    )}
    {...props}
  >
    {children}
    <ChevronRight className="ml-auto h-4 w-4" />
  </DropdownMenuPrimitive.SubTrigger>
))
DropdownMenuSubTrigger.displayName =
  DropdownMenuPrimitive.SubTrigger.displayName

const DropdownMenuSubContent = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.SubContent>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.SubContent>
>(({ className, ...props }, ref) => (
  <DropdownMenuPrimitive.SubContent
    ref={ref}
    className={cn(
      "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground
shadow-md animate-in data-[side=bottom]:slide-in-from-top-1 data-[side=left]:slide-in-from-right-1 data-
[side=right]:slide-in-from-left-1 data-[side=top]:slide-in-from-bottom-1",
      className
    )}
    {...props}
  >
    {children}
  </DropdownMenuPrimitive.SubContent>
))
DropdownMenuSubContent.displayName =
  DropdownMenuPrimitive.SubContent.displayName
```



```

    className
  })
  {...props}
/>
))
DropdownMenuSubContent.displayName =
  DropdownMenuPrimitive.SubContent.displayName

const DropdownMenuContent = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Content>
>(({ className, sideOffset = 4, ...props }, ref) => (
  <DropdownMenuPrimitive.Portal>
    <DropdownMenuPrimitive.Content
      ref={ref}
      sideOffset={sideOffset}
      className={cn(
        "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground
        shadow-md animate-in data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-right-2 data-
        [side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2",
        className
      )}
      {...props}
    />
  </DropdownMenuPrimitive.Portal>
))
DropdownMenuContent.displayName = DropdownMenuPrimitive.Content.displayName

const DropdownMenuItem = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Item> & {
    inset?: boolean
  }
>(({ className, inset, ...props }, ref) => (
  <DropdownMenuPrimitive.Item
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none
      transition-colors focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-
      [disabled]:opacity-50",
      inset && "pl-8",
      className
    )}
    {...props}
  />
))
DropdownMenuItem.displayName = DropdownMenuPrimitive.Item.displayName

const DropdownMenuCheckboxItem = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.CheckboxItem>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.CheckboxItem>
>(({ className, children, checked, ...props }, ref) => (
  <DropdownMenuPrimitive.CheckboxItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-

```

```
none transition-colors focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none
data-[disabled]:opacity-50",
```

```
  className
)}
checked={checked}
{...props}
>
  <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
    <DropdownMenuPrimitive.ItemIndicator>
      <Check className="h-4 w-4" />
    </DropdownMenuPrimitive.ItemIndicator>
  </span>
  {children}
</DropdownMenuPrimitive.CheckboxItem>
))
```

```
DropdownMenuCheckboxItem.displayName =
  DropdownMenuPrimitive.CheckboxItem.displayName
```

```
const DropdownMenuRadioItem = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.RadioItem>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.RadioItem>
>(({ className, children, ...props }, ref) => (
```

```
  <DropdownMenuPrimitive.RadioItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-
none transition-colors focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none
data-[disabled]:opacity-50",
      className
    )}
    {...props}
  >
```

```
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <DropdownMenuPrimitive.ItemIndicator>
        <Circle className="h-2 w-2 fill-current" />
      </DropdownMenuPrimitive.ItemIndicator>
    </span>
    {children}
  </DropdownMenuPrimitive.RadioItem>
))
```

```
DropdownMenuRadioItem.displayName = DropdownMenuPrimitive.RadioItem.displayName
```

```
const DropdownMenuLabel = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.Label>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Label> & {
    inset?: boolean
  }
>(({ className, inset, ...props }, ref) => (
```

```
  <DropdownMenuPrimitive.Label
    ref={ref}
    className={cn(
      "px-2 py-1.5 text-sm font-semibold",
      inset && "pl-8",
      className
    )}
    {...props}
  >
```

```

    />
  ))
  DropdownMenuLabel.displayName = DropdownMenuPrimitive.Label.displayName

  const DropdownMenuSeparator = React.forwardRef<
    React.ElementRef<typeof DropdownMenuPrimitive.Separator>,
    React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Separator>
  >(({ className, ...props }, ref) => (
    <DropdownMenuPrimitive.Separator
      ref={ref}
      className={cn("-mx-1 my-1 h-px bg-muted", className)}
      {...props}
    />
  ))
  DropdownMenuSeparator.displayName = DropdownMenuPrimitive.Separator.displayName

  const DropdownMenuShortcut = ({
    className,
    ...props
  }: React.HTMLAttributes<HTMLSpanElement>) => {
    return (
      <span
        className={cn("ml-auto text-xs tracking-widest opacity-60", className)}
        {...props}
      />
    )
  }
  DropdownMenuShortcut.displayName = "DropdownMenuShortcut"

  export {
    DropdownMenu,
    DropdownMenuTrigger,
    DropdownMenuContent,
    DropdownMenuItem,
    DropdownMenuCheckboxItem,
    DropdownMenuRadioItem,
    DropdownMenuLabel,
    DropdownMenuSeparator,
    DropdownMenuShortcut,
    DropdownMenuGroup,
    DropdownMenuPortal,
    DropdownMenuSub,
    DropdownMenuSubContent,
    DropdownMenuSubTrigger,
    DropdownMenuRadioGroup,
  }

```

Content of src/components/ui/input.tsx

```
import * as React from "react"

import { cn } from "@lib/utls"

export interface InputProps
  extends React.InputHTMLAttributes<HTMLInputElement> {}

const Input = React.forwardRef<HTMLInputElement, InputProps>(
  ({ className, type, ...props }, ref) => {
    return (
      <input
        type={type}
        className={cn(
          "flex h-10 w-full rounded-md border border-input bg-background px-3 py-2 text-sm ring-offset-
background file:border-0 file:bg-transparent file:text-sm file:font-medium placeholder:text-muted-
foreground focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-ring focus-visible:ring-offset-2
disabled:cursor-not-allowed disabled:opacity-50",
          className
        )}
        ref={ref}
        {...props}
      />
    )
  }
)
Input.displayName = "Input"

export { Input }
```

Content of src/components/ui/label.tsx

```
"use client"

import * as React from "react"
import * as LabelPrimitive from "@radix-ui/react-label"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@lib/utls"

const labelVariants = cva(
  "text-sm font-medium leading-none peer-disabled:cursor-not-allowed peer-disabled:opacity-70"
)

const Label = React.forwardRef<
  React.ElementRef<typeof LabelPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof LabelPrimitive.Root> &
  VariantProps<typeof labelVariants>
>(({ className, ...props }, ref) => (
  <LabelPrimitive.Root
    ref={ref}
    className={cn(labelVariants(), className)}
    {...props}
  />
))
Label.displayName = LabelPrimitive.Root.displayName

export { Label }
```

Content of src/components/ui/switch.tsx

```
"use client"

import * as React from "react"
import * as SwitchPrimitives from "@radix-ui/react-switch"

import { cn } from "@lib/utils"

const Switch = React.forwardRef<
  React.ElementRef<typeof SwitchPrimitives.Root>,
  React.ComponentPropsWithoutRef<typeof SwitchPrimitives.Root>
>(({ className, ...props }, ref) => (
  <SwitchPrimitives.Root
    className={cn(
      "peer inline-flex h-6 w-11 shrink-0 cursor-pointer items-center rounded-full border-2 border-transparent transition-colors focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-ring focus-visible:ring-offset-2 focus-visible:ring-offset-background disabled:cursor-not-allowed disabled:opacity-50 data-[state=checked]:bg-primary data-[state=unchecked]:bg-input",
      className
    )}
    {...props}
    ref={ref}
  >
    <SwitchPrimitives.Thumb
      className={cn(
        "pointer-events-none block h-5 w-5 rounded-full bg-background shadow-lg ring-0 transition-transform data-[state=checked]:translate-x-5 data-[state=unchecked]:translate-x-0"
      )}
    />
  </SwitchPrimitives.Root>
))
Switch.displayName = SwitchPrimitives.Root.displayName

export { Switch }
```

Content of src/components/ui/tabs.tsx

```
"use client"

import * as React from "react"
import * as TabsPrimitive from "@radix-ui/react-tabs"

import { cn } from "@lib/utils"

const Tabs = TabsPrimitive.Root

const TabsList = React.forwardRef<
  React.ElementRef<typeof TabsPrimitive.List>,
  React.ComponentPropsWithoutRef<typeof TabsPrimitive.List>
>(({ className, ...props }, ref) => (
  <TabsPrimitive.List
    ref={ref}
    className={cn(
      "inline-flex h-10 items-center justify-center rounded-md bg-muted p-1 text-muted-foreground",
      className
    )}
    {...props}
  />
))
TabsList.displayName = TabsPrimitive.List.displayName

const TabsTrigger = React.forwardRef<
  React.ElementRef<typeof TabsPrimitive.Trigger>,
  React.ComponentPropsWithoutRef<typeof TabsPrimitive.Trigger>
>(({ className, ...props }, ref) => (
  <TabsPrimitive.Trigger
    ref={ref}
    className={cn(
      "inline-flex items-center justify-center whitespace-nowrap rounded-sm px-3 py-1.5 text-sm font-
medium ring-offset-background transition-all focus-visible:outline-none focus-visible:ring-2 focus-
visible:ring-ring focus-visible:ring-offset-2 disabled:pointer-events-none disabled:opacity-50 data-
[state=active]:bg-background data-[state=active]:text-foreground data-[state=active]:shadow-sm",
      className
    )}
    {...props}
  />
))
TabsTrigger.displayName = TabsPrimitive.Trigger.displayName

const TabsContent = React.forwardRef<
  React.ElementRef<typeof TabsPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof TabsPrimitive.Content>
>(({ className, ...props }, ref) => (
  <TabsPrimitive.Content
    ref={ref}
    className={cn(
      "mt-2 ring-offset-background focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-ring
focus-visible:ring-offset-2",
      className
    )}
  />
))
```

```
    {...props}  
  />  
))  
TabsContent.displayName = TabsPrimitive.Content.displayName  
  
export { Tabs, TabsList, TabsTrigger, TabsContent }
```


Content of src/components/ui/textarea.tsx

```
import * as React from "react"

import { cn } from "@lib/utls"

export interface TextareaProps
  extends React.TextareaHTMLAttributes<HTMLTextAreaElement> {}

const Textarea = React.forwardRef<HTMLTextAreaElement, TextareaProps>(
  ({ className, ...props }, ref) => {
    return (
      <textarea
        className={cn(
          "flex min-h-[80px] w-full rounded-md border border-input bg-transparent px-3 py-2 text-sm ring-
offset-background placeholder:text-muted-foreground focus-visible:outline-none focus-visible:ring-2 focus-
visible:ring-ring focus-visible:ring-offset-2 disabled:cursor-not-allowed disabled:opacity-50",
          className
        )}
        ref={ref}
        {...props}
      />
    )
  }
)
Textarea.displayName = "Textarea"

export { Textarea }
```

Content of src/components/ui/toast.tsx

```
"use client"

import * as React from "react"
import * as ToastPrimitives from "@radix-ui/react-toast"
import { cva, type VariantProps } from "class-variance-authority"
import { X } from "lucide-react"

import { cn } from "@lib/utls"

const ToastProvider = ToastPrimitives.Provider

const ToastViewport = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Viewport>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Viewport>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Viewport
    ref={ref}
    className={cn(
      "fixed top-0 z-[100] flex max-h-screen w-full flex-col-reverse p-4 sm:bottom-0 sm:right-0 sm:top-auto
sm:flex-col md:max-w-[420px]",
      className
    )}
    {...props}
  />
))
ToastViewport.displayName = ToastPrimitives.Viewport.displayName

const toastVariants = cva(
  "group pointer-events-auto relative flex w-full items-center justify-between space-x-4 overflow-hidden
rounded-md border p-6 pr-8 shadow-lg transition-all data-[swipe=cancel]:translate-x-0 data-
[swipe=end]:translate-x-[var(--radix-toast-swipe-end-x)] data-[swipe=move]:translate-x-[var(--radix-toast-
swipe-move-x)] data-[swipe=move]:transition-none data-[state=open]:animate-in data-
[state=closed]:animate-out data-[swipe=end]:animate-out data-[state=closed]:fade-out-80 data-
[state=closed]:slide-out-to-right-full data-[state=open]:slide-in-from-top-full data-[state=open]:sm:slide-in-
from-bottom-full",
  {
    variants: {
      variant: {
        default: "border bg-background text-foreground",
        destructive:
          "destructive group border-destructive bg-destructive text-destructive-foreground",
      },
    },
    defaultVariants: {
      variant: "default",
    },
  }
)

const Toast = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Root>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Root> &
  VariantProps<typeof toastVariants>
>
```

```

>(({ className, variant, ...props }, ref) => {
  return (
    <ToastPrimitives.Root
      ref={ref}
      className={cn(toastVariants({ variant }), className)}
      {...props}
    />
  )
})
Toast.displayName = ToastPrimitives.Root.displayName

const ToastAction = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Action>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Action>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Action
    ref={ref}
    className={cn(
      "inline-flex h-8 shrink-0 items-center justify-center rounded-md border bg-transparent px-3 text-sm
font-medium ring-offset-background transition-colors hover:bg-secondary focus:outline-none focus:ring-2
focus:ring-ring focus:ring-offset-2 disabled:pointer-events-none disabled:opacity-50 group-
[.destructive]:border-muted/40 group-[.destructive]:hover:border-destructive/30 group-
[.destructive]:hover:bg-destructive group-[.destructive]:hover:text-destructive-foreground group-
[.destructive]:focus:ring-destructive",
      className
    )}
    {...props}
  />
))
ToastAction.displayName = ToastPrimitives.Action.displayName

const ToastClose = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Close>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Close>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Close
    ref={ref}
    className={cn(
      "absolute right-2 top-2 rounded-md p-1 text-foreground/50 opacity-0 transition-opacity hover:text-
foreground focus:opacity-100 focus:outline-none focus:ring-2 group-hover:opacity-100 group-
[.destructive]:text-red-300 group-[.destructive]:hover:text-red-50 group-[.destructive]:focus:ring-red-400
group-[.destructive]:focus:ring-offset-red-600",
      className
    )}
    toast-close=""
    {...props}
  >
    <X className="h-4 w-4" />
  </ToastPrimitives.Close>
))
ToastClose.displayName = ToastPrimitives.Close.displayName

const ToastTitle = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Title>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Title>
>(({ className, ...props }, ref) => (

```

```

    <ToastPrimitives.Title
      ref={ref}
      className={cn("text-sm font-semibold", className)}
      {...props}
    />
  ))
  ToastTitle.displayName = ToastPrimitives.Title.displayName

const ToastDescription = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Description>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Description>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Description
    ref={ref}
    className={cn("text-sm opacity-90", className)}
    {...props}
  />
))
ToastDescription.displayName = ToastPrimitives.Description.displayName

type ToastProps = React.ComponentPropsWithoutRef<typeof Toast>

type ToastActionElement = React.ReactElement<typeof ToastAction>

export {
  type ToastProps,
  type ToastActionElement,
  ToastProvider,
  ToastViewport,
  Toast,
  ToastTitle,
  ToastDescription,
  ToastClose,
  ToastAction,
}

```

Content of src/components/ui/toaster.tsx

```
"use client"

import {
  Toast,
  ToastClose,
  ToastDescription,
  ToastProvider,
  ToastTitle,
  ToastViewport,
} from "@components/ui/toast"
import { useToast } from "@components/ui/use-toast"

export function Toaster() {
  const { toasts } = useToast()

  return (
    <ToastProvider>
      {toasts.map(function ({ id, title, description, action, ...props }) {
        return (
          <Toast key={id} {...props}>
            <div className="grid gap-1">
              {title && <ToastTitle>{title}</ToastTitle>}
              {description && (
                <ToastDescription>{description}</ToastDescription>
              )}
            </div>
            {action}
            <ToastClose />
          </Toast>
        )
      })}
    <ToastViewport />
  </ToastProvider>
)
```

Content of src/components/ui/use-toast.ts

```
"use client"

import * as React from "react"

import type {
  ToastActionElement,
  ToastProps,
} from "@components/ui/toast"

const TOAST_LIMIT = 5
const TOAST_REMOVE_DELAY = 1000000

type ToasterToast = ToastProps & {
  id: string
  title?: React.ReactNode
  description?: React.ReactNode
  action?: ToastActionElement
}

const actionTypes = {
  ADD_TOAST: "ADD_TOAST",
  UPDATE_TOAST: "UPDATE_TOAST",
  DISMISS_TOAST: "DISMISS_TOAST",
  REMOVE_TOAST: "REMOVE_TOAST",
} as const

let count = 0

function genId() {
  count = (count + 1) % Number.MAX_SAFE_INTEGER
  return count.toString()
}

type ActionType = typeof actionTypes

type Action =
  | {
    type: ActionType["ADD_TOAST"]
    toast: ToasterToast
  }
  | {
    type: ActionType["UPDATE_TOAST"]
    toast: Partial<ToasterToast>
  }
  | {
    type: ActionType["DISMISS_TOAST"]
    toastId?: string
  }
  | {
    type: ActionType["REMOVE_TOAST"]
    toastId?: string
  }
```

```
interface State {
  toasts: ToasterToast[]
}
```

```
const toastTimeouts = new Map<string, ReturnType<typeof setTimeout>>()
```

```
const reducer = (state: State, action: Action): State => {
  switch (action.type) {
    case actionTypes.ADD_TOAST:
      return {
        ...state,
        toasts: [action.toast, ...state.toasts].slice(0, TOAST_LIMIT),
      }

```

```
    case actionTypes.UPDATE_TOAST:
      return {
        ...state,
        toasts: state.toasts.map((t) =>
          t.id === action.toast.id ? { ...t, ...action.toast } : t
        ),
      }

```

```
    case actionTypes.DISMISS_TOAST: {
      const { toastId } = action

```

```
      // ! Side effects ! - This could be extracted into a dismissToast() action,
      // but I'll keep it here for simplicity
      if (toastId) {
        toastTimeouts.set(
          toastId,
          setTimeout(() => {
            toastTimeouts.delete(toastId)
            dispatch({
              type: actionTypes.REMOVE_TOAST,
              toastId,
            })
          }, TOAST_REMOVE_DELAY)
        )
      }

```

```
      return {
        ...state,
        toasts: state.toasts.map((t) =>
          t.id === toastId || toastId === undefined
            ? {
                ...t,
                open: false,
              }
            : t
        ),
      }

```

```
    case actionTypes.REMOVE_TOAST:
      if (action.toastId === undefined) {
        return {
          ...state,

```

```

        toasts: [],
      }
    }
    return {
      ...state,
      toasts: state.toasts.filter((t) => t.id !== action.toastId),
    }
  }
}

```

```
const listeners: Array<(state: State) => void> = []
```

```
let memoryState: State = { toasts: [] }
```

```
function dispatch(action: Action) {
  memoryState = reducer(memoryState, action)
  listeners.forEach((listener) => {
    listener(memoryState)
  })
}

```

```
type Toast = Omit<ToasterToast, "id">
```

```
function toast({ ...props }: Toast) {
  const id = genId()

```

```

  const update = (props: ToasterToast) =>
    dispatch({
      type: actionTypes.UPDATE_TOAST,
      toast: { ...props, id },
    })

```

```
const dismiss = () => dispatch({ type: actionTypes.DISMISS_TOAST, toastId: id })
```

```

dispatch({
  type: actionTypes.ADD_TOAST,
  toast: {
    ...props,
    id,
    open: true,
    onOpenChange: (open) => {
      if (!open) dismiss()
    },
  },
})

```

```

return {
  id,
  dismiss,
  update,
}
}

```

```
function useToast() {
  const [state, setState] = React.useState<State>(memoryState)

```

```
  React.useEffect(() => {
```



```
listeners.push(setState)
return () => {
  const index = listeners.indexOf(setState)
  if (index > -1) {
    listeners.splice(index, 1)
  }
}
}, [state])

return {
  ...state,
  toast,
  dismiss: (toastId?: string) => dispatch({ type: actionTypes.DISMISS_TOAST, toastId }),
}
}

export { useToast, toast }
```

Content of src/components/config-panel.tsx

"use client"

```
import React from 'react';
import { Switch } from "@components/ui/switch";
import { Button } from "@components/ui/button";
import { Input } from "@components/ui/input";
import { Label } from "@components/ui/label";
import { cn } from "@lib/utls";
import { OpenFileButton } from "../open-file-button";
```

```
interface ConfigPanelProps {
  includeComments: boolean;
  onIncludeCommentsChange: (value: boolean) => void;
  newPageForEachFile: boolean;
  onNewPageForEachFileChange: (value: boolean) => void;
  outputFileName: string;
  onOutputFileNameChange: (value: string) => void;
  onGenerate: () => void;
  selectedFilesCount: number;
  lastGeneratedPdfPath?: string;
}
```

```
export function ConfigPanel({
  includeComments,
  onIncludeCommentsChange,
  newPageForEachFile,
  onNewPageForEachFileChange,
  outputFileName,
  onOutputFileNameChange,
  onGenerate,
  selectedFilesCount,
  lastGeneratedPdfPath
```

```
}: ConfigPanelProps) {
  // Aä?D 5CD5C´OCT< CðCD$ L CD;Dð 2D´2Cä4C DC 9C´0 (CD;Dð 8D ?Cä;DÄ7Cä2C =C„O C" :CÔ>Cô:CR >D$:D KD
  // A„ACð>C´LCtCCT< D$>C´LCα> D CD"5D BC$CDäIC„9 CðCD$ L, CTAC´8 Cä= CTAD$ L
  const pdfPath = lastGeneratedPdfPath || "";
  return (
```

```
    <div className="border border-gray-700 rounded-md p-4 space-y-4 bg-gray-800">
      <h2 className="text-lg font-semibold text-gray-100">AÔ0D BD >C":C, 3CT=CT@C FC„8</h2>
```

```
    <div className="space-y-4">
```

```
      <div className="flex items-center justify-between">
```

```
        <Label htmlFor="include-comments" className="text-gray-200">A$:C´NDt8D$ L Cα>CÄ<CT=D$0D 8Cf ÂôÆ &VÃä
```

```
        <Switch
```

```
          id="include-comments"
```

```
          checked={includeComments}
```

```
          onChange={onIncludeCommentsChange}
```

```
          className="data-[state=checked]:bg-blue-600"
```

```
        />
```

```
      </div>
```

```
    <div className="flex items-center justify-between">
```

```
      <Label htmlFor="new-page" className="text-gray-200">AÔ>C$0Dð AD$@C =C„FC 4C´O Cα0Cd4Cä3Câ DC 9C´
```

```

<Switch
  id="new-page"
  checked={newPageForEachFile}
  onCheckedChange={onNewPageForEachFileChange}
  className="data-[state=checked]:bg-blue-600"
/>
</div>

<div className="space-y-2">
  <Label htmlFor="output-file" className="text-gray-200">A,,<Dò 2D´ECä4CÔ>C4> DD0C";C ÂôÆ &VÃà
  <Input
    id="output-file"
    value={outputFileName}
    onChange={(e) => onOutputFileNameChange(e.target.value)}
    placeholder="project_code.pdf"
    className="bg-gray-700 border-gray-600 text-gray-200 focus:ring-blue-500 focus:border-
blue-500"
  />
</div>
</div>

<div className="pt-2">
  <div className="flex gap-2">
    <Button
      onClick={onGenerate}
      disabled={selectedFilesCount === 0}
      className={cn(
        "flex-1",
        selectedFilesCount === 0
          ? "bg-gray-600 cursor-not-allowed opacity-70"
          : "bg-blue-600 hover:bg-blue-700 text-white"
      )}
    >
      B 3CT=CT@C,,@Cä2C BDÂ Dg·6VÆV7FVDf–ÆW46÷VçB â ò ,G·6VÆV7FVDf–ÆW46÷VçGÒ DC 9C´>C"– '
    </Button>

    {pdfPath && (
      <OpenFileButton
        filePath={pdfPath}
        variant="outline"
        size="default"
        className="bg-gray-700 hover:bg-gray-600 border-gray-600 text-gray-200 px-3"
        tooltipText="AâBCα@D´BDÂ AC45CÔ5D 8D >C$0CÔ=D´9 PDF"
      />
    )}
  </div>
</div>
</div>
);
}

```

Content of src/components/editable-list.tsx

```
'use client';

import React, { useState } from 'react';
import { X, Plus } from 'lucide-react';
import { Button } from '@components/ui/button';
import { Input } from '@components/ui/input';

interface EditableListProps {
  items: string[];
  onItemsChange: (items: string[]) => void;
  placeholder?: string;
  badgeVariant?: 'default' | 'secondary' | 'destructive';
  validateItem?: (item: string) => boolean;
  errorMessage?: string;
}

export function EditableList({
  items,
  onItemsChange,
  placeholder = 'Add item...',
  badgeVariant = 'default',
  validateItem,
  errorMessage = 'Invalid input',
}: EditableListProps) {
  const [newItem, setNewItem] = useState('');
  const [error, setError] = useState<string | null>(null);

  const handleAddItem = () => {
    if (!newItem.trim()) {
      return;
    }

    if (validateItem && !validateItem(newItem)) {
      setError(errorMessage);
      return;
    }

    setError(null);
    onItemsChange([...items, newItem.trim()]);
    setNewItem('');
  };

  const handleRemoveItem = (index: number) => {
    const newItems = [...items];
    newItems.splice(index, 1);
    onItemsChange(newItems);
  };

  const handleKeyPress = (e: React.KeyboardEvent<HTMLInputElement>) => {
    if (e.key === 'Enter') {
      e.preventDefault();
      handleAddItem();
    }
  }
}
```

```

};

const getBadgeClass = () => {
  switch (badgeVariant) {
    case 'secondary':
      return 'bg-gray-700 text-gray-200 hover:bg-gray-600';
    case 'destructive':
      return 'bg-red-900/40 text-red-300 hover:bg-red-900/60';
    default:
      return 'bg-blue-900/40 text-blue-300 hover:bg-blue-900/60';
  }
};

return (
  <div>
    <div className="flex flex-wrap gap-2 mt-2 mb-3">
      {items.map((item, index) => (
        <div
          key={index}
          className={`inline-flex items-center rounded px-2 py-1 text-xs ${getBadgeClass()}`}
        >
          {item}
          <button
            type="button"
            onClick={() => handleRemoveItem(index)}
            className="ml-2 text-gray-400 hover:text-gray-200"
          >
            <X className="h-3 w-3" />
          </button>
        </div>
      ))}
      {items.length === 0 && (
        <div className="text-sm text-gray-500 italic">B ?C„ACä: CöCD B</div>
      )}
    </div>

    <div className="flex items-center gap-2">
      <Input
        value={newItem}
        onChange={(e) => {
          setNewItem(e.target.value);
          if (error) {
            setError(null);
          }
        }}
        onKeyDown={handleKeyPress}
        placeholder={placeholder}
        className="border-gray-700 bg-gray-700 text-gray-200 placeholder:text-gray-500"
      />
      <Button
        type="button"
        onClick={handleAddItem}
        disabled={!newItem.trim()}
        variant="outline"
        size="icon"
        className="bg-gray-700 border-gray-600 hover:bg-gray-600 text-gray-200"
      >

```

```
>
  <Plus className="h-4 w-4" />
</Button>
</div>

{error && <p className="text-red-400 text-xs mt-1">{error}</p>}
</div>
);
}
```

Content of src/components/file-tree.tsx

```
'use client';
```

```
import { Checkbox } from '@components/ui/checkbox';
import { formatFileSize } from '@lib/format-utils';
import type { FileNode } from '@lib/types';
import { cn } from '@lib/utls';
import { ChevronDown, ChevronRight, File, Folder } from 'lucide-react';
import React, { useState, useEffect } from 'react';
import { CodeViewer } from './code-viewer';
```

```
interface FileTreeProps {
  data: FileNode;
  onSelect: (path: string, selected: boolean) => void;
  searchQuery?: string; // AD>C 0C$;Dô5CÂ >CôFC,,>CÔ0C´LCÔKC´ ?C @C <CTBD ?Cä8D :Cä2Cä3Cä 7C ?D >D 0
}
```

```
// A,,ACô>C´LCtCCT< DT@C =C,,;C,,ICR 4C´O D >DT@C =CT=C,,O D >D BCäOCÔ8Dò @C AC¤@D´BD´E Cò0Cô>C¤ <
import { useLocalStorage } from '@lib/hooks/use-local-storage';
```

```
export function FileTree({ data, onSelect, searchQuery }: FileTreeProps) {
  // A,,ACô>C´LCtCCT< LocalStorage CD;Dò ED 0CÔ5CÔ8Dò ACäAD$>Dô=C,,O D 0D :D KD$KDR ?C ?Cä:
  const [expanded, setExpanded] = useLocalStorage<Record<string, boolean>>("file-tree-expanded-
state", {});
  const [selectedFile, setSelectedFile] = useState<string | null>(null);
  const [codeViewerOpen, setCodeViewerOpen] = useState<boolean>(false);
  const [clickTimer, setClickTimer] = useState<NodeJS.Timeout | null>(null);
```

```
// A¤>CÔAD$0CÔBC 4C´O Cä3D 0CÔ8Dt5CÔ8Dò :Cä;C,,GCTAD$2C @CT7D4;DÄBC BCä2 Cô>C,,AC¤0,
// Cò@C, :CäBCä@Cä< Cò0Cô:C, 1D44D4B C 2D$>CÄ0D$8Dt5D :C, @C AC¤@D´2C BDÄADđ
const AUTO_EXPAND_THRESHOLD = 10;
```

```
const toggleExpand = (path: string) => {
  setExpanded((prev) => ({
    ...prev,
    [path]: !prev[path],
  }));
};
```

```
// BDCCÔ:Dd8Dò 4C´O Cô>CDADt5D$0 C¤>C´8Dt5D BC$0 D >C$?C 4CT=C,,9 C" 4CT@CT2CP
const countSearchMatches = (node: FileNode, query: string): number => {
  // ATAC´8 CÔ5D" 7C ?D >D 0, C$>Ct2D 0D"0CT< 0
  if (!query) return 0;
```

```
let count = 0;
```

```
// Aô@Cä2CT@Dô5CÂÂ ACä2Cô0CD0CTB C´8 C,,<Dò BCT:D4ICT3Câ CCT;C A Ct0Cô@CäACä<
if (node.name.toLowerCase().includes(query.toLowerCase())) {
  count++;
}
```

```
// B 5C¤CD AC,,2CÔ> Cô@Cä2CT@Dô5CÂ 2D 5 CD>Dt5D =C,,5 D47C´K
if (node.children) {
  node.children.forEach((child) => {
```

```

        count += countSearchMatches(child, query);
    });
}

return count;
};

// BDCCÔ:Dd8Dò 4C´O D 0D :D KD$8Dò ?C ?Cä: D ACä2Cò0CD5CÔ8Dô<C€
const expandMatchingFolders = (node: FileNode, query: string, paths: string[] = []): string[] => {
    // ATAC´8 CÔ5D" 7C ?D >D 0 C,,;C, Cct5C² Ò =CR ?C ?C¤0, C,,;C, C CÔ5C4> CÔ5D" 4CTBCT9, Cò@CäAD$> C$>C
    if (!query || node.type !== 'directory' || !node.children) return paths;

    // Aô@Cä2CT@Dô5CÂÂ 5D BDÂ ;C, ACä2Cò0CD5CÔ8Dò AD 5CD8 CD>Dt5D =C,,E DÔ;CT<CT=D$>C
    let hasMatches = false;

    for (const child of node.children) {
        // Aô@Cä2CT@Dô5CÂ ACä2Cò0CD5CÔ8CR 8CÄ5CÔ8
        if (child.name.toLowerCase().includes(query.toLowerCase())) {
            hasMatches = true;
        }

        // Aô@Cä2CT@Dô5CÂ 4CTBCT9 D 5C¤CD AC,,2CÔ> C, 4Cä1C 2C´OCT< C,,E CòCD$8
        if (child.type === 'directory' && child.children) {
            const childPaths = expandMatchingFolders(child, query, []);
            if (childPaths.length > 0) {
                hasMatches = true;
                paths = [...paths, ...childPaths];
            }
        }
    }

    // ATAC´8 CTAD$L D >C$?C 4CT=C,,O, CD>C 0C$;Dô5CÂ BCT:D4IC,,9 CòCD$L C" ACô8D >C¢ ?D4BCT9 CD;Dò @C
    if (hasMatches) {
        paths.push(node.path);
    }

    return paths;
};

const handleSelectChange = (node: FileNode, checked: boolean) => {
    onSelect(node.path, checked);
};

// AäGC,,AD$:C BC 9CÄ5D 0 Cò@C, @C 7CÄ>CÔBC,,@Cä2C =C,,8 C¤>CÄ?Cä=CT=D$0
useEffect(() => {
    return () => {
        if (clickTimer) {
            clearTimeout(clickTimer);
        }
    };
}, [clickTimer]);

// BÔDDD5C¤B CD;Dò 0C$BCä<C BC,,GCTAC¤>C4> D 0D :D KD$8Dò ?C ?Cä: Cò@C, ?Cä8D :CP
useEffect(() => {
    // ATAC´8 CÔ5D" ?Cä8D :Cä2Cä3Câ 7C ?D >D 0 C,,;C, >CÒ AC´8D,,;Cä< C¤>D >D$:C,,9, CäGC,,IC 5CÂ @C AC¤@D
    if (!searchQuery || searchQuery.trim().length < 2) {

```



```

    return;
}

// Aô>CDADt8D$Kc$0CT< Cα>C´8Dt5D BC$> D >C$?C 4CT=C,,9
const matchesCount = countSearchMatches(data, searchQuery);

// ATAC´8 D >C$?C 4CT=C,,9 D ;C,,HCα>CÂ <CÔ>C4>, CÔ5 D 0D :D KC$0CT< Cô0Cô:C, 0C$BCä<C BC,,GCTACα8
if (matchesCount > AUTO_EXPAND_THRESHOLD) {
    console.log(
        `AÔ0C"4CT=Câ G¶Ö F6†W46÷VçGÒ ACä2Cô0CD5CÔ8C'Â ?D 5C$KD,,5CÒ ?Cä@Cä3 C 2D$>CÄ0D$8Dt5D :Cä3
    );
    return;
}

// Aô>C´CDt0CT< CôCD$8 Cô0Cô>C¢Â :CäBCä@D´5 CÔCCd=Câ @C ACα@D´BDÀ
const pathsToExpand = expandMatchingFolders(data, searchQuery);

// Aä1CÔ>C$;Dô5CÂ ACäAD$>Dô=C,,5 D 0D :D KD$KDR ?C ?Cä:
if (pathsToExpand.length > 0) {
    setExpanded((prev) => {
        const newExpanded = { ...prev };
        pathsToExpand.forEach((path) => {
            newExpanded[path] = true;
        });
        return newExpanded;
    });
}
}, [searchQuery, data]);

// BDCCÔ:Dd8Dò 4C´O D 0D GCTBC @C 7CÄ5D 0 Cô0Cô:C,Â AD4<CÄ8D CDò @C 7CÄ5D K C$ACTE DD0C";Cä2 C
const calculateDirectorySize = (node: FileNode): number => {
    if (node.type === 'file') {
        return node.size || 0;
    }

    if (!node.children || node.children.length === 0) {
        return 0;
    }

    return node.children.reduce((acc, child) => {
        return acc + calculateDirectorySize(child);
    }, 0);
};

const renderNode = (node: FileNode, depth = 0, isLastChild = false, parentsIsLast: boolean[] = []) => {
    const isExpanded = expanded[node.path];
    const hasChildren = Boolean(node.children && node.children.length > 0);
    // B 0D ADt8D$Kc$0CT< D 0Ct<CT@ CD;Dò 4C,,@CT:D$>D 8C•
    const directorySize = node.type === 'directory' ? calculateDirectorySize(node) : undefined;

    // B >Ct4C 5CÂ 8CÔ4C,,:C BCä@D² 2C´>Cd5CÔ=CäAD$8 (C$5D BC,,:C ;DÄ=D´5 C´8CÔ8C,•
    const renderTreeLines = () => {
        if (depth === 0) return null;

        return (
            <div className="absolute left-0 top-0 bottom-0" style={{ width: `${(depth + 1) * 12}px` }}>

```

```

{parentIsLast.map(
  (isLast, index) =>
    !isLast &&
    index > 0 && (
      <div
        key={index}
        className="absolute border-l border-gray-700"
        style={{
          left: `${(index) * 12 + 6}px`,
          top: 0,
          bottom: 0,
        }}
      />
    ),
  )}
{depth > 0 && (
  <div
    className={`absolute h-1/2 border-l border-gray-700 ${isLastChild ? 'bottom-1/2' : ''}`}
    style={{
      left: `${depth * 12 + 6}px`,
      top: 0,
      bottom: isLastChild ? undefined : 0,
    }}
  />
)}
{depth > 0 && (
  <div
    className="absolute border-t border-gray-700"
    style={{
      left: `${depth * 12 + 6}px`,
      width: '6px',
      top: '50%',
    }}
  />
)}
</div>
);
};

return (
  <div key={node.path} className="relative">
    {renderTreeLines()}
    {/* biome-ignore lint/a11y/useKeyWithClickEvents: <explanation> */}
    <div
      className={cn(
        'flex items-center py-1 hover:bg-gray-700/70 rounded-sm px-2 cursor-pointer z-10 relative
transition-colors duration-200',
        node.selected && 'bg-blue-800/20 border-l-2 border-blue-400',
        depth === 0 && 'mt-1',
        node.type === 'directory' && 'font-medium',
        node.type === 'file' && node.selected && 'text-blue-100',
      )}
      style={{ paddingLeft: `${(depth + 1) * 12 + 4}px` }}
      onClick={(e) => {
        // Aô@Că2CT@Dô5CÂÂ OC$;Dô5D$ADò ;C, FCT;CT2Că9 DÔ;CT<CT=D" GCT:C >CᵃACă< C,,;C, 5C4> Cᵃ>CÔ
        const isCheckedClick =

```

```

(e.target as HTMLInputElement).getAttribute('role') === 'checkbox' ||
(e.target as HTMLInputElement).closest('[role="checkbox"]') ||
(e.target as HTMLInputElement).closest('button');

// ATAC´8 Cα;C,,; C KC² =C GCT:C >CαACR 8C´8 C$=D4BD 8 Cα>CÔBCT9CÔ5D 0 Dt5Cα1Cä:D 0, C,,3CÔ>D 8
if (isCheckboxClick) {
    return;
}

// ATAC´8 Cα;C,,; CÔ0 Cô0Cô:CR Ò @C 7C$>D 0Dt8C$0CT</D 2Cä@C GC,,2C 5CÂ AD 0CtC
if (node.type === 'directory') {
    toggleExpand(node.path);
    return;
}

// ATAC´8 Cα;C,,; CÔ0 DD0C";CR Ò 8D ?Cä;DÄ7D45CÂ BC 9CÄ5D 4C´O Cä1D 0C >D$:C€
if (node.type === 'file') {
    // ATAC´8 CTAD$L C :D$8C$=D´9 D$0C"<CT@, CäGC,,IC 5CÂ 5C4>
    if (clickTimer) {
        clearTimeout(clickTimer);
    }

    // B4AD$0CÔ0C$;C,,2C 5CÂ =Cä2D´9 D$0C"<CT@, Ct0DT2C BD´2C O D$5CαCD"8C' æöFP
    const timer = setTimeout(() => {
        // BÔBCäB Cα>CB 2D´?Cä;CÔ8D$ADòÂ 5D ;C, =CR 1D´;Câ 2D$>D >C4> Cα;C,,;C
        // A,,ACô>C´LCtCCT< node C,,7 Ct0CÄKCα0CÔ8Dò 2CÄ5D BCâ 6Æ-0kedNode
        handleSelectChange(node, !node.selected);
        setClickTimer(null);
    }, 250); // 250ms Ct0CD5D 6Cα0

    setClickTimer(timer);
}
}}
onDoubleClick={() => {
    if (node.type === 'file') {
        // AäGC,,IC 5CÂ BC 9CÄ5D >CD8CÔ>Dt=Cä3Câ :C´8Cα0, DtBCä1D² GCT:C >CαA CÔ5 Cô5D 5Cα;DäGC,,;D O
        if (clickTimer) {
            clearTimeout(clickTimer);
            setClickTimer(null);
        }

        // AäBCα@D´2C 5CÂ ?D >D <CäBD DC 9C´0
        handleDoubleClick(node);
    }
}}
>
<div
    onClick={(e) => {
        e.stopPropagation(); // AäAD$0CÔ0C$;C,,2C 5CÂ 2D ?C´KD$8CR ACä1D´BC,,O Cα;C,,;C
    }}
    onDoubleClick={(e) => {
        e.stopPropagation(); // AäAD$0CÔ0C$;C,,2C 5CÂ 2D ?C´KD$8CR ACä1D´BC,,O CD2Cä9CÔ>C4> Cα;C,,;C
    }}
    className="cursor-pointer"
>
<Checkbox

```

```

      id={node.path}
      checked={node.selected}
      onCheckedChange={(checked: boolean | 'indeterminate') => handleSelectChange(node,
checked === true)}
      className="mr-2 border-gray-600 data-[state=checked]:bg-blue-600 data-
[state=checked]:border-blue-600"
    />
  </div>

  {/* BD8C␣AC,,@Cä2C =CÔ0Dò >C ;C AD$ L CD;Dò AD$@CT;Cä:, C$ACT3CD0 Cä4C,,=C :Cä2Cä9 D,,8D 8CÔK */}
  <div className="w-4 h-4 mr-2 flex items-center justify-center flex-shrink-0">
    {node.type === 'directory' &&
      hasChildren &&
      (isExpanded ? (
        <ChevronDown className="h-4 w-4 text-gray-400" />
      ) : (
        <ChevronRight className="h-4 w-4 text-gray-400" />
      ))}
  </div>

  {/* BD8C␣AC,,@Cä2C =CÔ0Dò >C ;C AD$ L CD;Dò 8C␣>CÔ>C␣ DC 9C´>C"ô?C ?Cä: */}
  <div className="w-5 h-4 flex items-center justify-center flex-shrink-0 mr-2">
    {node.type === 'directory' ? (
      <Folder className="h-4 w-4 text-blue-400" />
    ) : (
      <File className="h-4 w-4 text-gray-400" />
    )}
  </div>

  <span className="mr-2 text-sm text-gray-200">{node.name}</span>

  {/* AäBCä1D 0Cd0CT< D 0Ct<CT@ CD;Dò DC 9C´>C" 8 Cô0Cô>C␣ ␣÷Ð
  {node.type === 'file' && node.size !== undefined && (
    <span className="text-xs text-gray-400 ml-auto">{formatFileSize(node.size)}</span>
  )}
  {node.type === 'directory' && directorySize !== undefined && directorySize > 0 && (
    <span className="text-xs text-gray-400 ml-auto">{formatFileSize(directorySize)}</span>
  )}
  </div>

  {node.type === 'directory' && isExpanded && node.children && node.children.length > 0 && (
    <div>
      {node.children.map((child, index) => {
        // Bô2CÔ>CR CC␣0Ct0CÔ8CR 4C´8CÔK CD;Dò TypeScript
        const childrenLength = node.children?.length || 0;
        return renderNode(
          child,
          depth + 1,
          index === childrenLength - 1, // Dô2C´OCTBD O C´8 Cô>D ;CT4CÔ8CÂ MC´5CÄ5CÔBCä<
          [...parentIsLast, isLastChild], // CÔ0C␣0Cô;C,,2C 5CÂ 8CÔDCä@CÄ0Dd8Dâ >"Cô>D ;CT4CÔ8DR" @Cä4C,,B
        );
      })}
    </div>
  )}
</div>
);

```

```

};

// BDCCÔ:Dd8Dò 4C´O Că1D 0C >D$:C, 4C$>C"=Că3Că :C´8C=0 CÔ0 DD0C";CP
const handleDoubleClick = (node: FileNode) => {
  if (node.type === 'file') {
    setSelectedFile(node.path);
    setCodeViewerOpen(true);
  }
};

return (
  <div className="overflow-y-auto max-h-[calc(100vh-250px)] border border-gray-700 rounded-md p-3
bg-gray-800/90">
    {renderNode(data, 0, true, [])}

    {/* AÄ>CD0C´LCÔ>CR >C= Că 4C´O Cô@CăACÄ>D$@C :Că4C ¢÷D
    <CodeViewer isOpen={codeViewerOpen} onClose={() => setCodeViewerOpen(false)}
    filePath={selectedFile} />
    </div>
  );
}

```

Content of src/components/filter-settings.tsx

```
"use client"

import React, { useState } from 'react';
import { Tabs, TabsList, TabsTrigger, TabsContent } from '@components/ui/tabs';
import { EditableList } from '@components/editable-list';
import { Switch } from '@components/ui/switch';
import { Label } from '@components/ui/label';
import { Button } from '@components/ui/button';
import { Dialog, DialogContent, DialogHeader, DialogTitle, DialogFooter } from '@components/ui/dialog';
import { Settings } from 'lucide-react';
import { FilterSettings } from '@lib/types';

interface FilterSettingsProps {
  settings: FilterSettings;
  onSettingsChange: (settings: FilterSettings) => void;
}

const DEFAULT_IGNORED_DIRECTORIES = [
  'node_modules',
  '.git',
  'dist',
  'build',
  'tmp',
  'coverage',
  '.next',
  '.nuxt',
];

const DEFAULT_IGNORED_FILES = [
  '.DS_Store',
  'package-lock.json',
  'yarn.lock',
  'pnpm-lock.yaml',
];

const DEFAULT_IGNORED_EXTENSIONS = [
  '.svg',
  '.png',
  '.jpg',
  '.jpeg',
  '.gif',
  '.bmp',
  '.ico',
  '.webp',
  '.pdf',
  '.exe',
  '.dll',
  '.so',
  '.zip',
];

export function FilterSettingsButton({ settings, onSettingsChange }: FilterSettingsProps) {
  const [open, setOpen] = useState(false);
```

```

// B >Ct4C 5CÂ ;Cä:C ;DÄ=D4N C²>Cô8Dâ =C AD$@Cä5C¢Â :CäBCä@C O C CCD5D" >C =Cä2C´OD$LD O C$=D4B
const [localSettings, setLocalSettings] = useState<FilterSettings>({ ...settings });

// B 1D 0D KC$0CT< C´>C²0C´LCÔKCR =C AD$@Cä9C²8 Cô@C, >D$:D KD$8C, 4C,,0C´>C40
React.useEffect(() => {
  if (open) {
    setLocalSettings({ ...settings });
  }
}, [open, settings]);

// BDCCÔ:Dd8Dò 4C´O D >DT@C =CT=C,,O CÔ0D BD >CT:
const handleSave = () => {
  onSettingsChange(localSettings);
  setOpen(false);
};

return (
  <>
    <Button
      variant="outline"
      onClick={() => setOpen(true)}
      className="w-full flex items-center justify-center bg-gray-700 border-gray-600 hover:bg-gray-600
text-gray-200"
    >
      <Settings className="h-4 w-4 mr-2" />
      <span>AÔ0D BD >C":C, DC,,;DÄBD 0Dd8CfÂ÷7 ãà
    </Button>

    <Dialog open={open} onOpenChange={setOpen}>
      <DialogContent className="max-w-2xl max-h-[80vh] overflow-y-auto bg-gray-800 border-gray-700
text-gray-100">
        <DialogHeader>
          <DialogTitle className="text-gray-100">AÔ0D BD >C":C, DC,,;DÄBD 0Dd8CfÂôF—ÆöuF—FÆSà
        </DialogHeader>

        <div className="py-4">
          <p className="text-sm text-gray-400 mb-4">
            AÔ0D BD >C"BCR ?D 0C$8C´0 DD8C´LD$@C FC,,8 DD0C";Cä2 C, 4C,,@CT:D$>D 8C´ ?D >CT:D$0.
          </p>

          <Tabs defaultValue="directories">
            <TabsList className="w-full bg-gray-700">
              <TabsTrigger value="directories" className="flex-1 data-[state=active]:bg-blue-600 data-
[state=active]:text-white">AD8D 5C²BCä@C,,8</TabsTrigger>
              <TabsTrigger value="files" className="flex-1 data-[state=active]:bg-blue-600 data-
[state=active]:text-white">BD0C";D³Âð@absTrigger>
              <TabsTrigger value="extensions" className="flex-1 data-[state=active]:bg-blue-600 data-
[state=active]:text-white">B 0D HC,,@CT=C,,O</TabsTrigger>
            </TabsList>

            <TabsContent value="directories" className="mt-4 space-y-4">
              <div className="flex items-center justify-between space-x-2">
                <Label htmlFor="use-default-ignores" className="text-gray-200">A,,ACô>C´LCt>C$0D$L D BC =CD0D BCÔK
              </div>
              <Switch
                id="use-default-ignores"
                checked={localSettings.useDefaultIgnores}

```

```

onCheckedChange={(checked) => {
  setLocalSettings({
    ...localSettings,
    useDefaultIgnores: checked,
  });
}}
className="data-[state=checked]:bg-blue-600"
/>
</div>

{localSettings.useDefaultIgnores && (
  <div className="mb-4">
    <Label className="text-sm text-gray-400">B BC =CD0D BCÔKCR 8C4=Cä@C,,@D45CÄKCR 4C,,@CT:D$>
    <div className="flex flex-wrap gap-2 mt-2">
      {DEFAULT_IGNORED_DIRECTORIES.map((dir) => (
        <div key={dir} className="bg-gray-700 text-gray-300 text-xs rounded px-2 py-1">
          {dir}
        </div>
      ))}
    </div>
  </div>
)}

<div>
  <Label className="text-gray-200">AD>Cô>C´=C,,BCT;DÄ=D´5 C,,3CÔ>D 8D CCT<D´5 CD8D 5C▯BCä@C,,8>
  <EditableList
    items={localSettings.ignoredDirectories}
    onItemsChange={({items) => setLocalSettings({ ...localSettings, ignoredDirectories: items })}
    placeholder="A$2CT4C,,BCR 8CÄO CD8D 5C▯BCä@C,,8..."
    badgeVariant="secondary"
  />
</div>
</TabsContent>

<TabsContent value="files" className="mt-4 space-y-4">
  <Label className="text-gray-200">A,,3CÔ>D 8D CCT<D´5 DD0C";D² „<Cä6CÔ> C,,ACô>C´LCT>C$0D$L * C▯
  <EditableList
    items={localSettings.ignoredFiles}
    onItemsChange={({items) => setLocalSettings({ ...localSettings, ignoredFiles: items })}
    placeholder="A$2CT4C,,BCR 8CÄO DD0C";C 8C´8 D,,0C ;Cä=..."
    badgeVariant="destructive"
  />
</TabsContent>

<TabsContent value="extensions" className="mt-4 space-y-4">
  <div>
    <Label className="text-gray-200">A,,3CÔ>D 8D CCT<D´5 D 0D HC,,@CT=C,,O DD0C";Cä2:</Label>
    <EditableList
      items={localSettings.ignoredExtensions}
      onItemsChange={({items) => setLocalSettings({ ...localSettings, ignoredExtensions: items })}
      placeholder="A$2CT4C,,BCR @C AD,,8D 5CÔ8CR „A D$>Dt:Cä9, CÔ0Cô@C,,<CT@ .js)..."
      validateItem={({item) => item.startsWith('.')}}
      errorMessage="B 0D HC,,@CT=C,,5 CD>C´6CÔ> CÔ0Dt8CÔ0D$LD O D BCäGC▯8 (CÔ0Cô@C,,<CT@ .js)"
      badgeVariant="destructive"
    />
  </div>
</div>

```



```

<div className="mt-6">
  <Label className="text-gray-200">B 0Ct@CTHCT=CÔKCR @C AD,,8D 5CÔ8Dò DC 9C´>C#£ÂôÆ &VÃà
  <p className="text-sm text-gray-400 mb-2">
    ATAC´8 D4:C 7C =Câ ECäBDò 1D² >CD=Câ @C AD,,8D 5CÔ8CRÂ 1D44D4B C$:C´NDt5CÔK D$>C´LCα> D
  </p>
  <EditableList
    items={localSettings.allowedExtensions}
    onItemsChange={({items}) => setLocalSettings({ ...localSettings, allowedExtensions: items })}
    placeholder="A$2CT4C,,BCR @C AD,,8D 5CÔ8CR „A D$>Dt:Cä9, CÔ0Cô@C,,<CT@ .js)..."
    validateItem={({item}) => item.startsWith('.')}
    errorMessage="B 0D HC,,@CT=C,,5 CD>C´6CÔ> CÔ0Dt8CÔ0D$LD O D BCäGCα8 (CÔ0Cô@C,,<CT@ .js)"
    badgeVariant="default"
  />
</div>
</TabsContent>
</Tabs>
</div>

<DialogFooter>
  <Button onClick={handleSave} className="bg-blue-600 text-white hover:bg-blue-700">
    B >DT@C =C,,BDÀ
  </Button>
</DialogFooter>
</DialogContent>
</Dialog>
</>
);
}

```

Content of src/components/project-info.tsx

```
'use client';

import React from 'react';
import { useProjectsStore } from '@lib/stores/projects-store';
import { formatDate } from '@lib/format-utils';
import { Badge } from '@components/ui/badge';
import { Layers, Clock, FilePlus } from 'lucide-react';

export function ProjectInfo() {
  const {
    getActiveProject,
    getActiveProfile
  } = useProjectsStore();

  const activeProject = getActiveProject();
  const activeProfile = getActiveProfile();

  if (!activeProject) {
    return null;
  }

  return (
    <div className="border border-gray-700 rounded-md p-3 bg-gray-800 mb-4 text-sm text-gray-300">
      <div className="flex items-center gap-2 mb-2">
        <Layers className="h-4 w-4 text-blue-400" />
        <span className="font-medium text-gray-200">{activeProject.name}</span>

        <Badge variant="outline" className="ml-auto text-xs bg-gray-700 text-gray-300 border-gray-600">
          <Clock className="h-3 w-3 mr-1" />
          {formatDate(activeProject.updatedAt)}
        </Badge>
      </div>

      {activeProject.description && (
        <p className="mb-2 text-gray-400 text-xs">{activeProject.description}</p>
      )}

      {activeProfile && (
        <div className="border-t border-gray-700 mt-2 pt-2">
          <div className="flex items-center gap-2 mb-1">
            <FilePlus className="h-4 w-4 text-green-400" />
            <span className="font-medium text-gray-200">{activeProfile.name}</span>

            <Badge variant="outline" className="ml-auto text-xs bg-gray-700 text-gray-300 border-gray-600">
              <Clock className="h-3 w-3 mr-1" />
              {formatDate(activeProfile.updatedAt)}
            </Badge>
          </div>

          {activeProfile.description && (
            <p className="text-gray-400 text-xs">{activeProfile.description}</p>
          )}
        </div>
      )}
    </div>
  );
}
```

```

    </div>
  })

  <div className="border-t border-gray-700 mt-2 pt-2 text-xs">
    <div className="flex gap-4">
      <div>
        <span className="text-gray-400">Aα>CÄ<CT=D$0D 8Cf £Â÷7 ãç²r wÐ
        <span className="text-gray-200">{
          activeProfile ?
            (activeProfile.settings.includeComments ? 'A$:C´NDt5CÔK' : 'A,,ACα;DäGCT=D²r'
            (activeProject.baseSettings.includeComments ? 'A$:C´NDt5CÔK' : 'A,,ACα;DäGCT=D²r•
        }</span>
      </div>

      <div>
        <span className="text-gray-400">AÔ>C$0Dò AD$@C =C,,FC 4C´O DD0C";C £Â÷7 ãç²r wÐ
        <span className="text-gray-200">{
          activeProfile ?
            (activeProfile.settings.newPageForEachFile ? 'AD0' : 'AÔ5D"r'
            (activeProject.baseSettings.newPageForEachFile ? 'AD0' : 'AÔ5D"r•
        }</span>
      </div>

      <div>
        <span className="text-gray-400">BD0C";;</span>{ ' }
        <span className="text-gray-200 font-mono">{
          activeProfile ?
            activeProfile.settings.outputFileName :
            activeProject.baseSettings.outputFileName
        }</span>
      </div>
    </div>
  </div>
</div>
);
}

```

Content of src/components/project-manager.tsx

```
'use client';

import React, { useState } from 'react';
import { Button } from '@components/ui/button';
import { Dialog, DialogContent, DialogHeader, DialogTitle, DialogFooter } from '@components/ui/dialog';
import { Input } from '@components/ui/input';
import { Label } from '@components/ui/label';
import { Textarea } from '@components/ui/textarea';
import {
  DropdownMenu,
  DropdownMenuContent,
  DropdownMenuItem,
  DropdownMenuLabel,
  DropdownMenuSeparator,
  DropdownMenuTrigger
} from '@components/ui/dropdown-menu';
import { Check, ChevronDown, FilePlus, FolderPlus, Pencil, Trash2, Layers } from 'lucide-react';
import { useProjectsStore, Project, Profile } from '@lib/stores/projects-store';

// Að>CÄ?Cä=CT=D" 4C´O CäBCä1D 0Cd5CÔ8Dò 2D´1D 0CÔ=Cä3Câ ?D >CT:D$0 C, ?D >DD8C´O
export function ProjectSelector() {
  const {
    projects,
    activeProjectId,
    activeProfileId,
    getActiveProject,
    getActiveProfile,
    setActiveProject,
    setActiveProfile,
    createProject: storeCreateProject,
    createProfile: storeCreateProfile,
    updateProject,
    updateProfile,
    deleteProject,
    deleteProfile
  } = useProjectsStore();

  const activeProject = getActiveProject();
  const activeProfile = getActiveProfile();

  const [showNewProjectDialog, setShowNewProjectDialog] = useState(false);
  const [showNewProfileDialog, setShowNewProfileDialog] = useState(false);
  const [showEditProjectDialog, setShowEditProjectDialog] = useState(false);
  const [showEditProfileDialog, setShowEditProfileDialog] = useState(false);

  if (projects.length === 0) {
    return (
      <div className="flex items-center gap-2 border border-gray-700 rounded-md p-3 bg-gray-800 mb-4">
        <Button
          variant="outline"
          size="sm"
          onClick={() => setShowNewProjectDialog(true)}
        />
      </div>
    );
  }
}
```

```

        className="bg-gray-700 border-gray-600 hover:bg-gray-600 text-gray-200"
      >
      <FolderPlus className="h-4 w-4 mr-2" />
      B >Ct4C BDÂ ?CT@C$KC' ?D >CT:D
    </Button>

    <NewProjectDialog
      isOpen={showNewProjectDialog}
      onClose={() => setShowNewProjectDialog(false)}
      createProject={storeCreateProject}
    />
  </div>
);
}

return (
  <div className="flex items-center gap-2 border border-gray-700 rounded-md p-3 bg-gray-800 mb-4">
    <div className="flex-1 flex items-center gap-4">
      /* B 5C`5C▯BCä@ Cô@Cä5C▯BCä2 */
      <div className="flex-1">
        <DropdownMenu>
          <DropdownMenuTrigger asChild>
            <Button
              variant="outline"
              className="w-full justify-between bg-gray-700 border-gray-600 hover:bg-gray-600 text-
gray-200"
            >
              <div className="flex items-center">
                <Layers className="h-4 w-4 mr-2" />
                {activeProject ? activeProject.name : 'A$KC 5D 8D$5 Cô@Cä5C▯B'}
              </div>
                <ChevronDown className="h-4 w-4 ml-2" />
              </Button>
            </DropdownMenuTrigger>
            <DropdownMenuContent className="w-56 bg-gray-800 border-gray-700 text-gray-200">
              <DropdownMenuLabel>Aô@Cä5C▯BD³ÂôG&÷ FöwnMenuLabel>
              <DropdownMenuSeparator className="bg-gray-700" />
              {projects.map(project => (
                <DropdownMenuItem
                  key={project.id}
                  className="flex items-center cursor-pointer hover:bg-gray-700"
                  onClick={() => setActiveProject(project.id)}
                >
                  {activeProjectId === project.id && (
                    <Check className="h-4 w-4 mr-2 text-green-400" />
                  )}
                  <span className={activeProjectId === project.id ? "flex-1 font-medium" : "flex-1"}>
                    {project.name}
                  </span>
                </DropdownMenuItem>
              )}}
              <DropdownMenuSeparator className="bg-gray-700" />
              <DropdownMenuItem
                className="flex items-center cursor-pointer hover:bg-gray-700"
                onClick={() => setShowNewProjectDialog(true)}
              >

```

```

    <FolderPlus className="h-4 w-4 mr-2" />
    B >Ct4C BDÂ =Cä2D´9 Cö@Cä5CªB
  </DropdownMenuItem>
  {activeProject && (
    <>
    <DropdownMenuItem
      className="flex items-center cursor-pointer hover:bg-gray-700"
      onClick={() => setShowEditProjectDialog(true)}
    >
    <Pencil className="h-4 w-4 mr-2" />
    B 5CD0CªBC,,@Cä2C BDÂ ?D >CT:D
    </DropdownMenuItem>
  </>
  )}
</DropdownMenuContent>
</DropdownMenu>
</div>

{ /* B 5C´5CªBCä@ Cö@CäDC,,;CT9 (D$>C´LCª> CTAC´8 C$KC @C = Cö@Cä5CªB) */}
{activeProject && (
  <div className="flex-1">
    <DropdownMenu>
      <DropdownMenuTrigger asChild>
        <Button
          variant="outline"
          className="w-full justify-between bg-gray-700 border-gray-600 hover:bg-gray-600 text-
gray-200"
        >
          <div className="flex items-center">
            <FilePlus className="h-4 w-4 mr-2" />
            {activeProfile ? activeProfile.name : 'A 0Ct>C$KCR =C AD$@Cä9Cª8'}
          </div>
          <ChevronDown className="h-4 w-4 ml-2" />
        </Button>
      </DropdownMenuTrigger>
      <DropdownMenuContent className="w-56 bg-gray-800 border-gray-700 text-gray-200">
        <DropdownMenuLabel>Aô@CäDC,,;CfÂôG&÷ FöwnMenuLabel>
        <DropdownMenuSeparator className="bg-gray-700" />
        <DropdownMenuItem
          className="flex items-center cursor-pointer hover:bg-gray-700"
          onClick={() => setActiveProfile(undefined)}
        >
          {!activeProfile && (
            <Check className="h-4 w-4 mr-2 text-green-400" />
          )}
          <span className={!activeProfile ? "flex-1 font-medium" : "flex-1"}>
            A 0Ct>C$KCR =C AD$@Cä9Cª8 Cö@Cä5CªBC
          </span>
        </DropdownMenuItem>
        <DropdownMenuSeparator className="bg-gray-700" />
        {activeProject.profiles.map(profile => (
          <DropdownMenuItem
            key={profile.id}
            className="flex items-center cursor-pointer hover:bg-gray-700"
            onClick={() => setActiveProfile(profile.id)}
          >

```

```

    {activeProfileId === profile.id && (
      <Check className="h-4 w-4 mr-2 text-green-400" />
    )}
    <span className={activeProfileId === profile.id ? "flex-1 font-medium" : "flex-1"}>
      {profile.name}
    </span>
  </DropdownMenuItem>
)}}
<DropdownMenuSeparator className="bg-gray-700" />
<DropdownMenuItem
  className="flex items-center cursor-pointer hover:bg-gray-700"
  onClick={() => setShowNewProfileDialog(true)}
>
  <FilePlus className="h-4 w-4 mr-2" />
  B >Ct4C BDÂ =Cä2D´9 Cô@CäDC,,;DÀ
</DropdownMenuItem>
{activeProfile && (
  <>
    <DropdownMenuItem
      className="flex items-center cursor-pointer hover:bg-gray-700"
      onClick={() => setShowEditProfileDialog(true)}
    >
      <Pencil className="h-4 w-4 mr-2" />
      B 5CD0C¬BC,,@Cä2C BDÂ ?D >DD8C´L
    </DropdownMenuItem>
  </>
)}
</DropdownMenuContent>
</DropdownMenu>
</div>
)}
</div>

```

```

{ /* AD8C ;Cä3C, 4C´O D >Ct4C =C,,O C, @CT4C :D$8D >C$0CÔ8Dò ¢÷Ð
<NewProjectDialog
  isOpen={showNewProjectDialog}
  onClose={() => setShowNewProjectDialog(false)}
  createProject={storeCreateProject}
/>

```

```

{activeProject && (
  <>
    <EditProjectDialog
      isOpen={showEditProjectDialog}
      onClose={() => setShowEditProjectDialog(false)}
      project={activeProject}
      updateProject={updateProject}
      deleteProject={deleteProject}
    />

```

```

    <NewProfileDialog
      isOpen={showNewProfileDialog}
      onClose={() => setShowNewProfileDialog(false)}
      projectId={activeProject.id}
      createProfile={storeCreateProfile}
    />

```

```

    {activeProfile && (
      <EditProfileDialog
        isOpen={showEditProfileDialog}
        onClose={() => setShowEditProfileDialog(false)}
        projectId={activeProject.id}
        profile={activeProfile}
        updateProfile={updateProfile}
        deleteProfile={deleteProfile}
      />
    )}
  </>
)}
</div>
);
}

```

```
// AD8C ;Că3 D >Ct4C =C„O CÔ>C$>C4> Cô@Că5C¬BC
```

```

interface NewProjectDialogProps {
  isOpen: boolean;
  onClose: () => void;
  createProject: (name: string, description?: string) => Project;
}

```

```

function NewProjectDialog({ isOpen, onClose, createProject }: NewProjectDialogProps) {
  const [name, setName] = useState("");
  const [description, setDescription] = useState("");

  const handleSubmit = () => {
    if (!name.trim()) return;

    createProject(name.trim(), description.trim() || undefined);
    setName("");
    setDescription("");
    onClose();
  };
}

```

```

return (
  <Dialog open={isOpen} onOpenChange={open => !open && onClose()}>
    <DialogContent className="bg-gray-800 border-gray-700 text-gray-100">
      <DialogHeader>
        <DialogTitle>B >Ct4C BDÂ =Că2D´9 Cô@Că5C¬B</DialogTitle>
      </DialogHeader>

      <div className="space-y-4 py-4">
        <div className="space-y-2">
          <Label htmlFor="project-name">AÔ0Ct2C =C„5 Cô@Că5C¬BC ÂôÆ &VÃà
          <Input
            id="project-name"
            value={name}
            onChange={e => setName(e.target.value)}
            className="bg-gray-700 border-gray-600 text-gray-200"
            placeholder="A$2CT4C„BCR =C 7C$0CÔ8CR ?D >CT:D$0"
          />
        </div>
      </div>
    </DialogContent>
  </Dialog>
)

```



```

<div className="space-y-2">
  <Label htmlFor="project-description">Aä?C,,AC =C,,5 (Cä?Dd8Cä=C ;DÄ=Câ"ÂôÆ &VÃà
  <Textarea
    id="project-description"
    value={description}
    onChange={e => setDescription(e.target.value)}
    className="bg-gray-700 border-gray-600 text-gray-200 min-h-20"
    placeholder="A$2CT4C,,BCR >Cô8D 0CÔ8CR ?D >CT:D$0"
  />
</div>
</div>

<DialogFooter>
  <Button variant="outline" onClick={onClose} className="bg-gray-700 border-gray-600 hover:bg-
gray-600 text-gray-200">
    AäBCÄ5CÔ0
  </Button>
  <Button onClick={handleSubmit} disabled={!name.trim()} className="bg-blue-600 hover:bg-
blue-700 text-white">
    B >Ct4C BDÄ
  </Button>
</DialogFooter>
</DialogContent>
</Dialog>
);
}

// AD8C ;Cä3 D 5CD0CαBC,,@Cä2C =C,,O Cô@Cä5CαBC
interface EditProjectDialogProps {
  isOpen: boolean;
  onClose: () => void;
  project: Project;
  updateProject: (projectId: string, updates: Partial<Project>) => void;
  deleteProject: (projectId: string) => void;
}

function EditProjectDialog({
  isOpen,
  onClose,
  project,
  updateProject,
  deleteProject
}: EditProjectDialogProps) {
  const [name, setName] = useState(project.name);
  const [description, setDescription] = useState(project.description || "");
  const [showDeleteConfirm, setShowDeleteConfirm] = useState(false);

  const handleSubmit = () => {
    if (!name.trim()) return;

    updateProject(project.id, {
      name: name.trim(),
      description: description.trim() || undefined
    });
    onClose();
  };
}

```

```

const handleDelete = () => {
  deleteProject(project.id);
  onClose();
};

return (
  <Dialog open={isOpen} onOpenChange={open => !open && onClose()}>
    <DialogContent className="bg-gray-800 border-gray-700 text-gray-100">
      <DialogHeader>
        <DialogTitle>B 5CD0C▯BC,,@Cä2C BDÂ ?D >CT:D#ÂôF— ÆöuF—FÆSà
      </DialogHeader>

      <div className="space-y-4 py-4">
        <div className="space-y-2">
          <Label htmlFor="project-name-edit">AÔ0Ct2C =C,,5 Cô@Cä5C▯BC ÂôÆ &VÃà
          <Input
            id="project-name-edit"
            value={name}
            onChange={e => setName(e.target.value)}
            className="bg-gray-700 border-gray-600 text-gray-200"
          />
        </div>

        <div className="space-y-2">
          <Label htmlFor="project-description-edit">Aä?C,,AC =C,,5 (Cä?Dd8Cä=C ;DÄ=Câ“ÂôÆ &VÃà
          <Textarea
            id="project-description-edit"
            value={description}
            onChange={e => setDescription(e.target.value)}
            className="bg-gray-700 border-gray-600 text-gray-200 min-h-20"
          />
        </div>

        {!showDeleteConfirm ? (
          <Button
            variant="destructive"
            onClick={() => setShowDeleteConfirm(true)}
            className="w-full mt-4"
          >
            <Trash2 className="h-4 w-4 mr-2" />
            B44C ;C,,BDÂ ?D >CT:D
          </Button>
        ) : (
          <div className="border border-red-800 bg-red-900/20 rounded-md p-3 mt-4">
            <p className="text-red-300 mb-2">A$K D42CT@CT=D²Â GD$> DT>D$8D$5 D44C ;C,,BDÂ MD$>D" ?D >CT:D
            <div className="flex gap-2">
              <Button
                variant="outline"
                onClick={() => setShowDeleteConfirm(false)}
                className="flex-1 bg-gray-700 border-gray-600"
              >
                AäBCÄ5CÔ0
              </Button>
              <Button
                variant="destructive"

```

```

        onClick={handleDelete}
        className="flex-1"
      >
        Aô>CDBC$5D 4C,,BDÂ CCD0C'5CÔ8CP
      </Button>
    </div>
  </div>
)}
</div>

<DialogFooter>
  <Button variant="outline" onClick={onClose} className="bg-gray-700 border-gray-600 hover:bg-
gray-600 text-gray-200">
    AäBCÄ5CÔ0
  </Button>
  <Button onClick={handleSubmit} disabled={!name.trim()} className="bg-blue-600 hover:bg-
blue-700 text-white">
    B >DT@C =C,,BDÀ
  </Button>
</DialogFooter>
</DialogContent>
</Dialog>
);
}

```

```

// AD8C ;Cä3 D >Ct4C =C,,O CÔ>C$>C4> Cô@CäDC,,;Dă
interface NewProfileDialogProps {
  isOpen: boolean;
  onClose: () => void;
  projectId: string;
  createProfile: (projectId: string, name: string, description?: string, inheritFromProject?: boolean) =>
  Profile;
}

```

```

function NewProfileDialog({
  isOpen,
  onClose,
  projectId,
  createProfile
}: NewProfileDialogProps) {
  const [name, setName] = useState("");
  const [description, setDescription] = useState("");
  const [inheritSettings, setInheritSettings] = useState(true);

  const handleSubmit = () => {
    if (!name.trim()) return;

    createProfile(
      projectId,
      name.trim(),
      description.trim() || undefined,
      inheritSettings
    );
    setName("");
    setDescription("");
    setInheritSettings(true);
  };
}

```

```

    onClose();
  };

  return (
    <Dialog open={isOpen} onOpenChange={open => !open && onClose()}>
      <DialogContent className="bg-gray-800 border-gray-700 text-gray-100">
        <DialogHeader>
          <DialogTitle>B >Ct4C BDÂ =Cä2D´9 Cö@CäDC,,;DÃÂôF– ÆöuF—FÆSà
        </DialogHeader>

        <div className="space-y-4 py-4">
          <div className="space-y-2">
            <Label htmlFor="profile-name">AÔ0Ct2C =C,,5 Cö@CäDC,,;DóÂôÆ &VÃà
            <Input
              id="profile-name"
              value={name}
              onChange={e => setName(e.target.value)}
              className="bg-gray-700 border-gray-600 text-gray-200"
              placeholder="A$2CT4C,,BCR =C 7C$0CÔ8CR ?D >DD8C´O"
            />
          </div>

          <div className="space-y-2">
            <Label htmlFor="profile-description">Aä?C,,AC =C,,5 (Cä?Dd8Cä=C ;DÄ=Câ“ÂôÆ &VÃà
            <Textarea
              id="profile-description"
              value={description}
              onChange={e => setDescription(e.target.value)}
              className="bg-gray-700 border-gray-600 text-gray-200 min-h-20"
              placeholder="A$2CT4C,,BCR >Cö8D 0CÔ8CR ?D >DD8C´O"
            />
          </div>

          <div className="flex items-center space-x-2">
            <Checkbox
              id="inherit-settings"
              checked={inheritSettings}
              onCheckedChange={(checked) => setInheritSettings(checked as boolean)}
              className="border-gray-600 data-[state=checked]:bg-blue-600"
            />
            <Label htmlFor="inherit-settings" className="text-sm text-gray-300">
              AÔ0D ;CT4Cä2C BDÂ =C AD$@Cä9C=8 C,,7 C 0Ct>C$KDR =C AD$@Cä5C¢ ?D >CT:D$0
            </Label>
          </div>
        </div>

        <DialogFooter>
          <Button variant="outline" onClick={onClose} className="bg-gray-700 border-gray-600 hover:bg-gray-600 text-gray-200">
            AäBCÄ5CÔ0
          </Button>
          <Button onClick={handleSubmit} disabled={!name.trim()} className="bg-blue-600 hover:bg-blue-700 text-white">
            B >Ct4C BDÂ
          </Button>
        </DialogFooter>
      </DialogContent>
    </Dialog>
  );

```

```

    </DialogContent>
  </Dialog>
);
}

// AD8C ;Că3 D 5CD0CªBC,,@Că2C =C,,O Cõ@CăDC,,;Dă
interface EditProfileDialogProps {
  isOpen: boolean;
  onClose: () => void;
  projectId: string;
  profile: Profile;
  updateProfile: (projectId: string, profileId: string, updates: Partial<Profile>) => void;
  deleteProfile: (projectId: string, profileId: string) => void;
}

function EditProfileDialog({
  isOpen,
  onClose,
  projectId,
  profile,
  updateProfile,
  deleteProfile
}: EditProfileDialogProps) {
  const [name, setName] = useState(profile.name);
  const [description, setDescription] = useState(profile.description || "");
  const [showDeleteConfirm, setShowDeleteConfirm] = useState(false);

  const handleSubmit = () => {
    if (!name.trim()) return;

    updateProfile(projectId, profile.id, {
      name: name.trim(),
      description: description.trim() || undefined
    });
    onClose();
  };

  const handleDelete = () => {
    deleteProfile(projectId, profile.id);
    onClose();
  };

  return (
    <Dialog open={isOpen} onOpenChange={open => !open && onClose()}>
      <DialogContent className="bg-gray-800 border-gray-700 text-gray-100">
        <DialogHeader>
          <DialogTitle>B 5CD0CªBC,,@Că2C BDÂ ?D >DD8C´L</DialogTitle>
        </DialogHeader>

        <div className="space-y-4 py-4">
          <div className="space-y-2">
            <Label htmlFor="profile-name-edit">AÔ0Ct2C =C,,5 Cõ@CăDC,,;DóÂôÆ &VÃà
            <Input
              id="profile-name-edit"
              value={name}
              onChange={e => setName(e.target.value)}

```

```

        className="bg-gray-700 border-gray-600 text-gray-200"
      />
    </div>

    <div className="space-y-2">
      <Label htmlFor="profile-description-edit">Aä?C,,AC =C,,5 (Cä?Dd8Cä=C ;DÄ=Câ“Âô/Æ &VÃà
    <Textarea
      id="profile-description-edit"
      value={description}
      onChange={e => setDescription(e.target.value)}
      className="bg-gray-700 border-gray-600 text-gray-200 min-h-20"
    />
    </div>

    {!showDeleteConfirm ? (
      <Button
        variant="destructive"
        onClick={() => setShowDeleteConfirm(true)}
        className="w-full mt-4"
      >
        <Trash2 className="h-4 w-4 mr-2" />
        B44C ;C,,BDÂ ?D >DD8C´L
      </Button>
    ) : (
      <div className="border border-red-800 bg-red-900/20 rounded-md p-3 mt-4">
        <p className="text-red-300 mb-2">A$K D42CT@CT=D²Â GD$> DT>D$8D$5 D44C ;C,,BDÂ MD$>D" ?D >DD8C´L
        <div className="flex gap-2">
          <Button
            variant="outline"
            onClick={() => setShowDeleteConfirm(false)}
            className="flex-1 bg-gray-700 border-gray-600"
          >
            AäBCÄ5CÔ0
          </Button>
          <Button
            variant="destructive"
            onClick={handleDelete}
            className="flex-1"
          >
            Aô>CDBC$5D 4C,,BDÂ CCD0C´5CÔ8CP
          </Button>
        </div>
      </div>
    )}
  </div>

  <DialogFooter>
    <Button variant="outline" onClick={onClose} className="bg-gray-700 border-gray-600 hover:bg-gray-600 text-gray-200">
      AäBCÄ5CÔ0
    </Button>
    <Button onClick={handleSubmit} disabled={!name.trim()} className="bg-blue-600 hover:bg-blue-700 text-white">
      B >DT@C =C,,BDÂ
    </Button>
  </DialogFooter>

```

```
        </DialogContent>
    </Dialog>
);
}
```

```
// AÔ5 Ct0C CCDLD$5 C„<Cô>D BC„@Cä2C BDÂ 6†V0kbox
import { Checkbox } from '@components/ui/checkbox';
```

Content of src/components/search-filter.tsx

```
'use client';

import { Button } from '@components/ui/button';
import { Input } from '@components/ui/input';
import { Tooltip, TooltipContent, TooltipProvider, TooltipTrigger } from '@components/ui/tooltip';
import { cn } from '@lib/utls';
import { ChevronDown, ChevronUp, Info, Search, X } from 'lucide-react';
import type React from 'react';
import { useEffect, useRef, useState } from 'react';

import type { FilterSettings } from '@server/file-system';

interface SearchFilterProps {
  onSearch: (pattern: string) => void;
  filterSettings?: FilterSettings; // AD>C 0C$;Dô5CÂ =C AD$@Cä9C¤8 DD8C´LD$@C FC,,8
}

export function SearchFilter({ onSearch, filterSettings }: SearchFilterProps) {
  const [searchValue, setSearchValue] = useState('');
  const [suggestions, setSuggestions] = useState<string[]>([]);
  const [showSuggestions, setShowSuggestions] = useState(false);
  const [isLoading, setIsLoading] = useState(false);
  const [focusedSuggestion, setFocusedSuggestion] = useState(-1);
  const inputRef = useRef<HTMLInputElement>(null);
  const suggestionsRef = useRef<HTMLDivElement>(null);

  // BDCCÔ:Dd8Dò 4C´O Cò>C´CDt5CÔ8Dò ?D 5CD;Cä6CT=C,,9 C 2D$>C¤>CÄ?C´8D$0
  const fetchSuggestions = async (query: string) => {
    if (!query || query.length < 2) {
      setSuggestions([]);
      return;
    }
  }

  try {
    setIsLoading(true);

    // ATAC´8 CTAD$L CÔ0D BD >C¨:C, DC,,;DÄBD 0Dd8C,Â 8D ?Cä;DÄ7D45CÂ õ5B 7C ?D >D
    if (filterSettings) {
      const response = await fetch('/api/file-autocomplete', {
        method: 'POST',
        headers: {
          'Content-Type': 'application/json',
        },
        body: JSON.stringify({
          query,
          filterSettings,
        }),
      });
    }

    const data = await response.json();

    if (data.suggestions) {
      setSuggestions(data.suggestions);
    }
  }
}
```



```

    }
  } else {
    // A,,=C GCR 8D ?Cä;DÄ7D45CÂ tUB 7C ?D >D 1CT7 DD8C´LD$@C FC,,8
    const response = await fetch(`/api/file-autocomplete?query=${encodeURIComponent(query)}`);
    const data = await response.json();

    if (data.suggestions) {
      setSuggestions(data.suggestions);
    }
  }
} catch (error) {
  console.error('Error fetching suggestions:', error);
  setSuggestions([]);
} finally {
  setIsLoading(false);
}
};

```

```

// Aä1D 0C >D$GC,,; C,,7CÄ5CÔ5CÔ8Dò BCT:D BC 2 Cô>C´5 Cô>C,,AC¤0
const handleInputChange = (e: React.ChangeEvent<HTMLInputElement>) => {
  const value = e.target.value;
  setSearchValue(value);

  // B 1D >D 8D$L DD>C¤CD 8D >C$0CÔ=Cä5 Cô@CT4C´>Cd5CÔ8CR ?D 8 C,,7CÄ5CÔ5CÔ8C, 2C$>CD0
  setFocusedSuggestion(-1);

```

```

// Aô>C¤0Ct0D$L D ?C,,ACä: Cô@CT4C´>Cd5CÔ8C•
if (value.length >= 2) {
  setShowSuggestions(true);
  fetchSuggestions(value);
} else {
  setShowSuggestions(false);
  setSuggestions([]);
}
};

```

```

// Aä1D 0C >D$GC,,; C$KC >D 0 Cô@CT4C´>Cd5CÔ8Dð
const handleSelectSuggestion = (suggestion: string) => {
  // Aô>C´CDt0CT< C,,<Dò DC 9C´0 C,,;C, ?C ?C¤8 C,,7 Cô>C´=Cä3Câ ?D4BC€
  const fileName = suggestion.split('/').pop() || suggestion;
  setSearchValue(fileName);
  setShowSuggestions(false);
  onSearch(fileName);
};

```

```

// Aä1D 0C >D$GC,,; C¤;C 2C,,0D$CD =Cä9 CÔ0C$8C40Dd8C, Ò >CôBC,,<C,,7C,,@Cä2C =CÔ0Dò 2CT@D 8Dð
const handleKeyDown = (e: React.KeyboardEvent) => {
  // AÔ0C$8C40Dd8Dò ?Câ AD$@CT;C¤0CÂ 2C$5D E/C$=C,,7
  if (showSuggestions && suggestions.length > 0) {
    if (e.key === 'ArrowDown') {
      e.preventDefault();
      // Aô5D 5CÄ5D”5CÔ8CR 2CÔ8Cr ?Câ ACô8D :D0
      setFocusedSuggestion(prev => {
        const next = prev + 1 >= suggestions.length ? 0 : prev + 1;
        // B4AD$0CÔ0C$;C,,2C 5CÄ BC 9CÄ0D4B CD;Dò AC¤@Cä;C´0, DtBCä1D² 4C BDÂ &V 7B 2D 5CÄO CD;Dò >C =
        setTimeout(() => scrollToSuggestion(next), 0);
      });
    }
  }
};

```

```

    return next;
  });
} else if (e.key === 'ArrowUp') {
  e.preventDefault();
  // Aô5D 5CÄ5D"5CÔ8CR 2C$5D E Cô> D ?C,,ACαC
  setFocusedSuggestion(prev => {
    const next = prev - 1 < 0 ? suggestions.length - 1 : prev - 1;
    setTimeout(() => scrollToSuggestion(next), 0);
    return next;
  });
} else if (e.key === 'Enter' && focusedSuggestion >= 0) {
  e.preventDefault();
  // A$KC >D BCT:D4ICT3Câ ?D 5CD;Cä6CT=C,,O
  handleSelectSuggestion(suggestions[focusedSuggestion]);
} else if (e.key === 'Escape') {
  e.preventDefault();
  setShowSuggestions(false);
}
}
};

// BDCCÔ:Dd8Dò 4C´O Cô@Cä:D CD$:C, ACô8D :C : C$KC @C =CÔ>CÄC Cô@CT4C´>Cd5CÔ8Dà
const scrollToSuggestion = (index: number) => {
  if (suggestionsRef.current && suggestionsRef.current.children[index]) {
    const element = suggestionsRef.current.children[index] as HTMLElement;
    const container = suggestionsRef.current;

    // Aô@Cä2CT@Dô5CÄÂ =D46CÔ0 C´8 Cô@Cä:D CD$:C
    const elementTop = element.offsetTop;
    const elementBottom = elementTop + element.clientHeight;
    const containerTop = container.scrollTop;
    const containerBottom = containerTop + container.clientHeight;

    // ATAC´8 DÔ;CT<CT=D" 2D´HCR 2C,,4C,,<Cä9 Cä1C´0D BC,Â ?D >Cα@D4GC,,2C 5CÂ 2C$5D E
    if (elementTop < containerTop) {
      container.scrollTop = elementTop;
    }
    // ATAC´8 DÔ;CT<CT=D" =C,,6CR 2C,,4C,,<Cä9 Cä1C´0D BC,Â ?D >Cα@D4GC,,2C 5CÂ 2CÔ8Cp
    else if (elementBottom > containerBottom) {
      container.scrollTop = elementBottom - container.clientHeight;
    }
  }
};

// Aä1D 0C >D$GC,,: Cα;C,,:C 2CÔ5 Cα>CÄ?Cä=CT=D$0
useEffect(() => {
  const handleClickOutside = (e: MouseEvent) => {
    if (
      inputRef.current &&
      !inputRef.current.contains(e.target as Node) &&
      suggestionsRef.current &&
      !suggestionsRef.current.contains(e.target as Node)
    ) {
      setShowSuggestions(false);
    }
  };
};

```

```

document.addEventListener('mousedown', handleClickOutside);
return () => {
  document.removeEventListener('mousedown', handleClickOutside);
};
}, []);

// Aă1D 0C >D$GC,,: CăBCô@C 2Cª8 DD>D <D°
const handleSubmit = (e: React.FormEvent) => {
  e.preventDefault();
  setShowSuggestions(false);
  onSearch(searchValue);
};

// Aă1D 0C >D$GC,,: CăGC,AD$:C, ?Că;Dă
const handleClear = () => {
  setSearchValue("");
  setShowSuggestions(false);
  setSuggestions([]);
  onSearch("");
  inputRef.current?.focus();
};

// AăBCă1D 0Cd5CÔ8CR ?CăAC´5CD=CT3Câ ACT3CĂ5CÔBC ?D4BC, „8CĂO DD0C”;C 8C´8 Cô0Cô:C,•
const formatSuggestion = (path: string, index: number) => {
  const segments = path.split('/');
  const lastSegment = segments.pop() || path;
  const parentPath = segments.length > 0 ? segments.join('/') : "";
  const isSelected = index === focusedSuggestion;

  return (
    <div className="flex flex-col w-full">
      <span className="font-medium">{lastSegment}</span>
      {parentPath && (
        <span
          className={`text-xs truncate ${
            isSelected ? 'text-blue-100' : 'text-gray-500'
          }`}
          style={{
            opacity: isSelected ? 0.9 : 0.7
          }}
        >
          {parentPath}
        </span>
      )}
    </div>
  );
};

return (
  <form onSubmit={handleSubmit} className="flex gap-2 mb-4">
    <div className="relative flex-1">
      <Search className="absolute left-2.5 top-2.5 h-4 w-4 text-gray-400" />
      <Input
        ref={inputRef}
        type="text"

```

```

placeholder="A&gt;C,,AC¢ DC 9C´>C"âââ
value={searchValue}
onChange={handleInputChange}
onKeyDown={handleKeyDown}
onFocus={() => {
  if (searchValue.length >= 2) {
    setShowSuggestions(true);
    fetchSuggestions(searchValue);
  }
}}
className="pl-9 pr-9 border-gray-700 text-gray-200 focus:ring-blue-500 focus:border-blue-500"
style={{ backgroundColor: '#1f2937' }}
/>
{searchValue && (
  <button
    type="button"
    onClick={handleClear}
    className="absolute right-2.5 top-2.5 text-gray-400 hover:text-gray-200"
  >
    <X className="h-4 w-4" />
  </button>
)}

/* A,,:Cä=Cº0 C,,=DD>D <C FC,,8 D44C ;CT=C ¢÷Ð

/* A$KCô0CD0DäIC,,9 D ?C,,ACä: Cô@CT4C´>Cd5CÔ8C' ¢÷Ð
{showSuggestions && (
  <div
    ref={suggestionsRef}
    className="absolute z-50 mt-1 w-full max-h-60 overflow-auto rounded-md border border-
gray-700 shadow-lg py-1 autocomplete-dropdown"
    style={{
      backgroundColor: '#1e2030',
    }}
  >
    {isLoading ? (
      <div className="px-4 py-2 text-sm text-gray-400">At0C4@D47Cº0...</div>
    ) : suggestions.length > 0 ? (
      suggestions.map((suggestion, index) => (
        // biome-ignore lint/a11y/useKeyWithClickEvents: <explanation>
        <div
          key={suggestion}
          onClick={() => handleSelectSuggestion(suggestion)}
          style={{
            backgroundColor: focusedSuggestion === index ? '#2563eb' : '#1e2030',
            position: 'relative',
          }}
          className={`px-4 py-2 text-sm cursor-pointer hover:bg-blue-800 ${
            focusedSuggestion === index ? 'text-white' : 'text-gray-200'
          }}`
        >
          {formatSuggestion(suggestion, index)}
        </div>
      ))
    ) : (
      searchValue.length >= 2 && <div className="px-4 py-2 text-sm text-gray-400">AÔ5D" @CT7D4;DÄBC BCä2</div>
    )
  )
}

```

```
    })
  </div>
  })
</div>
<Button type="submit" size="sm" className="bg-blue-600 hover:bg-blue-700 text-white">
  AÔ0C"BC€
</Button>
</form>
);
}
```

Content of src/lib/stores/projects-store.ts

```
import type { FileNode, FilterSettings } from '@lib/types';
import { v4 as uuidv4 } from 'uuid';
import { create } from 'zustand';
import { persist } from 'zustand/middleware';

// B$8CôK CD;Dò AC,,AD$5CÄK Cò@Cä5C=BCä2 C, ?D >DD8C´5C•
export interface ProjectSettings {
  includeComments: boolean;
  newPageForEachFile: boolean;
  outputFileName: string;
  filterSettings: FilterSettings;
  selectedFiles: string[]; // AôCD$8 C¢ 2D´1D 0CÔ=D´< DD0C”;C <
}

export interface Profile {
  id: string;
  name: string;
  description?: string;
  settings: ProjectSettings;
  createdAt: number;
  updatedAt: number;
}

export interface Project {
  id: string;
  name: string;
  description?: string;
  baseSettings: ProjectSettings;
  profiles: Profile[];
  createdAt: number;
  updatedAt: number;
}

// AD5DD>C´BCÔKCR =C AD$@Cä9C=8 Cò@Cä5C=BC
export const DEFAULT_PROJECT_SETTINGS: ProjectSettings = {
  includeComments: true,
  newPageForEachFile: true,
  outputFileName: 'project_code.pdf',
  filterSettings: {
    ignoredDirectories: [],
    ignoredFiles: [],
    ignoredExtensions: [],
    allowedExtensions: [],
    useDefaultIgnores: true,
  },
  selectedFiles: [],
};

// B >D BCäOCÔ8CR 4C´O zustand
interface ProjectState {
  projects: Project[];
  activeProjectId?: string;
  activeProfileId?: string;
```

```

// A45D$BCT@D² 4C´O D44Cä1CÔ>C4> CD>D BD4?C : C :D$8C$=D´< Cä1D²5C²BC <
getActiveProject: () => Project | undefined;
getActiveProfile: () => Profile | undefined;
getActiveSettings: () => ProjectSettings;

// AÄ5D$>CDK CD;Dò 8Ct<CT=CT=C„O D >D BCäOCÔ8Dð
createProject: (name: string, description?: string) => Project;
updateProject: (projectId: string, updates: Partial<Project>) => void;
deleteProject: (projectId: string) => void;

createProfile: (projectId: string, name: string, description?: string, inheritFromProject?: boolean) =>
Profile;
updateProfile: (projectId: string, profileId: string, updates: Partial<Profile>) => void;
deleteProfile: (projectId: string, profileId: string) => void;

setActiveProject: (projectId?: string) => void;
setActiveProfile: (profileId?: string) => void;

updateActiveSettings: (updates: Partial<ProjectSettings>) => void;

// A$ACô>CÄ>C40D$5C´LCÔKCR CD$8C´8D$K
applySelectedFilesToTree: (fileTree: FileNode, selectedFiles: string[]) => FileNode;
}

// B >Ct4C 5CÂ ED 0CÔ8C´8D"5 D $W7F æ@
export const useProjectsStore = create<ProjectState>()(
  persist(
    (set, get) => ({
      projects: [],
      activeProjectId: undefined,
      activeProfileId: undefined,

// A45D$BCT@D°
getActiveProject: () => {
  const { projects, activeProjectId } = get();
  return projects.find((p) => p.id === activeProjectId);
},

getActiveProfile: () => {
  const { activeProfileId } = get();
  const activeProject = get().getActiveProject();

  if (!activeProject || !activeProfileId) {
    return undefined;
  }

  return activeProject.profiles.find((p) => p.id === activeProfileId);
},

getActiveSettings: () => {
  const activeProfile = get().getActiveProfile();
  const activeProject = get().getActiveProject();

  if (activeProfile) {
    return activeProfile.settings;

```

```

    }

    if (activeProject) {
      return activeProject.baseSettings;
    }

    return DEFAULT_PROJECT_SETTINGS;
  },

  // AÄ5D$>CDK CD;Dò ?D >CT:D$>C
  createProject: (name, description) => {
    const newProject: Project = {
      id: uuidv4(),
      name,
      description,
      baseSettings: { ...DEFAULT_PROJECT_SETTINGS },
      profiles: [],
      createdAt: Date.now(),
      updatedAt: Date.now(),
    };

    set((state) => ({
      projects: [...state.projects, newProject],
      activeProjectId: newProject.id,
      activeProfileId: undefined,
    }));

    return newProject;
  },

  updateProject: (projectId, updates) => {
    set((state) => ({
      projects: state.projects.map((project) =>
        project.id === projectId ? { ...project, ...updates, updatedAt: Date.now() } : project,
      ),
    }));
  },

  deleteProject: (projectId) => {
    set((state) => {
      // ATAC'8 D44C ;Dô5CÂ 0C=BC,,2CÔKC' ?D >CT:D"Â AC @C AD'2C 5CÂ 0C=BC,,2CÔKCR 2D'1Cä@D°
      const updatedState: Partial<ProjectState> = {
        projects: state.projects.filter((project) => project.id !== projectId),
      };

      if (state.activeProjectId === projectId) {
        updatedState.activeProjectId = undefined;
        updatedState.activeProfileId = undefined;
      }

      return updatedState as ProjectState;
    });
  },

  // AÄ5D$>CDK CD;Dò ?D >DD8C'5C•
  createProfile: (projectId, name, description, inheritFromProject = true) => {

```



```

const { projects } = get();
const project = projects.find((p) => p.id === projectId);

const settings = inheritFromProject && project ? { ...project.baseSettings } :
{ ...DEFAULT_PROJECT_SETTINGS };

const newProfile: Profile = {
  id: uuidv4(),
  name,
  description,
  settings,
  createdAt: Date.now(),
  updatedAt: Date.now(),
};

set((state) => ({
  projects: state.projects.map((project) => {
    if (project.id === projectId) {
      return {
        ...project,
        profiles: [...project.profiles, newProfile],
        updatedAt: Date.now(),
      };
    }
    return project;
  }),
  activeProfileId: newProfile.id,
})));

return newProfile;
},

updateProfile: (projectId, profileId, updates) => {
  set((state) => ({
    projects: state.projects.map((project) => {
      if (project.id === projectId) {
        return {
          ...project,
          profiles: project.profiles.map((profile) =>
            profile.id === profileId ? { ...profile, ...updates, updatedAt: Date.now() } : profile,
          ),
          updatedAt: Date.now(),
        };
      }
      return project;
    }),
  })));
},

deleteProfile: (projectId, profileId) => {
  set((state) => {
    const updatedState: Partial<ProjectState> = {
      projects: state.projects.map((project) => {
        if (project.id === projectId) {
          return {
            ...project,

```

```

        profiles: project.profiles.filter((profile) => profile.id !== profileId),
        updatedAt: Date.now(),
    };
}
return project;
}),
};

// ATAC`8 D44C ;Dô5CÂ 0C¬BC,,2CÔKC' ?D >DD8C'L, D 1D 0D KC$0CT< CT3Cà
if (state.activeProfileId === profileId) {
    updatedState.activeProfileId = undefined;
}

return updatedState as ProjectState;
});
},

// B4?D 0C$;CT=C,,5 C :D$8C$=D'<C, 2D'1Cä@C <C€
setActiveProject: (projectId) => {
    set({
        activeProjectId: projectId,
        activeProfileId: undefined, // Aô@C, ACÄ5CÔ5 Cô@Cä5C¬BC AC @C AD'2C 5CÂ ?D >DD8C'L
    });
},

setActiveProfile: (profileId) => {
    set({ activeProfileId: profileId });
},

// Aä1CÔ>C$;CT=C,,5 CÔ0D BD >CT:
updateActiveSettings: (updates) => {
    const { activeProjectId, activeProfileId } = get();
    const activeProfile = get().getActiveProfile();
    const activeProject = get().getActiveProject();

    if (activeProfile && activeProjectId) {
        // Aä1CÔ>C$;Dô5CÂ =C AD$@Cä9C¬8 C" 0C¬BC,,2CÔ>CÂ ?D >DD8C'5
        get().updateProfile(activeProjectId, activeProfile.id, {
            settings: { ...activeProfile.settings, ...updates },
        });
    } else if (activeProject) {
        // Aä1CÔ>C$;Dô5CÂ 1C 7Cä2D'5 CÔ0D BD >C":C, ?D >CT:D$0
        get().updateProject(activeProject.id, {
            baseSettings: { ...activeProject.baseSettings, ...updates },
        });
    }
},

// Aô@C,,<CT=CT=C,,5 C$KC @C =CÔKDR DC 9C'>C" : CD5D 5C$C
applySelectedFilesToTree: (fileTree, selectedFiles) => {
    const filesSet = new Set(selectedFiles);

    // B 5C¬CD AC,,2CÔ> Cä1DT>CD8CÂ 4CT@CT2Câ 8 Cô@CäAD$0C$;Dô5CÂ 6VÆV7FVC true CD;Dò CC¬0Ct0C
    const updateSelection = (node: FileNode): FileNode => {
        const selected = filesSet.has(node.path);

```

```

// ATAC'8 DÔBCâ DC 9C²Â ?D >D BCâ >C =Câ2C'OCT< C$KC >D
if (node.type === 'file') {
  return { ...node, selected };
}

// ATAC'8 DÔBCâ 4C,,@CT:D$>D 8DòÂ @CT:D4@D 8C$=Câ >C @C 1C BD'2C 5CÂ 4CäGCT@CÔ8CR MC'5CÄ5
if (node.children) {
  const updatedChildren = node.children.map((child) => updateSelection(child));

  // AD8D 5C▯BCä@C,,O D GC,,BC 5D$ADò 2D'1D 0CÔ=Cä9, CTAC'8 C$ACR 5CR 4CäGCT@CÔ8CR MC'5CÄ5
  const allChildrenSelected = updatedChildren.length > 0 && updatedChildren.every((child) =>
child.selected);

  return {
    ...node,
    selected: allChildrenSelected,
    children: updatedChildren,
  };
}

return node;
};

return updateSelection(fileTree);
},
)),
{
  name: 'code-consolidator-projects',
  // A$5D AC,,>CÔ8D >C$0CÔ8CR ED 0CÔ8C'8D"0 CD;Dò 2Cä7CÄ>Cd=D'E C CCD CD"8DR 8Ct<CT=CT=C,,9 D BD
  version: 1,
},
),
);

```

Content of src/lib/file-system.ts

```
'use client';

// BÔBCäB DD0C"; D >CD5D 6C,,B D$>C´LCα> D$8CôK C, DD4=CαFC,,8 CD;Dò @C 1CäBD² =C :C´8CT=D$5
import { FileNode } from './types';

// BD>D <C BC,,@Cä2C =C,,5 D 0Ct<CT@C DC 9C´0
export function formatFileSize(bytes: number): string {
  if (bytes === 0) return '0 Bytes';

  const k = 1024;
  const sizes = ['Bytes', 'KB', 'MB', 'GB', 'TB'];
  const i = Math.floor(Math.log(bytes) / Math.log(k));

  return parseFloat((bytes / Math.pow(k, i)).toFixed(2)) + ' ' + sizes[i];
}
```

Content of src/lib/format-utils.ts

```
// BD>D <C BC,,@Cä2C =C,,5 D 0Ct<CT@C DC 9C`0
export function formatFileSize(bytes: number): string {
  if (bytes === 0) return '0 B';

  const k = 1024;
  const sizes = ['B', 'KB', 'MB', 'GB', 'TB'];
  const i = Math.floor(Math.log(bytes) / Math.log(k));

  return parseFloat((bytes / Math.pow(k, i)).toFixed(1)) + ' ' + sizes[i];
}

// BD>D <C BC,,@Cä2C =C,,5 CD0D$K
export function formatDate(timestamp: number): string {
  const date = new Date(timestamp);

  // Aô>C`CDt0CT< CD5CÔL, CÄ5D ODbÂ 3Cä4, Dt0D K C, <C,,=D4BD°
  const day = String(date.getDate()).padStart(2, '0');
  const month = String(date.getMonth() + 1).padStart(2, '0');
  const year = date.getFullYear();
  const hours = String(date.getHours()).padStart(2, '0');
  const minutes = String(date.getMinutes()).padStart(2, '0');

  return `${day}.${month}.${year} ${hours}:${minutes}`;
}
```

Content of src/lib/projects-storage.ts

```
import { FilterSettings, FileNode } from './types';
import { v4 as uuidv4 } from 'uuid';

// B$8CöK CD;Dö AC,,AD$5CÄK Cö@Cä5C¬BCä2 C, ?D >DD8C´5C•
export interface ProjectSettings {
  includeComments: boolean;
  newPageForEachFile: boolean;
  outputFileName: string;
  filterSettings: FilterSettings;
  selectedFiles: string[]; // AöCD$8 C¢ 2D´1D 0CÔ=D´< DD0C”;C <
}

export interface Profile {
  id: string;
  name: string;
  description?: string;
  settings: ProjectSettings;
  createdAt: number;
  updatedAt: number;
}

export interface Project {
  id: string;
  name: string;
  description?: string;
  baseSettings: ProjectSettings;
  profiles: Profile[];
  createdAt: number;
  updatedAt: number;
}

// A¬>D =CT2Cä9 Cä1D¬5C¬B CD;Dö ED 0CÔ5CÔ8Dö 2 localStorage
export interface ProjectsStorage {
  projects: Project[];
  activeProjectId?: string;
  activeProfileId?: string;
}

// A¬;DäG CD;Dö Æö6 Å7F÷ age
const STORAGE_KEY = 'code-consolidator-projects';

// AD5DD>C´BCÔKCR =C AD$@Cä9C¬8 Cö@Cä5C¬BC
export const DEFAULT_PROJECT_SETTINGS: ProjectSettings = {
  includeComments: true,
  newPageForEachFile: true,
  outputFileName: 'project_code.pdf',
  filterSettings: {
    ignoredDirectories: [],
    ignoredFiles: [],
    ignoredExtensions: [],
    allowedExtensions: [],
    useDefaultIgnores: true,
  },
},
```

```

    selectedFiles: [],
  };

  // Að>C´CDt5CÔ8CR 4C =CÔKDR 8Cr Æö6 Å7F÷ age
  export function getProjectsStorage(): ProjectsStorage {
    if (typeof window === 'undefined') {
      return { projects: [] };
    }

    const storageData = localStorage.getItem(STORAGE_KEY);
    if (!storageData) {
      return { projects: [] };
    }

    try {
      return JSON.parse(storageData) as ProjectsStorage;
    } catch (error) {
      console.error('AäHC,,1Cð0 Cð@C, GD$5CÔ8C, 4C =CÔKDR ?D >CT:D$>C#¢rÂ W'&÷""°
      return { projects: [] };
    }
  }

  // B >Dt4C =C,,5 CD0CÔ=D´E C" Æö6 Å7F÷ age
  export function saveProjectsStorage(data: ProjectsStorage): void {
    if (typeof window === 'undefined') {
      return;
    }

    localStorage.setItem(STORAGE_KEY, JSON.stringify(data));
  }

  // B >Ct4C =C,,5 CÔ>C$>C4> Cð@Cä5CðBC
  export function createProject(name: string, description?: string): Project {
    return {
      id: uuidv4(),
      name,
      description,
      baseSettings: { ...DEFAULT_PROJECT_SETTINGS },
      profiles: [],
      createdAt: Date.now(),
      updatedAt: Date.now(),
    };
  }

  // B >Ct4C =C,,5 CÔ>C$>C4> Cð@CäDC,,Dð 2CÔCD$@C, ?D >CT:D$0
  export function createProfile(
    projectId: string,
    name: string,
    description?: string,
    inheritFromProject = true
  ): Profile {
    const storage = getProjectsStorage();
    const project = storage.projects.find(p => p.id === projectId);

    const settings = inheritFromProject && project
      ? { ...project.baseSettings }

```

```

: { ...DEFAULT_PROJECT_SETTINGS };

return {
  id: uuidv4(),
  name,
  description,
  settings,
  createdAt: Date.now(),
  updatedAt: Date.now(),
};
}

// Aô>C`CDt5CÔ8CR 0C▯BC,,2CÔ>C4> Cô@Cä5C▯BC
export function getActiveProject(): Project | undefined {
  const storage = getProjectsStorage();

  if (!storage.activeProjectId) {
    return undefined;
  }

  return storage.projects.find(p => p.id === storage.activeProjectId);
}

// Aô>C`CDt5CÔ8CR 0C▯BC,,2CÔ>C4> Cô@CäDC,,;Dö
export function getActiveProfile(): Profile | undefined {
  const storage = getProjectsStorage();
  const project = getActiveProject();

  if (!project || !storage.activeProfileId) {
    return undefined;
  }

  return project.profiles.find(p => p.id === storage.activeProfileId);
}

// Aô>C`CDt5CÔ8CR BCT:D4IC,,E C :D$8C$=D´E CÔ0D BD >CT: (C,,7 Cô@CäDC,,;Dò 8C´8 Cô@Cä5C▯BC •
export function getActiveSettings(): ProjectSettings {
  const activeProfile = getActiveProfile();
  const activeProject = getActiveProject();

  if (activeProfile) {
    return activeProfile.settings;
  }

  if (activeProject) {
    return activeProject.baseSettings;
  }

  return DEFAULT_PROJECT_SETTINGS;
}

// Aä1CÔ>C$;CT=C,,5 C$KC @C =CÔKDR DC 9C´>C" 2 C :D$8C$=Cä< C▯>CÔBCT:D BCP
export function updateSelectedFiles(selectedFiles: string[]): void {
  const storage = getProjectsStorage();
  const activeProject = storage.activeProjectId
    ? storage.projects.find(p => p.id === storage.activeProjectId)

```



```

: undefined;

if (!activeProject) return;

const activeProfile = storage.activeProfileId && activeProject
? activeProject.profiles.find(p => p.id === storage.activeProfileId)
: undefined;

if (activeProfile) {
// Aä1CÔ>C$;Dô5CÂ 2 C :D$8C$=Cä< Cò@CäDC,,,CP
storage.projects = storage.projects.map(project => {
  if (project.id === storage.activeProjectId) {
    return {
      ...project,
      profiles: project.profiles.map(profile => {
        if (profile.id === storage.activeProfileId) {
          return {
            ...profile,
            settings: { ...profile.settings, selectedFiles },
            updatedAt: Date.now(),
          };
        }
      })
    };
  }
  return profile;
});
}
return project;
});
} else if (activeProject) {
// Aä1CÔ>C$;Dô5CÂ 2 C 0Ct>C$KDR =C AD$@Cä9C=0DR ?D >CT:D$0
storage.projects = storage.projects.map(project => {
  if (project.id === storage.activeProjectId) {
    return {
      ...project,
      baseSettings: { ...project.baseSettings, selectedFiles },
      updatedAt: Date.now(),
    };
  }
  return project;
});
}

saveProjectsStorage(storage);
}

// A$ACô>CÄ>C40D$5C´LCÔ0Dò DD4=C¢FC,,O CD;Dò ?D 5Cä1D 0Ct>C$0CÔ8Dò ACô8D :C 2D´1D 0CÔ=D´E DD0C";
export function applySelectedFilesToTree(fileTree: FileNode, selectedFiles: string[]): FileNode {
  const filesSet = new Set(selectedFiles);

  // B 5C¢CD AC,,2CÔ> Cä1DT>CD8CÂ 4CT@CT2Câ 8 Cò@CäAD$0C$;Dô5CÂ 6V/ÆV7FVC true CD;Dò CC¢0Ct0CÔ=L
  const updateSelection = (node: FileNode): FileNode => {
    const selected = filesSet.has(node.path);

    // ATAC´8 DÔBCâ DC 9C²Â ?D >D BCâ >C =Cä2C´OCT< C$KC >D
    if (node.type === 'file') {
      return { ...node, selected };
    }
  };
}

```

```

}

// ATAC'8 DÔBCâ 4C,,@CT:D$>D 8DòÂ @CT:D4@D 8C$=Câ >C @C 1C BD'2C 5CÂ 4CäGCT@CÔ8CR MC'5CÄ5C
if (node.children) {
  const updatedChildren = node.children.map(child => updateSelection(child));

  // AD8D 5C▯BCä@C,,O D GC,,BC 5D$ADò 2D'1D 0CÔ=Cä9, CTAC'8 C$ACR 5CR 4CäGCT@CÔ8CR MC'5CÄ5CÔE
  const allChildrenSelected = updatedChildren.length > 0 &&
    updatedChildren.every(child => child.selected);

  return {
    ...node,
    selected: allChildrenSelected,
    children: updatedChildren,
  };
}

return node;
};

return updateSelection(fileTree);
}

// Aä1CÔ>C$;CT=C,,5 CÔ0D BD >CT: DD8C'LD$@C FC,,8 C" 0C▯BC,,2CÔ>CÂ :Cä=D$5C▯AD$5
export function updateSettings(settings: Partial<ProjectSettings>): void {
  const storage = getProjectsStorage();
  const activeProject = storage.activeProjectId
    ? storage.projects.find(p => p.id === storage.activeProjectId)
    : undefined;

  if (!activeProject) return;

  const activeProfile = storage.activeProfileId && activeProject
    ? activeProject.profiles.find(p => p.id === storage.activeProfileId)
    : undefined;

  if (activeProfile) {
    // Aä1CÔ>C$;Dô5CÂ 2 C :D$8C$=Cä< Cò@CäDC,,;CP
    storage.projects = storage.projects.map(project => {
      if (project.id === storage.activeProjectId) {
        return {
          ...project,
          profiles: project.profiles.map(profile => {
            if (profile.id === storage.activeProfileId) {
              return {
                ...profile,
                settings: { ...profile.settings, ...settings },
                updatedAt: Date.now(),
              };
            }
          })
        };
      }
      return project;
    });
  }
};

```

```

} else if (activeProject) {
  // Aâ1CÔ>C$;Dô5CÂ 2 C 0Ct>C$KDR =C AD$@Cä9C=0DR ?D >CT:D$0
  storage.projects = storage.projects.map(project => {
    if (project.id === storage.activeProjectId) {
      return {
        ...project,
        baseSettings: { ...project.baseSettings, ...settings },
        updatedAt: Date.now(),
      };
    }
    return project;
  });
}

saveProjectsStorage(storage);
}

```

Content of src/lib/tree-utils.ts

```
import { FileNode } from './types';

// BDCCÔ:Dd8Dò 4C´O Că1CÔ>C$;CT=C„O C$KC @C =CÔKDR DC 9C´>C" 2 CD5D 5C$5
export function updateNodeSelection(tree: FileNode, path: string, selected: boolean): FileNode {
  if (tree.path === path) {
    // ATAC´8 DÔBCâ 4C„@CT:D$>D 8DòÂ >C =Că2C´OCT< C$ACR 4CăGCT@CÔ8CR MC´5CĂ5CÔBD°
    if (tree.type === 'directory' && tree.children) {
      return {
        ...tree,
        selected,
        children: tree.children.map(child => ({
          ...child,
          selected,
          children: child.children
            ? child.children.map(grandchild => updateNodeSelection({
              ...grandchild,
              selected
            }, grandchild.path, selected))
            : undefined
        })))
      };
    }
  }

  // ATAC´8 DÔBCâ DC 9C²Â ?D >D BCâ >C =Că2C´OCT< CT3Câ AD$0D$CD
  return { ...tree, selected };
}

// ATAC´8 DÔBCâ =CR 8D :Că<D´9 D47CT;, CÔ> D2 =CT3Câ 5D BDÂ 4CTBC€
if (tree.children) {
  return {
    ...tree,
    children: tree.children.map(child => updateNodeSelection(child, path, selected))
  };
}

return tree;
}

// BDCCÔ:Dd8Dò 4C´O Că>C´CDt5CÔ8Dò ?D4BCT9 C$KC @C =CÔKDR DC 9C´>C
export function getSelectedFilePaths(node: FileNode): string[] {
  let paths: string[] = [];

  if (node.type === 'file' && node.selected) {
    paths.push(node.path);
  }

  if (node.children) {
    node.children.forEach(child => {
      paths = [...paths, ...getSelectedFilePaths(child)];
    });
  }

  return paths;
}
```

```
}
```

```
// BDCCÔ:Dd8Dò 4C´O Cô>CDADt5D$0 C$KC @C =CÔKDR DC 9C´>C" 2 CD5D 5C$5
```

```
export function countSelectedFiles(node: FileNode): number {
```

```
  let count = node.type === 'file' && node.selected ? 1 : 0;
```

```
  if (node.children) {
```

```
    count += node.children.reduce((acc, child) => acc + countSelectedFiles(child), 0);
```

```
  }
```

```
  return count;
```

```
}
```

Content of src/lib/types.ts

```
// B$8C0K CD;D0 DC 9C´>C$>C4> CD5D 5C$0
```

```
export interface FileNode {  
  name: string;  
  path: string;  
  type: 'file' | 'directory';  
  size?: number;  
  selected?: boolean;  
  children?: FileNode[];  
}
```

```
// B$8C0K CD;D0 DC,,;DÄBD 0Dd8C€
```

```
export interface FilterSettings {  
  ignoredDirectories: string[];  
  ignoredFiles: string[];  
  ignoredExtensions: string[];  
  allowedExtensions: string[];  
  useDefaultIgnores: boolean;  
}
```

Content of src/lib/use-projects.ts

```
import { useEffect, useState } from 'react';
import {
  Project,
  Profile,
  ProjectSettings,
  getProjectsStorage,
  saveProjectsStorage,
  createProject as createProjectUtil,
  createProfile as createProfileUtil,
  DEFAULT_PROJECT_SETTINGS
} from './projects-storage';

export function useProjects() {
  const [projects, setProjects] = useState<Project[]>([]);
  const [activeProjectId, setActiveProjectId] = useState<string | undefined>();
  const [activeProfileId, setActiveProfileId] = useState<string | undefined>();
  const [isLoading, setIsLoaded] = useState(false);

  // At0C4@D47C=0 CD0CÔ=D'E C,,7 localStorage C@C, 8CÔ8Dd8C ;C,,7C FC,,8
  useEffect(() => {
    const storage = getProjectsStorage();
    setProjects(storage.projects);
    setActiveProjectId(storage.activeProjectId);
    setActiveProfileId(storage.activeProfileId);
    setIsLoaded(true);
  }, []);

  // B >DT@C =CT=C,,5 C,,7CÄ5CÔ5CÔ8C' 2 localStorage
  useEffect(() => {
    if (!isLoading) return;

    const storage = getProjectsStorage();
    storage.projects = projects;
    storage.activeProjectId = activeProjectId;
    storage.activeProfileId = activeProfileId;
    saveProjectsStorage(storage);
  }, [projects, activeProjectId, activeProfileId, isLoading]);

  // A :D$8C$=D'9 C@Cä5C=B
  const activeProject = activeProjectId
    ? projects.find(p => p.id === activeProjectId)
    : undefined;

  // A :D$8C$=D'9 C@CäDC,,;DÄ
  const activeProfile = activeProject && activeProfileId
    ? activeProject.profiles.find(p => p.id === activeProfileId)
    : undefined;

  // A :D$8C$=D'5 CÔ0D BD >C":C, „8Cr ?D >DD8C'O C,,;C, 8Cr ?D >CT:D$0)
  const activeSettings = activeProfile
    ? activeProfile.settings
    : activeProject
    ? activeProject.baseSettings
```

```

: DEFAULT_PROJECT_SETTINGS;

// B >Ct4C =C,,5 CÔ>C$>C4> Cô@Cä5C▯BC
const createProject = (name: string, description?: string) => {
  const newProject = createProjectUtil(name, description);
  setProjects([...projects, newProject]);
  return newProject;
};

// Aä1CÔ>C$;CT=C,,5 Cô@Cä5C▯BC
const updateProject = (projectId: string, updates: Partial<Project>) => {
  setProjects(projects.map(project =>
    project.id === projectId
      ? { ...project, ...updates, updatedAt: Date.now() }
      : project
  ));
};

// B44C ;CT=C,,5 Cô@Cä5C▯BC
const deleteProject = (projectId: string) => {
  setProjects(projects.filter(project => project.id !== projectId));

  // ATAC'8 D44C ;Dô5CÂ 0C▯BC,,2CÔKC' ?D >CT:D"Â AC @C AD'2C 5CÂ 0C▯BC,,2CÔKCR ?D >CT:D" 8 Cô@CäDC,
  if (activeProjectId === projectId) {
    setActiveProjectId(undefined);
    setActiveProfileId(undefined);
  }
};

// B >Ct4C =C,,5 CÔ>C$>C4> Cô@CäDC,,;Dò 2 Cô@Cä5C▯BCP
const createProfile = (
  projectId: string,
  name: string,
  description?: string,
  inheritFromProject = true
) => {
  const newProfile = createProfileUtil(projectId, name, description, inheritFromProject);

  setProjects(projects.map(project => {
    if (project.id === projectId) {
      return {
        ...project,
        profiles: [...project.profiles, newProfile],
        updatedAt: Date.now()
      };
    }
    return project;
  }));

  return newProfile;
};

// Aä1CÔ>C$;CT=C,,5 Cô@CäDC,,;Dö
const updateProfile = (projectId: string, profileId: string, updates: Partial<Profile>) => {
  setProjects(projects.map(project => {
    if (project.id === projectId) {

```



```

return {
  ...project,
  profiles: project.profiles.map(profile =>
    profile.id === profileId
      ? { ...profile, ...updates, updatedAt: Date.now() }
      : profile
  ),
  updatedAt: Date.now()
};
}
return project;
});
};

```

```

// B44C ;CT=C,5 C@CäDC,,Dă
const deleteProfile = (projectId: string, profileId: string) => {
  setProjects(projects.map(project => {
    if (project.id === projectId) {
      return {
        ...project,
        profiles: project.profiles.filter(profile => profile.id !== profileId),
        updatedAt: Date.now()
      };
    }
  }
  return project;
}));

```

```

// ATAC`8 D44C ;Dô5CÂ 0C▯BC,,2CÔKC' ?D >DD8C`L, D 1D 0D KC$0CT< CT3Cà
if (activeProfileId === profileId) {
  setActiveProfileId(undefined);
}
};

```

```

// B4AD$0CÔ>C$:C 0C▯BC,,2CÔ>C4> C@Cä5C▯BC
const setActiveProject = (projectId?: string) => {
  setActiveProjectId(projectId);
  setActiveProfileId(undefined); // A@C, ACÄ5CÔ5 C@Cä5C▯BC AC @C AD`2C 5CÂ 0C▯BC,,2CÔKC' ?D >DD8C`L
};

```

```

// B4AD$0CÔ>C$:C 0C▯BC,,2CÔ>C4> C@CäDC,,Dă
const setActiveProfile = (profileId?: string) => {
  setActiveProfileId(profileId);
};

```

```

// Aä1CÔ>C$;CT=C,5 CÔ0D BD >CT: C :D$8C$=Cä3Câ ?D >CT:D$0 C,,C, ?D >DD8C`O
const updateActiveSettings = (updates: Partial<ProjectSettings>) => {
  if (activeProfile && activeProjectId) {
    // Aä1CÔ>C$;Dô5CÂ =C AD$@Cä9C▯8 C" 0C▯BC,,2CÔ>CÂ ?D >DD8C`5
    updateProfile(activeProjectId, activeProfile.id, {
      settings: { ...activeProfile.settings, ...updates }
    });
  } else if (activeProject) {
    // Aä1CÔ>C$;Dô5CÂ 1C 7Cä2D`5 CÔ0D BD >C":C, ?D >CT:D$0
    updateProject(activeProject.id, {
      baseSettings: { ...activeProject.baseSettings, ...updates }
    });
  }
};

```

```
    }  
};  
  
return {  
  projects,  
  activeProjectId,  
  activeProfileId,  
  activeProject,  
  activeProfile,  
  activeSettings,  
  createProject,  
  updateProject,  
  deleteProject,  
  createProfile,  
  updateProfile,  
  deleteProfile,  
  setActiveProject,  
  setActiveProfile,  
  updateActiveSettings,  
  isLoading  
};  
}
```

Content of src/lib/utils.ts

```
import { type ClassValue, clsx } from "clsx"
import { twMerge } from "tailwind-merge"

export function cn(...inputs: ClassValue[]) {
  return twMerge(clsx(inputs))
}

// BDCCÔ:Dd8Dð 4C´O D4AD$0CÔ>C$:C, :D4:C€
export function setCookie(name: string, value: string, days = 365) {
  const date = new Date();
  date.setTime(date.getTime() + (days * 24 * 60 * 60 * 1000));
  const expires = `expires=${date.toUTCString()}`;
  document.cookie = `${name}=${encodeURIComponent(value)}${expires};path=/;SameSite=Strict`;
}

// BDCCÔ:Dd8Dð 4C´O Cð>C´CDt5CÔ8Dð 7CÔ0Dt5CÔ8Dð :D4:C€
export function getCookie(name: string): string | null {
  if (typeof document === 'undefined') return null;

  const nameEQ = `${name}=`;
  const ca = document.cookie.split(';');

  for (let i = 0; i < ca.length; i++) {
    let c = ca[i];
    while (c.charAt(0) === ' ') c = c.substring(1, c.length);
    if (c.indexOf(nameEQ) === 0) {
      return decodeURIComponent(c.substring(nameEQ.length, c.length));
    }
  }

  return null;
}

// BDCCÔ:Dd8Dð 4C´O D44C ;CT=C,,O CðCCð8
export function deleteCookie(name: string) {
  document.cookie = `${name}=;expires=Thu, 01 Jan 1970 00:00:00 GMT;path=/;SameSite=Strict`;
}
```