

# Data Structures

## Stack Applications

### Finding a Path in a Labyrinth

- The problem of finding a path in a labyrinth can be solved using the stack data structure:
  - While traversing the labyrinth, the states at decision points where going in more than one direction is possible get pushed onto a stack.
- We select one of the possible directions and proceed in that direction.
- If the choice made is not a correct choice, and we cannot find the exit of the labyrinth in this way, we go back to the last decision point (by popping the last state from the stack) and continue to search for the exit in the other untraversed directions.
- In the example labyrinth below, the first four steps are shown.
- In this representation, x's represent walls, the empty spaces represent paths, and o's represent traversed positions.

ENTRANCE →



→ EXIT

3

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Stack Applications



4

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Stack Applications

```

XXXXXXXXXX
OOXXX
X  XXX  XX
X      X
X  X  XX X
X  XX X  X
X  X    X
XXXXXXXXXX

```

5

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Stack Applications

```



XXXXXXXXXX
OOXXX
XOXXX  XX
X      X
X  X  XX X
X  XX X  X
X  X    X
XXXXXXXXXX

```

6

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Stack Applications





9

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

```

typedef struct d{
    int x;
    int y;
    int right;
    int left;
    int down;
    int up;
    int camefrom;
}StackDataType, position;

struct Node{
    StackDataType data;
    Node *next;
};

```

0/1: cannot go/can go

10

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Stack Applications

## Labyrinth.cpp

```
#define RIGHT 1
#define LEFT 2
#define UP 3
#define DOWN 4

char lab[8][8]={{'x','x','x','x','x','x','x','x'},
                {' ',' ','x','x','x',' ',' ',' '},
                {'x',' ','x','x','x',' ','x','x'},
                {'x',' ',' ',' ',' ',' ',' ','x'},
                {'x',' ','x',' ','x','x',' ','x'},
                {'x',' ','x','x',' ','x',' ','x'},
                {'x',' ',' ','x',' ',' ',' ','x'},
                {'x','x','x','x','x','x','x','x'}};
```

11

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Stack Applications

```
void printlab(char l[8][8]) {
    for (int i = 0; i < 8; i++) {
        for (int j = 0; j < 8; j++)
            cout << l[i][j];
        cout << endl;
    }
    cout << endl << endl;
}
```

12

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Stack Applications

```

int main(){
    Stack s;
    s.create();
    position entrance = {0,1,0,0,0,0,0};
    position exit = {7,1,0,0,0,0,0};
    position p = entrance;
    p.camefrom = LEFT;
    printlab(lab);
    bool goback = false;

```

13

İTÜ, BLG 221E Data Structures, G. Eryigit, S. Kabadayi © 2012

Stack Applications

```

while (p.x != exit.x || p.y != exit.y) {
    lab[p.y][p.x]='o';
    printlab(lab);
    //first find in how many directions we can move
    if (!goback) { //if not calculated before
        p.right = 0; p.left = 0; p.down = 0; p.up = 0;
        if (p.x<7 && lab[p.y][p.x+1]!='x') p.right=1;//right
        if (p.x>0 && lab[p.y][p.x-1]!='x') p.left=1;//left
        if (p.y<7 && lab[p.y+1][p.x]!='x') p.down=1;//down
        if (p.y>0 && lab[p.y-1][p.x]!='x') p.up=1;//up
    }
    else goback = false;

```

14

İTÜ, BLG 221E Data Structures, G. Eryigit, S. Kabadayi © 2012

Stack Applications

```
//here, one of the possible moves is selected
bool moved = true;
position past = p;
if (p.down && p.camefrom != DOWN)
    {p.y++; p.camefrom = UP; past.down = 0;}
else if (p.up && p.camefrom != UP)
    {p.y--; p.camefrom = DOWN; past.up = 0;}
else if (p.left && p.camefrom != LEFT)
    {p.x--; p.camefrom = RIGHT; past.left = 0;}
else if (p.right && p.camefrom != RIGHT)
    {p.x++; p.camefrom = LEFT; past.right = 0;}
else moved = false; //one direction (the
                    //minimum) is open, but this is the direction
                    //we came from
```

15

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Stack Applications

```
if (p.x != exit.x || p.y != exit.y) {
    if ( (p.down + p.up + p.right + p.left) > 2) {
        //there is more than one choice, push onto stack and
        //continue in that chosen direction. Let the choices
        //you have not selected remain marked on the stack.

        s.push(past);
    }
    if (!moved) { // has to go back
        if ( !s.isempty() ) {
            p = s.pop();
            goback = true;
        }
    }
}
```

16

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Stack Applications



```

} //end of while
lab[p.y][p.x] = 'o';
printlab(lab);
cout << "PATH found" << endl;
s.close();

return EXIT_SUCCESS;
}

```

17

İTÜ, BLG 221E Data Structures, G. Eryigit, S. Kabadayı © 2012

Stack Applications

- Assuming that the code works step-by-step, the state of the stack after every stack operation (push and pull) is shown below.



s	{head=0x003b6138 size=-658993459 }
head	0x003b6138 {data={...} next=0x00000000 }
data	{x=1 y=3 right=1 ...}
x	1
y	3
right	1
left	0
down	0
up	1
camefrom	3

18

İTÜ, BLG 221E Data Structures, G. Eryigit, S. Kabadayı © 2012

Stack Applications

```

XXXXXXXXXX
OOXXXX
XOXXXX XX
XOOO  X
XOX  XX X
XOXX X X
XOOX  X
XXXXXXXXXX

```

s	{head=0x003b6138 size=-858993459 }
head	0x003b6138 {data={...} next=0x00000000 }
data	{x=3 y=3 right=1 ...}
x	3
y	3
right	1
left	1
down	0
up	0
camefrom	2
next	0x00000000 {data={...} next=??? }

19

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Stack Applications

```

XXXXXXXXXX
OOXXXX
XOXXXX XX
XOOOOO  X
XOXOXX  X
XOXX  X X
XOOX  X
XXXXXXXXXX

```

s	{head=0x003b6138 size=-858993459 }
head	0x003b6138 {data={...} next=0x00000000 }
data	{x=5 y=3 right=1 ...}
x	5
y	3
right	1
left	1
down	0
up	0
camefrom	2

20

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

- In the part of the code where a direction is selected, as a result of preference being given to going right, the state of the stack after every stack operation (push and pull):

```

if(p.right && p.camefrom != RIGHT)
    {p.x++;p.camefrom=LEFT;past.right=0;}
else if(p.down && p.camefrom != DOWN)
    {p.y++;p.camefrom=UP;past.down=0;}
else if(p.up && p.camefrom != UP)
    {p.y--;p.camefrom=DOWN;past.up=0;}
else if (p.left && p.camefrom != LEFT)
    {p.x--;p.camefrom=RIGHT;past.left=0;}
else moved = false;

```

21

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Stack Applications

Variable	Value
bas	0x00624f90 {veri={...} sonraki=0x00000000 }
veri	{x=1 y=3 sag=0 ...}
x	1
y	3
sag	0
sol	0
asagi	1
yukari	1
geleniyon	3

22


İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012



y	{bas=0x00621748 boyut=-858993458 }
bas	0x00621748 {veri={...} sonraki=0x00624f90 }
veri	{x=3 y=3 sag=0 ...}
x	3
y	3
sag	0
sol	1
asagi	1
yukari	0
gelinesyon	2
sonraki	0x00624f90 {veri={...} sonraki=0x00000000 }
veri	{x=1 y=3 sag=0 ...}
x	1
y	3
sag	0
sol	0
asagi	1
yukari	1
gelinesyon	3
sonraki	0x00000000 {veri={...} sonraki=??? }

23

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012



y	{bas=0x006217a8 boyut=-858993457 }
bas	0x006217a8 {veri={...} sonraki=0x00621748 }
veri	{x=5 y=3 sag=0 ...}
x	5
y	3
sag	0
sol	1
asagi	0
yukari	1
gelinesyon	2
sonraki	0x00621748 {veri={...} sonraki=0x00624f90 }
veri	{x=3 y=3 sag=0 ...}
x	3
y	3
sag	0
sol	1
asagi	1
yukari	0
gelinesyon	2
sonraki	0x00624f90 {veri={...} sonraki=0x00000000 }
veri	{x=1 y=3 sag=0 ...}
x	1
y	3
sag	0
sol	0
asagi	1
yukari	1
gelinesyon	3

24

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012