libcamera

Devendra Tewari

August 11, 2022

libcamera

Introduction

- Cameras have gone from highly complex black boxes to highly configurable sensors
- Complexity has migrated up the stack to user / app space revealing the need for libcamera framework

Camera Sensor applications

- Digital photo and video
- Home
- Industrial
- Intelligent agriculture and farming
- Medical and life sciences
- Smart Retail

Camera Sensor Characteristics

- Resolution
- Frame rate
- Exposure time
- Gain - analogue, digital
- Color - monochrome, RGB
- Shutter - rolling, global
- Focus lenses and filters - Infrared, manual, auto
- Communication interface - MIPI CSI-2, I2C, SPI, USB

V4L2/DVB architecture

- App communicates with camera using device files such as `/dev/video0` typically using libv4l
- Obtains image and video through camera driver such as `bcm2835_v4l2` that depends on camera sensor I2C driver, `videodev`, and other V4L kernel modules
- `v4l-utils` package provides commands such as `v4l2-ctl` and `v4l2-dbg`

v4l2-ctl

```
v4l2-ctl --list-devices

v4l2-ctl --info --device /dev/video0

v4l2-ctl --list-formats --device /dev/video0

v4l2-ctl --set-fmt-video=width=640,height=480,pixelformat='Y10 '

v4l2-ctl --stream-mmap --stream-count=1 --stream-to=output.raw --device /d
```

Raw Y'UV images can be viewed with an app such as yuview

libcamera architecture

- App communicates with camera through user space C++ framework library
- Raw data is obtained from camera driver such as `bcm2835_unicam`
- Camera sensor I2C driver such as `imx219` is used to send commands
- Data is processed using extensible image processing algorithms
- Supports legacy V4L apps and USB cameras
- Camera Tuning is supported
- Android Camera HAL3 implementation is available

Image processing Algorithms

- Defective pixel correction (DPC)
- Spatial Denoise (SDN)
- Automatic White Balance (AWB)
- Automatic Exposure Control (AEC)
- Automatic Gain Control (AGC)
- Automatic Lens Shading Correction (ALSC)

Camera Modules from Raspberry Pi

- Camera Module v1 with OmniVision OV5647
- Camera Module v2 with Sony IMX219
  - Filter-less Pi Noir version available
- HQ Camera with Sony IMX477

Camera Modules from Arducam

- Camera modules for Raspberry Pi and other SoCs
- Monochrome Global Shutter with sensors such as OmniVision OV9281
- 64MP Autofocus 10x Digital Zoom Camera with Sony IMX686 sensor
- Stereo/Quad-Scopic Cameras

libcamera-apps from Raspberry Pi

```
LIBCAMERA_LOG_LEVELS=*:DEBUG libcamera-hello --list-cameras

libcamera-jpeg -o test.jpg -t 2000 --shutter 20000 --gain 1.5

libcamera-still -r -o test.jpg
libcamera-still -o test.jpg --post-process-file drc.json

libcamera-vid -t 10000 -o test.h264 --save-pts timestamps.txt
mkvmerge -o test.mkv --timecodes 0:timestamps.txt test.h264

libcamera-vid -t 10000 --codec mjpeg -o test.mjpeg
```

libcamera C++ API

- Open camera
- Configure streams
- Start camera
- Stop camera
- Close camera

Open camera

Create instance of `libcamera::CameraManager` to acquire an instance of `libcamera::Camera`

```
camera_manager_ = std::make_unique<CameraManager>();
camera_manager_->start();
std::string const &cam_id = camera_manager_->cameras()[0]->id();
camera_ = camera_manager_->get(cam_id);
camera_->acquire();
```

Configure streams

```
StreamRoles stream_roles = { StreamRole::VideoRecording };
// { StreamRole::StillCapture, StreamRole::Raw };
// { StreamRole::Viewfinder };
configuration_ = camera_->generateConfiguration(stream_roles);
configuration_->at(0).pixelFormat = libcamera::formats::YUV420;
configuration_->at(0).bufferCount = 2;
configuration_->at(0).size.width = 640;
configuration_->at(0).size.height = 480;
configuration_->validate();
camera_->configure(configuration_.get());
```

Start camera

For each frame an application wants to capture it must queue a request for it to the camera

```
Stream *stream = configuration_->at(0).stream();
allocator_ = new FrameBufferAllocator(camera_);
allocator_->allocate(stream);
const std::vector<std::unique_ptr<FrameBuffer>> &buffers =
    allocator_->buffers(stream);
controls_.set(controls::ExposureTime, 15000);
controls_.set(controls::AnalogueGain, 2);
camera_->start(&controls_);
controls_.clear();
camera_->requestCompleted.connect(requestComplete);
for (unsigned int i = 0; i < buffers.size(); ++i) {
    std::unique_ptr<Request> request = camera_->createRequest();
    request->addBuffer(stream, buffers[i].get());
    camera_->queueRequest(request.get());
    requests_.push_back(std::move(request));
}
```

requestComplete

```
if (request->status() == Request::RequestCancelled)
    return;
const libcamera::Request::BufferMap &buffers = request->buffers();
Save(buffers);
std::unique_ptr<Request> requestToQueue = camera_->createRequest();
for (auto bufferPair : buffers) {
    FrameBuffer *buffer = bufferPair.second;
    const Stream *stream = bufferPair.first;
    requestToQueue->addBuffer(stream, buffer);
}
camera_->queueRequest(requestToQueue.get());
requests_.push_back(std::move(requestToQueue));
```

Save YUV420 when no padding in data

```
assert(configuration_->at(0).size.width == configuration_->at(0).stride);
unsigned int length = 0;
for (auto bufferPair : buffers) {
    FrameBuffer *buffer = bufferPair.second;
    const FrameMetadata &metadata = buffer->metadata();
    std::cout << " seq: " << std::setw(6) << std::setfill('0') << metadata
    for (unsigned i = 0; i < buffer->planes().size(); i++)
    {
        length += buffer->planes()[i].length;
    }
    const std::string& filename = GetTimestamp() + ".yuv";
    std::ofstream out(filename, std::ios::out | std::ios::binary);
    void *memory = mmap(NULL, length, PROT_READ | PROT_WRITE, MAP_SHARED,
        buffer->planes()[0].fd.get(), 0);
    out.write((char *)memory, length);
    munmap(memory, length);
    out.close();
}
```

Encoding image and video

- libcamera provides raw image frames from the sensor that are processed using image processing and control algorithms based on per sensor tuning file
- libcamera does not provide additional means to encode or display images or videos
- `libcamera-still` uses external libraries to encode images such as libjpeg for jpeg
- `libcamera-vid` uses hardware H.264 encoder on Raspberry Pi through `/dev/video11`, apps may use external libraries such as ffmpeg/libav codec for H.264

Stop camera

```
camera_->stop();
camera_->requestCompleted.disconnect(requestComplete);
requests_.clear();
```

Close camera

- Configure streams, start and stop camera can repeat multiple times
- The application is now finished with the camera and the resources the camera uses

```
Stream *stream = configuration_->at(0).stream();
allocator_->free(stream);
delete allocator_;
configuration_.reset();
camera_->release();
camera_manager_->stop();
```

Build and run example

```
c++ example.cpp -o example `pkg-config --cflags --libs libcamera` -std=c++
meson build
cd build
ninja
$ LIBCAMERA_LOG_LEVELS=*:DEBUG ./example
Press enter to exit...
 seq: 000004
 seq: 000005
 seq: 000006
```

Explore further

- libcamera: The Future of Cameras on Linux is Now
- libcamera Documentation
- libcamera API
- Raspberry Pi Camera Guide
- Raspberry Pi Camera Algorithm and Tuning Guide