

Tomasulo's Algorithm

```
For each ALU
  If the instruction is complete
    If there is a RAT entry for the completed instruction
      Put the instruction result into the register that corresponds to
      that RAT entry.
      Mark the RAT entry as unused.
    For each RS
      For each operand slot in the RS
        If the operand slot is waiting for the results of the completed
        instruction
          Put the result of the completed instruction into the operand
          slot.
      Mark the ALU as unused.
      Mark as unused the RS that was occupied by the completed instruction.

While there is an instruction to issue
  If there is an appropriate RS entry which was empty at the beginning of the
  cycle, or which became empty during the cycle and the processor allows reuse
  in the same cycle
    Put the instruction into that RS entry.
    For each operand
      If the RAT entry corresponding to the operand register indicates
      that a result is being waited on
        Put the RS number of the instruction that we are waiting on into
        the operand slot of the RS for the instruction that is being issued.
      else
        Fetch the value from the operand register and put it into the
        operand of the RS for the instruction that is being issued.
    Put the RS number for the instruction that is being issued into the RAT
    entry that corresponds to the destination register of the instruction
    that is being issued.
    Remove the instruction from the instruction queue.

For each RS
  If RS has instruction with actual values for operands
    If the appropriate ALU or processing unit is free
      Dispatch the instruction, including operands and the RS number.
```

Reorder Buffer

```
For each ALU
  If the instruction is complete
    Put the result into the ROB entry corresponding to the destination register.
    For each RS that is waiting for it
      Put the result into the RS as an operand.
    Free the ALU.

While there is an instruction to issue
  If there is an empty ROB entry and an empty appropriate RS
    Put opcode into RS.
    Put ROB entry number into RS.
    For each operand which is a register
```

```

        If there is a ROB entry number in the RAT for that register
            Put the ROB entry number into the RS as an operand.
        else
            Put the register value into the RS as an operand.
    Put opcode into ROB entry.
    Put destination register name into ROB entry.
    Put ROB entry number into RAT entry for the destination register.
    Take the instruction out of the instruction window.

For each RS
    If RS has instruction with actual values for operands
        If an appropriate ALU or processing unit is free
            Dispatch the instruction, including operands and the ROB entry number.
            Free the RS.

While the next ROB entry to be retired has a result
    Write the result to the register.
    If the ROB entry number is in the RAT, remove it.
    Free the ROB entry.

```