Phase 2 Abstract Code w/SQL | CS 6400 - Spring 2021 | **Team 058**

Table of Contents:

View Statistics

Abstract Code[1]

- Show *"**Holiday Maintenance**", "**View Product by Category Report**", "**View Actual vs. Predicted Revenue for Couches and Sofas Report**", "**View Store Revenue by Year by State Report**", "**View Groundhog Day Outdoor Furniture Report**", "**View State with Highest Volume by Category Report**", "**View Revenue by Population Report**", "**View Childcare Sales Volume Report**", "**View Restaurant Impact on Category Sales Report**", "**View Advertising Campaign Analysis Report**",* and *"**Population Maintenance**"* buttons/links on the **Dashboard** form.
- Upon:
    - Click *Holiday Maintenance* button – Jump to the **Holiday Maintenance** form.
    - Click *View Product by Category Report* button – Jump to the **View Product by Category Report** task.
    - Click *View Actual vs. Predicted Revenue for Couches and Sofas Report* button – Jump to the **View Actual vs. Predicted Revenue for Couches and Sofas Report** task.
    - Click *View Store Revenue by Year by State Report* button – Jump to the **Get Available State List** task.
    - Click *View Groundhog Day Outdoor Furniture Report* button – Jump to the **View Groundhog Day Outdoor Furniture Report** task.
    - Click *View State with Highest Volume by Category Report* button – Jump to the **Get Year and Month List** task.
    - Click *View Revenue by Population Report* button – Jump to the **View Revenue by Population Report** task.
    - Click *View Childcare Sales Volume Report* button – Jump to the **View Childcare Sales Volume Report** task.
    - Click *View Restaurant Impact on Category Sales Report* button – Jump to the **View Restaurant Impact on Category Sales Report** task.
    - Click *View Advertising Campaign Analysis Report* button – Jump to the **View Advertising Campaign Analysis Report** task.
    - Click *Population Maintenance* button – Jump to the **Population Maintenance** form.
- Display statistics for "the count of stores", "count of stores offering food (have a restaurant, a snack bar, or both)", "count of stores offering childcare", "count of products", and "count of distinct advertising campaigns" on the **Dashboard** form.
    - Show "the count of stores".
        - Query for total count of Store_Number in the STORE table.
        - Display the total count.

        ```
        SELECT COUNT(Store_Number) FROM STORE;
        ```

---

[1] MySQL is applied to our submission.

Revised: 3/21/2021

- o Show "count of stores offering food".
    - ▪ Query for the total count of Store_Number in the STORE table that has either or both Has_Restaurant and Has_Snack_Bar value as true.
    - ▪ Display the total count.

> SELECT COUNT(Store_Number)
> FROM STORE
> WHERE Has_Restaurant IS TRUE OR Has_Snack_Bar IS TRUE;

- o Show "count of stores offering childcare".
    - ▪ Query for the total count of Store_Number with a Time_Limit in the STORE table.
    - ▪ Display the total count.

> SELECT COUNT(Store_Number)
> FROM STORE
> WHERE Time_Limit IS NOT NULL;

- o Show "count of products".
    - ▪ Query for the total count of PID in the PRODUCT table.
    - ▪ Display the total count.

> SELECT COUNT(PID) FROM PRODUCT;

- o Show "count of distinct advertising campaigns".
    - ▪ Query for the total count of Description in ADVERTISING_CAMPAIGN table.
    - ▪ Display the total count.

> SELECT COUNT(Description) FROM ADVERTISING_CAMPAIGN;

Get Holiday List

Abstract Code

- User clicked on the ***Holiday Maintenance*** button from the **Dashboard** form.
- Run the **Get Holiday List** task: query for information about the available Name field from the HOLIDAY table.
    - o Display the Holiday Name list.

> SELECT `Date`, `Name` FROM HOLIDAY;

- Upon:

- o User enters Holiday Name ($HolidayName) in input textbox and selects Date ($HolidayDate) in Calendar Dropdown.
  - o Click **Add Holiday** button –
    - ▪ Jump to the **Add Holiday** task.
- When ready, user can click on the **Return** button to return to the **Dashboard** form.

Add Holiday

Abstract Code

- User enters Holiday Name ($HolidayName) in input textbox and selects Date ($HolidayDate) in Calendar Dropdown.
- Click **Add Holiday** button.
- Run the **Add Holiday** task:
  - o If data validation passed for both Holiday Name and Date in client side, then:
    - ▪ If Holiday Name does not exist but Date exists:
      - ▫ Store Holiday Name in HOLIDAY table and link its Date with DAY table.
      - ▫ Go back to **Holiday Maintenance** form and show success message.
    - ▪ If both Holiday Name and Date do not exist:
      - ▫ Store the Date in DAY table.
      - ▫ Store the Date and Holiday Name in HOLIDAY table.
      - ▫ Go back to **Holiday Maintenance** form and show success message.

```sql
INSERT INTO `DAY` (`Date`)
SELECT '$HolidayDate'
FROM `DAY`
WHERE NOT EXISTS (
      SELECT 1 FROM `DAY` WHERE `Date` = '$HolidayDate')
LIMIT 1;

INSERT INTO HOLIDAY (`Date`, `Name`)
SELECT '$HolidayDate', '$HolidayName'
FROM HOLIDAY
WHERE NOT EXISTS (
      SELECT 1 FROM HOLIDAY WHERE `Date` = '$HolidayDate' AND
      `Name` = '$HolidayName')
LIMIT 1;
```

  - o Else: display the invalid error message in **Holiday Maintenance** form.
- When ready, user can click on the **Return** button to return to the **Dashboard** form.

         Revised: 3/21/2021

Maintain Population

Abstract Code

- User clicked on the ***Population Maintenance*** button from the **<u>Dashboard</u>** form.
- Query for information about the available State_Location, City_Name, and Population fields from the CITY table.
  - o Display State_Location list in ascending order in the drop-down list.

    ```
    SELECT DISTINCT State_Location
    FROM CITY
    ORDER BY State_Location ASC;
    ```

  - o Display the available City_Name list in ascending order based on the selected $State_Location in the drop-down list.

    ```
    SELECT City_Name
    FROM CITY
    WHERE State_Location = '$State_Location'
    ORDER BY City_Name ASC;
    ```

  - o Display Population based on the selected $State_Location and $City_Name in the view population textbox.

    ```
    SELECT Population
    FROM CITY
    WHERE State_Location = '$State_Location' AND City_Name = '$City_Name';
    ```

- User edits population textbox.
- Upon:
  - o Click ***Update Population*** button –
    - ▪ Jump to the **Update Population** task.
- Run the **Update Population** task.
  - o If data validation passed for $Population in client side, then:
    - ▪ If the updated population entered is the same as the original population, do nothing.
    - ▪ Else: the updated population entered is different from the original population, update the Population in the CITY table.

    ```
    UPDATE CITY
    SET Population = '$Population'
    WHERE State_Location = '$State_Location' AND City_Name = '$City_Name'
    AND Population <> '$Population';
    ```

Revised: 3/21/2021

- o   Else: display the invalid error message in **Population Maintenance** form.
- When ready, user can click on the ***Return*** button to return to the **Dashboard** form.

View Product by Category Report

Abstract Code

- User clicked on the ***View Product by Category Report*** button from the **Dashboard** form.
- Run the **View Product by Category Report** task: query for each category from CATEGORY, ASSIGNED, and PRODUCT tables, including those without products.
    - o   Find all Category_Name data (from the CATEGORY table).
    - o   For each Category_Name including those without products:
        - Find total number of products by counting their PID data (from the PRODUCT table).
        - Find minimum, average, and maximum Retail_Price data for all products (from the PRODUCT table).
    - o   Sort by Category_Name in ascending order.

```
SELECT C.Category_Name, COUNT(P.PID) AS Cnt_Product,
MIN(P.Retail_Price) AS Min_RtlPrc, AVG(P.Retail_Price) AS Avg_RtlPrc,
MAX(P.Retail_Price) AS Max_RtlPrc
FROM CATEGORY AS C
LEFT JOIN ASSIGNED AS A ON C.Category_Name = A.Category_Name
LEFT JOIN PRODUCT AS P ON A.PID = P.PID
GROUP BY C.Category_Name
ORDER BY C.Category_Name ASC;
```

- When ready, user can click on the ***Return*** button to return to the **Dashboard** form.

View Actual vs. Predicted Revenue for Couches and Sofas Report

Abstract Code

- User clicked on the ***View Actual vs. Predicted Revenue for Couches and Sofas Report*** button from the **Dashboard** form.
- Run the **View Actual vs. Predicted Revenue for Couches and Sofas Report** task:
    - Find the 'Couches and Sofas' category (from the CATEGORY table).
    - For each product in 'Couches and Sofas' category:
        - Find PID, Product_Name, and Retail_Price data (from the PRODUCT table).
        - Find the total number of units ever sold by aggregating Quantity (from the SALE table).
        - Find the total number of units sold at a discount by aggregating Quantity (from the SALE table) when the product has a Discount_Price (from the DISCOUNT table).
        - Find the total number of units sold at retail price by aggregating Quantity (from the SALE table) when the product doesn't have a Discount_Price (from the DISCOUNT table).
        - Find the actual revenue by aggregating Total_Amount (from the SALE table).
            - Total_Amount (from the SALE table) is calculated based on the Date, Quantity, and individual item price.
            - Individual item price equals Retail_Price (from the PRODUCT table) when the product doesn't have a Discount_Price. Otherwise, individual item price equals Discount_Price (from the DISCOUNT table).
        - Find the predicted revenue by aggregating the following multiplication result: Retail_Price (from the PRODUCT table) * Quantity (from the SALE table) * quantity multiplier. The quantity multiplier equals 0.75 when the product has a Discount_Price (from the DISCOUNT table), otherwise, the quantity multiplier equals 1.
        - Find the revenue difference by subtracting predicted revenue from actual revenue.
    - If the revenue difference is greater than $5000 (positive or negative): Display revenue difference and sort in descending order.

```
SELECT P.PID, P.Product_Name, P.Retail_Price,
SUM(IFNULL(S.Quantity,0)) AS Tot_UnitSold,
SUM(IF(D.Discount_Price IS NULL,0,1) * IFNULL(S.Quantity,0)) AS Tot_UnitSold_AtDsct,
SUM(IF(D.Discount_Price IS NULL,1,0) * IFNULL(S.Quantity,0)) AS Tot_UnitSold_AtRtl,
SUM(IFNULL(S.Total_Amount,0)) AS Act_Revenue,
SUM(P.Retail_Price * IFNULL(S.Quantity,0) * IF(D.Discount_Price IS NULL, 1, 0.75)) AS
Pred_Revenue,
(SUM(IFNULL(S.Total_Amount,0)) - SUM(P.Retail_Price * IFNULL(S.Quantity,0) *
IF(D.Discount_Price IS NULL, 1, 0.75))) AS Diff_Act_Pred_Revenue
FROM CATEGORY AS C
LEFT JOIN ASSIGNED AS A ON C.Category_Name = A.Category_Name
LEFT JOIN PRODUCT AS P ON A.PID = P.PID
LEFT JOIN SALE AS S ON P.PID = S.PID
LEFT JOIN DISCOUNT AS D ON S.Date = D.Date AND S.PID = D.PID
WHERE C.Category_Name = 'Couches and Sofas'
GROUP BY P.PID
HAVING Diff_Act_Pred_Revenue > 5000 OR Diff_Act_Pred_Revenue < -5000
ORDER BY Diff_Act_Pred_Revenue DESC;
```

- When ready, user can click on the **_Return_** button to return to the **Dashboard** form.

Get Available State List

Abstract Code

- User clicked on **_View Store Revenue by Year by State Report_** button from the **Dashboard** form.
- Run the **Get Available State List** task: query for information about the available State_Location field from the CITY table.
    - Display State_Location list in ascending order on the drop-down list.

    ```
    SELECT DISTINCT State_Location
    FROM CITY
    ORDER BY State_Location ASC;
    ```

- On the drop-down list, show **_Run Report_** button.
- Upon:
    - Click **_Run Report_** button –
        - If $State_Location is selected – Jump to the **View State Revenue by Year by State Report** task.
        - If $State_Location is empty – Display a message asking for user input.
- When ready, user can click on the **_Return_** button to return to the **Dashboard** form.

View Store Revenue by Year by State Report

Abstract Code

- User clicked on the ***Run Report*** button from the drop-down list.
- Run the **View State Revenue by Year by State Report** task:
  - o Find all stores from the STORE table based on the selected $State_Location.
  - o For each store and each year,
    - ▪ Display Store_Number, Street_Address, and City_Name (from the STORE table), and the year of Date (from the SALE table).
    - ▪ Find the total revenue by aggregating all products' sale revenue based on Total_Amount (from the SALE table).
  - o Sort by year ascendingly, and then sort by total revenue descendingly.

```
SELECT STORE.Store_Number, Street_Address, City_Name, YEAR(Date),
SUM(IFNULL(Total_Amount, 0)) AS Revenue
FROM STORE
LEFT JOIN SALE ON STORE.Store_Number = SALE.Store_Number
WHERE State_Location = '$State_Location'
GROUP BY STORE.Store_Number, YEAR(Date)
ORDER BY YEAR(Date) ASC, Revenue DESC;
```

- When ready, user can click on the ***Return*** button to return to the **Dashboard** form.

View Groundhog Day Outdoor Furniture Report

Abstract Code

- User clicked on the ***View Groundhog Day Outdoor Furniture Report*** button from the **Dashboard** form.
- Run the **View Groundhog Day Outdoor Furniture Report** task:
  - o Get the outdoor furniture category (from the CATEGORY table).
  - o For each year:
    - • Find year based on Date (from the SALE table).
    - ▪ Find total number of products sold by aggregating Quantity (from the SALE table) in that year.
    - ▪ Find average number of products sold per day by dividing total number of products sold by 365.
    - ▪ Find total number of products sold on Groundhog Day by aggregating Quantity (from the SALE table) on Feb 2 in that year.
  - o Sort by year in ascending order.

```
SELECT YEAR(Date),
SUM(IFNULL(Quantity, 0)) AS Tot_Quantity,
(SUM(IFNULL(Quantity, 0)) / 365) AS Avg_Quantity,
SUM(IF(MONTH(Date)=2 AND DAY(Date)=2,1,0) * IFNULL(Quantity, 0)) AS
GhDay_Quantity
FROM CATEGORY AS C
LEFT JOIN ASSIGNED AS A ON C.Category_Name = A.Category_Name
LEFT JOIN PRODUCT AS P ON A.PID = P.PID
LEFT JOIN SALE AS S ON P.PID = S.PID
WHERE C.Category_Name = 'Outdoor Furniture'
GROUP BY YEAR(Date)
ORDER BY YEAR(Date) ASC;
```

- When ready, user can click on the ***Return*** button to return to the **Dashboard** form.

Get Year and Month List

Abstract Code

- User clicked on the ***View State with Highest Volume by Category Report*** button from the **Dashboard** form.
- Run the **Get Year and Month List** task: query for information about the available Year and Month fields from the DAY table.
  - ○ Display Year list in descending order in the drop-down list.

    ```
    SELECT DISTINCT YEAR(`Date`) AS `Year`
    FROM `DAY`
    ORDER BY `Year` DESC;
    ```

  - ○ Display Month list in descending order based on the selected $Year in the drop-down list.

    ```
    SELECT DISTINCT MONTH(`Date`) AS `Month`
    FROM `DAY`
    WHERE YEAR(`Date`) = '$Year'
    ORDER BY `Month` DESC;
    ```

- On the drop-down list, show ***Run Report*** button.
- Upon:
  - ○ Click ***Run Report*** button –

- If both $Year and $Month are selected – Jump to the **View State with Highest Volume by Category Report** task.
- If one or both fields are empty – Display a message asking for user input.
- When ready, user can click on the *Return* button to return to the **<u>Dashboard</u>** form.

View State with Highest Volume by Category Report

Abstract Code

- User clicked on the *Run Report* button from the drop-down list.
- If data validation is successful for both $Year and $Month input fields, then proceed.
- Run the **View State with Highest Volume by Category Report** task:
  - Based on the selected $Year and $Month,
  - For each category,
    - Find the states that sold the highest number of units in the category.
      - If two or more states tied for having the highest number of units, then display all these states.
    - Display Category_Name (from the CATEGORY table) and State_Location (from the STORE table).
    - Find the number of units that were sold by stores in that state by aggregating Quantity (from the SALE table).
  - Sort by Category_Name ascendingly.

```
SELECT C.Category_Name, T.State_Location, SUM(IFNULL(S.Quantity,0)) AS Tot_UnitSold
FROM CATEGORY AS C
LEFT JOIN ASSIGNED AS A ON C.Category_Name = A.Category_Name
LEFT JOIN PRODUCT AS P ON A.PID = P.PID
LEFT JOIN SALE AS S ON P.PID = S.PID AND YEAR(S.`Date`) = '$Year' AND
MONTH(S.`Date`) = '$Month'
LEFT JOIN STORE AS T ON S.Store_Number = T.Store_Number
GROUP BY C.Category_Name, T.State_Location
HAVING Tot_UnitSold >= ALL
  (
       SELECT SUM(IFNULL(S2.Quantity,0))
       FROM CATEGORY AS C2
       LEFT JOIN ASSIGNED AS A2 ON C2.Category_Name = A2.Category_Name
       LEFT JOIN PRODUCT AS P2 ON A2.PID = P2.PID
       LEFT JOIN SALE AS S2 ON P2.PID = S2.PID AND YEAR(S2.`Date`) = '$Year' AND
MONTH(S2.`Date`) = '$Month'
       LEFT JOIN STORE AS T2 ON S2.Store_Number = T2.Store_Number
       WHERE C2.Category_Name = C.Category_Name
       GROUP BY C2.Category_Name, T2.State_Location
  )
ORDER BY C.Category_Name ASC;
```

- When ready, user can click on the ***Return*** button to return to the **Dashboard** form.

View Revenue by Population Report

Abstract Code

- User clicked on the ***View Revenue by Population Report*** button from the **Dashboard** form.
- Run the **View Revenue by Population Report** task:
  - Find the Date, Population, and Total_Amount from the SALE, STORE, and CITY tables.
  - For each year of Date:
    - Find total revenue for each city size category by aggregating Total_Amount.
  - Display total revenue based on year and city size category:
    - Row: Years, sorted in ascending order.
    - Column: City size categories, sorted in ascending order. Specifically, SmallCity, MediumCity, LargeCity, and ExtraLargeCity.

```
SELECT
        YEAR(SRC.`Date`) AS Years,
        SUM(IF(Population < 3700000, Total_Amount, 0)) AS SmallCity,
        SUM(IF(Population >= 3700000 AND Population < 6700000,
        Total_Amount, 0)) AS MediumCity,
        SUM(IF(Population >= 6700000 AND Population < 9000000,
        Total_Amount, 0)) AS LargeCity,
        SUM(IF(Population >= 9000000, Total_Amount, 0)) AS
        ExtraLargeCity
FROM (
        SELECT
                SALE.`Date`,
                SALE.Total_Amount,
                CITY.Population
        FROM CITY
                INNER JOIN STORE ON CITY.State_Location =
STORE.State_Location AND CITY.City_Name = STORE.City_Name
                INNER JOIN SALE ON STORE.Store_Number =
SALE.Store_Number
        ) AS SRC
GROUP BY YEAR(SRC.`Date`)
ORDER BY YEAR(SRC.`Date`) ASC;
```

- When ready, user can click on the *Return* button to return to the **Dashboard** form.

View Childcare Sales Volume Report

Abstract Code

- User clicked on the *View Childcare Sales Volume Report* button from the **Dashboard** form.
- Run the **View Childcare Sales Volume Report** task:
  - Find Childcare_Category based on Time_Limit (from the STORE table). If Childcare_Category doesn't have a value, set Childcare_Category to 'No childcare'.
  - For each Sale_Year_Month based on `Date` (from the SALE table) in last 12 months:
    - Find the total sales by aggregating Total_Amount (from the SALE table) in each Childcare_Category.
  - Display total sales based on Sale_Year_Month and Childcare_Category:
    - Row: Sale_Year_Month, sorted in ascending order.
    - Column: Childcare_Category.

```
SET @Sql = '';

SELECT @Sql:=CONCAT(@Sql,
'SUM(IF(Childcare_Category=\'',Childcare_Category,'\',',Total_Amount,0)) AS \'',
Childcare_Category,'\',')
FROM (
        SELECT DISTINCT
        IF(STORE.Time_Limit IS NOT NULL, CAST(STORE.Time_Limit AS CHAR(10)),
        "No childcare") AS Childcare_Category
        FROM STORE
        ) AS TL;


SET @Sql = CONCAT('SELECT Sale_Year_Month,',LEFT(@Sql, LENGTH(@Sql)-1),'
FROM (
        SELECT
        DATE_FORMAT(SALE.`Date`, "%Y-%m") AS Sale_Year_Month,
        SALE.Total_Amount AS Total_Amount,
        IF( STORE.Time_Limit IS NOT NULL, CAST(STORE.Time_Limit AS CHAR(10)),
        "No childcare") AS Childcare_Category
        FROM STORE
        INNER JOIN SALE ON STORE.Store_Number = SALE.Store_Number
        WHERE SALE.`Date` >= DATE_ADD( LAST_DAY(DATE_SUB(CURDATE(),
        INTERVAL 12 MONTH) ), INTERVAL 1 DAY)
        ) AS REV
GROUP BY Sale_Year_Month
ORDER BY Sale_Year_Month ASC');

PREPARE stmt FROM @Sql;
EXECUTE stmt;
```

- When ready, user can click on the ***Return*** button to return to the **<u>Dashboard</u>** form.

View Restaurant Impact on Category Sales Report

Abstract Code

- User clicked on the ***View Restaurant Impact on Category Sales Report*** button from the **Dashboard** form.
- Run the **View Restaurant Impact on Category Sales Report** task:
  - Get Category_Name that has product(s) assigned (from the CATEGORY, ASSIGNED, and PRODUCT tables) and has sales data (from the SALE table).
  - Get `Store Type` based on Has_Restaurant (from the STORE table). If Has_Restaurant is true, set `Store Type` to 'Restaurant', otherwise, set `Store Type` to 'Non-restaurant'.
  - For each Category_Name and `Store Type`:
    - Include either 'Restaurant' or 'Non-restaurant', even if there's no sales data.
    - Find `Quantity Sold` by aggregating all products' Quantity (from the SALE table).
  - Sort by Category_Name ascendingly and then by `Store Type` with 'Non-restaurant' listed first.

```
SELECT COLS.Category, COLS.`Store Type`, IFNULL(ACT.`Quantity Sold`, 0)
FROM
        ( ( SELECT C01.Category_Name AS Category, 'Restaurant' AS `Store Type`
          FROM CATEGORY AS C01)
        UNION
        ( SELECT C02.Category_Name AS Category, 'Non-restaurant' AS `Store Type`
          FROM CATEGORY AS C02)
        ) AS COLS
LEFT JOIN
        (SELECT
                C.Category_Name AS Category,
                IF(T.Has_Restaurant IS TRUE, 'Restaurant', 'Non-restaurant') AS `Store Type`,
                SUM(S.Quantity) AS `Quantity Sold`
        FROM CATEGORY AS C
        INNER JOIN ASSIGNED AS A ON C.Category_Name = A.Category_Name
        INNER JOIN PRODUCT AS P ON A.PID = P.PID
        INNER JOIN SALE AS S ON P.PID = S.PID
        INNER JOIN STORE AS T ON S.Store_Number = T.Store_Number
        GROUP BY Category, `Store Type`
        ) AS ACT
ON COLS.Category = ACT.Category AND COLS.`Store Type` = ACT.`Store Type`
ORDER BY COLS.Category ASC, COLS.`Store Type` ASC;
```

- When ready, user can click on the ***Return*** button to return to the **Dashboard** form.

View Advertising Campaign Analysis Report

Abstract Code

- User clicked on the ***View Advertising Campaign Analysis Report*** button from the **Dashboard** form.
- Run the **View Advertising Campaign Analysis Report** task: query for information if a product has Discount_Price (from the DISCOUNT table).
  - ○ For each product:
    - ▪ Display PID and Product_Name (from the PRODUCT table).
    - ▪ Find total quantity sold during campaign by aggregating Quantity (from the SALE table) in all discount sale days when any advertising campaign was active.
    - ▪ Find total quantity sold outside campaign by aggregating Quantity (from the SALE table) in all discount sale days when no advertising campaign was active.
    - ▪ Find the difference by subtracting quantity sold outside campaign from quantity sold during campaign.
  - ○ Sort by difference in descending order and only display the top 10 followed by the bottom 10.

```sql
SELECT `Product ID`, `Product Name`, `Sold During Campaign`, `Sold Outside Campaign`, Difference
FROM(
        (
        SELECT P.PID AS `Product ID`, P.Product_Name AS `Product Name`,
        SUM(IF(A.`Description` IS NULL,0,1) * IFNULL(S.Quantity,0)) AS `Sold During Campaign`,
        SUM(IF(A.`Description` IS NULL,1,0) * IFNULL(S.Quantity,0)) AS  `Sold Outside Campaign`,
        (SUM(IF(A.`Description` IS NULL,0,1) * IFNULL(S.Quantity,0)) -
         SUM(IF(A.`Description` IS NULL,1,0) * IFNULL(S.Quantity,0))) AS Difference
        FROM PRODUCT AS P
        INNER JOIN DISCOUNT AS I ON P.PID = I.PID
        LEFT JOIN SALE AS S ON I.`Date` = S.`Date` AND I.PID = S.PID
        LEFT JOIN DAY AS D ON S.`Date` = D.`Date`
        LEFT JOIN HOLD AS H ON D.`Date` = H.`Date`
        LEFT JOIN ADVERTISING_CAMPAIGN AS A ON H.`Description` = A.`Description`
        GROUP BY `Product ID`
        ORDER BY Difference DESC
        LIMIT 10
        )
        UNION
        (
        SELECT P2.PID AS `Product ID`, P2.Product_Name AS `Product Name`,
        SUM(IF(A2.`Description` IS NULL,0,1) * IFNULL(S2.Quantity,0)) AS `Sold During Campaign`,
        SUM(IF(A2.`Description` IS NULL,1,0) * IFNULL(S2.Quantity,0)) AS  `Sold Outside Campaign`,
        (SUM(IF(A2.`Description` IS NULL,0,1) * IFNULL(S2.Quantity,0)) -
         SUM(IF(A2.`Description` IS NULL,1,0) * IFNULL(S2.Quantity,0))) AS Difference
        FROM PRODUCT AS P2
        INNER JOIN DISCOUNT AS I2 ON P2.PID = I2.PID
        LEFT JOIN SALE AS S2 ON I2.`Date` = S2.`Date` AND I2.PID = S2.PID
        LEFT JOIN DAY AS D2 ON S2.`Date` = D2.`Date`
        LEFT JOIN HOLD AS H2 ON D2.`Date` = H2.`Date`
        LEFT JOIN ADVERTISING_CAMPAIGN AS A2 ON H2.`Description` = A2.`Description`
        GROUP BY `Product ID`
        ORDER BY Difference ASC
        LIMIT 10
        )
        ) AS UN
ORDER BY Difference DESC;
```

- When ready, user can click on the *Return* button to return to the **Dashboard** form.

Revised: 3/21/2021