Absolute encoder package

Fabien Le Mentec
lementec@esrf.fr

version: SVN revision exported

Contents

1 Description

1.1 Overview

The abs_enc_pkg implements components for absolute encoder masters and slaves.

The term *master* refers to the component driving the clock, or at least initiating the data transfer. It is sometimes called the controller. The term *slave* refers to the actual encoder device.

This package is optimized for applications that can be dynamically configured to implement one amongst different types of encoders at a particular time. As much as possible, exclusive resources that can be shared across encoder types are factorized (counters, comparators, shift registers ...). However, and in order to avoid penalizing simpler applications, static configuration allows to exclude resources associated with an unused encoder type.

1.2 Supported features

TODO:

The following encoder types are available:

- ENDAT (version 2.1, send position mode),
- BISS,
- SSI.

1.3 Performances

TODO:

1.4 Architecture

TODO:

2 Interfaces

2.1 abs_enc_pkg.master

Extracted from file ./../src/abs_enc_pkg.vhd at line 332

```
component master
generic
(
 CLK_FREQ: integer;
 ENABLE_ENDAT: boolean := TRUE;
 ENABLE_BISS: boolean := TRUE;
 ENABLE_SSI: boolean := TRUE
);
port
(
 -- local clock
 clk: in std_logic;
 rst: in std_logic;

 -- generated clock for slave
 -- fdiv divides CLK_FREQ
 ma_fdiv: in unsigned;
 ma_clk: out std_logic;

 -- master out, slave in
 mosi: out std_logic;
 miso: in std_logic;

 -- gate to drive output (1 to drive it)
 gate: out std_logic;

 -- data from slave, and data length
 data: out std_logic_vector;
 len: in unsigned;

 -- encoder type
 enc_type: in integer
);
end component;
```

2.2 abs_enc_pkg.slave

Extracted from file ./../src/abs_enc_pkg.vhd at line 152

```
component slave
generic
(
 CLK_FREQ: integer;
 ENABLE_ENDAT: boolean := TRUE;
 ENABLE_BISS: boolean := TRUE;
 ENABLE_SSI: boolean := TRUE
);
port
(
 -- local clock
 clk: in std_logic;
 rst: in std_logic;

 -- master clock
 ma_clk: in std_logic;

 -- master in, slave out
 miso: out std_logic;
 mosi: in std_logic;

 -- gate to drive output (1 to drive it)
 gate: out std_logic;
```

```
 -- data and length
 data: in std_logic_vector;
 len: in unsigned;

 -- encoder type
 enc_type: in integer
);
end component;
```

error: invalid kind: notes

AN ERROR OCCURED

3 Examples

3.1 master

Extracted from file ./../sim/common/main.vhd at line 90

```
master: work.abs_enc_pkg.master
generic map
(
 CLK_FREQ => CLK_FREQ
)
port map
(
 clk => clk,
 rst => rst,
 ma_fdiv => ma_fdiv,
 ma_clk => ma_clk,
 mosi => mosi,
 miso => miso,
 gate => open,
 data => master_data,
 len => len,
 enc_type => enc_type
);
```

3.2 slave

Extracted from file ./../sim/common/main.vhd at line 71

```
slave: work.abs_enc_pkg.slave
generic map
(
 CLK_FREQ => CLK_FREQ
)
port map
(
 clk => clk,
 rst => rst,
 ma_clk => ma_clk,
 miso => miso,
 mosi => mosi,
 gate => open,
 data => slave_data,
 len => len,
 enc_type => enc_type
);
```