



PytroAI



Cloud Native



Modbus RTU



Modbus TCP



Modbus Cellular



Modbus Radio

Legacy Controller
Support

- Alarming & Notifications
- GPS/GNSS Remote tracking
- PytroAI USB Web Interface
- Modbus RTU over RS-232
- Modbus RTU over RS-485
- Modbus TCP over Ethernet
- Modbus Cellular over LTE 4G
- Modbus Radio over 900MHz ISM
- Logging via microSD



PX-A300 is an Industrial Edge Controller built specifically to interface to any modbus controller to provide an advanced monitoring, alarming and control layer. **PX-A300** has a built-in Edge MPU(aka PytroAI) for processing complex algorithms that add an advanced logic layer to legacy controllers to implement new algorithms. **PytroAI** has a USB-Web Interface to easily browse, download, and install pre-built apps via a simple USB connection—eliminating complex proprietary software. **PX-A300** is Modbus Master Controller that supports wired Modbus (RS-232, RS-485, Ethernet TCP) and wireless Modbus (LTE 4G, Radio ISM). **PX-A300** is a Cloud-Native Controller that allow bidirectional communication to/from any Modbus compatible device while consolidating control, monitoring, and analytics onto a single device.

Specification Table

Hardware Specifications		Software Specifications	
Supply voltage	12 – 24 VDC	Device Setup	PytroAI USB Web Interface
Dimensions(LxWxH)	3.937" x 3.244" x 1.114"	Edge engine	MicroPython
IP Rating	IP 64	Device Troubleshooting	PytroAI USB debugger
Logging	MicroSD card	Device Programming	PytroAI USB DFU
USB	Debugger, DFU update	Device Bootloader	DFU, Recovery mode
Modbus(+) Wired Interfaces		Modbus(+) Wireless Interfaces	
RS-232	1× port- Modbus RTU Slave	LTE 4G	Modbus Cellular via API
RS-485	1× port- Modbus RTU Slave 1× port- Modbus RTU Master	Radio 900Mz ISM	Modbus Radio Master Modbus Radio Slave
Ethernet	1× port- Modbus TCP Slave	Certifications	FCC, IC

Ordering Options

Part Number	Description of Product
PX-A300	RS-232, RS-485, Ethernet (internet via on-site LAN or Starlink), microSD, RTC, 12–24 VDC.
PX-A300-CELL	All features as above plus Cellular LTE 4G module for remote telemetry.
PX-A300-RADIO	All features as above plus Radio 900MHz module for local telemetry.
Warranty	1 year standard. See www.pytrowell.com/warranty for terms.

