

AMR-300 MOBILE ROBOT

INTRALOGISTICS THAT DRIVES ITSELF



OVERVIEW

The AMR-300 moves material between stations, stores and production lines without operators, tracks, or magnetic tape. LiDAR-based natural navigation maps your plant as-is, the fleet manager dispatches jobs from your ERP or MES, and roller-top or lift-top modules match your load units. Dual safety LiDAR plus bumpers keep it safe around people and forklifts.

PRIMARY APPLICATIONS

Line-side
Delivery

Warehouse
Transfer

WIP
Movement

Finished
Goods
Transport

SPECIFICATIONS

Type	AGV / Autonomous Mobile Robot
Payload	300 kg
Navigation	Natural navigation (LiDAR SLAM)
Docking Accuracy	±10 mm
Top Modules	Roller-top / Lift-top / Custom
Fleet Management	Texsonics fleet manager, ERP/MES integration
Charging	Opportunity charging, auto-dock
Safety	Dual safety LiDAR + bumpers

WORKING RANGE

Travel speed	≤ 1.5 m/s
Runtime	~8 h per charge
Min aisle width	900 mm

Gradeability	≤ 5% incline
Turning footprint	Turns in place (differential drive)

KEY HIGHLIGHTS

- Payload capacity 300 kg
- Docking accuracy ±10 mm docking
- LiDAR-based natural navigation (no tape, no reflectors)
- Designed, manufactured and supported from Coimbatore, India
- Fleet manager with ERP / MES integration
- Dual safety LiDAR, bumpers and emergency stop

WORK ENVELOPE & INSTALLATION

The AMR-300 operates fleet-wide across your facility with a 300 kg payload and LiDAR-based natural navigation. Every unit ships with the Texsonics fleet manager, opportunity charging, and is supported locally by our engineering team from Coimbatore.

DISCLAIMER

Specifications and visuals may change without notice as part of ongoing product improvements. Images are for reference only; actual performance may vary by application. Unauthorized reproduction of this catalogue is prohibited without written permission from Texsonics Systems India Private Limited.